
Dimensions are

millimetres over inches

Keying Plan from Mating Direction

Keying Plan

- 1 Locking Latch
- 2 Keying Rib
- 3 Polarisation Rib
- 4 Cavity Number



AMP MONO-SHAPE - 3 Position Satellite Connector (Variable Keying)*

Suitable for RAST 5 Version Colour Marking	RAST 5 Version	Part Numbers			Packaging Unit		
		On Tray Lo	ose Piece	On Reel	On Reel	Loose Piece	On Reel
03-A 03-I Black		1-282099-1	_	_	4.160	_	_

AMP MONO-SHAPE - 2 Position Satellite Connector

(Variable Keying)* Bridge between Contacts. Cavity Numbers 1-2 to have Short Circuit

(variable keying)" Bridge i	between Contacts. Cavity Numbe	ers 1-2 to have Short	t Circuit				
02-L 02-P —		1-284288-1	284288-1	_	6.500	_	_
02-L 02-P Orange		_	284288-2	_	_	3.000	_
02-L 02-P Blue		1-284288-3	284288-3	_	6.500	3.000	_
02-L 02-P Green		_	284288-4	_	_	3.000	_
02-L 02-P Violet		_	284288-5	_	_	3.000	_
02-L 02-P Black		1-284288-6	284288-6	_	6.500	3.000	_
02-C —		_	284288-7	_	_	3.000	_

^{*} Final keying version is produced on the Application Tooling Machines.