



# Azure Champ

Azure Champ







# Onur Yüksektepeli | @oyuksektepeli

- Microsoft Cloud Solutions Architect
- Microsoft MVP, Microsoft MCT
- Community Lead
- [V-onyuks@microsoft.com](mailto:V-onyuks@microsoft.com)
- [Onur.yuksektepeli@mshowto.org](mailto:Onur.yuksektepeli@mshowto.org)
- <https://twitter.com/oyuksektepeli>
- <https://www.linkedin.com/in/onuryuksektepeli/>
- <https://github.com/oyuksektepeli>
- <https://notebooks.azure.com/oyuksektepeli/>
- <http://www.youtube.com/c/onuryuksektepeli>
- <https://www.facebook.com/onuryuksektepeli/>





# Azure Resource Groups

Azure Champ



# Connect to Azure

Azure  
Portal

Azure  
Cloud Shell

Azure  
Powershell

Azure CLI  
v2.0

Azure  
SDKs

# Azure Cloud Shell

## You have no storage mounted ✕

Azure Cloud Shell requires an Azure file share to persist files. [Learn more](#)  
This will create a new storage account for you and this will incur a small monthly cost. [View pricing](#)

\* Subscription

Diagnostics



[Show advanced settings](#)

Create storage

Close

# Azure Cloud Shell

```
PowerShell | ? | ? | ? | ? | {}
Requesting a Cloud Shell.Succeeded.
Connecting terminal...

MOTD: Scripts installed with 'Install-Script' can be run from the shell

VERBOSE: Authenticating to Azure ...
VERBOSE: Building your Azure drive ...
Azure:/
PS Azure:\> Get-CloudDrive

FileShareName      : cs-onur-yuksektepeli-yuksektek-com-1003bffd9f20c732
FileSharePath      : //csb7fd89b160998x418fxac1.file.core.windows.net/cs-onur-yuksektepeli-yuksektek-com-1003bffd9f20c732
MountPoint         : /home/onur/cloudrive
Name               : csb7fd89b160998x418fxac1
ResourceGroupName  : cloud-shell-storage-westeuropa
StorageAccountName : csb7fd89b160998x418fxac1
SubscriptionId     : 7fd89b16-0998-418f-ac17-236f38d101bc
```

```
Bash | ? | ? | ? | ? | {}
Requesting a Cloud Shell.Succeeded.
Connecting terminal...

onur@Azure:~$ clouddrive -h

Group
  clouddrive                :Manage storage settings for Azure Cloud Shell.

Commands
  mount                     :Mount a file share to Cloud Shell.
  unmount                   :Unmount a file share from Cloud Shell.

onur@Azure:~$
```

# Azure Cloud Drive

cloudshell

>\_📁🔔⚙️?😊

[Dashboard](#) > [Resource groups](#) > [cloud-shell-storage-west europe](#) > [csb7fd89b160998x418fxac1 - Files](#) > [cs-onur-yuksektepeli-yuksektek-com-1003bffd9f20c732](#)

**cs-onur-yuksektepeli-yuksektek-com-1003bffd9f20c732**  
File share

«

Overview

Access Control (IAM)

Settings

Access policy

Properties

Connect

Upload

Add directory

Refresh

Delete share

Quota

View snapshots


Create Snapshot

Backup (Preview) is not enabled for this file share. Click here to enable backup.

Location: cs-onur-yuksektepeli-yuksektek-com-1003bffd9f20c732

NAME	TYPE	SIZE
.cloudconsole	Directory	

# Visual Studio


 | **Visual Studio** Visual Studio IDE Features ▾ Offerings ▾ Downloads Support ▾ Subscriber Access [Free Visual Studio](#)

All Microsoft ▾ Search 🔍 Sign in


## Visual Studio Community

A fully-featured, extensible, free IDE for creating modern applications for Android, iOS, Windows, as well as web applications and cloud services.

[Windows](#) [macOS](#)


[Download Visual Studio](#) 

## Everything you need all in one place




### Flexibility

Build apps for any platform




### Productivity

Designers, editors, debuggers, profilers, in one single tool



### Ecosystem

Access to thousands of extensions




### Languages

Code in C#, Visual Basic, F#, C++, HTML, JavaScript, TypeScript, Python, and more

<https://visualstudio.microsoft.com/vs/community/>



# Azure Development



# Azure Resource Groups

- Resources in a resource group should share the same lifecycle
- Each resource can only exist in one resource group
- Resources can be added or removed to a resource group at any time
- Resources can be moved from one resources group to another
- Resource groups can contain resources that reside in different regions
- Resources can interact with resources in other resources groups

# Resource Group Management

- Tags
- Locks
- Access Control (IAM)
- Policies

# Sample Resource Group

- Ms-net-rg
- Purpose: Isolate the Virtual networks
- Need: Prevent unwanted changes to any of the network resources
- Admin: It will deploy and maintain RG
- Notes: Resources in other RGs will use the resources int this group
- Dept: IT
- Owner: Onur YUKSEKTEPELI

# Demo

- Creating a Resource

# Azure Resource Tags

- Logically organize resources. Each tag has a name and a value. Allows related resources from different resource groups to be identified. Organize by billing and management.

# TAG Rules

- Tags are NOT inherited
- Names can't contain these characters: <, >, %, &, \, ?, /
- Tag name is limited to 512 characters
- Tag value is limited to 256 characters

# Demo

- Create Tag



# Resource Group Locks

- Prevent accidental deletion or changes to resources in resource groups. Consists of two locks:
  - CanNotDelete
  - ReadOnly

# Demo

- Create Resource Locks

# Access Control (IAM)

- A system that provides fine-grained access Management of resources in Azure. Grant only the amount of Access to users needed to perform their jobs

# Demo



- Access Control (IAM)

# Azure Policy

- Allows you to manage and prevent IT issues with policy definitions that enforce rules and effects for your resources. Policies allow you to keep compliant with corporate standards and SLAs.

# Demo

- Azure Policy



# Azure Compute

Azure Champ



# Azure Compute

- Azure Compute Unit

The concept of the Azure Compute Unit (ACU) provides a way of comparing compute (CPU) performance across Azure SKUs. This will help you easily identify which SKU is most likely to satisfy your performance needs. ACU is currently standardized on a Small (Standard\_A1) VM being 100 and all other SKUs then represent approximately how much faster that SKU can run a standard benchmark.



# Azure Compute Unit(ACU)

SKU Family	ACU \ vCPU	vCPU: Core
A0	50	1:1
A1 - A4	100	1:1
A5 - A7	100	1:1
A1_v2 - A8_v2	100	1:1
A2m_v2 - A8m_v2	100	1:1
A8 - A11	225*	1:1
D1 - D14	160 - 250	1:1
D1_v2 - D15_v2	210 - 250*	1:1
DS1 - DS14	160 - 250	1:1
DS1_v2 - DS15_v2	210 - 250*	1:1
D_v3	160 - 190*	2:1***
Ds_v3	160 - 190*	2:1***
E_v3	160 - 190*	2:1***
Es_v3	160 - 190*	2:1***
F2s_v2 - F72s_v2	195 - 210*	2:1***
F1 - F16	210 - 250*	1:1
F1s - F16s	210 - 250*	1:1
G1 - G5	180 - 240*	1:1
GS1 - GS5	180 - 240*	1:1
H	290 - 300*	1:1

# Azure Virtual Machines

	General Purpose	Compute Optimized	Memory Optimized	Storage Optimized	GPU	High Performance Compute
Type	DC, Av2, Dv2, Dv3, B, Dsv3	Fsv2, F	M, Dv2, G, Dsv2, GS, Ev3	Ls	NC, NCv2, ND, BV, NVv2	H
Description	Balanced CPU and memory	High ratio of compute to memory	High ratio of memory to compute	High disk throughput and IO	Specialized with single or multiple NVIDIA GPUs	High memory and compute power – fastest and most powerful
Uses	Testing and dev, small-med databases, low traffic web servers	Medium traffic web servers, network appliances, batch processing, app servers	Relational database services, analytics, and larger caches	Big Data, SQL, NoSQL databases	Compute intensive, graphics-intensive, and visualization workloads	Batch processing, analytics, molecular modeling, and fluid dynamics, low latency RDMA networking

# Standard vs. Premium Storage Disks

Standard Disks	Premium Disks
Backed by cost-effective HDDs	Backed by high-speed SSDs
Stored in Azure storage account	IOPS values are predictable, expected performance levels
Standard SSD (Preview) available for managed disks (dev/test/entry level production applications)	Pre-pay for all storage used (fixed disk sizes P10, 128 GB, 500 IOPs, 50 MB/sec
Standard storage provides maximum IOPS values for each VHD	

# Managed vs. Unmanaged Disks

Unmanaged Disks	Managed Disks
Original method to store VM VHDs	Azure manages the disks, so you don't have to worry about storage account level IOPS restrictions
VHDs stored as page blobs in an Azure storage account	Pre-pay for disk size (no need for SA) S10, 128 GB, 500 IOPS, 60 MB/sec
Maximum 256 TB of storage per VM	Supports Standard and Premium SSD and Standard HDD
You need to manage storage account availability	
20,000 IOPS limit across all VM disks in a standard storage account	

# Ultra SSD – the next generation of Azure Disks technology

## Ultra SSD

supported VM types will be limited

Ultra SSD Disks come in several fixed sizes from 4 GiB up to 64 TiB and feature a flexible performance configuration model that allows you to independently configure IOPS and throughput.

Ultra SSDs support IOPS limits of 300 IOPS/GiB, up to a maximum of 160K IOPS per disk. To achieve the IOPS that you provisioned, ensure that the selected Disk IOPS is less than the VM IOPS.

With Ultra SSD Disks, the throughput limit of a single disk is 256 KiB/s for each provisioned IOPS, up to a maximum of 2000 MBps per disk (where MBps =  $10^6$  Bytes per second).

# Azure Ultra SSD


## Ultra SSD Managed Disk Offerings

<b>Disk size (GiB)</b>	4	8	16	32	64	128	256	512	1,024-65,536 (in increments of 1 TiB)
<b>IOPS range</b>	100-1,200	100-2,400	100-4,800	100-9,600	100-19,200	100-38,400	100-76,800	100-153,600	100-160,000
<b>Throughput Cap (MBps)</b>	300	600	1,200	2,000	2,000	2,000	2,000	2,000	2,000

# Planning High Availability



Availability Sets



Availability Zones




Region Pairs

Blast Radius

Feature	Capability / Provide
Availability Sets	High-availability <b>protection from hardware, network, and power failures in a DC</b>
Availability Zones	High-availability <b>protection</b> against the <b>loss of entire DC(s)</b>
Region pairs	Disaster Recovery that <b>protects from the loss of an entire region</b>


# Availability Sets

- %99.95 Availability SLA with Availability set
- Must be configured at VM Deployment
- Otherwise %99.9 single instance SLA with Premium storage






# Availability Zone



<http://aka.ms/azoverview>

# Supported Linux Distributions in Azure



<https://docs.microsoft.com/en-us/azure/virtual-machines/linux/endorsed-distros>

# Azure Deployment Tools

Azure Portal

Azure Cloud Shell

Azure Powershell

Azure CLI v2.0

Azure SDKs

ARM Templates

# Demo

- Deploy a Linux VM in Azure
- Deploy a Windows VM in Azure with Visual Studio



# Demo

Connect Windows VM via Serial

# Azure VM Disk Types

OS Disk	Data Disk	Temporary Disk
Generation 1 .VHD	# dependent on VM instance size	D: or /dev/sdb1
Registered as SATA drive	Registered as SCSI disk	Bound to the hardware host
Max capacity 2 TB	Max capacity 4 TB	Do not store permanent data!

<https://docs.microsoft.com/en-us/azure/virtual-machines/linux/disks-types>

<https://docs.microsoft.com/en-us/azure/virtual-machines/windows/disks-types>

# Demo

- Add Data Disk to VM

# Demo

- Deploy VM from Existing Managed Disk



# Demo

- Extend the Managed Disk

# Demo

- Convert to Managed Disk

# Demo

- Azure Disk Encryption



# Move Azure Resources

<https://docs.microsoft.com/en-us/azure/azure-resource-manager/resource-group-move-resources>



Demo

Move Azure Resources




# Virtual Machine Scale Set

Azure Champ



# Azure Virtual Machine Scale Set

- Control it like IaaS, scale it like PaaS





# Demo

## Azure Virtual Machine Scale Test





# Microsoft Identity

Azure Champ




# Terminology

<https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/active-directory-what-is>

Azure subscription	Used to pay for Azure cloud services. You can have many subscriptions and they're linked to a credit card.
Azure tenant	A dedicated and trusted instance of Azure AD that's automatically created when your organization signs up for a Microsoft cloud service subscription, such as Microsoft Azure, Microsoft Intune, or Office 365. An Azure tenant represents a single organization.
Azure AD directory	Each Azure tenant has a dedicated and trusted Azure AD directory. The Azure AD directory includes the tenant's users, groups, and apps and is used to perform identity and access management functions for tenant resources.
Custom domain	Every new Azure AD directory comes with an initial domain name, domainname.onmicrosoft.com. In addition to that initial name, you can also add your organization's domain names, which include the names you use to do business and your users use to access your organization's resources, to the list. Adding custom domain names helps you to create user names that are familiar to your users, such as alain@contoso.com.


# Microsoft Identity



<https://docs.microsoft.com/en-us/office365/enterprise/microsoft-cloud-it-architecture-resources>

# Cloud-based Identity as a Service (IDaaS)

---



## 1 Security principal



User



Group



Service  
principal



Managed  
identity


- A security principal is an object that represents a user, group, service principal, or managed identity that is requesting access to Azure resources.

# Security Principal




# Scope

---


## 3 Scope



# (RBAC) for Azure resources

		Role			
		Reader	Resource-specific or custom role	Contributor	Owner
Scope	 Subscription	Observers	Users managing resources		Admins
	 Resource group				
	 Resource	Automated processes			

# Management Groups









Demo

IAM in Resources



# Azure Blob Storage

Azure Champ



# Azure Storage Accounts

- Storage Account is parent container for storage types.

**Blob Storage**  
Object and Disk  
Storage

**File Storage**  
SMB File Shares

**Table Storage**  
NoSQL Data Store

**Queue  
Storage**  
Message Based

# Azure Storage Account Links

- [http://mystorageaccount.\*\*blob\*\*.core.windows.net](http://mystorageaccount.blob.core.windows.net)
- [http://mystorageaccount.\*\*file\*\*.core.windows.net](http://mystorageaccount.file.core.windows.net)
- [http://mystorageaccount.\*\*table\*\*.core.windows.net](http://mystorageaccount.table.core.windows.net)
- [http://mystorageaccount.\*\*queue\*\*.core.windows.net](http://mystorageaccount.queue.core.windows.net)

# Storage HA Levels

- Locally redundant storage (LRS): Low-cost data redundancy for Azure Storage

Locally redundant storage (LRS) provides at least 99.999999999% (11 nines) durability of objects over a given year. LRS provides this object durability by replicating your data to a storage scale unit.

<https://docs.microsoft.com/en-us/azure/storage/common/storage-redundancy-lrs?toc=%2fazure%2fstorage%2fblobs%2ftoc.json>

# Storage HA Levels

- Zone-redundant storage (ZRS): Highly available Azure Storage applications

Zone-redundant storage (ZRS) replicates your data synchronously across three storage clusters in a single region. Each storage cluster is physically separated from the others and is located in its own availability zone (AZ).

<https://docs.microsoft.com/en-us/azure/storage/common/storage-redundancy-zrs?toc=%2fazure%2fstorage%2fblobs%2ftoc.json>

# Storage HA Levels

- Geo-redundant storage (GRS): Cross-regional replication for Azure Storage

Geo-redundant storage (GRS) is designed to provide at least 99.999999999999999% (16 9's) durability of objects over a given year by replicating your data to a secondary region that is hundreds of miles away from the primary region. If your storage account has GRS enabled, then your data is durable even in the case of a complete regional outage or a disaster in which the primary region isn't recoverable.

<https://docs.microsoft.com/en-us/azure/storage/common/storage-redundancy-grs?toc=%2fazure%2fstorage%2fblobs%2ftoc.json>

# Storage HA Levels

- Read-access geo-redundant storage (RA-GRS) is based on GRS. RA-GRS replicates your data to another data center in a secondary region, and also provides you with the option to read from the secondary region.

<https://docs.microsoft.com/en-us/azure/storage/common/storage-redundancy-grs?toc=%2fazure%2fstorage%2fblobs%2ftoc.json>



# What is the RPO and RTO with GRS?

- The RPO indicates the point in time to which data can be recovered. Azure Storage typically has an RPO of less than 15 minutes, although there's currently no SLA on how long geo-replication takes.
- **Recovery Time Objective (RTO):** The RTO is a measure of how long it takes to perform the failover and get the storage account back online. The time to perform the failover includes the following actions:
  - The time until the customer initiates the failover of the storage account from the primary to the secondary region.
  - The time required by Azure to perform the failover by changing the primary DNS entries to point to the secondary location.

<https://docs.microsoft.com/en-us/azure/storage/common/storage-redundancy-grs?toc=%2fazure%2fstorage%2fblobs%2ftoc.json>

# Azure Storage Account Types



General Purpose v1

Blob

General Purpose v2

# Azure Storage Account Limits

- <https://docs.microsoft.com/en-us/azure/storage/common/storage-scalability-targets>

Contact Azure Support if you need more!

# Azure Storage Blob Service

- BLOB (Binary Large Object)
  - File, document, image, video, VM Disk, database etc.

<https://docs.microsoft.com/en-us/rest/api/storageservices/understanding-block-blobs--append-blobs--and-page-blobs>

# Blob Types




## Block Blob

- Block blobs are comprised of blocks
- Each of which is identified by a block ID
- Each block can be a different size, up to a maximum of 100 MB
- Block blob can include up to 50,000 blocks
- Insert, replace, delete blocks supported
- MAX 4.77 TB



## Append Blob

- is optimized for append operations
- blocks are added to the end of the blob only
- Updating or deleting of existing blocks is not supported
- append blob does not expose its block IDs.
- Each block in an append blob can be a different size, up to a maximum of 4 MB
- Ideal for logging, auditing
- MAX 195 GB



## Page Blob

- collection of 512-byte pages optimized for random read and write operations
- Azure virtual machine disks are backed by page blobs
- Azure offers two types of durable disk storage: premium and standard
- MAX 8TB

# Azure Storage Pricing

Data Storage (Capacity)

Data Operations

Output Data Transfer

Geo-Replication Data Transfer

# Blob Storage Tiers

Hot Storage Tier

Highest Storage Cost  
Lowest Data Access Cost


Cool Storage Tier

Higher Data Access Cost  
Lower storage cost

Archive Storage Tier

Lowest storage cost  
Highest data retrieval cost  
Data is offline

# Blob Containers





# Public Access Level Container

- Private Access Level (by default)  
Requires Authentication
- Public read access for blobs only: Blobs within the container can be read by anonymous request, but container data is not available. Anonymous clients cannot enumerate the blobs within the container.
- Full public read access: All container and blob data can be read by anonymous request. Clients can enumerate blobs within the container by anonymous request, but cannot enumerate containers within the storage account.

<https://docs.microsoft.com/en-us/azure/storage/blobs/storage-manage-access-to-resources>



# Demo

Create a Storage Account from portal

# Demo

Create a Storage Account from command line



# Demo

Blob properties and create blob snapshot