





PACKAGING INFORMATION




Size in cm: Lenght: 35 - Widht: 23 - Heigth: 35.5

Code	Description	Pcs/pallet
BH30/504/HS	Electromechanical HIGH SPEED BRUSHLESS motor, low voltage, super intensive use, with native encoder onboard, irreversible ideal for sliding gates up to 500 Kg. with built-in digital controller B70 series, magnetic limit switch.	44

Product technical specifications	BH30/504/HS	
Max gate weight	500 kg	
Power line supply	230V AC - 50Hz	
Motor power supply	24V	
Power rating	130W	
Frequency of use	Intensive use	
Thrust	50 - 400N	
Operating temperature	-20+55°C	
Protection level	IP43	
Reductor Type	Irreversible	
Manoeuvre speed	24 m/min (0.4 m/s)	
Limit switch	Magnetic	
Onboard control unit	B70/1DC	
Encoder	Digital native encoder + magnetic digital SENSORED, 4096 PPR	
Batteries recovery	Optional 2 internal battery 12V 1,2AH - Optional 2 external battery 12V 4,5AH	
Type exit gear	Z15/mod 4	
Operating cycles per day (opening/closing - 24 hours no stop)	800	
Maximum dimension product in mm (L x W x H)	315 x 165,8 x 329	
Product weight packed (Kg)	11,9	



PRODUCT DIMENSIONS AND PREPARING FOR INSTALLATION



B Rack

B Fixing plate

DIMENSIONS

PREDISPOSITION FOR STANDARD INSTALLATION

PRODUCT ACCESSORIES



B71/BC
Batteries charger for brushless digital controller B70/1DC.



BT12V12 Pair of batteries 12V 1.2 Ah.



BT12V45 Pair of batteries 12V 4.5 Ah.



KT214
Fixing plate with stay
bolts and screws H30
series.



K1214/SC Adapter plate with stay bolts and screws H30 series.



KT221 Raised fixing plate for H30 series (+3,5 cm).



HT418 External box without batteries, for battery BT12V45 (12V DC 4,5 Ah)



GA550 Galvanised steel rack 22x22x1000 module 4.



GA551
Galvanised steel rack
30x12x1000 module 4
with spacers and screws.



GA553 Nylon rack module 4 with 6 connectors L.1000.



GA554 Pocket of 6 spacers (2,5 Cm) and screws.



MC775
Kit magnetic limit switch
for control unit
H70/103AC, H70/104AC,
B70/1DC, B70/1DCHP.



R99/C/001 Signboard Automatic Opening".