

CMPT 379

Compilers

Anoop Sarkar

<http://www.cs.sfu.ca/~anoop>

11/1/11

1

Run-time Support

- Tracking variable usage is done using activation or liveness analysis
- Functions or procedures have more complex activation behaviour
- Problem: functions can be recursive
- This means each function activation has to keep its locals and parameters distinct

11/1/11

2


Activation Trees

- An activation of a function is a particular invocation of that function
- Each activation will have particular values for the function parameters
- Each activation can call another activation before it becomes inactive
- The sequence of function calls can be represented as an *activation tree*

11/1/11

3

Activation Tree



11/1/11

4

Problems with Functions

- Recursive functions
- If a function has local variables, and if it calls another function: what happens to locals after control returns
- Function can access non-local (global) variables
- Parameter passing into a function

11/1/11

5

More problems

- Can we pass functions as parameters?
- Can functions be returned as the result of a function?
- Storage allocation within a function
- Is de-allocation to be done by the programmer before leaving the function
- Dangling pointers

11/1/11

6

Activation Records

- Information for a single execution of a function is called an *activation record* or *procedure call frame*
- A frame contains:
 - Temporary local register values for caller
 - Local data
 - Snapshot of machine state (important registers)
 - Return address
 - Link to global data
 - Parameters passed to function
 - Return value for the caller

11/1/11

7

Storage Allocation for Functions

- Static Allocation
 - Layout all storage for all data objects at compile time
 - Essentially every variable is stored globally
 - But the symbol table can still control local activation and de-activation of variables
 - Very restricted recursion is allowed
 - Fortran 77

11/1/11

8

Storage Allocation for Functions

- Stack Allocation ✓
 - Storage for recursive functions is organized as a stack: last-in first-out (LIFO) order
 - Activation records are associated with each function activation
 - Activation records are pushed onto the stack when a call is made to the function
 - Size of activation records can be fixed or variable

11/1/11

9

Storage Allocation for Functions

- Stack Allocation ✓
 - Sometimes a minimum size is required
 - Variable length data is handled using pointers
 - Locals are deleted after activation ends
 - Caller locals are reinstated and execution continues
 - C, Pascal and most modern programming languages

11/1/11

10

Storage Allocation for Functions

- Heap Allocation
 - In some special cases stack allocation is not possible
 - If local variables must be retained after the activation ends
 - If called activation outlives the caller
 - Anything that violates the last-in first-out nature of stack allocation e.g. closures in Lisp and other functional PLs

11/1/11

11

Heap Allocation

```

class Ret {
  int a; a = 10;
  fun foo (int m) {
    int addm (int n) { return (a+m+n); }
    return addm;
  }
  int main() {
    callout("print_int", (foo(2))(3));
  }
}

```

11/1/11

12

Storage Allocation for Functions

- Function Composition: $(f \bullet g)(x) = f(g(x))$

```
class Compose {
  fun sq (int x) { return (x * x); }
  fun f (fun m) { return (m•h); }
  fun h () { return sq; }
  fun g (fun z) { return (sq•z); }
  int main() {
    fun v = g•h;
    callout("print_int", (v())(3));
  }
}
```

11/1/11

13

Storage Allocation for Functions


- Function Composition: $(f \bullet g)(x) = f(g(x))$

class Compose {	$v = g \bullet h$
fun sq (int x) { return (x * x); }	$v() = (g \bullet h)()$
fun f (fun m) { return (m•h); }	$v() = g(h())$
fun h () { return sq; }	$v() = g(sq)$
fun g (fun z) { return (sq•z); }	$v() = (sq \bullet sq)$
int main() {	$v()(3) = (sq \bullet sq)(3)$
fun v = g•h;	$v()(3) = (sq(sq(3)))$
callout("print_int", (v())(3));	
}	
}	


11/1/11

14


Run-time Memory




Stack frame



Example: MIPS stack frame



Stack frame




```
#include <stdio.h>

main ()
{
    int n = 10;
    printf("The factorial of 10 is %d\n", fact(n));
}

int fact (int n)
{
    if (n < 1)
        return(1);
    else
        return(n * fact(n - 1));
}
```

11/1/11

19



11/1/11

20

Parameter Passing Conventions

- Differences based on:
 - The parameter represents an r-value (the rhs of an expr)
 - An l-value
 - Or the text of the parameter itself
- Call by Value
 - Each parameter is evaluated
 - Pass the r-value to the function
 - No side-effect on the parameter

11/1/11

21

Parameter Passing Conventions

- Call by Reference
 - Also called call by address/location
 - If the parameter is a name or expr that is an l-value then pass the l-value
 - Else create a new temporary l-value and pass that
 - Typical example: passing array elements `a[i]`

11/1/11

22

Parameter Passing Conventions

- Copy Restore Linkage
 - Pass only r-values to the called function (but keep the l-value around for those parameters that have it)
 - When control returns back, take the r-values and copy it into the l-values for the parameters that have it
 - Fortran
- Call by Name
 - Function is treated like a macro (a #define) or in-line expansion
 - The parameters are literally re-written as passed arguments (keep caller variables distinct by renaming)

11/1/11

23

Parameter Passing Conventions

- Lazy evaluation
 - In some languages, call-by-name is accomplished by sending a function (also called a thunk) instead of an r-value
 - When the r-value is needed the function is called with zero arguments to produce the r-value
 - This avoids the time-consuming evaluation of r-values which may or may not be used by the called function (especially when you consider short-circuit evaluation)
 - Used in lazy functional languages

11/1/11

24

Parameter Passing Conventions

- Call-by-need
 - Similar to lazy evaluation, but more efficient
 - To avoid executing similar r-values multiple times, some languages used a memo slot to avoid repeated function evaluations
 - A function parameter is only evaluated when used inside the called function
 - When used multiple times there is no overhead due to the memo table
 - Haskell

11/1/11

25

Summary

- Run-time support for functions
- Dealing with (potentially infinite) recursion
- Activation records for each function invocation
- Storage allocation for activation records in recursive function calls
- Stack allocation is easiest to implement while retaining recursion
- Functional PLs use heap allocation

11/1/11

26