

CMPT 379

Compilers

Anoop Sarkar

<http://www.cs.sfu.ca/~anoop>

NFA to DFA Complexity Analysis


NFA to DFA

- Subset construction converts NFA to DFA
- Complexity:
 - For FSAs, we measure complexity in terms of initial cost (creating the automaton) and per string cost
 - Let r be the length of the regexp and n be the length of the input string
 - NFA, Initial cost: $O(r)$; Per string: $O(rn)$
 - DFA, Initial cost: $O(r^2s)$; Per string: $O(n)$
 - DFA, common case, $s = r$, but worst case $s = 2^r$


NFA to DFA

- A regexp of size r can become a 2^r state DFA, an exponential increase in complexity
 - Try the subset construction on NFA built for the regexp $\mathbf{A^*aA^{n-1}}$ where \mathbf{A} is the regexp $\mathbf{(a|b)}$
- Note that the NFA for regexp of size r will have r states
- Minimization can reduce the number of states
- But minimization requires determinization



NFA to DFA



NFA to DFA



NFA to DFA



NFA vs. DFA in the wild

Engine Type	Programs
DFA	<i>awk</i> (most versions), <i>egrep</i> (most versions), <i>flex</i> , <i>lex</i> , MySQL, Procmail
Traditional NFA	GNU <i>Emacs</i> , Java, <i>grep</i> (most versions), <i>less</i> , <i>more</i> , .NET languages, PCRE library, Perl, PHP (pcre routines), Python, Ruby, <i>sed</i> (most versions), vi
POSIX NFA	<i>mawk</i> , MKS utilities, GNU <i>Emacs</i> (when requested)
Hybrid NFA/DFA	GNU <i>awk</i> , GNU <i>grep/egrep</i> , Tcl

Extensions to Regular Expressions

- Most modern regexp implementations provide extensions:
 - matching groups; `\1` refers to the string matched by the first grouping `()`, `\2` to the second match, etc.,
 - e.g. `([a-z]+)\1` which matches `abab` where `\1=ab`
 - match and replace operations,
 - e.g. `s/([a-z]+)/\1\1/g` which changes `ab` into `abab` where `\1=ab`
- These extensions are no longer “regular”. In fact, extended regexp matching is NP-hard
 - Extended regular expressions (including POSIX and Perl) are called REGEX to distinguish from regexp (which *are* regular)
- In order to capture these difficult cases, the algorithms used even for simple regexp matching run in time exponential in the length of the input