

CMPT-825

Natural Language Processing

Anoop Sarkar

<http://www.cs.sfu.ca/~anoop>

Grammar Development: Inflectional morphology

- Write an NFA for the following data such that each suffix type gets a single transition (e.g. adding an -s is the plural suffix):

cat cats

dog dogs

fox foxes

mouse mice

- Note that `foxes` is not an isolated case (irregular), e.g. `suffix`,
`suffixes`

Grammar Development: Derivational morphology

- Write an NFA for the following data (ignore the parts of speech, also you can use substrings on the transitions, e.g. a transition can have demon on it):

demon/N demon+ize/V

demon+ize+ation/N demon+ize+able/A

demon+ize+er/N

formal/A formal+ity/N

formal+ness/N

Grammar Development: Derivational morphology

- Does your NFA accept the following additional strings (ignore the parts of speech). If not, what do you need to add to your previous NFA?

formal+ize/V formal+ize+ation/N

formal+ize+able/A formal+ize+er/N


demon+ize+able+ity/N

Dealing with foxes: Finite-state transducers


- $a : 0$ is notation for a map between two alphabets: Σ_1 and Σ_2
- FSTs accept pairs of strings. Language accepted by an FST:
 $L \subseteq (\Sigma_1^*, \Sigma_2^*)$

Dealing with foxes: Finite-state transducers

- FST for $(ab, 00), (aa, 0)$




- FST for $(\epsilon, \epsilon), (ab, 01), (abab, 0101), \dots$



Dealing with foxes: Finite-state transducers

- Draw FST for (ϵ, ϵ) , $(ab, 00)$, $(ab, 01)$, $(ab, 10)$, $(ab, 11)$, $(abab, 0000)$, \dots



Finite-state Transducers

- The mystery transducer: what does it do?

Morphological Parsing with Transducers

- Simpler to start by thinking of it as generation
- Start with `cat +N +PL` and then use a FST to produce `cats`
- Advantage: since we can add/delete material, we can handle `fox +N +PL` to get the correct form `foxes`
- To deal with orthographic rules (like the one above), J&M provide an analysis which is made very modular with the use of an intermediate FST

Morphological Parsing with Transducers

- Draw a transducer for the following examples:

| Input | Output | Input | Output |
|------------|--------|------------|--------|
| cat+N+PL | cat^s# | cat+N+SG | cat# |
| dog+N+PL | dog^s# | dog+N+SG | dog# |
| fox+N+PL | fox^s# | fox+N+SG | fox# |
| mouse+N+PL | mice# | mouse+N+SG | mouse# |

Morphological Parsing with Transducers

- A transducer for the *e*-insertion rule
if word ends in $x^{\wedge}s\#$ then output xes ; similarly for $z^{\wedge}\#$ and $s^{\wedge}\#$
note the use of the intermediate output from the previous transducer
define `other = [a-r, t-w, y]`

| Input | Inter. | Output | Input | Inter. | Output |
|-----------------------|---------------------|--------------|-----------------------|-------------------|------------|
| <code>cat+N+PL</code> | <code>cat^s#</code> | <i>cats</i> | <code>cat+N+SG</code> | <code>cat#</code> | <i>cat</i> |
| <code>fox+N+PL</code> | <code>fox^s#</code> | <i>foxes</i> | <code>fox+N+SG</code> | <code>fox#</code> | <i>fox</i> |

Ambiguity when Parsing with FSTs

- Global ambiguity:

foxes \rightarrow *f**ox*+N+PL OR *foxes*+V+3SG

I saw two foxes yesterday

That trickster foxes me every time

- Local ambiguity:

assess has a prefix string which can be analyzed:

ass+N+PL \rightarrow *asses*

- An FST will return the two answers in the first case, but only return one answer in the second case (even though it will consider a false analysis partway through the string)

Deterministic vs. Non-deterministic

- Deterministic transducers are called **subsequential** transducers (no backtracking when translating one string to another)
- Deterministic transducers where all the states are final states are called **sequential** transducers.

Porter Stemmer

- Unlike our previous FSTs, the Porter Stemmer has no stems
This makes the FST much smaller as a result – leading to a simple implementation (available widely on the web in many programming languages)
- *ational* → *ate*
ing → ϵ if stem contains vowel (e.g. motoring, motor)
- Performs well enough most of the time, but suffers from problems that the FSTs we saw earlier do not have: *organization* → *organ*
Still, it is used often for quick and dirty stemming in many NLP applications due to its simplicity and speed

FST Software in Research and Industry

- FSTs are used for many applications in NLP: morphology, stemming, segmentation
- FST software:

Van Noord fsa

URL:<http://odur.let.rug.nl/~Evannoord/Fsa/>

AT&T fsm toolkit

URL:<http://www.research.att.com/sw/tools/fsm/>

Xerox LinguistX

URL:<http://www.inxight.com/products/oem/linguistx/>

Teragram

URL:<http://www.teragram.com/>

- FSTs are also widely used in aligning sequences in genomics