

# CMPT 379

## Compilers

Anoop Sarkar

<http://www.cs.sfu.ca/~anoop>

10/18/10

1

## Parsing - Roadmap

- Parser:
  - decision procedure: builds a parse tree
- Top-down vs. bottom-up
- LL(1) – Deterministic Parsing
  - recursive-descent
  - table-driven
- LR(k) – Deterministic Parsing
  - LR(0), SLR(1), LR(1), LALR(1)
- Parsing arbitrary CFGs – Polynomial time parsing

10/18/10

2

# Top-Down vs. Bottom Up

Grammar:  $S \rightarrow A B$       Input String: ccbca  
 $A \rightarrow c \mid \epsilon$   
 $B \rightarrow cbB \mid ca$

Top-Down/leftmost		Bottom-Up/rightmost	
$S \Rightarrow AB$	$S \rightarrow AB$	$ccbca \Leftarrow Acbca$	$A \rightarrow c$
$\Rightarrow cB$	$A \rightarrow c$	$\Leftarrow AcbB$	$B \rightarrow ca$
$\Rightarrow ccbB$	$B \rightarrow cbB$	$\Leftarrow AB$	$B \rightarrow cbB$
$\Rightarrow ccbca$	$B \rightarrow ca$	$\Leftarrow S$	$S \rightarrow AB$

10/18/10

3

## Top-Down: Backtracking

$S \rightarrow A B$   
 $A \rightarrow c \mid \epsilon$   
 $B \rightarrow cbB \mid ca$

True/False  
 $S \Rightarrow^* cbca?$

S	cbca	try $S \rightarrow AB$
AB	cbca	try $A \rightarrow c$
cB	cbca	match c
B	bca	dead-end, try $A \rightarrow \epsilon$
$\epsilon B$	cbca	try $B \rightarrow cbB$
cbB	cbca	match c
bB	bca	match b
B	ca	try $B \rightarrow cbB$
cbB	ca	match c
bB	a	dead-end, try $B \rightarrow ca$
ca	ca	match c
a	a	match a, Done!

10/18/10



4

# Backtracking

$S \rightarrow cAd \mid c$   
 $A \rightarrow a \mid ad$

Input: cad

$S \rightarrow cAd \mid c$   
 $A \rightarrow ad \mid a$




10/1 For some grammars, rule ordering is crucial for backtracking parsers, e.g  $S \rightarrow aSa$ ,  $S \rightarrow aa$


5

## Transition Diagram


$S \rightarrow cAa$



$A \rightarrow cB \mid B$



$B \rightarrow bcB \mid \epsilon$



10/18/10

6

# Predictive Top-Down Parser

- Knows which production to choose based on single lookahead symbol
- Need LL(1) grammars
  - First L: reads input Left to right
  - Second L: produce Leftmost derivation
  - 1: one symbol of lookahead
- Can't have left-recursion
- Must be left-factored (no left-factors)
- Not all grammars can be made LL(1)

10/18/10

7

## Leftmost derivation for **id + id \* id**

$E \rightarrow E + E$	$E \Rightarrow E + E$
$E \rightarrow E * E$	$\Rightarrow \mathbf{id} + E$
$E \rightarrow ( E )$	$\Rightarrow \mathbf{id} + E * E$
$E \rightarrow - E$	$\Rightarrow \mathbf{id} + \mathbf{id} * E$
$E \rightarrow \mathbf{id}$	$\Rightarrow \mathbf{id} + \mathbf{id} * \mathbf{id}$

$E \Rightarrow_{\text{lm}}^* \mathbf{id} + E * E$

10/18/10

8

# Predictive Parsing Table

Productions	
1	$T \rightarrow F T'$
2	$T' \rightarrow \epsilon$
3	$T' \rightarrow * F T'$
4	$F \rightarrow id$
5	$F \rightarrow ( T )$

	*	(	)	id	\$
T		$T \rightarrow F T'$		$T \rightarrow F T'$	
T'	$T' \rightarrow * F T'$		$T' \rightarrow \epsilon$		$T' \rightarrow \epsilon$
F		$F \rightarrow ( T )$		$F \rightarrow id$	

10/18/10

9

Trace “(id)\*id”

	*	(	)	id	\$
T		$T \rightarrow FT'$		$T \rightarrow FT'$	
T'	$T' \rightarrow *FT'$		$T' \rightarrow \epsilon$		$T' \rightarrow \epsilon$
F		$F \rightarrow (T)$		$F \rightarrow id$	

Stack	Input	Output
\$T	(id)*id\$	
\$T'F	(id)*id\$	$T \rightarrow F T'$
\$T')T(	(id)*id\$	$F \rightarrow ( T )$
\$T')T	id)*id\$	
\$T')T'F	id)*id\$	$T \rightarrow F T'$
\$T')T'id	id)*id\$	$F \rightarrow id$
\$T')T'	)*id\$	
\$T')	)*id\$	$T' \rightarrow \epsilon$

10/18/10

10

Trace “(id)\*id”

	*	(	)	id	\$
T		$T \rightarrow FT'$		$T \rightarrow FT'$	
T'	$T' \rightarrow *FT'$		$T' \rightarrow \epsilon$		$T' \rightarrow \epsilon$
F		$F \rightarrow (T)$		$F \rightarrow id$	

Stack	Input	Output
\$T'	*id\$	
\$T'F*	*id\$	$T' \rightarrow *FT'$
\$T'F	id\$	
\$T'id	id\$	$F \rightarrow id$
\$T'	\$	
\$	\$	$T' \rightarrow \epsilon$

10/18/10

11

## Table-Driven Parsing

```

stack.push($); stack.push(S);
a = input.read();
forever do begin
    X = stack.peek();
    if X = a and a = $ then return SUCCESS;
    elseif X = a and a != $ then
        pop X; a = input.read();
    elseif X != a and X ∈ N and M[X,a] then
        pop X; push right-hand side of M[X,a];
    else ERROR!
end

```

10/18/10

12

# Predictive Parsing table

- Given a grammar produce the predictive parsing table
- We need to know for all rules  $A \rightarrow \alpha \mid \beta$  the lookahead symbol
- Based on the lookahead symbol the table can be used to pick which rule to push onto the stack
- This can be done using two sets: FIRST and FOLLOW

10/18/10

13

## FIRST and FOLLOW

$a \in \text{FIRST}(\alpha)$  if  $\alpha \Rightarrow^* a\beta$

if  $\alpha \Rightarrow^* \epsilon$  then  $\epsilon \in \text{FIRST}(\alpha)$

$a \in \text{FOLLOW}(A)$  if  $S \Rightarrow^* \alpha A a \beta$

$a \in \text{FOLLOW}(A)$  if  $S \Rightarrow^* \alpha A \gamma a \beta$

and  $\gamma \Rightarrow^* \epsilon$

10/18/10

14

# Conditions for LL(1)

- Necessary conditions:
  - no ambiguity
  - no left recursion
  - Left factored grammar
- A grammar G is LL(1) if - whenever  $A \rightarrow \alpha \mid \beta$ 
  1.  $\text{First}(\alpha) \cap \text{First}(\beta) = \emptyset$
  2.  $\alpha \Rightarrow^* \epsilon$  implies  $\neg(\beta \Rightarrow^* \epsilon)$
  3.  $\alpha \Rightarrow^* \epsilon$  implies  $\text{First}(\beta) \cap \text{Follow}(A) = \emptyset$

10/18/10

15

## ComputeFirst( $\alpha$ : string of symbols)

```
// assume  $\alpha = X_1 X_2 X_3 \dots X_n$ 
if  $X_1 \in T$  then  $\text{First}[\alpha] := \{X_1\}$ 
else begin
   $i := 1$ ;  $\text{First}[\alpha] := \text{ComputeFirst}(X_1) \setminus \{\epsilon\}$ ;
  while  $X_i \Rightarrow^* \epsilon$  do begin
    if  $i < n$  then
       $\text{First}[\alpha] := \text{First}[\alpha] \cup \text{ComputeFirst}(X_{i+1}) \setminus \{\epsilon\}$ ;
    else
       $\text{First}[\alpha] := \text{First}[\alpha] \cup \{\epsilon\}$ ;
     $i := i + 1$ ;
  end
end
```

10/18/10

16



## ComputeFirst( $\alpha$ : string of symbols)

```
// assume  $\alpha = X_1 X_2 X_3 \dots X_n$ 
if  $X_1 \in T$  then First[ $\alpha$ ] := { $X_1$ }
else begin
  i:=1; First[ $\alpha$ ] := ComputeFirst( $X_1$ )\{\epsilon\};
  while  $X_i \Rightarrow^* \epsilon$  do begin
    if  $i < n$  then
      First[ $\alpha$ ] := First[ $\alpha$ ]  $\cup$  ComputeFirst( $X_{i+1}$ )\{\epsilon\};
    else
      First[ $\alpha$ ] := First[ $\alpha$ ]  $\cup$  {\epsilon};
    i := i + 1;
  end
end
```

Recursion in computing FIRST causes problems when faced with recursive grammar rules

10/18/10

17

## ComputeFirst; modified

```
foreach  $X \in T$  do First[ $X$ ] := { $X$ };
foreach  $p \in P : X \rightarrow \epsilon$  do First[ $X$ ] := {\epsilon};
repeat foreach  $X \in N, p : X \rightarrow Y_1 Y_2 Y_3 \dots Y_n$  do
  begin i:=1;
    while  $Y_i \Rightarrow^* \epsilon$  and  $i \leq n$  do begin
      First[ $X$ ] := First[ $X$ ]  $\cup$  First[ $Y_i$ ]\{\epsilon\};
      i := i+1;
    end
    if  $i = n+1$  then First[ $X$ ] := First[ $X$ ]  $\cup$  {\epsilon};
  until no change in First[ $X$ ] for any  $X$ ;
```

10/18/10

18

## ComputeFirst; modified

```

foreach  $X \in T$  do  $\text{First}[X] := X$ ;
foreach  $p \in P : X \rightarrow \epsilon$  do  $\text{First}[X] := \{\epsilon\}$ ;
repeat foreach  $X \in N, p : X \rightarrow Y_1 Y_2 Y_3 \dots Y_n$  do
  begin  $i := 1$ ;
    while  $Y_i \Rightarrow^*$ 
       $\text{First}[X] := \text{First}[X] \cup \text{First}[Y_i]$ ;
       $i := i + 1$ ;
    end
  if  $i = n + 1$  then  $\text{First}[X] := \text{First}[X] \cup \{\epsilon\}$ ;
until no change in  $\text{First}[X]$  for any  $X$ ;

```

Non-recursive FIRST computation  
works with left-recursive grammars.  
Computes a fixed point for FIRST[X]  
for all non-terminals X in the grammar.  
But this algorithm is very inefficient.

10/18/10

19

## ComputeFollow

```

 $\text{Follow}(S) := \{\$ \}$ ;
repeat
  foreach  $p \in P$  do
    case  $p = A \rightarrow \alpha B \beta$  begin
       $\text{Follow}[B] := \text{Follow}[B] \cup \text{ComputeFirst}(\beta) \setminus \{\epsilon\}$ ;
      if  $\epsilon \in \text{First}(\beta)$  then
         $\text{Follow}[B] := \text{Follow}[B] \cup \text{Follow}[A]$ ;
      end
    case  $p = A \rightarrow \alpha B$ 
       $\text{Follow}[B] := \text{Follow}[B] \cup \text{Follow}[A]$ ;
until no change in any  $\text{Follow}[N]$ 

```

10/18/10

20

## Example First/Follow

$S \rightarrow AB$

$A \rightarrow c \mid \epsilon$

Not an LL(1) grammar

$B \rightarrow cbB \mid ca$

$\text{First}(A) = \{c, \epsilon\}$

$\text{Follow}(A) = \{c\}$

$\text{First}(B) = \{c\}$

$\text{Follow}(A) \cap$

$\text{First}(cbB) =$

$\text{First}(c) = \{c\}$

$\text{First}(ca) = \{c\}$

$\text{Follow}(B) = \{\$ \}$

$\text{First}(S) = \{c\}$

$\text{Follow}(S) = \{\$ \}$

10/18/10

21

## ComputeFirst on Left-recursive Grammars

- ComputeFirst as defined earlier loops on left-recursive grammars
- Here is an alternative algorithm for ComputeFirst
  1. Compute non left-recursive cases of FIRST
  2. Create a graph of recursive cases where FIRST of a non-terminal depends on another non-terminal
  3. Compute Strongly Connected Components (SCC)
  4. Compute FIRST starting from root of SCC to avoid cycles

## ComputeFirst on Left-recursive Grammars

- Each Strongly Connected Component can have recursion)
- But the connections between SCC means that (by defn) what we have now is a directed acyclic graph – hence without left recursion
- Unlike top-down LL parsing, bottom-up LR parsing allows left-recursive grammars, so this algorithm is useful for LR parsing

10/18/10

23

## ComputeFirst on Left-recursive Grammars

- $S \rightarrow BD \mid D$
- $D \rightarrow d \mid Sd$
- $A \rightarrow CB \mid a$
- $C \rightarrow Bb \mid \epsilon$
- $B \rightarrow Ab \mid b$


$\text{FIRST}_0[A] := \{a, b\}$

$\text{FIRST}_0[C] := \{\}$

$\text{FIRST}_0[B] := \{b\}$

$\text{FIRST}_0[S] := \{b, d\}$

$\text{FIRST}_0[D] := \{d\}$



Compute  
Strongly  
Connected  
Components

2 SCCs: e.g. consider B-A-C

$\text{FIRST}[B] := \text{FIRST}_0[B] + \text{FIRST}[A]$

$\text{FIRST}[A] := \text{FIRST}_0[A] + \text{FIRST}[C]$

$\text{FIRST}[C] := \text{FIRST}_0[C] + \text{FIRST}_0[B]$

$\text{FIRST}[C] := \text{FIRST}[C] + \{\epsilon\}$

10/18/10

24

## How to compute: Does $X \Rightarrow^* \epsilon$ ?

- The question 'Does  $X \Rightarrow^* \epsilon$  ?' can be written as the predicate: nullable(X)

```

Nullable = {} (set containing nullable non-terminals)
Changed = True
While (changed):
    changed = False
    if X is not in Nullable:
        if
            1.  $X \rightarrow \epsilon$  is in the grammar, or
            2.  $X \rightarrow Y_1 \dots Y_n$  is in the grammar and  $Y_i$  is in Nullable for all i
        then
            add X to Nullable; changed = True
    
```

10/18/10

25


## Converting to LL(1)

$S \rightarrow AB$

$A \rightarrow c \mid \epsilon$

$B \rightarrow cbB \mid ca$

Note that grammar  
is regular:  $c? (cb)^* ca$



same as:

$c c? (bc)^* a$

$S \rightarrow cAa$

$A \rightarrow cB \mid B$

$B \rightarrow bcB \mid \epsilon$

10/18/10

26

## Verifying LL(1) using F/F sets

$$S \rightarrow cAa$$

$$A \rightarrow cB \mid B$$

$$B \rightarrow bcB \mid \varepsilon$$

$$\text{First}(A) = \{b, c, \varepsilon\} \quad \text{Follow}(A) = \{a\}$$

$$\text{First}(B) = \{b, \varepsilon\} \quad \text{Follow}(B) = \{a\}$$

$$\text{First}(S) = \{c\} \quad \text{Follow}(S) = \{\$\}$$

10/18/10

27

## Building the Parse Table

- Compute First and Follow sets
- For each production  $A \rightarrow \alpha$ 
  - foreach  $a \in \text{First}(\alpha)$  add  $A \rightarrow \alpha$  to  $M[A, a]$
  - If  $\varepsilon \in \text{First}(\alpha)$  add  $A \rightarrow \alpha$  to  $M[A, b]$  for each  $b$  in  $\text{Follow}(A)$
  - If  $\varepsilon \in \text{First}(\alpha)$  add  $A \rightarrow \alpha$  to  $M[A, \$]$  if  $\$ \in \text{Follow}(\alpha)$
  - All undefined entries are errors

10/18/10

28

# Predictive Parsing Table

Productions	
1	$T \rightarrow F T'$
2	$T' \rightarrow \epsilon$
3	$T' \rightarrow * F T'$
4	$F \rightarrow \text{id}$
5	$F \rightarrow ( T )$

$\text{FIRST}(T) = \{\text{id}, (\}$   
 $\text{FIRST}(T') = \{*, \epsilon\}$   
 $\text{FIRST}(F) = \{\text{id}, (\}$

$\text{FOLLOW}(T) = \{\$, )\}$   
 $\text{FOLLOW}(T') = \{\$, )\}$   
 $\text{FOLLOW}(F) = \{*, \$, )\}$

	*	(	)	id	\$
T		$T \rightarrow F T'$		$T \rightarrow F T'$	
T'	$T' \rightarrow * F T'$		$T' \rightarrow \epsilon$		$T' \rightarrow \epsilon$
F		$F \rightarrow ( T )$		$F \rightarrow \text{id}$	

10/18/10

29

## Revisit conditions for LL(1)

- A grammar G is LL(1) iff - whenever  $A \rightarrow \alpha \mid \beta$ 
  1.  $\text{First}(\alpha) \cap \text{First}(\beta) = \emptyset$
  2.  $\alpha \Rightarrow^* \epsilon$  implies  $\neg(\beta \Rightarrow^* \epsilon)$
  3.  $\alpha \Rightarrow^* \epsilon$  implies  $\text{First}(\beta) \cap \text{Follow}(A) = \emptyset$
- No more than one entry per table field

10/18/10

30

# Error Handling

- Reporting & Recovery
  - Report as soon as possible
  - Suitable error messages
  - Resume after error
  - Avoid cascading errors
- Phrase-level vs. Panic-mode recovery

10/18/10

31

## Panic-Mode Recovery

- Skip tokens until *synchronizing set* is seen
  - Follow(A)
    - garbage or missing things after
  - Higher-level start symbols
  - First(A)
    - garbage before
  - Epsilon
    - if nullable
  - Pop/Insert terminal
    - “auto-insert”
- Add “synch” actions to table

10/18/10

32



# Summary so far

- LL(1) grammars, necessary conditions
  - No left recursion
  - Left-factored
- Not all languages can be generated by LL(1) grammar
- LL(1) – Parsing:  $O(n)$  time complexity
  - recursive-descent and table-driven predictive parsing
- LL(1) grammars can be parsed by simple predictive recursive-descent parser
  - Alternative: table-driven top-down parser