

CMPT 379

Compilers

Anoop Sarkar

<http://www.cs.sfu.ca/~anoop>

10/5/11

1

Parsing - Roadmap

- Parser:
 - decision procedure: builds a parse tree
- Top-down vs. bottom-up
- LL(1) – Deterministic Parsing
 - recursive-descent
 - table-driven
- LR(k) – Deterministic Parsing
 - LR(0), SLR(1), LR(1), LALR(1)
- Parsing arbitrary CFGs – Polynomial time parsing

10/5/11

2

Top-Down vs. Bottom Up

Grammar: $S \rightarrow AB$ Input String: ccbca
 $A \rightarrow c \mid \epsilon$
 $B \rightarrow cbB \mid ca$

Top-Down/leftmost		Bottom-Up/rightmost	
$S \Rightarrow AB$	$S \rightarrow AB$	$ccbca \Leftarrow Acbca$	$A \rightarrow c$
$\Rightarrow cB$	$A \rightarrow c$	$\Leftarrow AcbB$	$B \rightarrow ca$
$\Rightarrow ccbB$	$B \rightarrow cbB$	$\Leftarrow AB$	$B \rightarrow cbB$
$\Rightarrow ccbca$	$B \rightarrow ca$	$\Leftarrow S$	$S \rightarrow AB$

10/5/11

3

Top-Down: Backtracking

$S \rightarrow AB$
 $A \rightarrow c \mid \epsilon$
 $B \rightarrow cbB \mid ca$

True/False

$S \Rightarrow^* ccbca?$

S	cbca	try $S \rightarrow AB$
AB	cbca	try $A \rightarrow c$
cB	cbca	match c
B	bca	dead-end, try $A \rightarrow \epsilon$
ϵB	cbca	try $B \rightarrow cbB$
cbB	cbca	match c
bB	bca	match b
B	ca	try $B \rightarrow cbB$
cbB	ca	match c
bB	a	dead-end, try $B \rightarrow ca$
ca	ca	match c
a	a	match a, Done!

10/5/11



4

Backtracking

$S \rightarrow cAd \mid c$
 $A \rightarrow a \mid ad$

Input: cad

$S \rightarrow cAd \mid c$
 $A \rightarrow ad \mid a$



10/5 For some grammars, rule ordering is crucial for backtracking parsers, e.g $S \rightarrow aSa$, $S \rightarrow aa$


5

Transition Diagram


$S \rightarrow cAa$



$A \rightarrow cB \mid B$



$B \rightarrow bcB \mid \epsilon$



10/5/11

6

Predictive Top-Down Parser

- Knows which production to choose based on single lookahead symbol
- Need LL(1) grammars
 - First L: reads input Left to right
 - Second L: produce Leftmost derivation
 - 1: one symbol of lookahead
- Can't have left-recursion
- Must be left-factored (no left-factors)
- Not all grammars can be made LL(1)

10/5/11

7

Leftmost derivation for **id + id * id**

$E \rightarrow E + E$	$E \Rightarrow E + E$
$E \rightarrow E * E$	$\Rightarrow \mathbf{id} + E$
$E \rightarrow (E)$	$\Rightarrow \mathbf{id} + E * E$
$E \rightarrow - E$	$\Rightarrow \mathbf{id} + \mathbf{id} * E$
$E \rightarrow \mathbf{id}$	$\Rightarrow \mathbf{id} + \mathbf{id} * \mathbf{id}$

$$E \Rightarrow_{\text{lm}}^* \mathbf{id} + E * E$$

10/5/11

8

Predictive Parsing Table

Productions	
1	$T \rightarrow FT'$
2	$T' \rightarrow \epsilon$
3	$T' \rightarrow *FT'$
4	$F \rightarrow id$
5	$F \rightarrow (T)$

	*	()	id	\$
T		$T \rightarrow FT'$		$T \rightarrow FT'$	
T'	$T' \rightarrow *FT'$		$T' \rightarrow \epsilon$		$T' \rightarrow \epsilon$
F		$F \rightarrow (T)$		$F \rightarrow id$	

10/5/11

9

Trace “(id)*id”

	*	()	id	\$
T		$T \rightarrow FT'$		$T \rightarrow FT'$	
T'	$T' \rightarrow *FT'$		$T' \rightarrow \epsilon$		$T' \rightarrow \epsilon$
F		$F \rightarrow (T)$		$F \rightarrow id$	

Stack	Input	Output
\$T	(id)*id\$	
\$T'F	(id)*id\$	$T \rightarrow FT'$
\$T')T((id)*id\$	$F \rightarrow (T)$
\$T')T	id)*id\$	
\$T')T'F	id)*id\$	$T \rightarrow FT'$
\$T')T'id	id)*id\$	$F \rightarrow id$
\$T')T')*id\$	
\$T'))*id\$	$T' \rightarrow \epsilon$

10/5/11

10

Trace “(id)*id”

	*	()	id	\$
T		$T \rightarrow FT'$		$T \rightarrow FT'$	
T'	$T' \rightarrow *FT'$		$T' \rightarrow \epsilon$		$T' \rightarrow \epsilon$
F		$F \rightarrow (T)$		$F \rightarrow id$	

Stack	Input	Output
\$T'	*id\$	
\$T'F*	*id\$	$T' \rightarrow *FT'$
\$T'F	id\$	
\$T'id	id\$	$F \rightarrow id$
\$T'	\$	
\$	\$	$T' \rightarrow \epsilon$

10/5/11

11

Table-Driven Parsing

```

stack.push($); stack.push(S);
a = input.read();
forever do begin
  X = stack.peek();
  if X = a and a = $ then return SUCCESS;
  elseif X = a and a != $ then
    pop X; a = input.read();
  elseif X != a and X ∈ N and M[X,a] then
    pop X; push right-hand side of M[X,a];
  else ERROR!
end

```

10/5/11

12

Predictive Parsing table

- Given a grammar produce the predictive parsing table
- We need to know for all rules $A \rightarrow \alpha \mid \beta$ the lookahead symbol
- Based on the lookahead symbol the table can be used to pick which rule to push onto the stack
- This can be done using two sets: FIRST and FOLLOW

10/5/11

13

FIRST and FOLLOW

$a \in \text{FIRST}(\alpha)$ if $\alpha \Rightarrow^* a\beta$

if $\alpha \Rightarrow^* \epsilon$ then $\epsilon \in \text{FIRST}(\alpha)$

$a \in \text{FOLLOW}(A)$ if $S \Rightarrow^* \alpha A a \beta$

$a \in \text{FOLLOW}(A)$ if $S \Rightarrow^* \alpha A \gamma a \beta$

and $\gamma \Rightarrow^* \epsilon$

10/5/11

14

Conditions for LL(1)

- Necessary conditions:
 - no ambiguity
 - no left recursion
 - Left factored grammar
- A grammar G is LL(1) if - whenever $A \rightarrow \alpha \mid \beta$
 1. $\text{First}(\alpha) \cap \text{First}(\beta) = \emptyset$
 2. $\alpha \Rightarrow^* \epsilon$ implies $\neg(\beta \Rightarrow^* \epsilon)$
 3. $\alpha \Rightarrow^* \epsilon$ implies $\text{First}(\beta) \cap \text{Follow}(A) = \emptyset$

10/5/11

15

ComputeFirst(α : string of symbols)

```
// assume  $\alpha = X_1 X_2 X_3 \dots X_n$ 
if  $X_1 \in T$  then  $\text{First}[\alpha] := \{X_1\}$ 
else begin
   $i := 1$ ;  $\text{First}[\alpha] := \text{ComputeFirst}(X_1) \setminus \{\epsilon\}$ ;
  while  $X_i \Rightarrow^* \epsilon$  do begin
    if  $i < n$  then
       $\text{First}[\alpha] := \text{First}[\alpha] \cup \text{ComputeFirst}(X_{i+1}) \setminus \{\epsilon\}$ ;
    else
       $\text{First}[\alpha] := \text{First}[\alpha] \cup \{\epsilon\}$ ;
     $i := i + 1$ ;
  end
end
```

10/5/11

16

ComputeFirst(α : string of symbols)

```
// assume  $\alpha = X_1 X_2 X_3 \dots X_n$ 
if  $X_1 \in T$  then First[ $\alpha$ ] := { $X_1$ }
else begin
  i:=1; First[ $\alpha$ ] := ComputeFirst( $X_1$ )\{\epsilon\};
  while  $X_i \Rightarrow^* \epsilon$  do begin
    if  $i < n$  then
      First[ $\alpha$ ] := First[ $\alpha$ ]  $\cup$  ComputeFirst( $X_{i+1}$ )\{\epsilon\};
    else
      First[ $\alpha$ ] := First[ $\alpha$ ]  $\cup$  {\epsilon};
    i := i + 1;
  end
end
```

Recursion in computing FIRST
causes problems when faced with
recursive grammar rules

10/5/11

17

ComputeFirst; modified

```
foreach  $X \in T$  do First[ $X$ ] := { $X$ };
foreach  $p \in P : X \rightarrow \epsilon$  do First[ $X$ ] := {\epsilon};
repeat foreach  $X \in N, p : X \rightarrow Y_1 Y_2 Y_3 \dots Y_n$  do
  begin i:=1;
    while  $Y_i \Rightarrow^* \epsilon$  and  $i \leq n$  do begin
      First[ $X$ ] := First[ $X$ ]  $\cup$  First[ $Y_i$ ]\{\epsilon\};
      i := i+1;
    end
    if  $i = n+1$  then First[ $X$ ] := First[ $X$ ]  $\cup$  {\epsilon};
until no change in First[ $X$ ] for any  $X$ ;
```

10/5/11

18

ComputeFirst; modified

```

foreach  $X \in T$  do First[X] := X;
foreach  $p \in P : X \rightarrow \epsilon$  do First[X] := { $\epsilon$ };
repeat foreach  $X \in N, p : X \rightarrow Y_1 Y_2 Y_3 \dots Y_n$  do
  begin i:=1;
    while  $Y_i \Rightarrow^*$ 
      First[X] := First[X]  $\cup$  First[Yi];
      i := i+1;
    end
  if i = n+1 then First[X] := First[X]  $\cup$  { $\epsilon$ };
until no change in First[X] for any X;

```

Non-recursive FIRST computation
works with left-recursive grammars.
Computes a fixed point for FIRST[X]
for all non-terminals X in the grammar.
But this algorithm is very inefficient.

10/5/11

19

ComputeFollow

```

Follow(S) := {$};
repeat
  foreach  $p \in P$  do
    case  $p = A \rightarrow \alpha B \beta$  begin
      Follow[B] := Follow[B]  $\cup$  ComputeFirst( $\beta$ )\{ $\epsilon$ };
      if  $\epsilon \in \text{First}(\beta)$  then
        Follow[B] := Follow[B]  $\cup$  Follow[A];
      end
    case  $p = A \rightarrow \alpha B$ 
      Follow[B] := Follow[B]  $\cup$  Follow[A];
until no change in any Follow[N]

```

10/5/11

20

Example First/Follow

$S \rightarrow AB$

$A \rightarrow c \mid \epsilon$

Not an LL(1) grammar

$B \rightarrow cbB \mid ca$

$\text{First}(A) = \{c, \epsilon\}$ $\text{Follow}(A) = \{c\}$

$\text{First}(B) = \{c\}$ $\text{Follow}(A) \cap$

$\text{First}(cbB) =$ $\text{First}(c) = \{c\}$

$\text{First}(ca) = \{c\}$ $\text{Follow}(B) = \{\$ \}$

$\text{First}(S) = \{c\}$ $\text{Follow}(S) = \{\$ \}$

10/5/11

21

ComputeFirst on Left-recursive Grammars

- ComputeFirst as defined earlier loops on left-recursive grammars
- Here is an alternative algorithm for ComputeFirst
 1. Compute non left-recursive cases of FIRST
 2. Create a graph of recursive cases where FIRST of a non-terminal depends on another non-terminal
 3. Compute Strongly Connected Components (SCC)
 4. Compute FIRST starting from root of SCC to avoid cycles

10/5/11

22

ComputeFirst on Left-recursive Grammars

- Each Strongly Connected Component can have recursion
- But the connections between SCC means that (by defn) what we have now is a directed acyclic graph – hence without left recursion
- Unlike top-down LL parsing, bottom-up LR parsing allows left-recursive grammars, so this algorithm is useful for LR parsing

10/5/11


23

ComputeFirst on Left-recursive Grammars

- $S \rightarrow BD \mid D$
- $D \rightarrow d \mid Sd$

$\text{FIRST}_0[A] := \{a, b\}$
 $\text{FIRST}_0[C] := \{\}$
 $\text{FIRST}_0[B] := \{b\}$
 $\text{FIRST}_0[S] := \{b, d\}$
 $\text{FIRST}_0[D] := \{d\}$

- $A \rightarrow CB \mid a$
- $C \rightarrow Bb \mid \epsilon$
- $B \rightarrow Ab \mid b$



Compute
Strongly
Connected
Components

2 SCCs: e.g. consider B-A-C

$\text{FIRST}[B] := \text{FIRST}_0[B] + \text{FIRST}[A]$

$\text{FIRST}[A] := \text{FIRST}_0[A] + \text{FIRST}[C]$

$\text{FIRST}[C] := \text{FIRST}_0[C] + \text{FIRST}_0[B]$

$\text{FIRST}[C] := \text{FIRST}[C] + \{\epsilon\}$

10/5/11

24

How to compute: Does $X \Rightarrow^* \epsilon$?

- The question 'Does $X \Rightarrow^* \epsilon$?' can be written as the predicate: nullable(X)

```

Nullable = {} (set containing nullable non-terminals)
Changed = True
While (changed):
    changed = False
    if X is not in Nullable:
        if
            1.  $X \rightarrow \epsilon$  is in the grammar, or
            2.  $X \rightarrow Y_1 \dots Y_n$  is in the grammar and  $Y_i$  is in Nullable for all i
        then
            add X to Nullable; changed = True

```

10/5/11

25


Converting to LL(1)

$$S \rightarrow AB$$

$$A \rightarrow c \mid \epsilon$$

$$B \rightarrow cbB \mid ca$$

Note that grammar
is regular: $c?(cb)^*ca$



same as:

$$c c? (bc)^* a$$

$$S \rightarrow cAa$$

$$A \rightarrow cB \mid B$$

$$B \rightarrow bcB \mid \epsilon$$

10/5/11

26

Verifying LL(1) using F/F sets

$$S \rightarrow cAa$$

$$A \rightarrow cB \mid B$$

$$B \rightarrow bcB \mid \epsilon$$

$$\text{First}(A) = \{b, c, \epsilon\} \quad \text{Follow}(A) = \{a\}$$

$$\text{First}(B) = \{b, \epsilon\} \quad \text{Follow}(B) = \{a\}$$

$$\text{First}(S) = \{c\} \quad \text{Follow}(S) = \{\$ \}$$

10/5/11

27

Building the Parse Table

- Compute First and Follow sets
- For each production $A \rightarrow \alpha$
 - foreach $a \in \text{First}(\alpha)$ add $A \rightarrow \alpha$ to $M[A, a]$
 - If $\epsilon \in \text{First}(\alpha)$ add $A \rightarrow \alpha$ to $M[A, b]$ for each b in $\text{Follow}(A)$
 - If $\epsilon \in \text{First}(\alpha)$ add $A \rightarrow \alpha$ to $M[A, \$]$ if $\$ \in \text{Follow}(\alpha)$
 - All undefined entries are errors

10/5/11

28

Predictive Parsing Table

Productions	
1	$T \rightarrow F T'$
2	$T' \rightarrow \epsilon$
3	$T' \rightarrow * F T'$
4	$F \rightarrow \text{id}$
5	$F \rightarrow (T)$

$\text{FIRST}(T) = \{\text{id}, (\}$
 $\text{FIRST}(T') = \{*, \epsilon\}$
 $\text{FIRST}(F) = \{\text{id}, (\}$

$\text{FOLLOW}(T) = \{\$,)\}$
 $\text{FOLLOW}(T') = \{\$,)\}$
 $\text{FOLLOW}(F) = \{*, \$,)\}$

	*	()	id	\$
T		$T \rightarrow F T'$		$T \rightarrow F T'$	
T'	$T' \rightarrow * F T'$		$T' \rightarrow \epsilon$		$T' \rightarrow \epsilon$
F		$F \rightarrow (T)$		$F \rightarrow \text{id}$	

10/5/11

29

Revisit conditions for LL(1)

- A grammar G is LL(1) iff - whenever
 $A \rightarrow \alpha \mid \beta$
 - $\text{First}(\alpha) \cap \text{First}(\beta) = \emptyset$
 - $\alpha \Rightarrow^* \epsilon$ implies $\neg(\beta \Rightarrow^* \epsilon)$
 - $\alpha \Rightarrow^* \epsilon$ implies $\text{First}(\beta) \cap \text{Follow}(A) = \emptyset$
- No more than one entry per table field

10/5/11

30

Error Handling

- Reporting & Recovery
 - Report as soon as possible
 - Suitable error messages
 - Resume after error
 - Avoid cascading errors
- Phrase-level vs. Panic-mode recovery

10/5/11

31

Panic-Mode Recovery

- Skip tokens until *synchronizing set* is seen
 - Follow(A)
 - garbage or missing things after
 - Higher-level start symbols
 - First(A)
 - garbage before
 - Epsilon
 - if nullable
 - Pop/Insert terminal
 - “auto-insert”
- Add “synch” actions to table

10/5/11

32

Summary so far

- LL(1) grammars, necessary conditions
 - No left recursion
 - Left-factored
- Not all languages can be generated by LL(1) grammar
- LL(1) – Parsing: $O(n)$ time complexity
 - recursive-descent and table-driven predictive parsing
- LL(1) grammars can be parsed by simple predictive recursive-descent parser
 - Alternative: table-driven top-down parser

10/5/11

33