


Applying Co-Training Methods to Statistical Parsing

Anoop Sarkar


<http://www.cis.upenn.edu/~anoop/>
anoop@linc.cis.upenn.edu

Statistical Parsing:




the company 's clinical trials of both its animal and human-based insulins indicated no difference in the level of hypoglycemia between users of either product



Bilexical CFG (History-based parsers)




Bilexical CFG: $VP\{\text{indicate}\} \rightarrow VB\{+H:\text{indicate}\} NP\{\text{difference}\} PP\{\text{in}\}$




Independence Assumptions (Collins 99)


2.23%




0.06%




60.8%





0.7%



Tree Adjoining Grammars: Different Modeling of Bilexical Dependencies





Probabilistic TAGs: Substitution



$$\sum_{t'} \mathcal{P}(t, \eta \rightarrow t') = 1$$

Probabilistic TAGs: Adjunction



$$\mathcal{P}(t, \eta \rightarrow NA) + \sum_{t'} \mathcal{P}(t, \eta \rightarrow t') = 1$$

Tree Adjoining Grammars

- Simple and well-defined model for parsing. (Schabes 92, Resnik 92, Sarkar 98)
Performance (Chiang 2000): 86.9% LR 86.6% LP (≤ 40 words)
- Locality and independence assumptions are captured elegantly.
- Parsing can be treated in two steps (Srinivas 97):
 1. Classification: structured labels (elementary trees) are assigned to each word in the sentence.
 2. Attachment: Apply substitution or adjunction to combine the elementary trees to form the parse.

Training a Statistical Parser

- How should the parameters (e.g., rule probabilities) be chosen?
- Several alternatives:
 - EM algorithm: Inside-Outside Algorithm (Schabes 92; Hwa 98)
 - Supervised training from a Treebank (Chiang 2000)
 - Parsing as Classification. Explore new machine learning techniques.
 - * Achieving higher performance when using limited amounts of annotated data.
 - * Conditional independence of features in the data.
can we exploit this . . .

Statistical Parsing: Supervised vs. Unsupervised Methods

- “Stone soup” approaches to unsupervised learning of parsers cannot handle structurally rich parses found in the Penn Treebank.
(Lafferty et al 92; Della Pietra et al 94; de Marcken 95)
- A feasible technique: Combining Labeled and Unlabeled Data
 - Active Learning: Bet on which examples are the hardest.
(and annotate them) (Hwa 2000)
 - Co-Training: Bet on which examples can be handled with high confidence. (use as labeled data)

Case Study in Unsupervised Methods: POS Tagging

- POS Tagging: finding categories for words
- ... *the stocks* rose /V ... vs. ... *a* rose /N *bouquet* ...
- Tag dictionary: rose: N, V
and nothing else

Case Study: Unsupervised POS Tagging

- (Cutting et al. 92) The Xerox Tagger: used HMMs with hand-built tag dictionaries. High performance: 96% on Brown
- (Merialdo 94; Elworthy 94) used varying amounts of labeled data as seed information for training HMMs.


Conclusion: HMMs do not effectively combine labeled and unlabeled data

- (Brill 97) aggressively used tag dictionaries taken from labeled data to train an unsupervised POS tagger. c.f. text classification results
Performance: 95% on WSJ. Approach does not easily extend to parsing: no notion of tag dictionary.

Co-Training (Blum and Mitchell 98; Yarowsky 95)

- Pick two “views” of a classification problem.
- Build separate models for each of these “views” and train each model on a small set of labeled data.
- Sample an unlabeled data set and to find examples that each model independently labels with high confidence. (Nigam and Ghani 2000)
- Pick confidently labeled examples.
(Collins and Singer 99; Goldman and Zhou 2000); Active Learning
- Each model labels examples for the other in each iteration.

Pierre Vinken will join the board as a non-executive director



Recursion in Parse Trees

- Usual decomposition of parse trees:

$S(\text{join}) \rightarrow NP(\text{Vinken}) VP(\text{join})$


$NP(\text{Vinken}) \rightarrow \text{Pierre Vinken}$

$VP(\text{join}) \rightarrow \text{will } VP(\text{join})$

$VP(\text{join}) \rightarrow \text{join } NP(\text{board}) PP(\text{as})$


...

Parsing as Tree Classification and Attachment: (Srinivas 97; Xia 2000)



$$\text{Model H1: } \mathcal{P}(T_i \mid T_{i-2}T_{i-1}) \times \mathcal{P}(w_i \mid T_i)$$

Parsing as Tree Classification and Attachment



Model H2: $\mathcal{P}(\text{TOP} = w, T) \times \prod_i \mathcal{P}(w_i, T_i \mid \eta, w, T)$

The Co-Training Algorithm

1. Input: *labeled* and *unlabeled*
2. Update cache
 - Randomly select sentences from *unlabeled* and refill *cache*
 - If *cache* is empty; exit
3. Train models H1 and H2 using *labeled*
4. Apply H1 and H2 to cache.
5. Pick most probable n from H1 (run through H2) and add to *labeled*.
6. Pick most probable n from H2 and add to *labeled*
7. $n = n + k$; Go to Step ??

Results

- *labeled* was set to Sections 02-06 of the Penn Treebank WSJ (9625 sentences)
- *unlabeled* was 30137 sentences (Section 07-21 of the Treebank stripped of all annotations).
- A tree dictionary of all lexicalized trees from *labeled* and *unlabeled*.
Similar to the approach of (Brill 97)
Novel trees were treated as unknown tree tokens
- The *cache* size was 3000 sentences.

Results

- Test set: Section 23
- Baseline Model was trained only on the *labeled* set:
and Labeled Bracketing Precision = 72.23% Recall = 69.12%
- After 12 iterations of Co-Training:
Labeled Bracketing Precision = 80.02% Recall = 79.64%

Summary

- Methods that combine labeled and unlabeled data provide a promising new direction towards unsupervised learning.
- Co-Training, previously used for classifiers with 2/3 labels, was extended to the complex problem of statistical parsing.
- Parsing treated as providing structured (tree) labels with attachments computed between these labels.
- Evaluation of a unsupervised method for parsing directly comparable with supervised approaches.

Current Work

- Still needs human supervision to create the tree dictionary.
For small datasets, this is unavoidable.
- Another application: use a large labeled dataset
But improve performance using a much larger unlabeled dataset.
- Current expt: 1M words *labeled* and 23M words *unlabeled*.
Tree dictionary is completely defined by the labeled set.
- Investigating the relationship between Co-Training and EM.

Co-Training and EM

	gradient descent over unlabeled	iterative selection from unlabeled
max output of a generative model	EM	co-EM*
select new examples independently	<i>Discriminative Objective Function</i>	Co-Training

* (Nigam and Ghani, 2000)