

Sentence Simplification for SRL: A Neural Approach

Logan Born
Simon Fraser University
loborn@sfu.ca

1 Nov 2016

Intent

- To investigate the effectiveness of neural nets on SRL tasks.

Intent

- To investigate the effectiveness of neural nets on SRL tasks.
- Replicate the results of Vickrey & Koller 2008:

Intent

- To investigate the effectiveness of neural nets on SRL tasks.
- Replicate the results of Vickrey & Koller 2008:
 - ▶ Jointly learn to simplify input sentences and to label simplified sentences.

- Combined system for sentence simplification and SRL.

Vickrey & Koller 2008

- Combined system for sentence simplification and SRL.
- Four stages:

Vickrey & Koller 2008

- Combined system for sentence simplification and SRL.
- Four stages:
 - ▶ Simplify: repeatedly apply transformation rules to the input parse to obtain a set of simpler parses.

Vickrey & Koller 2008

- Combined system for sentence simplification and SRL.
- Four stages:
 - ▶ Simplify: repeatedly apply transformation rules to the input parse to obtain a set of simpler parses.
 - ▶ Extract role patterns: what argument structures are possible for a given simplified parse?

- Combined system for sentence simplification and SRL.
- Four stages:
 - ▶ Simplify: repeatedly apply transformation rules to the input parse to obtain a set of simpler parses.
 - ▶ Extract role patterns: what argument structures are possible for a given simplified parse?
 - ★ Each simple sentence–role pattern pair defines a possible labeling.

- Combined system for sentence simplification and SRL.
- Four stages:
 - ▶ Simplify: repeatedly apply transformation rules to the input parse to obtain a set of simpler parses.
 - ▶ Extract role patterns: what argument structures are possible for a given simplified parse?
 - ★ Each simple sentence–role pattern pair defines a possible labeling.
 - ▶ Extract other features from the candidate labelings: POS tags, argument positions, and head words.

- Combined system for sentence simplification and SRL.
- Four stages:
 - ▶ Simplify: repeatedly apply transformation rules to the input parse to obtain a set of simpler parses.
 - ▶ Extract role patterns: what argument structures are possible for a given simplified parse?
 - ★ Each simple sentence–role pattern pair defines a possible labeling.
 - ▶ Extract other features from the candidate labelings: POS tags, argument positions, and head words.
 - ▶ Learn a set of weights for these features which assign high likelihood to good labelings.

Example

Input: "I was given a sandwich by John."

Example

Input:

"I was given a sandwich by John."

Simplification:

—————→ "John gave me a sandwich"
Depassivize

Example

Input: "I was given a sandwich by John."

Simplification: $\xrightarrow{\text{Depassivize}}$ "John gave me a sandwich"

Role pattern: {ARG0 = Subj NP, ARG1 = PV NP2, ARG2 = PV NP1}

Example

Input:

"I was given a sandwich by John."

Simplification:

—————→ "John gave me a sandwich"
Depassivize

Role pattern:

{ARG0 = Subj NP, ARG1 = PV NP2, ARG2 = PV NP1}

Feature set:

Rule = Depassivize

Pattern = {ARG0=Subj NP, ARG1=PV NP2, ARG2=PV NP1}

Role = ARG0, Head Word = John

Role = ARG1, Head Word = sandwich

Role = ARG2, Head Word = I

Role = ARG0, Category = NP

Role = ARG1, Category = NP

Role = ARG2, Category = NP

Role = ARG0, Position = Subject NP

Role = ARG1, Position = Postverb NP2

Role = ARG2, Position = Postverb NP1

Training Weights

- For each candidate simplification c_k of an input sentence c , construct a feature vector f_k (last slide).

Training Weights

- For each candidate simplification c_k of an input sentence c , construct a feature vector f_k (last slide).
- Define the probability of a candidate labeling as

$$P(c_k) = \frac{e^{w^\top f_k}}{\sum_{k'} e^{w^\top f_{k'}}}$$

Training Weights

- For each candidate simplification c_k of an input sentence c , construct a feature vector f_k (last slide).
- Define the probability of a candidate labeling as

$$P(c_k) = \frac{e^{w^\top f_k}}{\sum_{k'} e^{w^\top f_{k'}}}$$

- Objective function seeks to maximize total probability of all correct labelings:

$$F(w) = \sum_s \left(\log \sum_{c_k^s \in K^s} e^{w \cdot f_k^s} - \log \sum_{c_{k'}^s \in C^s} e^{w \cdot f_{k'}^s} \right) - \underbrace{\frac{w^\top w}{2\sigma^2}}_{\text{L2 regularization}}$$

Neural SRL

- Idea: generate simplified sentences as in Vickrey & Koller 2008, but train a neural net to select the best labeling.

Neural SRL

- Idea: generate simplified sentences as in Vickrey & Koller 2008, but train a neural net to select the best labeling.
- Sequence-to-sequence learning problem: given a sequence of simplified parses as input, output a sequence of role labels.

- Idea: generate simplified sentences as in Vickrey & Koller 2008, but train a neural net to select the best labeling.
- Sequence-to-sequence learning problem: given a sequence of simplified parses as input, output a sequence of role labels.
 - ▶ Suitable for RNN encoder-decoder network.

Network Architecture


- Series of RNN encoders, one per simplified parse.

Network Architecture

- Series of RNN encoders, one per simplified parse.
- Following Zoph & Knight 2016, combine these encodings and pass them as inputs to an RNN decoder.


Network Architecture

- Series of RNN encoders, one per simplified parse.
- Following Zoph & Knight 2016, combine these encodings and pass them as inputs to an RNN decoder.
- Decoder will produce role labels as output.




Network Architecture

- Series of RNN encoders, one per simplified parse.
- Following Zoph & Knight 2016, combine these encodings and pass them as inputs to an RNN decoder.
- Decoder will produce role labels as output.
 - ▶ Output sequence format?



Network Architecture

- Series of RNN encoders, one per simplified parse.
- Following Zoph & Knight 2016, combine these encodings and pass them as inputs to an RNN decoder.
- Decoder will produce role labels as output.
 - ▶ Output sequence format?



- Remark: no need to pass lexical features, role patterns, etc as inputs.

Evaluation

- Following Vickrey & Koller 2008, evaluate on the PropBank WSJ dataset, using the CoNLL 2005 evaluation metrics.

Evaluation

- Following Vickrey & Koller 2008, evaluate on the PropBank WSJ dataset, using the CoNLL 2005 evaluation metrics.
- Compare against Vickrey & Koller 2008 and previous SOTA (Punyakank et al. 2008); also compare with recent neural SRL like FitzGerald et al. 2015.

Contributions

- Novel application of the multi-source encoder-decoder framework from Zoph & Knight 2016.

Contributions

- Novel application of the multi-source encoder-decoder framework from Zoph & Knight 2016.
- Novel approach to neural SRL: contrast FitzGerald et al. 2015 (no simplification), Zhou & Xu 2015 (ignores syntactic features).

References

- Alberti, Chris, David Weiss, Greg Coppola, Slav Petrov. 2015. Improved Transition-Based Parsing and Tagging with Neural Networks. EMNLP 2015.
- Firat, Orhan, Kyunghyun Cho, and Yoshua Bengio. 2016. Multi-Way, Multilingual Neural Machine Translation with a Shared Attention Mechanism. NAACL 2016.
- Jia, Robin and Percy Liang. 2016. Data Recombination for Neural Semantic Parsing. ACL 2016
- Vickrey, David and Daphne Koller. 2008. Sentence Simplification for Semantic Role Labeling. ACL 2008.
- Vickrey, David. 2010. Learning Structured Probabilistic Models for Semantic Role Labeling. Dissertation, Stanford University.
- Vinyals, Oriol, Lukasz Kaiser, Terry Koo, Slav Petrov, Ilya Sutskever, and Geoffrey Hinton. 2015. Grammar as a foreign language. NIPS 2015.
- Zhou, Jie and Wei Xu. 2015. End-to-end Learning of Semantic Role Labeling Using Recurrent Neural Networks. ACL 2015.
- Zoph, Barret and Kevin Knight. 2016. Multi-Source Neural Translation. NAACL 2016.