

HKUST Future-Ready Scholars

Introduction to Game Programming using Python

Part 1

20 April 2024



THE HONG KONG
UNIVERSITY OF SCIENCE
AND TECHNOLOGY

Open a tab on your browser, then go to
<https://www.menti.com/>




Number Guessing Game

Let's play the number guessing game.

Set-up your Gmail account.

Then head to
<https://colab.research.google.com/>

All materials today are at:
<https://bit.ly/ustidpo>



Download all files that belong to **Workshop 1** today.

Jupyter Notebook

Now upload your Jupyter Notebook file with **Files** → **Open Notebook**.



Upload the file **Hangman.ipynb**.

Using Jupyter Notebook

You can type your code in these blocks. We call these blocks code cells.




```
print("Mum I am in HKUST typing code in a code block")
```

You can run a code cell with the button on the left.




```
print("Hello World!") # Prints "Hello World!"
```

World of Game Coding



Contents



Imagine you borrow a box from the computer.



Imagine you borrow a box from the computer.



Give it a name and a value, you can now recall this value with the name!

Variables

The code usually goes:

```
variable_name = data
```

This means whatever data is, it is now stored in a variable with name `variable_name`.

In these workshops we will only deal with integer numbers and strings.

Integers: numbers WITHOUT decimal points.

String: Words/Letters surrounded by (single OR double) quotation marks.

```
box_a = 5           # Integer
box_b = -100        # Integer
box_c = "Some text" # String
box_d = 'Some more' # String
```

Variables - Integers

What are integers?

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

`a = 5`

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

```
a = 5          # Valid
```


Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

```
a = 5          # Valid
```

```
b = 12
```

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

```
a = 5          # Valid
```

```
b = 12         # Valid
```

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

`a = 5` `# Valid`

`b = 12` `# Valid`

`c = 1000000`

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

a = 5 # Valid

b = 12 # Valid

c = 1000000 # Valid

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

a = 5 # Valid

b = 12 # Valid

c = 1000000 # Valid

d = -1984

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

a = 5 # Valid

b = 12 # Valid

c = 1000000 # Valid

d = -1984 # Valid

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

a = 5 # Valid

b = 12 # Valid

c = 1000000 # Valid

d = -1984 # Valid

e = 32.5

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

`a = 5` `# Valid`

`b = 12` `# Valid`

`c = 1000000` `# Valid`

`d = -1984` `# Valid`

`e = 32.5` `# This is NOT an integer`

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

```
a = 5          # Valid
b = 12         # Valid
c = 1000000    # Valid
d = -1984      # Valid
e = 32.5       # This is NOT an integer
f = 5.0
```

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

```
a = 5          # Valid
b = 12         # Valid
c = 1000000    # Valid
d = -1984      # Valid
e = 32.5       # This is NOT an integer
f = 5.0        # This is NOT an integer
```

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

```
a = 5          # Valid
b = 12         # Valid
c = 1000000    # Valid
d = -1984      # Valid
e = 32.5       # This is NOT an integer
f = 5.0        # This is NOT an integer
g = '5'
```

Variables - Integers

What are integers?

Integers are just like what you've learnt in Maths, numbers without decimal points. Are the following valid?

```
a = 5          # Valid
b = 12         # Valid
c = 1000000    # Valid
d = -1984      # Valid
e = 32.5       # This is NOT an integer
f = 5.0        # This is NOT an integer
g = '5'        # This would become a string instead
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3  
b = 80 - 52
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3  
b = 80 - 52  # b stores the integer 28
```


Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3  
b = 80 - 52  # b stores the integer 28  
c = 69 * -2
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3  
b = 80 - 52  # b stores the integer 28  
c = 69 * -2  # c stores the integer -138
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52   # b stores the integer 28
c = 69 * -2   # c stores the integer -138
d = 6 / 4
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52  # b stores the integer 28
c = 69 * -2  # c stores the integer -138
d = 6 / 4    # d stores the number 1.5
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52  # b stores the integer 28
c = 69 * -2  # c stores the integer -138
d = 6 / 4    # d stores the number 1.5
e = 18 / 2
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52  # b stores the integer 28
c = 69 * -2  # c stores the integer -138
d = 6 / 4    # d stores the number 1.5
e = 18 / 2   # e stores the number 9.0
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52  # b stores the integer 28
c = 69 * -2  # c stores the integer -138
d = 6 / 4    # d stores the number 1.5
e = 18 / 2   # e stores the number 9.0
```

Division in Python

Whether a number can be precisely divided or not, division does NOT return an integer. The way to turn it into an integer is in the additional content section.

Variables - Integer Arithmetic Operations

Some more examples on operations, with variables:

```
a = 100
```

```
b = 12
```


Variables - Integer Arithmetic Operations

Some more examples on operations, with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b
```

Variables - Integer Arithmetic Operations

Some more examples on operations, with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

Variables - Integer Arithmetic Operations

Some more examples on operations, with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a
```

Variables - Integer Arithmetic Operations

Some more examples on operations, with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a    # d stores the integer -88
```

Variables - Integer Arithmetic Operations

Some more examples on operations, with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a    # d stores the integer -88
```

```
e = a * -b
```

Variables - Integer Arithmetic Operations

Some more examples on operations, with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a    # d stores the integer -88
```

```
e = a * -b    # e stores the integer -1200
```

Variables - Integer Arithmetic Operations

Some more examples on operations, with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a    # d stores the integer -88
```

```
e = a * -b    # e stores the integer -1200
```

```
f = a / b
```

Variables - Integer Arithmetic Operations

Some more examples on operations, with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a    # d stores the integer -88
```

```
e = a * -b    # e stores the integer -1200
```

```
f = a / b     # f stores the number 8.333333333333334
```


Variables - Strings

What are strings?

Variables - Strings

What are strings?

```
a = "word"
```

Variables - Strings

What are strings?

```
a = "word"  # a stores the string "word"
```

Variables - Strings

What are strings?

```
a = "word"  # a stores the string "word"  
b = 'word2'
```

Variables - Strings

What are strings?

```
a = "word" # a stores the string "word"  
b = 'word2' # b stores the string "word2"
```

Variables - Strings

What are strings?

```
a = "word"    # a stores the string "word"  
b = 'word2'   # b stores the string "word2"  
c = '5.20'
```

Variables - Strings

What are strings?

```
a = "word"    # a stores the string "word"  
b = 'word2'   # b stores the string "word2"  
c = '5.20'    # c stores the string "5.20"
```

Variables - Strings

What are strings?

```
a = "word"    # a stores the string "word"  
b = 'word2'   # b stores the string "word2"  
c = '5.20'    # c stores the string "5.20"  
d = 'abc'
```


Variables - Strings

What are strings?

```
a = "word"    # a stores the string "word"  
b = 'word2'   # b stores the string "word2"  
c = '5.20'    # c stores the string "5.20"  
d = 'abc"     # error
```

Variables - Strings


What are strings?

```
a = "word"    # a stores the string "word"  
b = 'word2'   # b stores the string "word2"  
c = '5.20'    # c stores the string "5.20"  
d = 'abc"     # error
```

Quotes

In Python you must use corresponding quotation marks for strings.

Contents



The print() function

```
print("This is the print function.")
```

The `print()` function

`print()` is a function that lets you print something, also known as text output. What this means is whenever you want to put something on screen it has to be *printed* out.

```
print("Word") # This prints the word "Word".
```

Examples:

```
>>> print("Hello World")
```

```
Hello World
```

```
>>> print("Haha hehe")
```

```
Haha hehe
```

```
>>> print(5)
```

```
5
```

Printing multiple things

You can use a comma (,) to separate different things with a space.

```
>>> print("Alpha", "Beta", "Gamma")
```

```
Alpha Beta Gamma
```

```
>>> print("Haha", "hehe")
```

```
Haha hehe
```

```
>>> print(19, 91)
```

```
19 91
```

Variables in output using the `print()` function

How do we print variables?

```
a = 5  
print(a)
```

Variables in output using the `print()` function

How do we print variables?

```
a = 5
```

```
print(a)          # 5
```


Variables in output using the print() function

How do we print variables?

```
a = 5  
print(a)          # 5  
b = "haha"  
print(b)
```

Variables in output using the print() function

How do we print variables?

```
a = 5
```

```
print(a)          # 5
```

```
b = "haha"
```

```
print(b)          # haha
```

Variables in output using the print() function

How do we print variables?

```
a = 5
```

```
print(a)          # 5
```

```
b = "haha"
```

```
print(b)          # haha
```

```
print(a + 2)
```

Variables in output using the print() function

How do we print variables?

```
a = 5
print(a)          # 5
b = "haha"
print(b)          # haha
print(a + 2)      # 7
```

Variables in output using the print() function

How do we print variables?

```
a = 5
print(a)          # 5
b = "haha"
print(b)          # haha
print(a + 2)      # 7
```

Calculation

We can calculate expressions inside the print() function.

Variables in output using the `print()` function

How do we print variables?

```
a = 5  
print(a)
```

Variables in output using the `print()` function

How do we print variables?

```
a = 5
```

```
print(a)          # 5
```

Variables in output using the print() function

How do we print variables?

```
a = 5  
print(a)          # 5  
b = "haha"  
print(a, b)
```


Variables in output using the print() function

How do we print variables?

```
a = 5
```

```
print(a)          # 5
```

```
b = "haha"
```

```
print(a, b)       # 5 haha
```

Variables in output using the print() function

How do we print variables?

```
a = 5
print(a)          # 5
b = "haha"
print(a, b)       # 5 haha
print(b, b)
```

Variables in output using the print() function

How do we print variables?

```
a = 5
print(a)          # 5
b = "haha"
print(a, b)       # 5 haha
print(b, b)       # haha haha
```

Variables in output using the print() function

How do we print variables?

```
a = 5
print(a)          # 5
b = "haha"
print(a, b)       # 5 haha
print(b, b)       # haha haha
```

The comma

Using , in print() would add a space in between the 2 items.

input() function

We know how to output (print), what about input?

```
input("This is the input function.")
```

input() function

`input()` is a function that outputs a prompt and lets the user enter something.

```
>>> input("Enter a number: ")  
Enter a number: 5
```

Simply inputting doesn't do anything, but we can print it.

```
>>> print(input("Enter a number: "))  
Enter a number: 100  
100
```

input() function

Another example:

```
>>> input("Enter something: ")  
Enter something: I am in HKUST
```

Simply inputting doesn't do anything, but we can print it.

```
>>> print(input("Enter a number: "))  
Enter something: I am in HKUST  
I am in HKUST
```

Generating a random integer using random library

In Python, we can import libraries to help us with tasks. One of them is generating random numbers. The library/package `random` allows us to get a random number.

The `randint` function provided allows us to generate a random integer given a range.


```
import random
num = random.randint(1, 10) # generates a random number
                             # We passed 1 and 10 into randint,
                             # so the number can only be
                             # from 1 to 10
print(num) # prints the number
```


Generating a random integer using random library

Another example:

```
import random
min = 15
max = 30
print(random.randint(min, max)) # prints a random number
                                # from 15 to 30
```


Contents



What is decision making?

What is decision making?

We use condition(s) to decide whether some code should be run.



The if clause

```
a = 5 # a stores the integer 5
if a == 5:
    print("a stores 5.") # This line is activated

b = 10 # b stores the integer 10
if b == 5:
    print("b stores 5.") # This line is not activated
```

The if clause

If the condition is true, then the code under it is run.

The == operator

```
a = 5 # a stores the integer 5
if a == 5:
    print("a stores 5.") # This line is activated

b = 10 # b stores the integer 10
if b == 5:
    print("b stores 5.") # This line is not activated
```

The == operator

The operator == is used to compare 2 values. If the values on the both sides are the same, then it we consider it as true, false otherwise.

The if-else clause

```
a = 5 # a stores the integer 5
if a == 5:
    print("a stores 5.") # This line is activated
else:
    print("a does not store 5.")

b = 10 # b stores the integer 10
if b == 5:
    print("b stores 5.")
else:
    print("b does not store 5.") # This line is activated
```

The else statement

Code under the else statement is executed when the condition in if is not true.

The if-else clause

```
a = 5 # a stores the integer 5
if a == 5:
    print("a stores 5.") # This line is activated
else:
    print("a does not store 5.")

b = 10 # b stores the integer 10
if b == 5:
    print("b stores 5.")
else:
    print("b does not store 5.") # This line is activated
```

Indentation in Python

Indentation decides whether the code is under the if/else statements. It does not have to be 4 spaces, but they have to be **consistent**.

The if-elif-else clause

```
a = 5 # a stores the integer 5
if a == 5:
    print("a stores 5.") # This line is activated
elif a == 10:
    print("a stores 10.")
else:
    print("a does not store 5 or 10.")
```

The elif statement

The elif (stands for else-if) statement is a secondary if statement that is run if the previous if/elif condition(s) are not true.

The if-elif-else clause

```
a = 15 # a stores the integer 15
if a == 5:
    print("a stores 5.")
elif a == 10:
    print("a stores 10.")
elif a == 15:
    print("a stores 15") # This line is activated
else:
    print("a does not store 5, 10 or 15.")
```

Stacking the elif statement

The elif statement can be stacked on top of one another.

Comparison Operators

We've learnt that `==` means "equal to". What are some other operators?

Operator	Meaning
<code>==</code>	equal to
<code>></code>	larger than
<code>>=</code>	larger than or equal to
<code><</code>	smaller than
<code><=</code>	smaller than or equal to
<code>!=</code>	not equal to

Decision Making and Comparison Operators

```
a = 10 # a stores the integer 10
if a > 5:
    print("a is larger than 5")

if a >= 10:
    print("a is larger than or equal to 10")
```

In this example, both `print()` statements are activated.

Decision Making and Comparison Operators

```
a = 10 # a stores the integer 10
if a > 5:
    print("a is larger than 5")
elif a >= 10:
    print("a is larger than or equal to 10") # Not run
```

Decision Making and Comparison Operators

```
a = 10 # a stores the integer 10
if a > 5:
    print("a is larger than 5")
elif a >= 10:
    print("a is larger than or equal to 10") # Not run
```

In this example, only the first `print()` statements are activated.

if vs elif

If a condition is fulfilled, any `elif` clauses afterwards will not be considered.

Logic Operators - and

The and operator denotes whether the 2 conditions are fulfilled **at the same time**.

Example:

```
a = 10 # a stores the integer 10
if a > 5 and a < 9:
    print("a is between 5 and 9")
else:
    print("a is not between 5 and 9") # This line is run
```

The or operator denotes whether **any** of the 2 conditions are fulfilled.

Example:

```
a = 10 # a stores the integer 10
if a < 5 or a > 9:
    print("a is not between 5 and 9") # This line is run
else:
    print("a is between 5 and 9")
```


Logic Operators - not

The not operator reverses the condition.

Example:

```
a = 10 # a stores the integer 10
if not a == 5: # Same as a != 5
    print("a is not 5") # This line is run
else:
    print("a is 5")
```

Multiple Logic Operators

```
a = 10 # a stores the integer 10
if not a == 0 or a == 1: # Same as a % 2 == 0 or a == 1
    print("a is 0 or 1")
else:
    print("a is not 0 or 1")

b = 10 # b stores the integer 10
if b == 5 and not b != 5: # Impossible condition
    print("b is 5 and somehow not 5?")
else:
    print("Else statement")
```

Multiple Logic Operator (out of control)

We can use multiple logic operators together, but what about the rules?

```
a = 10 # a stores the integer 10
if not a == 0 and a == 1 or a == 3 and a * 2 == 10:
    print("What is going on in the conditions?")
else:
    print("Else statement")
```

Multiple Logic Operator (out of control)

We add brackets () to make our conditions clear.

```
a = 10 # a stores the integer 10
if (not a == 0 and a == 1) or (a == 3 and a * 2 == 10):
    print("Now the conditions are clearer")
else:
    print("Else statement")
```

Multiple Logic Operator (out of control)

We add brackets () to make our conditions clear.

```
a = 10 # a stores the integer 10
if (not a == 0 and a == 1) or (a == 3 and a * 2 == 10):
    print("Now the conditions are clearer")
else:
    print("Else statement")
```

Reminder

If you ever use > 1 and/or operators, add brackets to keep track of what your conditions are.

Summary

Examples of valid integers

```
a = 5  
b = 1000000  
c = -1984
```

Examples of valid strings

```
a = "5"  
b = "haha"  
c = 'some words'
```

Arithmetic Operators

Some basic and commonly-used operators:

+	add	-	minus,
*	multiply	/	divide

Summary

The `print()` statement

```
print(*objects)
```

`*objects` - the things you want to print

The `input()` statement

```
input(prompt)
```

where `prompt` is quite literally what it means. It prints the output, then returns the value inputted as a string.

`random.randint()`

```
random.randint(a, b)
```

`a` - the lower bound of your range

`b` - the upper bound of your range

This generates an integer `n` where $a \leq n \leq b$.

Summary

if, elif and else

if, elif and else clauses are used to decide whether some code should be executed. Whenever one is fulfilled, all others are ignored.

```
if condition1: # if condition1 is true
    # Do something, ignore all elif and else below

elif condition2: # if condition2 is true
    # Do something, ignore all elif and else below

elif condition3: # if condition3 is true
    # Do something, ignore all elif and else below

else: # if all the conditions above are false
    # Do something
```


Summary

The and logic operator

The and operator makes it so that both conditions have to be fulfilled in order for the code it is under to execute.

The or logic operator

The or operator makes it so that only 1 of the conditions have to be fulfilled in order for the code it is under to execute.

The not logic operator

The not operator reverses the condition it is attached to.

Multiple logic operators

One can chain multiple logic operators together, but to be safe add brackets () to make sure the condition works as intended.

The End
Thank you!

Additional content

Here are some additional content that we didn't think we would have time to mention in the workshop.

Variable Types

There are other variable types other than integers and strings.
Some basic variable types:

```
a = 5
```

Variable Types

There are other variable types other than integers and strings.
Some basic variable types:

```
a = 5          # This is an integer (int) stored in a
```

Variable Types

There are other variable types other than integers and strings.
Some basic variable types:

```
a = 5          # This is an integer (int) stored in a
b = True
```

Variable Types

There are other variable types other than integers and strings.
Some basic variable types:

```
a = 5          # This is an integer (int) stored in a
b = True       # This is a boolean (bool) stored in b
```

Variable Types

There are other variable types other than integers and strings.
Some basic variable types:

```
a = 5          # This is an integer (int) stored in a
b = True       # This is a boolean (bool) stored in b
c = 3.2
```


Variable Types

There are other variable types other than integers and strings.
Some basic variable types:

```
a = 5          # This is an integer (int) stored in a
b = True       # This is a boolean (bool) stored in b
c = 3.2        # This is a float (float) stored in c
```

Variable Types

There are other variable types other than integers and strings.
Some basic variable types:

```
a = 5          # This is an integer (int) stored in a
b = True       # This is a boolean (bool) stored in b
c = 3.2        # This is a float (float) stored in c
d = "abc"
```

Variable Types

There are other variable types other than integers and strings.
Some basic variable types:

```
a = 5          # This is an integer (int) stored in a
b = True       # This is a boolean (bool) stored in b
c = 3.2        # This is a float (float) stored in c
d = "abc"      # This is a string (str) stored in d
```

Variable Types

There are other variable types other than integers and strings.
Some basic variable types:

```
a = 5          # This is an integer (int) stored in a
b = True       # This is a boolean (bool) stored in b
c = 3.2        # This is a float (float) stored in c
d = "abc"      # This is a string (str) stored in d
e = 'abc'
```

Variable Types

There are other variable types other than integers and strings.
Some basic variable types:

```
a = 5          # This is an integer (int) stored in a
b = True       # This is a boolean (bool) stored in b
c = 3.2        # This is a float (float) stored in c
d = "abc"      # This is a string (str) stored in d
e = 'abc'      # This is also a string stored in e
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
```

```
b = 80 - 52
```


Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3  
b = 80 - 52  # b stores the integer 28
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52  # b stores the integer 28
c = 69 * -2
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52  # b stores the integer 28
c = 69 * -2  # c stores the integer -138
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52  # b stores the integer 28
c = 69 * -2  # c stores the integer -138
d = 6 / 4
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52  # b stores the integer 28
c = 69 * -2  # c stores the integer -138
d = 6 / 4    # d stores the float 1.5
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52  # b stores the integer 28
c = 69 * -2  # c stores the integer -138
d = 6 / 4    # d stores the float 1.5
e = 18 / 2
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52  # b stores the integer 28
c = 69 * -2  # c stores the integer -138
d = 6 / 4    # d stores the float 1.5
e = 18 / 2   # e stores the float 9.0
```

Variables - Integer Arithmetic Operations

You can do normal operations on integers:

```
a = 1 + 2    # a stores the integer 3
b = 80 - 52  # b stores the integer 28
c = 69 * -2  # c stores the integer -138
d = 6 / 4    # d stores the float 1.5
e = 18 / 2   # e stores the float 9.0
```

Division in Python

Whether a number can be precisely divided or not, division returns a float.

Variables - Integer Arithmetic Operations

Operations with variables:

```
a = 100
```

```
b = 12
```

Variables - Integer Arithmetic Operations

Operations with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b
```

Variables - Integer Arithmetic Operations

Operations with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

Variables - Integer Arithmetic Operations

Operations with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a
```

Variables - Integer Arithmetic Operations

Operations with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a    # d stores the integer -88
```

Variables - Integer Arithmetic Operations

Operations with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a    # d stores the integer -88
```

```
e = a * -b
```

Variables - Integer Arithmetic Operations

Operations with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a    # d stores the integer -88
```

```
e = a * -b    # e stores the integer -1200
```

Variables - Integer Arithmetic Operations

Operations with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a    # d stores the integer -88
```

```
e = a * -b    # e stores the integer -1200
```

```
f = a / b
```


Variables - Integer Arithmetic Operations

Operations with variables:

```
a = 100
```

```
b = 12
```

```
c = a + b    # c stores the integer 112
```

```
d = b - a    # d stores the integer -88
```

```
e = a * -b    # e stores the integer -1200
```

```
f = a / b    # f stores the float 8.333333333333334
```

Variables - Integer Arithmetic Operations

Then how do we get an integer output?

Variables - Integer Arithmetic Operations

Then how do we get an integer output?

```
a = 100
```

```
b = 12
```

Variables - Integer Arithmetic Operations

Then how do we get an integer output?

```
a = 100
```

```
b = 12
```

```
c = a // b
```

Variables - Integer Arithmetic Operations

Then how do we get an integer output?

```
a = 100
```

```
b = 12
```

```
c = a // b # c stores the integer 8
```

Variables - Integer Arithmetic Operations

Then how do we get an integer output?

```
a = 100
```

```
b = 12
```

```
c = a // b  # c stores the integer 8  
            # // operator takes the closest and smaller  
            # integer from the division operation
```

Variables - Integer Arithmetic Operations

Then how do we get an integer output?

```
a = 100
```

```
b = 12
```

```
c = a // b  # c stores the integer 8  
            # // operator takes the closest and smaller  
            # integer from the division operation
```

```
d = a % b
```

Variables - Integer Arithmetic Operations

Then how do we get an integer output?

```
a = 100
```

```
b = 12
```

```
c = a // b    # c stores the integer 8  
              # // operator takes the closest and smaller  
              # integer from the division operation
```

```
d = a % b     # d stores the integer 4
```


Variables - Integer Arithmetic Operations

Then how do we get an integer output?

```
a = 100
```

```
b = 12
```

```
c = a // b  # c stores the integer 8  
            # // operator takes the closest and smaller  
            # integer from the division operation  
d = a % b   # d stores the integer 4  
            # % operator takes the remainder of a  
            # division operation
```

Variables - Integer Arithmetic Operations

Also, the power (exponent) operation:

`a = 2`

`b = 5`

Variables - Integer Arithmetic Operations

Also, the power (exponent) operation:

```
a = 2
```

```
b = 5
```

```
c = a ** b
```

Variables - Integer Arithmetic Operations

Also, the power (exponent) operation:

```
a = 2
```

```
b = 5
```

```
c = a ** b  # c stores the integer 32  
            # ** operator means power
```

Variables - Floats

What are floats?

Variables - Floats

What are floats?

Floats are numbers with decimal points.

Variables - Floats

What are floats?

Floats are numbers with decimal points.

Arithmetic operators we learnt can be applied as well.

```
a = 0.2      # a stores the float 0.2
```

```
b = 3.0      # b stores the float 3.0
```

Variables - Floats

What are floats?

Floats are numbers with decimal points.

Arithmetic operators we learnt can be applied as well.

```
a = 0.2      # a stores the float 0.2
b = 3.0      # b stores the float 3.0
c = a + b
```


Variables - Floats

What are floats?

Floats are numbers with decimal points.

Arithmetic operators we learnt can be applied as well.

```
a = 0.2      # a stores the float 0.2  
b = 3.0      # b stores the float 3.0  
c = a + b    # c stores the float 3.2
```

Variables - Floats

What are floats?

Floats are numbers with decimal points.

Arithmetic operators we learnt can be applied as well.

```
a = 0.2      # a stores the float 0.2
b = 3.0      # b stores the float 3.0
c = a + b    # c stores the float 3.2
d = b / a
```

Variables - Floats

What are floats?

Floats are numbers with decimal points.

Arithmetic operators we learnt can be applied as well.

```
a = 0.2      # a stores the float 0.2
b = 3.0      # b stores the float 3.0
c = a + b    # c stores the float 3.2
d = b / a    # d stores the float 15.0
```

Variables - Floats

What are floats?

Floats are numbers with decimal points.

Arithmetic operators we learnt can be applied as well.

```
a = 0.2      # a stores the float 0.2
b = 3.0      # b stores the float 3.0
c = a + b    # c stores the float 3.2
d = b / a    # d stores the float 15.0
e = a ** b
```

Variables - Floats

What are floats?

Floats are numbers with decimal points.

Arithmetic operators we learnt can be applied as well.

```
a = 0.2      # a stores the float 0.2
b = 3.0      # b stores the float 3.0
c = a + b    # c stores the float 3.2
d = b / a    # d stores the float 15.0
e = a ** b   # e stores the float 0.0080000000000000002
```

Variables - Floats

What are floats?

Floats are numbers with decimal points.

Arithmetic operators we learnt can be applied as well.

```
a = 0.2      # a stores the float 0.2
b = 3.0      # b stores the float 3.0
c = a + b    # c stores the float 3.2
d = b / a    # d stores the float 15.0
e = a ** b   # e stores the float 0.0080000000000000002
```

Inaccuracies

Inaccuracies happen with decimals in Python. Be careful when dealing with floats.

Variables - Floats

What happens when you combine floats and integers?

Variables - Floats

What happens when you combine floats and integers?

```
a = 0.2      # a stores the float 0.2  
b = 3        # b stores the integer 3
```


Variables - Floats

What happens when you combine floats and integers?

```
a = 0.2      # a stores the float 0.2
b = 3        # b stores the integer 3
c = a + b    # c stores the float 3.2
d = b / a    # d stores the float 15.0
e = a ** b   # e stores the float 0.0080000000000000002
```

Variables - Floats

What happens when you combine floats and integers?

```
a = 0.2      # a stores the float 0.2
b = 3        # b stores the integer 3
c = a + b    # c stores the float 3.2
d = b / a    # d stores the float 15.0
e = a ** b   # e stores the float 0.0080000000000000002
```

Arithmetic operations between int and float

Arithmetic operations between integers and floats converts the integer into a float first before operating.

Variables - Boolean values

What are boolean values?

Variables - Boolean values

What are boolean values?

There are only 2 boolean values in existence: `True` and `False`.

Variables - Boolean values

What are boolean values?

There are only 2 boolean values in existence: True and False.

```
a = True
```

```
b = False
```

Variables - Strings

Example:

```
a = "haha"
```

```
b = "hehe"
```

```
c = a + b
```

Variables - Strings

Example:

```
a = "haha"
```

```
b = "hehe"
```

```
c = a + b      # c stores the string "hahahehe"
```

Variables - Strings

Example:

```
a = "haha"
```

```
b = "hehe"
```

```
c = a + b      # c stores the string "hahahehe"
```

Concatenation of strings

You can concatenate (add) strings together with the addition symbol.

Variables - Strings

How do I put the symbols ' and " into a string?

Variables - Strings

How do I put the symbols ' and " into a string?
For ":

Variables - Strings

How do I put the symbols ' and " into a string?
For ":

```
a = "word\" # a stores the string "word"
```

Variables - Strings

How do I put the symbols ' and " into a string?

For ":

```
a = "word\" # a stores the string "word"  
b = 'word'  # b stores the same string as a
```

Variables - Strings

How do I put the symbols ' and " into a string?

For ":

```
a = "word\" # a stores the string "word"  
b = 'word"' # b stores the same string as a
```

Same goes for single quotes ':

```
a = 'word\'' # a stores the string "word"  
b = "word'" # b stores the same string as a
```

Variables - Strings

There are additional symbols in strings.

```
a = "word\n" # \n represents the newline character  
b = "word\t" # \t represents the tab character
```

Variables in output using the print() function

How do we print variables?

```
a = 5
```

```
print(a)          # 5
```

```
b = "haha"
```

```
print(b)          # haha
```

Variables in output using the print() function

How do we print variables?

```
a = 5
```

```
print(a)          # 5
```

```
b = "haha"
```

```
print(b)          # haha
```

```
print(a + "5")
```


Variables in output using the print() function

How do we print variables?

```
a = 5
```

```
print(a)          # 5
```

```
b = "haha"
```

```
print(b)          # haha
```

```
print(a + "5")    # error
```

Variables in output using the print() function

How do we print variables?

```
a = 5
print(a)          # 5
b = "haha"
print(b)          # haha
print(a + "5")    # error
print(b + 2)
```

Variables in output using the print() function

How do we print variables?

```
a = 5
```

```
print(a)          # 5
```

```
b = "haha"
```

```
print(b)          # haha
```

```
print(a + "5")    # error
```

```
print(b + 2)      # error
```

Variables in output using the print() function

How do we print variables?

```
a = 5
print(a)          # 5
b = "haha"
print(b)          # haha
print(a + "5")    # error
print(b + 2)      # error
print(a + b)
```

Variables in output using the print() function

How do we print variables?

```
a = 5
print(a)          # 5
b = "haha"
print(b)          # haha
print(a + "5")    # error
print(b + 2)      # error
print(a + b)      # error
```

Variables in output using the print() function

How do we print variables?

```
a = 5
print(a)          # 5
b = "haha"
print(b)          # haha
print(a + "5")    # error
print(b + 2)      # error
print(a + b)      # error
```

Addition

You cannot use addition to print things of incompatible types.

int and float types are not incompatible because all int are converted to float if needed during operation.

Variables in output using the print() function

How do we print variables?

```
a = 5
```

```
b = 32
```

```
c = 32.0
```

```
print(a * b)      # 160
```

```
print(a * c)      # 160.0
```

Variables in output using the print() function

How do we print variables?

```
a = 5
```

```
b = 32
```

```
c = 32.0
```

```
print(a * b)      # 160
```

```
print(a * c)      # 160.0
```

Takeaway

print() function evaluates the expression inside the brackets first before actually printing.

More on print() function

In Python, the `print()` function automatically adds a new line after execution. We, however, can stop that.

The `end=` tag allows us to define the character added when `print()` is executed.

```
print(5, end="")  
print(4)  
print("a", end="abc")  
print("d", end=" ")  
print("e")
```

More on print() function

In Python, the `print()` function automatically adds a new line after execution. We, however, can stop that.

The `end=` tag allows us to define the character added when `print()` is executed.

```
print(5, end="")  
print(4)  
print("a", end="abc")  
print("d", end=" ")  
print("e")  
# What is the output?
```

More on print() function

In Python, the `print()` function automatically adds a new line after execution. We, however, can stop that.

The `end=` tag allows us to define the character added when `print()` is executed.

```
print(5, end="")  
print(4)  
print("a", end="abc")  
print("d", end=" ")  
print("e")  
# What is the output?  
# Output: 54  
#          aabcd e
```

End of line

Remember to include a new line `\n` in the last line of a printed string. Else it may mess up the future outputs from other lines of the code or the computer terminal.

More on `print()` function

We mentioned that whenever `,` is used in `print()`, the items would be separated by a space.

This can actually be changed using the `sep=` tag.

More on print() function

We mentioned that whenever , is used in print(), the items would be separated by a space.

This can actually be changed using the sep= tag.

```
>>> print("100", 100, end="\n3\n")
```

More on print() function

We mentioned that whenever , is used in print(), the items would be separated by a space.

This can actually be changed using the sep= tag.

```
>>> print("100", 100, end="\n3\n")  
>>> 100 100  
3
```

More on print() function

We mentioned that whenever `,` is used in `print()`, the items would be separated by a space.

This can actually be changed using the `sep=` tag.

```
>>> print("100", 100, end="\n3\n")
>>> 100 100
      3
>>> print("100", 100, sep="a", end="\n3\n")
```

More on print() function

We mentioned that whenever , is used in print(), the items would be separated by a space.

This can actually be changed using the sep= tag.

```
>>> print("100", 100, end="\n3\n")
```

```
>>> 100 100
```

```
3
```

```
>>> print("100", 100, sep="a", end="\n3\n")
```

```
>>> 100a100
```

```
3
```


More on print() function

Another example:

```
>>> a = 5  
>>> b = 10  
>>> print(a, b, a + b, end="20\n")
```

More on print() function

Another example:

```
>>> a = 5
>>> b = 10
>>> print(a, b, a + b, end="20\n")
>>> 5 10 1520
```

More on print() function

Another example:

```
>>> a = 5
>>> b = 10
>>> print(a, b, a + b, end="20\n")
>>> 5 10 1520
>>> print(a, b, a + b, sep="", end="20\n")
```

More on print() function

Another example:

```
>>> a = 5
>>> b = 10
>>> print(a, b, a + b, end="20\n")
>>> 5 10 1520
>>> print(a, b, a + b, sep="", end="20\n")
>>> 5101520
>>> print(a, b, a + b, end="20\n", sep="")
```

More on print() function

Another example:

```
>>> a = 5
>>> b = 10
>>> print(a, b, a + b, end="20\n")
>>> 5 10 1520
>>> print(a, b, a + b, sep="", end="20\n")
>>> 5101520
>>> print(a, b, a + b, end="20\n", sep="")
>>> 5101520
```

More on print() function

Another example:

```
>>> a = 5
>>> b = 10
>>> print(a, b, a + b, end="20\n")
>>> 5 10 1520
>>> print(a, b, a + b, sep="", end="20\n")
>>> 5101520
>>> print(a, b, a + b, end="20\n", sep="")
>>> 5101520
```

Command Parameters

As long as you mark `sep` and `end` clearly **and** after the things you want to print, the ordering doesn't matter!

Converting the type of an input

How do we convert the data type of variables?

```
>>> number = input("Enter your number: ")
```

```
Enter your number: 50
```

```
>>> print(number)
```

Converting the type of an input

How do we convert the data type of variables?

```
>>> number = input("Enter your number: ")
```

```
Enter your number: 50
```

```
>>> print(number)
```

```
50
```


Converting the type of an input

How do we convert the data type of variables?

```
>>> number = input("Enter your number: ")
```

```
Enter your number: 50
```

```
>>> print(number)
```

```
50
```

```
>>> print(number + 1000)
```

Converting the type of an input

How do we convert the data type of variables?

```
>>> number = input("Enter your number: ")
```

```
Enter your number: 50
```

```
>>> print(number)
```

```
50
```

```
>>> print(number + 1000) # Error occurs. Why?
```

Converting the type of an input

How do we convert the data type of variables?

```
>>> number = input("Enter your number: ")
```

Enter your number: 50

```
>>> print(number)
```

50

```
>>> print(number + 1000) # Error occurs. Why?
```

Explanation

number is a string type while 1000 is an integer.

Converting the type of an input

How do we convert the data type of variables?

```
>>> number = input("Enter your number: ")
```

```
Enter your number: 50
```

```
>>> print(number)
```

Converting the type of an input

How do we convert the data type of variables?

```
>>> number = input("Enter your number: ")
```

```
Enter your number: 50
```

```
>>> print(number)
```

```
50
```

Converting the type of an input

How do we convert the data type of variables?

```
>>> number = input("Enter your number: ")
```

```
Enter your number: 50
```

```
>>> print(number)
```

```
50
```

```
>>> print(int(number) + 1000)
```

Converting the type of an input

How do we convert the data type of variables?

```
>>> number = input("Enter your number: ")
Enter your number: 50
>>> print(number)
50
>>> print(int(number) + 1000) # 1050
```

Type conversion

`input()` returns the input as string. We need to convert the input to the suitable type when needed.

We use `int()` to convert something into an integer.

This will be useful.

Converting between types

You can convert between types with their type names in Python.

Data Type	Command
Integer	<code>int()</code>
Float	<code>float()</code>
String	<code>str()</code>
Boolean	<code>bool()</code>

int()

`int()` tries to convert a variable into an integer.

```
a = 10          # int  
print(int(a))
```

int()

`int()` tries to convert a variable into an integer.

```
a = 10          # int  
print(int(a))  # 10
```

int()

int() tries to convert a variable into an integer.

```
a = 10          # int
print(int(a))   # 10
                # Nothing occurs
```

int()

int() tries to convert a variable into an integer.

```
a = 10          # int
print(int(a))   # 10
                # Nothing occurs
```

```
b = 3.7         # float
print(int(b))
```

int()

int() tries to convert a variable into an integer.

```
a = 10          # int
print(int(a))   # 10
                # Nothing occurs
```

```
b = 3.7         # float
print(int(b))   # 3
```

int()

int() tries to convert a variable into an integer.

```
a = 10          # int
print(int(a))   # 10
                # Nothing occurs

b = 3.7         # float
print(int(b))   # 3
                # Discards values to the right of
                # the decimal point
```

int()

int() tries to convert a variable into an integer.

```
a = 10          # int
print(int(a))   # 10
                # Nothing occurs

b = 3.7         # float
print(int(b))   # 3
                # Discards values to the right of
                # the decimal point

c = True        # boolean
print(int(c))
```

int()

int() tries to convert a variable into an integer.

```
a = 10          # int
print(int(a))   # 10
                # Nothing occurs

b = 3.7         # float
print(int(b))   # 3
                # Discards values to the right of
                # the decimal point

c = True        # boolean
print(int(c))   # 1
```


int()

int() tries to convert a variable into an integer.

```
a = 10          # int
print(int(a))   # 10
                # Nothing occurs

b = 3.7         # float
print(int(b))   # 3
                # Discards values to the right of
                # the decimal point

c = True        # boolean
print(int(c))   # 1

d = False       # boolean
print(int(d))
```

int()

int() tries to convert a variable into an integer.

```
a = 10          # int
print(int(a))   # 10
                # Nothing occurs

b = 3.7         # float
print(int(b))   # 3
                # Discards values to the right of
                # the decimal point

c = True        # boolean
print(int(c))   # 1

d = False       # boolean
print(int(d))   # 0
```

int()

int() tries to convert a variable into an integer.

```
a = 10          # int
print(int(a))   # 10
                # Nothing occurs

b = 3.7         # float
print(int(b))   # 3
                # Discards values to the right of
                # the decimal point

c = True        # boolean
print(int(c))   # 1

d = False       # boolean
print(int(d))   # 0
                # For boolean: 0 if False, True otherwise
```

int()

```
i = "123abc" # string  
print(int(i))
```

int()

```
i = "123abc" # string  
print(int(i)) # Error
```

int()

```
i = "123abc" # string  
print(int(i)) # Error
```

```
j = "123" # string with ONLY numbers  
print(int(j))
```

int()

```
i = "123abc" # string  
print(int(i)) # Error
```

```
j = "123" # string with ONLY numbers  
print(int(j)) # 123
```

int()

```
i = "123abc" # string  
print(int(i)) # Error
```

```
j = "123" # string with ONLY numbers  
print(int(j)) # 123  
# Only integers in strings would be  
# successfully converted
```


int()

```
i = "123abc" # string
print(int(i)) # Error
```

```
j = "123" # string with ONLY numbers
print(int(j)) # 123
# Only integers in strings would be
# successfully converted
```

```
k = "123.123" # string with ONLY numbers, but with
# a number that represents a float
print(int(k))
```

int()

```
i = "123abc" # string
print(int(i)) # Error
```

```
j = "123" # string with ONLY numbers
print(int(j)) # 123
# Only integers in strings would be
# successfully converted
```

```
k = "123.123" # string with ONLY numbers, but with
# a number that represents a float
print(int(k)) # Error
```

float()

The concepts of `int()` and `float()` are quite similar.

float()

The concepts of `int()` and `float()` are quite similar.

```
a = 10          # int  
print(float(a))
```

float()

The concepts of `int()` and `float()` are quite similar.

```
a = 10          # int
print(float(a)) # 10.0
```

float()

The concepts of `int()` and `float()` are quite similar.

```
a = 10          # int
print(float(a)) # 10.0
               # From int -> float
```

float()

The concepts of `int()` and `float()` are quite similar.

```
a = 10          # int
print(float(a)) # 10.0
               # From int -> float

b = 3.7         # float
print(float(b))
```

float()

The concepts of `int()` and `float()` are quite similar.

```
a = 10          # int
print(float(a)) # 10.0
               # From int -> float
```

```
b = 3.7         # float
print(float(b)) # 3.7
```


float()

The concepts of `int()` and `float()` are quite similar.

```
a = 10          # int
print(float(a)) # 10.0
               # From int -> float
```

```
b = 3.7         # float
print(float(b)) # 3.7
               # Nothing happens
```

float()

The concepts of `int()` and `float()` are quite similar.

```
a = 10          # int
print(float(a)) # 10.0
               # From int -> float
```

```
b = 3.7         # float
print(float(b)) # 3.7
               # Nothing happens
```

```
c = True        # boolean
print(float(c))
```

float()

The concepts of `int()` and `float()` are quite similar.

```
a = 10          # int
print(float(a)) # 10.0
                # From int -> float
```

```
b = 3.7         # float
print(float(b)) # 3.7
                # Nothing happens
```

```
c = True        # boolean
print(float(c)) # 1.0
```

float()

The concepts of `int()` and `float()` are quite similar.

```
a = 10          # int
print(float(a)) # 10.0
                # From int -> float
```

```
b = 3.7         # float
print(float(b)) # 3.7
                # Nothing happens
```

```
c = True        # boolean
print(float(c)) # 1.0
```

```
d = False       # boolean
print(float(d))
```

float()

The concepts of `int()` and `float()` are quite similar.

```
a = 10          # int
print(float(a)) # 10.0
                # From int -> float
```

```
b = 3.7         # float
print(float(b)) # 3.7
                # Nothing happens
```

```
c = True        # boolean
print(float(c)) # 1.0
```

```
d = False       # boolean
print(float(d)) # 0.0
```

float()

```
i = "123abc"    # string  
print(float(i))
```

float()

```
i = "123abc"    # string  
print(float(i)) # Error
```

float()

```
i = "123abc"    # string
print(float(i)) # Error

j = "123"       # string with ONLY numbers
print(float(j))
```


float()

```
i = "123abc"    # string  
print(float(i)) # Error
```

```
j = "123"       # string with ONLY numbers  
print(float(j)) # 123.0
```

float()

```
i = "123abc"    # string  
print(float(i)) # Error
```

```
j = "123"       # string with ONLY numbers  
print(float(j)) # 123.0
```

```
k = "123.123"   # string with ONLY numbers, but with  
                # a number that represents a float  
print(float(k))
```

float()

```
i = "123abc"    # string  
print(float(i)) # Error
```

```
j = "123"       # string with ONLY numbers  
print(float(j)) # 123.0
```

```
k = "123.123"   # string with ONLY numbers, but with  
                # a number that represents a float  
print(float(k)) # 123.123
```

str()

All of the 3 data types below can be transformed into strings.

str()

All of the 3 data types below can be transformed into strings.

```
a = 10          # int  
print(str(a))
```

str()

All of the 3 data types below can be transformed into strings.

```
a = 10          # int  
print(str(a))  # 10
```

str()

All of the 3 data types below can be transformed into strings.

```
a = 10          # int  
print(str(a))  # 10
```

```
b = 3.7         # float  
print(str(b))
```

str()

All of the 3 data types below can be transformed into strings.

```
a = 10          # int  
print(str(a))  # 10
```

```
b = 3.7         # float  
print(str(b))  # 3.7
```


str()

All of the 3 data types below can be transformed into strings.

```
a = 10          # int
print(str(a))  # 10
```

```
b = 3.7         # float
print(str(b))  # 3.7
```

```
c = True        # boolean
print(str(c))
```

str()

All of the 3 data types below can be transformed into strings.

```
a = 10          # int  
print(str(a))  # 10
```

```
b = 3.7         # float  
print(str(b))  # 3.7
```

```
c = True        # boolean  
print(str(c))  # True
```

str()

All of the 3 data types below can be transformed into strings.

```
a = 10          # int
print(str(a))  # 10
```

```
b = 3.7         # float
print(str(b))  # 3.7
```

```
c = True        # boolean
print(str(c))  # True
```

```
d = False       # boolean
print(str(d))
```

str()

All of the 3 data types below can be transformed into strings.

```
a = 10          # int
print(str(a))  # 10
```

```
b = 3.7         # float
print(str(b))  # 3.7
```

```
c = True        # boolean
print(str(c))  # True
```

```
d = False       # boolean
print(str(d))  # False
```

str()

```
e = "abcdef"    # string  
print(str(e))
```

str()

```
e = "abcdef"    # string  
print(str(e))   # abcdef
```

str()

```
e = "abcdef"    # string
print(str(e))   # abcdef
                # Nothing happens
```

bool()

```
a = 0          # int  
print(bool(a))
```


bool()

```
a = 0          # int  
print(bool(a)) # False
```

bool()

```
a = 0                # int
print(bool(a))      # False
                    # 0 means False
```

bool()

```
a = 0                # int
print(bool(a))       # False
                     # 0 means False
```

```
b = 3.7              # float
print(bool(b))
```

bool()

```
a = 0                # int
print(bool(a))       # False
                    # 0 means False
```

```
b = 3.7              # float
print(bool(b))       # True
```

bool()

```
a = 0                # int
print(bool(a))      # False
                    # 0 means False
```

```
b = 3.7              # float
print(bool(b))      # True
```

True and False values

Any integers or floats, if they are not zero, then `bool()` returns `True`, `False` otherwise.

bool()

```
a = 0                # int
print(bool(a))      # False
                    # 0 means False
```

```
b = 3.7              # float
print(bool(b))      # True
```

True and False values

Any integers or floats, if they are not zero, then bool() returns True, False otherwise.

```
c = True             # boolean
print(bool(c))      # True
```

```
d = False            # boolean
print(bool(d))      # False
```

bool()

```
a = 0                # int
print(bool(a))      # False
                    # 0 means False
```

```
b = 3.7              # float
print(bool(b))      # True
```

True and False values

Any integers or floats, if they are not zero, then bool() returns True, False otherwise.

```
c = True            # boolean
print(bool(c))      # True
```

```
d = False           # boolean
print(bool(d))      # False
                    # Nothing happens for the 2 above
```

bool()

`bool()`, when applied to a string, checks whether it has content:

bool()

bool(), when applied to a string, checks whether it has content:

```
e = "abcdefg"
print(bool(e)) # True
f = "False"
print(bool(f)) # True
g = " tRuE "
print(bool(g)) # True
h = "0"
print(bool(h)) # True
i = ""
print(bool(i)) # False
```

Strings

If the string has a length > 0 , then bool() returns True, False otherwise.

Example of input and type conversion

```
age = int(input("How old are you? "))  
print("You are", age, "years old.")
```

Example of input and type conversion

```
age = int(input("How old are you? "))  
print("You are", age, "years old.")
```

Running the program:

How old are you? 69

Example of input and type conversion

```
age = int(input("How old are you? "))  
print("You are", age, "years old.")
```

Running the program:

```
How old are you? 69  
You are 69 years old.
```

Example of input and type conversion

```
age = int(input("How old are you? "))  
print("You are", age, "years old.")
```

Running the program:

```
How old are you? 69  
You are 69 years old.
```

Invalid input

If the input does not contain *only* an integer, then the program would throw an error.

Example of input and type conversion

```
age = int(input("How old are you? "))  
print("You are", age, "years old.")
```

Running the program with an invalid input:

How old are you? *69.420*

Example of input and type conversion

```
age = int(input("How old are you? "))  
print("You are", age, "years old.")
```

Running the program with an invalid input:

How old are you? *69.420*

Traceback (most recent call last):

File "<stdin>", line 1, in <module>

ValueError: invalid literal for int() with base 10: '69.420'

Example of input and type conversion

```
age = int(input("How old are you? "))  
print("You are", age, "years old.")
```

Running the program with an invalid input:

How old are you? 69.420

Traceback (most recent call last):

File "<stdin>", line 1, in <module>

ValueError: invalid literal for int() with base 10: '69.420'

Invalid input

This also applies to data types like boolean values and strings.

Summary

Variable types

There are 4 basic variable types: `int`, `bool`, `float` and `str`.

Arithmetic Operators

Some basic and commonly-used operators:

<code>+</code> :	add	<code>-</code> :	minus,
<code>*</code> :	multiply	<code>/</code> :	divide,
<code>//</code> :	quotient	<code>%</code> :	remainder,
<code>**</code> :	power		

Summary

The print() statement

```
print(*objects, sep=' ', end='\n', file=None, flush=False)
```

`*objects` - the things you want to print,

`sep` - the string that separates objects (when using commas),

`end` - the string to end the print statement with.

The other arguments can be ignored as they are rarely used.

Type Conversion

To convert between types, you can simply surround the target with brackets, and call the type.

```
int -> int(); bool -> bool(); float -> float(); str -> str().
```

End of Additional Contents
Made in L^AT_EX
Last updated: 9 Apr 2024