```
function const = update4Const(p1,val1,p2,val2,p3,val3,p4,val4)
% This function is the same as updateConst, just working for 4 different
% parameters. This function works for exactly 4 values. No more, no less.
% INPUTS:
% p(i) is a string, the name of the struct value being changed. In
% order for this function to work, it must be identical to the name of the
% value in struct
% val(i) is the value being changed to.
% OUTPUTS:
% const is the const struct that will be used in the calculations
const.g = 9.807; %m/s^2 (gravitational constant)
   const.c dis = 0.8; %(Discharge constant)
   const.rho_air = 0.961; %kg/m^3 (Density of ambient air)
   const.V_b = 0.002; %m^3 (Volume of bottle)
   const.p_atm = 12.1 * 6894.76; %psia to Pa (pressure of atmosphere)
   const.gamma = 1.4; %unitless (specific heat reatio constant)
   const.rho_w = 1000; %kg/m^3 (density of water)
   const.d_e = 2.1; %cm (diameter of exit)
   const.d_b = 10.5; %cm (diameter of bottle)
   const.R_air = 287; %J/kgK (Gas constant for air)
   const.m b = 0.15; %kg (mass of bottle)
   const.c_D = 0.48; %Coefficient of drag)
   const.p_0 = 52* 6894.76 + const.p_atm; %psig to Pa (initial pressure in
bottle)
   const.V_0w = 0.00095; %m^3 (Initial volume of water)
   const.T_0 = 300; %k (Initial temperature of air)
   const.v_0 = 0.0; %m/s (initial velocity)
   const.theta_i = 42*(pi/180); % degrees to radian (launch angle)
   const.x_0 = 0; %m (initial x position)
   const.z_0 = 0.25; %m (initial z position)
   const.l_s = 0.5; %m (length of launch stand)
   Reassigning the values
   const.(p1) = val1;
   const.(p2) = val2;
   const.(p3) = val3;
   const.(p4) = val4;
   %Calculating values that may or may not change based on the inputted
   %parameter values
```

```
const.At = pi*((const.d_e/2)*0.01)^2; %m^2 (Cross sectional area of
throat)
    const.Ab = pi*((const.d_b/2)*0.01)^2; %m^2 (Cross sectional area of
bottle)

    const.m_0w = const.rho_w * const.V_0w; %kg (initial mass of water)
    rho_0a = const.p_0/(const.R_air*const.T_0); %kg/m^3 (initial density of
air)
    const.V_0a = const.V_b - const.V_0w; %m^3 (Initial volume of air)
    const.m_0a = const.V_0a * rho_0a; %kg (initial mass of air)

    const.m_0tot = const.m_b + const.rho_w * (const.V_b - const.V_0a) +
    (const.p_0*const.V_0a)/(const.R_air*const.T_0);
end

Not enough input arguments.

Error in update4Const (line 45)
    const.(p1) = vall;
```

Published with MATLAB® R2023a