



Contents

- **50 Overview of Web and security vulnerabilities**
- **∞ Cross Site Scripting**
- **∞ Cross Site Request Forgery**

2





| B | - | | 1 | J |
|---|---|--------------------------|---|---|
| I | | $\overline{\mathscr{C}}$ | 4 | - |
| 4 | Ų | 1 | | > |
| 8 | ~ | y | ~ | b |

Cookie Quiz


| Which of the following are true statements? |
|--|
| Cookies are created by ads that run on websites |
| Cookies are created by websites a user is visiting |
| Cookies are compiled pieces of code |
| Cookies can be used as a form of virus |
| Cookies can be used as a form of spyware |
| All of the above |
| |
| |

The Web and Security



- Web page contains both static and dynamic contents, e.g.,
 JavaScript
 - •Sent from a web site(s)
 - •Run on the user's browser/machine

The Web and Security



- •Web sites run applications (e.g., PHP) to generate response/page
 - According to requests from a user/browser
 - Often communicate with backend servers



Web Browser Quiz

| Mark each statement as true or false. |
|--|
| Web browser can be attacked by any web site that it visits |
| Even if a browser is compromised, the rest of the computer is still secure |
| Web servers can be compromised because of exploits on web applications |
| |
| |

Cross-Site Scripting (XSS)


If a website allows users to input content without controls, then attackers can insert malicious code as well.




- Social networking sites, blogs, forums, wikis
- Suppose a website echoes user-supplied data, e.g., his name, back to user on the html page


Cross-Site Scripting (XSS)

Suppose the browser sends to the site <script type="text/javascript">alert("Hello World"); </script> as his "name"



- •What if the script is malicious, and the browser had sent it without the user knowing about it?
 - •But can this happen?






XSRF: Cross-Site Request Forgery



- A browser runs a script from a "good" site and a malicious script from a "bad" site
- Malicious script can make forged requests to "good" site with user's cookie




XSRF: Example

<form name=BillPayForm
action=http://bank.com/BillPay.php>
<input name=recipient value=badguy>
...
<script>

document.BillPayForm.submit();


</script>





XSRF vs XSS

- Cross-site scripting
 - •User trusts a badly implemented website
 - Attacker injects a script into the trusted website
 - User's browser executes attacker's script
- Cross-site request forgery
 - A badly implemented website trusts the user
 - Attacker tricks user's browser into issuing requests
 - Website executes attacker's requests



Web Security - Lesson Summary

- Both browser and servers are vulnerable: dynamic contents based on user input
- XSS: attacker injects a script into a website and the user's browser executes it
- XSRF: attacker tricks user's browser into issuing request, and the website executes it

Practice web security

- Use Damn Vulnerable Web App (DVWA) to execute some website attacks:
 - XSS
 - XSRF
 - •....

