









Name length = 2 char (min) Name length = 24 char (median) Name length = 25.9 char (mean) Name length = 83 char (max)





IEEE 802.15.4+6LoWPAN worst header
CoAP "worst" header (URI-Path "/dns")






IEEE 802.15.4+6LoWPAN worst header
CoAP "best" header (URI-Path "/d")







IEEE 802.15.4+6LoWPAN worst header
CoAP with OSCORE, Content-Format and URI-Path "/dns"






IEEE 802.15.4+6LoWPAN best header (w/o L2 security)
CoAP "worst" header (URI-Path "/dns")







IEEE 802.15.4+6LoWPAN best header (w/o L2 security)
CoAP "best" header (URI-Path "/d")







IEEE 802.15.4+6LoWPAN best header (w/o L2 security)
CoAP with OSCORE, Content-Format and URI-Path "/dns"







IEEE 802.15.4+6LoWPAN best header (w/ L2 security, 16-bit key)
CoAP "worst" header (URI-Path "/dns")







IEEE 802.15.4+6LoWPAN best header (w/ L2 security, 16-bit key)
CoAP "best" header (URI-Path "/d")







IEEE 802.15.4+6LoWPAN best header (w/ L2 security, 16-bit key)
CoAP with OSCORE, Content-Format and URI-Path "/dns"







IEEE 802.15.4+6LoWPAN RIOT-most (w/o L2 security)
CoAP "worst" header (URI-Path "/dns")







IEEE 802.15.4+6LoWPAN RIOT-most (w/o L2 security)
CoAP "best" header (URI-Path "/d")







IEEE 802.15.4+6LoWPAN RIOT-most (w/o L2 security)
CoAP with OSCORE, Content-Format and URI-Path "/dns"



IEEE 802.15.4+6LoWPAN RIOT-most (w/ L2 security)
CoAP "worst" header (URI-Path "/dns")



IEEE 802.15.4+6LoWPAN RIOT-most (w/ L2 security)
CoAP "best" header (URI-Path "/d")



IEEE 802.15.4+6LoWPAN RIOT-most (w/ L2 security)
CoAP with OSCORE, Content-Format and URI-Path "/dns"

