



DATASHEET | MAY 2022

Transforming Navigation



Applications

- General Aviation / Flight Control
- AHRS (Attitude Heading Reference System)
- GPS-aided Navigation
- Autonomous Vehicles
- Remotely Operated Vehicles
- Aerial and Marine Geomapping / Surveying
- Commercial Pipeline Inspection
- Mining / Agriculture
- Robotics

Key Performance Features

- 1 to 20°/hr Gyro Bias Over Temperature
- 19 in.3 Compact Size
- 12 g rms, Vibration Operating Performance Environment (20-2,000 Hz random)
- Superior Quality & Reliability
- Greater Than 100,000 hr MTBF
- Data Time of Validity (TOV) Input & Output Synchronization
- Smaller, Lower Power, and Cost-Effective Replacement for open-loop Fiber Optical Gyro (FOG) IMU

Ideal for High-Precision Civil & Industrial Applications

The compact SDC500 Quartz MEMS Inertial Measurement Unit (IMU) meets commercial aerospace, industrial and marine application needs globally. It is available in several performance-cost options ranging from 1°/hr / 1 mg to 20°/hr / 5 mg over thermal, shock and vibration environments. The SDC500 IMU is constructed with EMCORE's latest generation quartz gyros, quartz accelerometers, and high-speed signal processing to achieve outstanding precision performance. The SDC500's breakthrough gyro design retains Quartz MEMS sensitivity and linearity and greatly improves noise immunity.



The small, light, low-power, hermetically sealed SDC500 IMU provides industry-standard serial communication, configurable communications protocols, TOV sync, continuous Built-in Test (BIT), electromagnetic interference (EMI) protection, long MTBF and flexible input power compatibility making the SDC500 IMU easy to use in a wide range of challenging applications and operating environments.

Performance Highlights

Parameter	SDC500-AA00	SDC500-BA00	SDC500-CA00	SDC500-DA00
Gyro Performance				
Bias (over temperature) 1 σ	1.0°/hr	3.0°/hr	10.0°/hr	20.0°/hr
Bias In-Run Stability 1 σ	1.0°/hr	1.5°/hr	3.0°/hr	5.0°/hr
Angle Random Walk (max)	0.02°/√hr	0.02°/√hr	0.03°/√hr	0.04°/√hr
Bandwidth, Phase Shift (-90o Phase) (min)	90Hz	90Hz	90Hz	90Hz
Accelerometer Performance				
Bias Variation (over temperature) 1 σ	1.0 milli-g	2.0 milli-g	3.0 milli-g	5.0 milli-g
Bias In-Run Stability 1 σ	150 μ g	200 μ g	250 μ g	400 μ g
Velocity Random Walk 1 σ	100 μ g/√Hz	120 μ g/√Hz	150 μ g/√Hz	200 μ g/√Hz



SDC500

Non-ITAR Quartz MEMS Inertial Measurement Unit

Transforming Navigation

Performance Specifications

Specifications are based on 100 Hz Inertial Data ($\Delta V/\Delta \theta$)

Parameter	SDC500-AA00	SDC500-BA00	SDC500-CA00	SDC500-DA00
System Performance				
Start-Up Time for Valid Data Output (max)	<1.5 secs	<1.5 secs	<2.0 secs	<2.0 secs
Gyro Channels				
Bias (over temperature) 1σ	1.0°/hr	3.0°/hr	10.0°/hr	20.0°/hr
Bias In-Run Stability 1σ	1.0°/hr	1.5°/hr	3.0°/hr	5.0°/hr
Scale Factor Error 1σ	200 ppm	200 ppm	250 ppm	400 ppm
Angle Random Walk (max)	0.02°/√hr	0.02°/√hr	0.03°/√hr	0.04°/√hr
Bandwidth, Phase Shift (-90° Phase) (min)	90Hz	90Hz	90Hz	90Hz
Angular Rate – Dynamic Range (min)	±490°/sec	±490°/sec	±490°/sec	±490°/sec
Accelerometer Channels				
Bias Variation (over temperature) 1σ	1.0 milli-g	2.0 milli-g	3.0 milli-g	5.0 milli-g
Bias In-Run Stability 1σ	150 µg	200 µg	250 µg	400 µg
Scale Factor Error 1σ	200 ppm	200 ppm	250 ppm	400 ppm
Velocity Random Walk 1σ	100 µg/√Hz	120 µg/√Hz	150 µg/√Hz	200 µg/√Hz
Acceleration - Calibrated Range (min)	±20g	±20g	±20g	±20g
System Physical & Environmental				
Input Voltage	10 to 42 Vdc			
Power	<5.0 watts			
I/O	RS232/422			
Data Synchronization Pulse	(1Hz, 100Hz, 200Hz, 400Hz, 600Hz, 1200Hz Input or Output) and (2400Hz Output only)			
Dimensions (height x diameter)	2.9 x 2.9 inches			
Volume	19 cu in			
Weight	1.3 lbs			
Temperature	-40 to +71°C			
Vibration (Operating/Survival)	12 g, rms			
Shock	150, 11 g, ms			
MTBF @ 35o C (ground benign)	100,000 hrs			

Dimensions/Scale



For More Information

+1 866.234.4976 | navigation-sales@emcore.com | emcore.com/nav

EMCORE Corporation


2015 Chestnut Street
Alhambra, CA 91803 USA

P +1 626.293.3700

F +1 626.293.3429

emcore®

ISO9001
CERTIFIED



© 2022 EMCORE Corporation. All rights reserved.

Information contained herein is deemed to be reliable and accurate as of issue date. EMCORE reserves the right to change the design or specifications of our products at any time without notice. EMCORE and Systron Donner Inertial are registered trademarks of EMCORE Corporation in the U.S. and other countries.

**MADE IN
USA**

Released 05.05.2022