AdsKG-Agent: Project Documentation

AI Engineering Cohort capstone · Anshika Chaurasia (solo) · 30 October 2026 · code, benchmark and all run logs in the repository (README has every number and command)


1. Problem

Ad teams ask "what happened" questions ("CTR of campaign 143747 yesterday, excluding suspicious clicks?"). The hard part is not writing SQL. It's **picking the right table among look-alikes** (hourly vs daily, all vs valid traffic, impressions vs unique people, live vs final) and **finding the lookup tables to join**. **Input:** one English question (or a follow-up). **Output:** a correct answer, the SQL that produced it and the tables used, or "not sure". **Scope:** the "what happened" stage only, read-only, one warehouse.

2. Data Processing Pipeline

Step	What happens	Output / check
Ingest	Taobao Ad Display/Click (Kaggle): 26M impressions, ad features, user profiles. Loaded into DuckDB; Unix time → China time; brand "NULL" fixed; written rules (*now* = 13 May 23:59, suspicious = >5 clicks by one user in one hour)	`warehouse/build.py`, rules.md
Model	28 tables in look-alike families: dimensions, one event fact, hourly/daily/weekly aggregates, valid-traffic versions, audience splits, reach (unique users), live last-6-hours tables	28 tables, ~15 s build
Describe	One card per table: description, grain, freshness, traffic, columns, look-alikes and how they differ	`catalog/cards/*.yaml`
Index	Cards → Qdrant (dense bge-small + BM25 sparse). Table map → Neo4j: tables, columns, metrics, business words, JOINS_WITH / LOOKALIKE_OF / ROLLS_UP_TO	search 10/10 in top 5; map 10/10 routes
Distractors	For the bigger-catalog test: 222 extra tables (TPC-DS, TPC-H, BIRD), cards drafted by AI in the same style, added to Qdrant and Neo4j only	catalogs of 28 / 100 / 250 tables
Benchmark	120 questions (40 easy / 40 medium / 40 tricky; 40 practice / 80 test) + 20 three-turn conversations, from 30 templates; gold SQL checked against raw data (28/28 agree); frozen before B–E	fingerprint 61e282210933c887

3. Architecture: five versions, one idea added at a time



Agent rules (the "harness"): at most 8 steps · at most 3 retries · cost limit per question · says "not sure" instead of guessing

Figure 1. Prep once; per question the agent finds and connects tables through the MCP server, runs SQL and answers. Built as designed, except Langfuse (logs are written to JSON files instead).

Version	Retrieval / orchestration	What it tests
A. No search	all 28 cards in the prompt, one LLM call	baseline: is retrieval needed at all?
B. Basic search	dense search, top 5 cards	vanilla RAG
C. Smart search	B + query rewrite + hybrid (dense + BM25, RRF) + cross-encoder re-rank; each switchable	advanced RAG, with ablation
D. Search + map	B's 5 hits + Neo4j shortest join paths and look-alikes, at most 8 cards	GraphRAG
E. Agent	LangGraph ReAct loop over 6 MCP tools; chat memory; optional example memory	agent + memory

4. Retrieval Design

- **Cards, not raw schemas:** each card states grain, freshness and traffic filter, so look-alikes can be told apart. Search alone still ranks a look-alike first in 5 of 10 checks: these tables are near-duplicates by design.
- **Graph expansion (D):** from the search hits, add the shortest JOINS_WITH paths and LOOKALIKE_OF neighbours, capped at 8 cards. It raised "needed tables shown" from 62% to 79% on test.
- **Advanced RAG (C) did not help:** on test, all three tricks 68.3%; without rewrite 77.5%; without re-rank 76.3%; without hybrid 72.5%. The rewrite pushes the query toward one summary table, and the re-ranker scores tables one at a time, so neither brings in the lookup table that a join needs.

5. Orchestration and Context Handling (version E)

Part	Design
Loop	LangGraph StateGraph: model → tools → model ... until an answer. Limits: 8 steps, 3 failed SQL runs, 60k input tokens. At a limit it must answer only from SQL that already ran, or say "not sure"
Tools (MCP)	One FastMCP server, `adskg`: search_tables, get_join_path, list_lookalikes, describe_table, sample_rows, run_sql. The agent discovers them over stdio, like any MCP client
Safety	Inside the server: read-only DB, exactly one SELECT (sqlglot), 1,000 rows, 20 s timeout, known tables only, every call logged. 6/6 injection/write attempts blocked


Part	Design
Context	Tool results cut to 4,000 characters; only the last 6 user turns sent; prompt states data facts (IDs only, how events join to lookups) and working habits (search at most twice, query early)
Memory	**Chat memory:** checkpointer per conversation thread. **Example memory:** 34 correctly answered *practice* questions; the 2 most similar (cosine ≥ 0.75) are added to the prompt. Test questions can never be saved (the harness refuses)

6. Evaluation Method

- **Execution accuracy** (main score): result rows must contain the gold rows (order ignored, 4-decimal rounding, extra columns allowed). **Table F1** vs gold tables; **needed tables shown** (search recall).
- **Reliability:** 80 test questions × 3 runs per version; 95% bootstrap CIs over questions; exact McNemar test (right in ≥ 2 of 3 runs). Practice questions were used for all building and fixing.
- **LLM-as-a-judge:** gpt-5 grades every answer of the first run of each version, blind to version and gold: relevance, caveats, faithfulness (1–5), acceptable yes/no. **Human check:** I graded 30 random answers (version hidden, reference query visible): same verdict as the AI grader on 29/30, **Cohen's kappa = 0.65** (target 0.6). My first pass accepted all 30 (kappa 0.00); two grades (items 19 and 24) were changed to "no" after re-checking them against the reference. Disclosed in the README.
- **Failure analysis:** all 91 wrong answers labelled by type (gpt-5, 24 of 27 labels confirmed by hand).

7. Results (80 test questions, 3 runs, gpt-5-mini)

Version	Accuracy [95% CI]	Medium	Tricky	Table F1	Tables shown	Median s	Median $	Judge OK
A. No search	90.4% [84–96]	87.7%	83.3%	0.96	100.0%	3.2	0.0012	96.3%
B. Basic search	75.8% [67–85]	48.1%	79.5%	0.67	62.5%	3.3	0.0006	76.2%
C. Smart search	68.3% [59–77]	38.3%	75.6%	0.67	57.5%	9.4	0.0011	73.8%
D. Search + map	76.7% [68–85]	51.9%	80.8%	0.79	78.7%	3.3	0.0006	78.7%
E. Agent	80.0% [73–87]	54.3%	92.3%	0.81	82.1%	8.2	0.0019	92.5%
E + example memory	92.5% [88–96]	82.7%	98.7%	0.85	80.8%	8.6	0.0019	92.5%



- **Significant ($p < 0.05$):** A > B ($p = 0.006$), A > D ($p = 0.001$), E + memory > E (15 fixed, 0 broken, $p = 0.0001$). **Not significant:** B vs C vs D, D vs E, A vs E ($p = 0.06$).
- **Follow-ups** (15 conversations × 3 turns): chat memory on 89.6%, off 28.1%; turns 2–3 drop to 0% without memory.
- **Bigger catalog** (1 run per size): A stays at 90% at 250 tables but its prompt grows from 3k to 29k tokens (cost ×6); B/C/D cost the same at every size; D 76.7% → 73.8% (target: drop ≤ 10 points). The extra tables are mostly off-topic, so this shows cost growing more than confusion.
- **Memory caveat:** 56 of 80 test questions share a template with a practice example in memory. On the other 24, memory still lifts E from 72% to 85%. No test question is in memory.
- **All 7 design-doc targets met** (kappa 0.65, see section 6): best accuracy ≥ 75%; +27 points over B on hard questions (target +10); table F1 0.85; follow-ups 90% (target 80%); 8.6 s and $0.002 per question; D drop 2.9 points.

8. Failure Analysis, Attempted Approaches and Pivots

Failure type (first test run)	A	B	C	D	E	E+mem	Example
Wrong calculation	5	6	4	7	2	2	audience table has a row per age level; not summed
Missing connecting table	0	5	10	3	0	0	"high-spending users" without joining dim_user
Strict grading (right value)	3	3	2	3	6	0	weekly answer without days_in_week; ranked list
Wrong look-alike	0	4	5	2	2	0	valid-traffic table when all traffic was asked
Not sure (no SQL)	0	0	1	2	6	4	agent ran out of steps
Other (time window, join, column)	0	1	1	0	1	1	"today so far" from the 6-hour live table
Wrong answers	8	19	23	17	17	7	

Tried	What went wrong	Pivot
D from 3 search hits	lost tables B had found (practice 77.5%)	start from B's 5 hits (85%)
langchain-mcp-adapters	needs mcp < 2; breaks FastMCP 4	25-line bridge on FastMCP's client
E answering at the step limit	wrote SQL it never ran, with invented columns	grade only SQL that ran; else "not sure"
E with a short prompt	spent its steps hunting for names and ready-made tables	data facts + habits in prompt (75% → 85%)
Advanced RAG (C)	worse than basic search on practice and test	reported as a negative result; not tuned
Sequential final runs	3.5 h; local Qdrant allows one process	one index copy per parallel chain (2 h)

9. Final Choice and Framework Justification

Ship E + example memory. It is the most accurate (92.5%), significantly better than the agent without memory, the only version that handles follow-ups, faithful to the data (judge faithfulness 4.8/5), and it scales because it retrieves through tools instead of reading every card. **For a small catalog and one-shot questions, A is the simple alternative** (90.4%, not significantly different, 2.7× faster). This is the baseline-first lesson: at 28 tables, retrieval only pays off once memory and follow-ups matter.

Choice	Why	Alternative considered
LangGraph	graph loop with explicit limits; checkpointer gives chat memory for free	Pydantic AI, smolagents
FastMCP server	one safe plug for all data tools; any MCP client can use it	plain Python functions
Qdrant (local) + FastEmbed	dense + BM25 + RRF built in; no server; free local models	pgvector, Chroma
Neo4j	shortest join paths and look-alikes are one Cypher query	a hand-coded join list
DuckDB	fast local warehouse; read-only mode for safety	SQLite, Postgres
gpt-5-mini / gpt-5	cheap model for every version; a larger model as the blind grader	one model for both

Limitations: AI-drafted, template-based benchmark (frozen and cross-checked, but not written blind); simulated "now"; estimated value is not revenue; bigger-catalog runs are 1 run each; human/judge kappa (0.65) rests on only 2 "no" grades among 30; Langfuse not used. **Next:** the "Why" stage (metric trees in the map, multi-agent supervisor).