

```
exp12.java
// Employee.java
package com.example.employeeapi;
import jakarta.persistence.Entity;
import jakarta.persistence.Id;
@Entity
public class Employee {
    @Id
    private int id;
    private String name;
    private String department;
    private double salary;
    public Employee() {
    }
    public Employee(int id, String name, String department, double salary) {
        this.id = id;
        this.name = name;
        this.department = department;
        this.salary = salary;
    }
    public int getId() {
        return id;
    }
    public void setId(int id) {
        this.id = id;
    }
    public String getName() {
        return name;
    }
    public void setName(String name) {
        this.name = name;
    }
    public String getDepartment() {
        return department;
    }
    public void setDepartment(String department) {
        this.department = department;
    }
    public double getSalary() {
        return salary;
    }
}
```

```

    }
    public void setSalary(double salary) {
        this.salary = salary;
    }
}

// EmployeeRepository.java
package com.example.employeeapi;
import org.springframework.data.jpa.repository.JpaRepository;
public interface EmployeeRepository extends JpaRepository<Employee, Integer> {
}

// EmployeeService.java
package com.example.employeeapi;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;
import java.util.List;
import java.util.Optional;
@Service
public class EmployeeService {
    @Autowired
    private EmployeeRepository repository;
    public Employee addEmployee(Employee employee) {
        return repository.save(employee);
    }
    public List<Employee> getAllEmployees() {
        return repository.findAll();
    }
    public Optional<Employee> getEmployeeById(int id) {
        return repository.findById(id);
    }
    public Employee updateEmployee(Employee employee) {
        return repository.save(employee);
    }
    public void deleteEmployee(int id) {
        repository.deleteById(id);
    }
}

// EmployeeController.java
package com.example.employeeapi;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.web.bind.annotation.*;

```

```

import java.util.List;
import java.util.Optional;
@RestController
@RequestMapping("/employees")
public class EmployeeController {
    @Autowired
    private EmployeeService service;
    @PostMapping
    public Employee addEmployee(@RequestBody Employee employee) {
        return service.addEmployee(employee);
    }
    @GetMapping
    public List<Employee> getAllEmployees() {
        return service.getAllEmployees();
    }
    @GetMapping("/{id}")
    public Optional<Employee> getEmployeeById(@PathVariable int id) {
        return service.getEmployeeById(id);
    }
    @PutMapping
    public Employee updateEmployee(@RequestBody Employee employee) {
        return service.updateEmployee(employee);
    }
    @DeleteMapping("/{id}")
    public String deleteEmployee(@PathVariable int id) {
        service.deleteEmployee(id);
        return "Employee deleted successfully";
    }
}

// EmployeeApiApplication.java
package com.example.employeeapi;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
@SpringBootApplication
public class EmployeeApiApplication {
    public static void main(String[] args) {
    }
}

SpringApplication.run(EmployeeApiApplication.class, args)}

```