

FOCP-II

This project is a C++ console application that generates funny roast messages using AI-assisted code generation.

The program takes user input and displays a random roast message.

PROMPTS USED

ChatGPT

Write a beginner-friendly C++ console program that generates funny roast messages. Requirements: 1- Ask the user to enter their name
2- Store at least 8–10 funny roast templates in a vector
3-Each template must include a placeholder {name}
4-Use a random function to select one roast from the vector
5-Use srand(time(0)) so that a different roast appears each time the program runs
6-Replace the {name} placeholder with the actual user input
7-Display the final roast message clearly on the console
8-Add proper comments in the code so a beginner can understand it easily
Here are some additional info that you can use-
1- Make the roasts creative, funny, and safe
2-Ensure the program does not crash on invalid or empty input
3-Keep the code simple and readable

Here's a clean, beginner-friendly C++ console program that meets all your requirements. It's simple, safe, and well-commented so you can understand every step.

Features covered:

Ask anything

ChatGPT can make mistakes. Check important info. See [Cookie Preferences](#).

ChatGPT

My C++ program is generating the same roast every time I run it, even though I am using rand().

Here is the code:

```
#include <iostream>
#include <vector>
#include <cstdlib>
#include <ctime>
#include <string>

using namespace std;

// Function to replace {name} with actual user name
string replaceName(string roast, string name) {
    size_t pos = roast.find("{name}");

    if (pos != string::npos) {
        roast.replace(pos, 6, name);
    }

    return roast;
}
```

Ask anything

ChatGPT can make mistakes. Check important info. See [Cookie Preferences](#).

ChatGPT

```
if (pos != string::npos) {
    roast.replace(pos, 6, name);
}

return roast;
}

int main() {

    srand(1);

    string name;

    // Ask user for input
    cout << "Enter your name: ";
    getline(cin, name);

    // Handle empty input
    if (name.empty()) {
        name = "Mystery Person";
    }

    // Roast templates (clean ASCII)
    vector<string> roasts = {
```

Ask anything

ChatGPT can make mistakes. Check important info. See [Cookie Preferences](#).

ChatGPT

```
// Roast templates (clean ASCII)
vector<string> roasts = {
    "{name}, you're not useless... you could be used as a bad example.",
    "{name}, if laziness were a sport, you'd come second... because you'd be too lazy to come first.",
    "{name}, your brain has more buffering than a slow YouTube video.",
    "{name}, you're like a cloud... when you disappear, it's a beautiful day.",
    "{name}, I'd explain it to you, but I left my crayons at home.",
    "{name}, you bring everyone so much joy... when you leave the room.",
    "{name}, you're proof that even Google doesn't have all the answers.",
    "{name}, you have something on your chin... no, the third one down.",
    "{name}, you're like a software update - nobody likes you when you show up.",
    "{name}, your secrets are always safe with me... I never even listen!"
};
```

Ask anything

ChatGPT can make mistakes. Check important info. See [Cookie Preferences](#).

ChatGPT ▾

 Share ...

listen!

};

```
// Random selection (but bug makes it same every time)
int randomIndex = rand() % roasts.size();
string selectedRoast = roasts[randomIndex];
```

```
// Replace placeholder
string finalRoast = replaceName(selectedRoast, name);
```

```
// Output
cout << "\nHere's your roast:\n";
cout << finalRoast << endl;
```

```
return 0;
```

}

I think there is an issue with random number generation.

Please fix the issue and explain the problem in simple terms.



You're right—the issue is with your random number setup, but it's actually a **very common beginner**

mistake! 🤔

+ Ask anything



Bug Description

The program was generating the same roast every time due to incorrect random seed initialization.

Bug Fix Explanation

The issue was caused by using `srand(1)`, which sets a fixed seed. Replacing it with `srand(time(0))` ensures different outputs each time the program runs.

BEFORE

```
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
Code + - [ ] [ ] ... | [ ] [ ] X

PS C:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT> cd "c:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT\" ; if ($?) { g++ AIroastgenerator.cpp -o AIroastgenerator } ; if ($?) { .\AIroastgenerator }
● Enter your name: ansh

Here's your roast:
ansh, if laziness were a sport, you'd come second... because you'd be too lazy to come first.
PS C:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT> cd "c:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT\" ; if ($?) { g++ AIroastgenerator.cpp -o AIroastgenerator } ; if ($?) { .\AIroastgenerator }
● Enter your name: raman

Here's your roast:
raman, if laziness were a sport, you'd come second... because you'd be too lazy to come first.
● PS C:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT> cd "c:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT\" ; if ($?) { g++ AIroastgenerator.cpp -o AIroastgenerator } ; if ($?) { .\AIroastgenerator }
Enter your name: aryan

Here's your roast:
aryan, if laziness were a sport, you'd come second... because you'd be too lazy to come first.
○ PS C:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT> 
```

AFTER

```
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
Code + - [ ] [ ] ... | [ ] [ ] X

● PS C:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT> cd "c:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT\" ; if ($?) { g++ AIroastgenerator.cpp -o AIroastgenerator } ; if ($?) { .\AIroastgenerator }
Enter your name: ansh

Here's your roast:
ansh, you're not useless... you could be used as a bad example.
● PS C:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT> cd "c:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT\" ; if ($?) { g++ AIroastgenerator.cpp -o AIroastgenerator } ; if ($?) { .\AIroastgenerator }
Enter your name: raman

Here's your roast:
raman, you bring everyone so much joy... when you leave the room.
PS C:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT> cd "c:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT\" ; if ($?) { g++ AIroastgenerator.cpp -o AIroastgenerator } ; if ($?) { .\AIroastgenerator }
● Enter your name: aryan

Here's your roast:
aryan, your brain has more buffering than a slow YouTube video.
○ PS C:\Users\Ansh Kumar\Desktop\FOCP II- ASSIGNMENT> 
```


CONCLUSION

This question helped me understand random number generation, string replacement, and how to use AI tools effectively for coding and debugging.