Range Sensors: the Beam Model

Contents

1. Overview . . . 2
2. What a range sensor measures . . . 3
   - 2.1 Range finders and scans . . . 3
   - 2.2 Why we need a measurement model . . . 4
   - 2.3 Why a whole scan is a product of beams . . . 5
3. Why a Gaussian alone fails . . . 6
4. The four causes of a reading . . . 8
   - 4.1 Measurement noise: a Gaussian around the expected range . . . 8
   - 4.2 Unexpected objects: why the curve falls off, and why it stops . . . 9
   - 4.3 Failures: a spike at the maximum range . . . 13
   - 4.4 Random readings: the uniform part . . . 13
5. The beam model: one mixture of four shapes . . . 14
   - 5.1 The mixture . . . 14
   - 5.2 Back to the opening scan . . . 15
6. Learning the model's numbers from data . . . 16
   - 6.1 Why the numbers must be learned . . . 17
   - 6.2 Maximum likelihood, and why it needs a search . . . 17
   - 6.3 EM for the beam model . . . 18
7. A catalogue of sensor models . . . 20
8. Summary . . . 22
9. Sources . . . 23
10. Key terms . . . 24

1. Overview

> **Key point:** A robot judges a guess about its **pose** (G-2280) by asking how likely its laser readings would be from there. The beam model gives that number for one reading as a mix of four causes, so that a person walking past does not make the right pose look impossible.




Figure 1: A 5 m by 4 m room seen from above. The robot at (2, 2), facing along x, sends four laser beams. The forward beam should reach the wall 3 m away but stops at a person 1 m ahead; the other three read 1.97, 2.04 and 1.99 m

So far the robot has a grid map of its room: the room split into small cells, each marked free or occupied. The map does not say where the robot is on it; the robot can only guess poses and test each guess against what its sensors report. Figure 1 shows where that test breaks. The robot stands at pose (2, 2, 0) in a 5 m by 4 m room; its laser measures the distance to the nearest surface in four directions. A person stands 1 m in front of it, so the forward beam reads 1.00 m, although the map says the wall is 3 m away. Is the robot at (2, 2, 0), or one metre further along at (3, 2, 0)? This Note adds the rule that answers it.

The room is smaller and emptier than the 7 m by 4 m room with poles and furniture used for maps: a laser needs only walls, and bare walls keep every **expected range** (G-2375) a round number we can check by hand.

A sensor reading is a measurement (G-2317): what the sensors report about the world at one moment. To test a guessed pose we need a rule that answers one question: how likely are these four readings if the robot stood at that pose? This Note builds the standard rule for range sensors:

- what a range sensor reports, and why the question above is the one to ask (Section 2);

- why a Gaussian around the expected range is not enough (Section 3);
- the four causes of a reading and the shape each one gives, with the reason for every shape (Section 4);
- how the four shapes combine into one model, and what the model says about Figure 1 (Section 5);
- how to learn the model's numbers from recorded readings, by maximum likelihood and the **EM algorithm** (G-675) (Section 6);
- the other kinds of sensor models a robot uses (Section 7).

2. What a range sensor measures

> **Key point:** A range sensor reports, for each direction, the distance to the first surface the beam meets. A measurement model scores a guessed **pose** (G-2280) by how likely those distances are from there.

2.1 Range finders and scans

The four numbers of Figure 1 come from a **range finder** (G-2371), which measures the distance to the nearest surface in one direction. A laser range finder, or LiDAR (G-1083), sends a short pulse of light and times its return. The pulse travels to the surface and back, so the time of flight multiplied by the speed of light is twice the distance; halved, it is the distance. A sonar does the same with a sound pulse (LaValle §11.5.1).

A scanning laser turns, so one sweep gives many readings, for example one every half degree. The list of readings from one sweep is a **range scan** (G-2372). For one scan:

- z^k is the reading of beam k, in m (1.00 m for the forward beam of Figure 1);
- K is the number of beams, 4 in Figure 1;
- z is the whole scan, the list of all K readings.

$$z = (z^1, z^2, \ldots, z^K)$$

Figure 1's four beams point at 0°, 90°, 180° and 270° from the robot's heading:

$$z = (1.00,\ 1.97,\ 2.04,\ 1.99)$$

Every sensor has a longest distance it can report. When no surface returns the pulse in time, the sensor reports that longest distance itself. This is the **maximum range** (G-2373) $z_{\max}$; our laser has:

$$z_{\max} = 5 \text{ m}$$

2.2 Why we need a measurement model


Suppose the robot is unsure whether it is at pose A, (2, 2, 0), or at pose B, (3, 2, 0): one metre further along the room. To decide, it compares its readings with what each pose would predict. The map predicts, for each pose and each beam, the distance the beam should travel before it meets a wall: the **expected range** (G-2375), written z^*.

We find it by **ray casting** (G-2376): start at the robot, walk along the beam's direction in small steps, and stop at the first occupied cell of the grid map (Figure 2). The distance walked is z^*. For the forward beam:

- z_A^* is its expected range from pose A, in m;
- z_B^* is its expected range from pose B, in m.

$$z_A^* = 3.0 \text{ m}$$

$$z_B^* = 2.0 \text{ m}$$



each ray walks cell by cell (shaded) until it enters an occupied wall cell (dark grey); both rays start at $y = 2$, drawn apart so both show

Figure 2: Ray casting in a grid map: from pose A at (2, 2) the forward ray walks cell by cell and enters the wall cells after 3.0 m; from pose B at (3, 2) it does so after 2.0 m

The reading was 1.00 m, which matches neither 3.0 nor 2.0. We need a number for "how well does a reading of 1.00 m fit an expected range of 3.0 m?", one that tolerates small sensor errors and an odd reading now and then. That number is the **measurement model** (G-2374), also called the sensor model or observation model (Thrun §6.1). For one scan and one guessed pose:

- z is the scan, the four readings (1.00, 1.97, 2.04, 1.99) m;

- x is the guessed pose, such as A;
- m is the map, the grid map of the room;
- the bar | reads "given".

$$p(z \mid x, m)$$

In words: the density of getting the readings z, given that the robot is at pose x and the world looks like map m. The pose x is the pose (G-2280) of a floor robot, position and heading:

- its first entry x is the position along the room, in m (2 m at pose A);
- y is the position across the room, in m (2 m at pose A);
- θ is the heading, in degrees (0° at pose A, facing along x).

$$x = (x,\ y,\ \theta)$$

For a fixed set of readings, $p(z \mid x, m)$ read as a function of the pose is the likelihood (G-1086) of that pose: the poses under which the readings are more likely score higher. That is how a localization filter uses it; the **Bayes filter** (G-2446) multiplies its belief by this likelihood in its correction step.

A range reading is a continuous quantity, so $p(z \mid x, m)$ is a probability density (G-1569), not a probability: per metre for one reading, per m^4 for our scan of four readings. A density can be larger than 1; only areas under it are probabilities.

2.3 Why a whole scan is a product of beams

A scan has many beams, and writing one density for all of them at once is hard. We split it into one density per beam and multiply. With the symbols of Section 2.1 and Section 2.2:

- z^k is the reading of beam k, in m;
- K is the number of beams, 4;
- x is the guessed pose, such as A;
- m is the map;
- $\prod$ means "multiply the terms for $k = 1$ to K".

$$p(z \mid x, m) = \prod_{k=1}^{K} p(z^k \mid x, m)$$

Multiplying is allowed when the beams are independent: knowing one beam's error tells us nothing about another's. That is not true in general, but it is close to true once the **pose** (G-2280) and the map are known (Thrun §6.3.1):

- **Without a map**, beams are linked: if one beam hits something at 2 m, the beam half a degree away probably hits the same object at about 2 m.

- **With the map and the pose given**, that shared object is already in the map, so each beam's remaining error is its own sensor noise, and the beams are close to independent.

Independence that holds only once a third thing is known is conditional independence (G-443), the same assumption Naive Bayes makes for features given the class.

> **Extra:** The assumption is not exact. A person blocks several neighbouring beams at once, and their errors are then linked. The product then counts that one person several times, which makes the model overconfident (Freiburg sensor-model slides, "Summary beam-based model"). Implementations therefore use only a subset of the beams of each scan: the ROS localization package AMCL uses 30 evenly spaced beams per scan by default (ROS amcl, `laser_max_beams`).

3. Why a Gaussian alone fails

> **Key point:** A narrow Gaussian around the expected range gives a reading caused by a passer-by a density of practically zero, and the product then rejects the true **pose** (G-2280) outright.

The first rule that comes to mind fails on the person's 1.00 m reading of Figure 1. It says the reading should be the **expected range** (G-2375) plus a small sensor error, and small errors follow a Gaussian distribution (G-827). A good laser's readings typically lie about 0.05 m from the true distance: its **standard deviation** (G-1870) is $\sigma = 0.05$ m. For one beam:

- z is the beam's reading, in m (1.00 m for the forward beam);
- z^* is its expected range, 3 m for the forward beam at pose A;
- σ is the sensor's standard deviation, 0.05 m;
- $\mathcal{N}(z;\ z^*, \sigma^2)$ is the Gaussian density of the reading, with mean z^* and variance σ^2, in per m.

$$\mathcal{N}(z;\ z^*, \sigma^2) = \frac{1}{\sigma\sqrt{2\pi}}\, e^{-\frac{1}{2}\left(\frac{z-z^*}{\sigma}\right)^2}$$

Figure 3 draws it for the forward beam at the true pose A, where $z^* = 3$ m. Now put the person's reading, 1.00 m, into it. The distance from the expected range, in units of σ:

$$\frac{1.00 - 3.00}{0.05} = -40$$

The exponent:

$$-\tfrac{1}{2} \times 40^2 = -800$$

The factor in front of the exponential:

$$\frac{1}{0.05 \times \sqrt{2\pi}} = 7.98$$

The density:

$$7.98 \times e^{-800}$$

$$\approx 0$$

The number e^{-800} is so small that a computer stores it as exactly 0 (the notebook checks).




Figure 3: A Gaussian with standard deviation 0.05 m around the expected range 3 m. The reading 1.00 m, caused by a person, sits far out in the tail, where the density is about e to the minus 800, effectively 0

Because the scan density is a product, one zero beam makes the whole scan density zero, whatever the other beams say. So the true pose A gets 0. The wrong pose B does worse on most beams but escapes the zero: its forward beam expects 2 m, and its backward beam expects 3 m but reads 2.04 m. Those two densities are tiny but not zero, and B ends up with a scan density of about 4×10^{-164}. A Gaussian alone would prefer the wrong pose, only because a person stepped in front of the robot.

The cure is not a wider Gaussian: that would make every reading near the wall less informative too. Instead we list the other ways a reading can come about, and give each its own shape.

4. The four causes of a reading

> **Key point:** A reading is a correct hit with small noise, a hit on something not in the map, a failure that reports the **maximum range** (G-2373), or plain junk. Each cause has its own density shape, and each shape follows from how that cause works.

The person's reading is one of four ways a beam can come back. Figure 4 shows the shape each gives for the forward beam at **pose** (G-2280) A (expected range $z^* = 3$ m, maximum range $z_{\max} = 5$ m). They come from Thrun §6.3.1 and the Freiburg sensor-model slides; the reason for each shape follows below.




Figure 4: The four densities of the beam model for an expected range of 3 m: a narrow Gaussian at 3 m (measurement noise), a curve that starts high at 0 and falls off until it stops at 3 m (unexpected objects), a spike at 5 m (failures), and a flat line at height 0.2 from 0 to 5 m (random readings)

4.1 Measurement noise: a Gaussian around the expected range

When the beam does reach the mapped wall, the reading still differs a little from z^*: limited resolution, temperature, the surface. This **measurement noise** (G-2378) is the Gaussian of Section 3, with one change. Readings below 0 or above $z_{\max}$ cannot occur, so the Gaussian is cut to the range from 0 to $z_{\max}$ and scaled up so its area is 1 again. For one beam:

- z is the reading, in m;
- z^* is the expected range, 3 m for the forward beam at pose A;
- $z_{\max}$ is the maximum range, 5 m;
- σ_{hit} is the standard deviation of the hits, the σ of Section 3, 0.05 m;
- η (eta) is the **normalizer** (G-2382): one over the area of the Gaussian that lies inside the range, so that the whole density again has area 1 (Thrun §6.3.1); 1.000 for our wall

at 3 m;
- $p_{\text{hit}}(z)$ is the density of the reading when the beam hits the mapped wall, in per m.

$$p_{\text{hit}}(z) = \eta\, \mathcal{N}(z;\ z^*, \sigma^2_{\text{hit}})$$

for $0 \le z \le z_{\max}$, and 0 outside. A Gaussian cut to a range and rescaled is a truncated normal (G-2023).

For our wall at 3 m, the Gaussian lies far inside the range (at least 40 σ from 0 and from 5 m), so $\eta = 1.000$. It matters near the edge. If the wall were 4.98 m away, about a third of the Gaussian would lie beyond 5 m:

$$\text{area inside} = 0.655$$

$$\eta = 1/0.655 = 1.53$$

Worked example. At **pose** (G-2280) A the forward beam expects 3 m. A reading of 3.02 m has the density:

$$\frac{3.02 - 3.00}{0.05} = 0.4$$

$$p_{\text{hit}}(3.02) = 7.98 \times e^{-0.08}$$

$$= 7.37 \text{ per m}$$

4.2 Unexpected objects: why the curve falls off, and why it stops

A person, a chair or an open door that is not in the map can block the beam first. The reading is then shorter than z^*. This is an **unexpected object** (G-2379), and its reading a short reading. Figure 4 shows its shape: high at 0, falling off, and zero after z^*. Both features have a reason.

Why it stops at the expected range. An object behind the wall cannot block the beam: the wall is hit first. So a short reading is always shorter than z^*, and the density is 0 beyond it.

Why it falls off. Only the first object along the beam matters; anything behind it is hidden. Cut the beam into 4 equal cells and let each cell be either blocked (1) or free (0), all 16 patterns equally likely. Figure 5 sorts the 16 patterns by the first blocked cell:

First blocked cell	Patterns
1	8
2	4
3	2
4	1
none	1




Figure 5: The 16 ways to fill 4 cells along a beam, grouped by the first blocked cell: 8 patterns stop at cell 1, 4 at cell 2, 2 at cell 3, 1 at cell 4 and 1 pattern is never blocked

The first cell is blocked in 8 of the 16 patterns, more than all the patterns that first stop further out:

$$1 + 2 + 4 = 7$$

The count halves with each cell, because each extra free cell in front is one more condition the pattern must meet.

The same holds for any blocking chance. Let each cell be blocked independently of the others:

- p is the chance that one cell is blocked, a number from 0 to 1 (0.2 below);
- k is a cell's number along the beam, counted from the robot (1, 2, 3, ...);
- $P(\text{first stop at cell } k)$ is the probability that the beam stops at cell k and not before.

For the beam to stop at cell k, the $k - 1$ cells before it must be free and cell k blocked:

$$P(\text{first stop at cell } k) = (1 - p)^{k-1}\, p$$

Each further cell multiplies the chance by the same factor $1 - p$. With cells of 0.1 m and $p = 0.2$:

$$P(\text{cell } 1) = 0.2$$

$$P(\text{cell } 2) = 0.8 \times 0.2 = 0.16$$

$$P(\text{cell } 3) = 0.8^2 \times 0.2 = 0.128$$

Figure 6 runs this as an experiment: in each trial, cells of a 3 m beam are blocked at random, and we record where the beam stops. After 5000 trials the shares match the formula.




Figure 6: Animation: in each trial, 0.1 m cells along a 3 m beam are blocked with probability 0.2; the beam stops at the first blocked cell. The histogram of where it stopped builds up trial by trial and settles on the curve 0.2 times 0.8 to the power k minus 1

A curve that falls by the same factor at every step is exponential. Make the cells shorter and keep the blocking chance per metre fixed:

- Δ is the cell length, in m (0.1 m, then shorter);
- λ is the blocking chance per metre, 2 per m;
- z is the distance along the beam, in m (1 m in the table).

The chance per cell is then:

$$p = \lambda\Delta$$

The share per metre at 1 m approaches $\lambda e^{-\lambda z}$:

Cell length Δ	Share per metre at 1 m
0.1 m	0.215
0.01 m	0.265
0.001 m	0.270
limit: $2e^{-2}$	0.271

So the short-reading density is an exponential distribution (G-733), cut at z^*. The exponential holds under the assumption made above: objects are spread evenly and block the beam with the same chance per metre at every distance (De Laet et al. 2008, §3.6). Its rate λ_{short} is large in a crowded hall and small in an empty one. For one beam:

- z is the reading, in m;
- z^* is the expected range, 3 m for the forward beam at pose A;
- λ_{short} is the rate of unexpected objects, the λ above: the chance per metre that one blocks the beam, 2 per m;
- η is again the normalizer, now one over the area of the exponential between 0 and z^* (1.0025, worked out below);
- $p_{\text{short}}(z)$ is the density of a short reading, in per m.

$$p_{\text{short}}(z) = \eta \ \lambda_{\text{short}} \ e^{-\lambda_{\text{short}} z}$$

for $0 \le z \le z^*$, and 0 otherwise (Thrun §6.3.1).

The normalizer. The exponential's area from 0 to z^* is:

$$\int_0^{z^*} \lambda e^{-\lambda z} \, dz = 1 - e^{-\lambda z^*}$$

So η is one over that area. With $\lambda_{\text{short}} = 2$ per metre and $z^* = 3$ m:

$$1 - e^{-6} = 0.9975$$

$$\eta = 1.0025$$

Worked example. The person's reading, 1.00 m:

$$p_{\text{short}}(1.00) = 1.0025 \times 2e^{-2}$$

$$= 1.0025 \times 0.2707$$

$$= 0.271 \text{ per m}$$

4.3 Failures: a spike at the maximum range

Sometimes no pulse comes back: the beam hits glass or a black, light-absorbing surface, bounces off a shiny surface at a slant, or the wall is simply out of range (Thrun §6.3.1). The sensor then reports $z_{\max}$. Such a **max-range reading** (G-2380) lands on exactly one value, 5 m, however far the wall is. So its density is a single spike at $z_{\max}$:

- z is the reading, in m;
- $z_{\max}$ is the maximum range, 5 m;
- $p_{\max}(z)$ is the failure part of the model.

$$p_{\max}(z) = 1 \text{ if } z = z_{\max}, \text{ else } 0$$

A distribution that puts all its probability on one value is a **point mass** (G-2383). A point mass has no height, only a probability, so it cannot be added to densities as it stands. In code we draw it as a narrow box one sensor step wide (1 cm), of height 100 per metre, so its area is 1 (Figure 4, third panel).

4.4 Random readings: the uniform part

Some readings have no cause we can model: cross-talk between sonars, reflections that come back by a strange path, electronic glitches (Thrun §6.3.1; Freiburg slides). We know nothing about where such a **random measurement** (G-2381) lands, so we give every value from 0 to $z_{\max}$ the same density, a uniform distribution (G-2043):

- z is the reading, in m, anywhere from 0 to $z_{\max}$;
- $z_{\max}$ is the maximum range, 5 m;
- $p_{\text{rand}}(z)$ is the density of a random reading, in per m.

$$p_{\text{rand}}(z) = \frac{1}{z_{\max}}$$

$$= \frac{1}{5} = 0.2 \text{ per m}$$

The uniform part p_{rand} has a job: no reading between 0 and 5 m ever gets a density of exactly 0, so one strange reading can never wipe out a whole scan.

5. The beam model: one mixture of four shapes

> **Key point:** The beam model adds the four densities with weights that sum to 1. With it, the person's reading costs **pose** (G-2280) A a factor, not everything, and the true pose wins.

5.1 The mixture

We do not know whether the forward beam's 1.00 m came from the person or from junk, only how often each cause happens. So the density of a reading is the weighted sum of the four densities, a mixture density like a Gaussian mixture, but with parts of different shapes. For one beam k:

- $p(z^k \mid x, m)$ is the density of beam k's reading z^k, given the pose x and the map m, in per m;
- p_{hit} is the Gaussian around the expected range (Section 4.1);
- p_{short} is the falling exponential of unexpected objects (Section 4.2);
- p_{max} is the failure spike at 5 m (Section 4.3);
- p_{rand} is the uniform part, 0.2 per m (Section 4.4);
- w_{hit} is the share of readings that are hits, 0.75;
- w_{short} is the share caused by unexpected objects, 0.12;
- w_{max} is the share of failures, 0.05;
- w_{rand} is the share of random readings, 0.08.

$$p(z^k \mid x, m) = w_{\text{hit}}\ p_{\text{hit}} + w_{\text{short}}\ p_{\text{short}}$$

$$+ w_{\text{max}}\ p_{\text{max}} + w_{\text{rand}}\ p_{\text{rand}}$$

The mixture weights (G-1238) are the shares of readings each cause produces. They are not negative and add up to 1, so the mixture's area is 1 too. Thrun writes them $z_{\text{hit}}, \ldots$; we write w so that z always means a reading. This weighted mixture of four densities is the **beam model** (G-2377) of a **range finder** (G-2371), also called the beam-based proximity model (Thrun §6.3; Freiburg slides). We use these weights in Sections 5 and 6:

Cause	Weight	Shape
hit, measurement noise	$w_{\text{hit}} = 0.75$	Gaussian, $\sigma_{\text{hit}} = 0.05$ m
unexpected object	$w_{\text{short}} = 0.12$	exponential, $\lambda_{\text{short}} = 2$ per m
failure	$w_{\text{max}} = 0.05$	spike at 5 m
random	$w_{\text{rand}} = 0.08$	uniform, 0.2 per m

Figure 7 stacks the four weighted parts; the black top edge is the mixture. Its odd shape, with the falling start, the dip just before the wall, the Gaussian, the uniform part and the spike at the end, is the sum of four simple shapes.




Figure 7: The beam model for an expected range of 3 m, built by stacking the weighted parts: a green uniform layer (random), an orange falling curve up to 3 m (unexpected objects), the blue Gaussian at 3 m (measurement noise, cut off at the top) and the purple spike at 5 m (failure). The black top edge is the mixture; it is 0.049 at 1.00 m and 0.016 at 4.00 m

Worked example: the person's reading, 1.00 m, at pose A. The Gaussian and the spike give 0 there. The other two parts:

$$0.12 \times 0.271 = 0.0326$$

$$0.08 \times 0.2 = 0.016$$

$$p(1.00 \mid A) = 0.0326 + 0.016$$

$$= 0.049 \text{ per m}$$

Small, because a short reading is less common than a hit, but not zero.

5.2 Back to the opening scan

Now score both **poses** (G-2280) with the beam model. Ray casting gives the expected ranges z^* of the four beams:

Beam	Reading (m)	z^* at A (m)	z^* at B (m)
0°	1.00	3.0	2.0
90°	1.97	2.0	2.0
180°	2.04	2.0	3.0
270°	1.99	2.0	2.0

The beam densities (per m), from the notebook:

Beam	Pose A	Pose B
0°	0.049	0.049
90°	5.019	5.019
180°	4.361	0.020
270°	5.886	5.886
product (per m^4)	6.26	0.029

The forward beam costs both poses about the same, because both explain 1.00 m only as a short reading. The backward beam decides: it fits A's expected 2 m well and B's expected 3 m badly. The ratio of the two scan densities:

$$\frac{6.26}{0.029} = 215$$

So the scan says pose A is about 215 times more likely than pose B, the right answer. The Gaussian alone gave A exactly 0.

Python: the **beam model** (G-2377) for a whole scan, as in the UChicago class 05 algorithm.

```
def beam_model(readings, expected):  # metres
    q = 1.0
    for z, zs in zip(readings, expected):
        q *= mixture(z, zs)  # four weighted parts
    return q
beam_model([1.00, 1.97, 2.04, 1.99], [3, 2, 2, 2])   # 6.26 (pose A)
beam_model([1.00, 1.97, 2.04, 1.99], [2, 2, 3, 2])   # 0.029 (pose B)
```

`mixture` is defined in the notebook `RO-010-range-sensors-beam-model.ipynb`.

6. Learning the model's numbers from data

Key point: Record many readings of a wall at a known distance and choose the weights and widths that make those readings most likely. The causes are hidden, so EM finds them by alternating "which cause made each reading?" with "refit each cause".

6.1 Why the numbers must be learned

The answer of Section 5.2, **pose** (G-2280) A about 215 times more likely than pose B, rests on six numbers we chose: the four weights, the standard deviation of the hits σ_{hit} (0.05 m) and the rate of short readings λ_{short} (2 per m). These are the model's **intrinsic parameters** (G-2384): they belong to the sensor and its surroundings, not to the pose (Thrun §6.3.4). A sonar is noisier than a laser, and a busy hall has more short readings than an empty lab, so no textbook value fits every robot. We measure them.

The experiment: place the robot 3 m from a wall and record 1000 readings of the beam that faces it while people walk past (Freiburg slides, "Raw sensor data" for an expected distance of 300 cm). Figure 8 shows the result as counts per 0.05 m bin. We built these readings in the notebook from the model of Section 5, so that we can check the fit against known values; real recordings look the same (Freiburg slides, "Raw sensor data").




Figure 8: 1000 readings of a wall 3 m away as counts per 0.05 m bin. Left: a tall peak at 3 m. Right, zoomed to counts up to 25: a falling pile of short readings near 0, a thin uniform layer of random readings, and a bar of 47 readings at the maximum range of 5 m

Some numbers are easy. With nobody around, the readings scatter only by **measurement noise** (G-2378), and σ_{hit} is their **standard deviation** (G-1870), the MLE of a normal distribution (G-1242). The weights cannot be read off like that: a reading of 2.95 m could be a hit or a short reading, and nothing in the reading says which.

6.2 Maximum likelihood, and why it needs a search

The principle is maximum likelihood estimation (G-1191): choose the six numbers that make the 1000 recorded readings most likely. With the log-likelihood (G-1113), we maximise a sum over the readings:

- z_i is recorded reading number i, in m;

- n is the number of readings, 1000;
- z^* is the expected range, the wall's distance, 3 m;
- $p(z_i \mid z^*)$ is the mixture of Section 5 at reading z_i, in per m;
- ℓ is the log-likelihood, the sum of the logs of those densities.

$$\ell = \sum_{i=1}^{n} \log p(z_i \mid z^*)$$

The log of a sum of four parts does not split into simple pieces, so setting the derivative to zero gives no closed formula, exactly as for a Gaussian mixture. The standard way out for mixtures is EM, which guesses which cause made each reading, refits each cause to its readings, and repeats; each of its steps has a simple formula (UW CSE 571 slides; Thrun §6.3.4; De Laet et al. 2008, Algorithm 1).

6.3 EM for the beam model

The hidden piece of information is the cause of each reading, a latent variable (G-1050). The EM algorithm (G-675) repeats two steps from a starting guess. We start from equal weights 0.25, a standard deviation of the hits σ_{hit} of 0.3 m and a rate of short readings λ_{short} of 0.5 per m.

E-step: share each reading among the causes. For each reading, compute each weighted part and divide by their sum. The shares are the responsibilities (G-1687) $e_{i,c}$ of cause c for reading i; they add up to 1 over the four causes (**E-step** (G-654)). With the starting guess, the weighted parts (per m) for three readings:

Reading	hit	short	max	rand	sum
3.02 m	0.332	0	0	0.05	0.382
1.00 m	0	0.098	0	0.05	0.148
5.00 m	0	0	25	0.05	25.05

Dividing each row by its sum gives the responsibilities:

Reading	hit	short	max	rand
3.02 m	0.869	0	0	0.131
1.00 m	0	0.661	0	0.339
5.00 m	0	0	0.998	0.002

The 3.02 m reading is mostly a hit, the 1.00 m reading mostly a short reading, the 5.00 m reading almost surely a failure.

M-step: refit each cause to its share of the readings. Each cause is now fitted like a single distribution, with each reading counted by its responsibility (the **M-step** (G-1139)). With our numbers:

- $e_{i,c}$ is the responsibility of cause c for reading i, a number from 0 to 1 (0.869 of the hit cause for the 3.02 m reading above);
- n is the number of readings, 1000;
- z_i is reading number i, in m;
- z^* is the wall's distance, 3 m;
- w_c is the new weight of cause c, its share of the readings.

The three refits (Thrun §6.3.4; De Laet et al. 2008, Eq. 65–66):

- **Weights:** a cause's weight is its average responsibility, its share of the readings.

$$w_c = \frac{1}{n} \sum_i e_{i,c}$$

- **Standard deviation of the hits:** the responsibility-weighted variance around z^*, the same formula as the MLE of a normal with weighted readings.

$$\sigma^2_{\text{hit}} = \frac{\sum_i e_{i,\text{hit}} \ (z_i - z^*)^2}{\sum_i e_{i,\text{hit}}}$$

- **Rate of the short readings:** the MLE of an exponential rate (G-1243) is the number of waits over their sum. With weighted readings, the count becomes the sum of responsibilities:

$$\lambda_{\text{short}} = \frac{\sum_i e_{i,\text{short}}}{\sum_i e_{i,\text{short}} \ z_i}$$

This last formula ignores the cut at z^*. That is safe when the curve has nearly died out before z^*, as here, where only $e^{-6} = 0.0025$ of the exponential lies beyond 3 m.

Figure 9 plays the rounds. After round 1 the Gaussian has already narrowed onto the wall; after a few rounds the curve follows the bars, and the **log-likelihood** (G-1113) has stopped rising. EM never lowers the log-likelihood from one round to the next (why the log-likelihood never decreases).




Figure 9: Animation of EM fitting the beam model. Each frame is one round: blue bars are the 1000 readings, the black line is how many readings the current model expects per bin, the right panel is the log-likelihood. Round 0 is a flat, wide guess with log-likelihood −932; by round 60 the weights are hit 0.733, short 0.150, max 0.047, rand 0.070, sigma 0.051 m, lambda 1.75 per m, log-likelihood 448

Round	w_{hit}	w_{short}	w_{max}	w_{rand}	σ_{hit} (m)	λ_{short}	log-likelihood
0	0.250	0.250	0.250	0.250	0.300	0.50	−932
1	0.621	0.163	0.047	0.169	0.081	0.88	280
2	0.727	0.135	0.047	0.092	0.052	1.53	445
60	0.733	0.150	0.047	0.070	0.051	1.75	448

Random readings below 3 m look exactly like short ones, because there the two shapes overlap, so EM moves some weight between those two causes.

7. A catalogue of sensor models

> **Key point:** Every sensor needs its own measurement model $p(z \mid x, m)$, the density of its reading z given the pose x and the map m, because each reports a different kind of number. Four kinds cover most mobile robots: landmark, range, boundary and odometry sensors.

The **beam model** (G-2377) answers the question of Figure 1 for a laser; it is one entry in a family. A model is needed for every sensor the robot uses, and its shape follows from what the sensor reports. LaValle collects the common kinds (LaValle §11.5.1); Figure 10 draws four of them in our room.




Figure 10: Four kinds of sensors in the 5 m by 4 m room: a landmark sensor measures range or bearing to a known point; a depth sensor measures distances to the nearest surface along many beams; a boundary sensor says whether the robot touches or is near a wall; an odometry sensor reports how far the wheels say the robot moved

Kind	What it reports	Example	Where we model it
Landmark sensor (G-2385)	the direction or distance to a known point	a camera sees a coloured pole 3 m away at 37° to the left	**landmark measurement model** (G-2401)
Depth-mapping sensor (G-2386)	the distance to the nearest surface along each beam	the laser scan of Figure 1	this Note and the **likelihood field** (G-2393)
Boundary sensor (G-2387)	whether the robot touches, or is close to, an obstacle	a bumper, or "within 0.5 m of a wall"	yes/no readings
Odometry sensor (G-2388)	how far the robot has moved, from its wheel turns	"1.02 m since the last step"	the **odometry motion model** (G-2323)

8. Summary

Part	Density	Why this shape
measurement noise	Gaussian around the expected range z^*, cut at 0 and at the maximum range $z_{\max}$ (5 m)	small errors scatter symmetrically around the true distance
unexpected object	exponential, from 0 up to z^*	only the first blocker counts, and each extra free stretch is one more condition; nothing behind the wall can block
failure	spike at $z_{\max}$	a lost pulse is reported as the maximum range
random	uniform at height $1/z_{\max}$, 0.2 per m	no reading may ever have density 0

- The four readings of Figure 1 are about 215 times more likely from **pose** (G-2280) A than from pose B, even though a person blocks the forward beam, because the beam model lets a short reading cost a pose a factor instead of everything; the six numbers behind that answer can be learned from a thousand readings of one wall.
- A **range finder** (G-2371) reports the distance to the first surface along each beam, so a guessed pose can be tested by ray casting the map to get the expected ranges and comparing.
- The **measurement model** (G-2374) $p(z \mid x, m)$, the density of the readings z given the pose x and the map m, scores a pose by how likely the readings are from there; read over poses it is the **likelihood** (G-1086) that a localization filter multiplies into its belief.
- A scan's density is the product of its beams' densities, because once the pose and map are known the beams are nearly independent; the leftover dependence makes the product overconfident, so implementations use a subset of beams.
- A Gaussian alone fails, because one reading caused by a passer-by gets density 0 and the product then rejects the true pose.
- The **beam model** (G-2377) mixes four causes with weights that add up to 1, so a short reading costs a pose a factor instead of everything; in our scan it makes the true pose 215 times more likely than the wrong one.
- The short-reading curve is exponential because the beam stops at the first of many evenly spread blockers, which halves (or shrinks by a fixed factor) the chance with every extra stretch of beam.
- The weights and widths are learned by maximum likelihood from recorded readings; the causes are hidden, so EM alternates responsibilities and weighted refits, and it never lowers the **log-likelihood** (G-1113).
- Each sensor kind (landmark, range, boundary, odometry) needs its own model, because each reports a different kind of number.

Now the robot can score a guessed pose from a laser scan on a grid map, even with a person

in the way. Still missing is speed: every guessed pose needs a ray cast per beam, and a filter tries hundreds of poses per scan, so the next step is a score that looks only at where each beam ends.

9. Sources

Built from

- Cyrill Stachniss, "Observation Models", YouTube, https://www.youtube.com/watch?v=SfwxLpdFB-o (Stachniss, observation models)
- Carlotta A. Berry, PhD, "Advanced Mobile Robotics: Lecture 4-1b - Probabilistic Sensor Models", YouTube, https://www.youtube.com/watch?v=l6Xk37fpQHg (Berry, lecture 4-1b)
- NPTEL - IIT Madras, "#40 Range Finder Measurement Model", *Introduction to Robotics*, YouTube, https://www.youtube.com/watch?v=SwzKOMm1X_I (NPTEL #40)
- Burgard, W. et al., *Introduction to Mobile Robotics*, "Probabilistic Sensor Models" slides, University of Freiburg, http://ais.informatik.uni-freiburg.de/teaching/ss23/robotics/slides/07-sensor-models.pdf (Freiburg slides)
- University of Chicago, CMSC 20600 *Introduction to Robotics*, "Class Meeting 05: Measurement Models for Range Finders", https://classes.cs.uchicago.edu/archive/2025/fall/20600-1/class_meeting_05.html (the beam-model algorithm and the four formulas)
- University of Washington, CSE 571 *Robotics*, "Motion and sensor models" slides, https://courses.cs.washington.edu/courses/cse571/26wi/slides/03-motion-sensor-models.pdf (UW CSE 571 slides: EM for the mixture parameters)
- De Laet, T., De Schutter, J. and Bruyninckx, H. (2008). "A Rigorously Bayesian Beam Model and an Adaptive Full Scan Model for Range Finders in Dynamic Environments". *Journal of Artificial Intelligence Research* 33, 179–222. https://arxiv.org/abs/1401.3432 (§3.6: the assumptions behind the exponential; §4.1 and Algorithm 1: EM for the beam model)
- LaValle, S. M. (2006). *Planning Algorithms*. Cambridge University Press. §11.5.1 "Sensor models". Free online: https://lavalle.pl/planning/node570.html (LaValle)
- Thrun, S., Burgard, W. and Fox, D. (2005). *Probabilistic Robotics*. MIT Press. §6.1–6.3 (measurement models, the beam model, learning its parameters). Cited only for what the free sources above confirm. (Thrun)

Other references

- ROS `amcl` package, parameter definitions `AMCL.cfg`, https://github.com/ros-planning/navigation/blob/noetic-devel/amcl/cfg/AMCL.cfg (ROS amcl)
- Cyrill Stachniss's lecture is part of his course on state estimation; the same slides appear in "MSR Course 05: Motion and Sensor Models", YouTube, https://www.youtube.com/watch?v=rjpbE-X23wc

10. Key terms

Terms taught in this Note come first; linked terms are recaps, taught in the Note the link opens.

Term	Meaning
Expected range z^* (G-2375)	The distance a beam would read with a perfect sensor, if the robot were at a given pose in the map; the measurement model compares each real reading with it.
Range finder (G-2371)	A sensor that measures the distance to the nearest surface in one direction, for example by timing a laser or sound pulse; robots use it to compare what they see with a map.
Range scan (G-2372)	The list of readings from one sweep of a scanning range finder, one distance per beam direction, such as $z = (1.00, 1.97, 2.04, 1.99)$; it is the measurement a laser-based robot tests poses against.
Maximum range $z_{\max}$ (G-2373)	The longest distance a range sensor can report, such as 5 m; when no pulse returns, the sensor reports this value, so a reading of $z_{\max}$ usually means a failure, not a wall.
Ray casting (G-2376)	Finding the expected range by walking along a beam's direction through the map until the first occupied cell; it turns a guessed pose and a map into the readings the robot should see.
Measurement model $p(z \mid x, m)$ (G-2374)	The density of getting sensor readings z if the robot were at pose x in map m (also sensor or observation model); read over poses it is a likelihood that tells a filter which poses fit the readings.
Hit part p_{hit} (measurement noise in the beam model) (G-2378)	The small scatter of a reading around the true distance when the beam does hit the mapped surface; modelled as a Gaussian around z^* cut to $[0, z_{\max}]$.
Normalizer η (G-2382)	The factor that rescales a set of numbers, or a density, so that they add up (or integrate) to 1; it is always one over the current total: the sum of the products in the Bayes filter ($1/0.4 = 2.5$ after a reading in the door world), the area under the cut curve in the beam model ($1/0.655 = 1.53$).

Term	Meaning
Unexpected object (p_{short}) (G-2379)	Something not in the map, such as a person, that blocks the beam before the mapped surface and gives a short reading; modelled as an exponential from 0 up to z^*, because only the first blocker counts.
Max-range reading (p_{max}) (G-2380)	A reading of exactly z_{max} that a sensor gives when its pulse never returns (glass, black or shiny surfaces, nothing in range); modelled as a spike at z_{max}.
Point mass (G-2383)	A distribution that puts all its probability on one value, such as a reading of exactly z_{max}; it has no density height, so code draws it as a very narrow box of area 1.
Random measurement (p_{rand}) (G-2381)	A reading with no modelled cause, such as cross-talk or a stray reflection; modelled as a uniform density $1/z_{\text{max}}$ (the uniform part p_{rand}) so that no reading ever has density 0.
Beam model (G-2377)	The measurement model of a range finder that mixes four densities for one reading (measurement noise, unexpected objects, failures, random readings) with weights that add up to 1, so no single odd reading can rule out the true pose.
Intrinsic parameters (of a sensor model) (G-2384)	The numbers that describe a sensor and its surroundings rather than the pose, such as the beam model's four weights, σ_{hit} and λ_{short}; they are learned from recorded readings.
Landmark sensor (G-2385)	A sensor that reports the direction or distance to a known point in the world, such as a camera that sees a coloured pole; each kind of report needs its own measurement model.
Depth-mapping sensor (G-2386)	A sensor that reports the distance to the nearest surface along each of many directions, such as a laser scanner or a ring of sonars; the beam model describes its readings.
Boundary sensor (G-2387)	A sensor that reports whether the robot touches, or is close to, an obstacle, such as a bumper or a proximity sensor; it gives yes/no readings.

Term	Meaning
Odometry sensor (G-2388)	A sensor that reports how far the robot has moved, from counting wheel turns; robots usually feed it into the motion model rather than the measurement model.
Pose (G-2280)	Where a robot is and which way it faces: on a floor, its position (x, y) and heading θ, such as (2 m, 1 m, 30°); needed because a robot at one spot drives off differently depending on its heading.
Measurement z_t (G-2317)	What a robot's sensors report about the world at time t, such as "door", a laser scan or a camera image; it does not change the state but tells the robot something about it, which narrows its distribution.
EM algorithm (expectation maximization) (G-675)	A method for finding the maximum likelihood when some variables are hidden (latent): it repeats two steps, an E-step and an M-step, until the fit settles.
LiDAR (G-1083)	A sensor that measures distances to nearby objects with laser light.
Likelihood (G-1086)	How probable the observed data is under given parameter values; read as a function of the parameters with the data fixed.
Bayes filter (G-2446)	The algorithm that keeps a robot's belief up to date one step at a time: a prediction step after each command and a correction step after each reading; it gives the exact belief without storing the history, under the Markov assumption.
Probability density (G-1569)	The height of a continuous distribution's curve; compares how likely nearby values are.
Conditional independence (G-443)	Independence that holds once a third variable is known: given the class, knowing one feature tells nothing more about another. Naive Bayes assumes it so it can multiply one probability per feature.
Gaussian distribution (G-827)	Another name for the normal distribution: the symmetric, bell-shaped continuous distribution set by its mean and standard deviation, used to model many measurements.

Term	Meaning
Standard deviation of a random variable (G-1870)	The square root of a random variable's variance, in the units of X; it says how far values typically fall from the expected value.
Truncated normal (G-2023)	A normal distribution restricted to a range and rescaled so its area is 1; it keeps its bell shape inside the range. Keras' normal initialisers cut at two standard deviations: values beyond are redrawn.
Exponential distribution (G-733)	The pattern of waiting times between random events: short waits are common and long waits rare (a right-skewed continuous distribution).
Uniform distribution (G-2043)	A distribution in which every outcome in a range is equally likely.
Mixture weight π_k (G-1238)	How big a share of a mixture one component k gets; the weights are non-negative and add up to 1.
MLE of a normal distribution (G-1242)	The normal curve that makes the data most likely: its mean is the sample mean and its variance the average squared distance from that mean (dividing by n), $\hat{\mu} = \bar{x}$ and $\hat{\sigma}^2 = \sum(x_i - \bar{x})^2/n$.
Maximum likelihood estimation (MLE) (G-1191)	Fitting parameters by making the likelihood of the observed data as large as possible.
Log-likelihood (G-1113)	The logarithm of the likelihood, which turns the product of probabilities into a sum of log probabilities; it peaks at the same parameters as the likelihood and is easier to compute and maximise.
Latent variable (G-1050)	A variable in a model that is never observed, such as the component that produced a point.
Responsibility r_{nk} (G-1687)	In a mixture model, how likely it is that component k produced point n, given that point (the posterior probability).
E-step (G-654)	The expectation step of the EM algorithm: using the current parameters, give every point its responsibilities (the probability that it came from each component), a soft assignment that the M-step then uses.

Term	Meaning
M-step (G-1139)	The second step of each EM round (maximisation): with the responsibilities held fixed, re-estimate each component's mean, covariance and weight as responsibility-weighted averages, so the fit to the data improves.
MLE of an exponential rate (G-1243)	The rate of an exponential distribution that makes the observed waiting times most likely: one over their mean, $\hat{\lambda} = n/\sum x_i = 1/\bar{x}$.
Landmark measurement model (G-2401)	The density of a landmark reading (range, bearing) given a pose and the map: a Gaussian of the range error times a Gaussian of the bearing error, with the errors taken as independent; it scores how well a guessed pose explains what the robot saw.
Likelihood field (G-2393)	A grid over the map that stores, for each cell, the density of a beam endpoint landing there; computed once from the distance transform, so scoring a pose becomes one look-up per beam.
Odometry motion model (G-2323)	A motion model that splits the pose change reported by odometry into a first turn, a straight drive and a second turn, and adds independent noise to each, with a standard deviation that grows with the motion; used when wheel encoders exist.