HTML5 & CSS3 quick reference

Web Development Fundamentals, VertexLearn. The elements and selectors used throughout the course.

Semantic HTML5 elements

`<header>`	Introductory content or navigation for a page or section.
`<nav>`	A block of major navigation links.
`<main>`	The dominant content of the page. Use once per page.
`<section>`	A thematic group of content, normally with its own heading.
`<article>`	Self-contained content that makes sense on its own (a post, a card).
`<aside>`	Content related to, but separate from, the main content.
`<footer>`	Closing information for a page or section.
`<figure> / <figcaption>`	An image, diagram or code listing with its caption.
`<time datetime="...">`	A machine-readable date or time.
`<details> / <summary>`	A disclosure widget the user can open and close.
`<video> / <audio>`	Native media players with the controls attribute.
`<progress> / <meter>`	Task completion, and a value within a known range.

Form input types and validation attributes

`type="email"`	Browser checks for a valid email format.
`type="number" min max`	Numeric input with limits.
`type="range"`	A slider, often paired with <output>.
`required`	The field must be filled in before the form submits.
`minlength / maxlength`	Length limits on text.
`pattern="regex"`	Value must match a regular expression.
`<datalist>`	Suggested values for an input.

Ways to apply CSS

`External`	<link rel="stylesheet" href="site.css"> shared by many pages.
`Internal`	<style> ... </style> inside the <head> of one page.
`Inline`	style="color: red" on a single element. Highest priority.

Useful selectors and layout

`.class #id element`	Class, id and type selectors.
`a:hover input:focus`	Pseudo-classes for states.
`li::before`	Pseudo-element for generated content.
`display: flex`	One-dimensional layout (rows or columns).
`display: grid`	Two-dimensional layout with grid-template-columns.

`@media (max-width: 760px)`	Responsive styles for small screens.
`var(--color-navy)`	Custom properties (CSS variables) for a design system.