

Name:Anshul Dod

PRN:202501040040

PRACTICAL: 02

2.1.1. List operations

08:32

Write a Python program that implements a menu-driven interface for managing a list of integers. The program should have the following menu options:

1. Add
2. Remove
3. Display
4. Quit

The program should repeatedly prompt the user to enter a choice from the menu.

Depending on the choice selected, the program should perform the following actions:

- **Add:** Prompts the user to enter an integer and add it to the integer list. If the input is not a valid integer, display "Invalid input".
- **Remove:** Prompts the user to enter an integer to remove from the list. If the integer is found in the list, remove it; otherwise, display "Element not found". If the list is empty, display "List is empty".
- **Display:** Displays the current list of integers. If the list is empty, display "List is empty".
- **Quit:** Exits the program.
- The program should handle invalid menu choices by displaying "Invalid choice". Ensure that the program continues to prompt the user until they choose to quit (option 4).

```
# listOps.py
```

```
int_list = []
```

```
while True:
```

```
    print("1. Add")
```

```
    print("2. Remove")
```

```
    print("3. Display")
```

```
    print("4. Quit")
```

```
choice = input("Enter choice: ")
```

```
if choice == '1': # Add
```

```
    value = input("Integer: ")
```

```
    try:
```

```
        num = int(value)
```

```
        int_list.append(num)
```

```
        print("List after adding:", int_list)
```

```
    except ValueError:
```

```
        print("Invalid input")
```

```
elif choice == '2': # Remove
```

```
    if not int_list:
```

```
        print("List is empty")
```

```
    else:
```



```
value = input("Integer: ")

try:
    num = int(value)
    if num in int_list:
        int_list.remove(num)
        print("List after removing:", int_list)
    else:
        print("Element not found")
except ValueError:
    print("Invalid input")


elif choice == '3': # Display
    if not int_list:
        print("List is empty")
    else:
        print(int_list)


elif choice == '4': # Quit
    break


else:
    print("Invalid choice")
```

Average time
0.070 s
64.07 ms

Maximum time
0.100 s
100.00 ms

2 out of 2 shown test case(s) passed
1 out of 1 hidden test case(s) passed

Test case 1

Expanded output

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 1

Integer: 11

List after adding: [11]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 1

Integer: 25

List after adding: [11, 25]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 26

Element not found

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 15

List after removing: [25]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 26

List after removing: []

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 4

List is empty

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

List is empty

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 4

Invalid choice

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 4

Actual output

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 1

Integer: 11

List after adding: [11]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 1

Integer: 25

List after adding: [11, 25]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 26

Element not found

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 15

List after removing: [25]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 26

List after removing: []

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 4

List is empty

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

List is empty

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 4

Invalid choice

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 4

Test case 2

Explorer

Average time

0.072 s

71.67 ms

Maximum time

0.089 s

89.00 ms

2 out of 2 shown test case(s) passed

1 out of 1 hidden test case(s) passed

Debugger

Integer: 11	Integer: 11
List after removing: [25]	List after removing: [25]
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 2	Enter choice: 2
Integer: 25	Integer: 25
List after removing: []	List after removing: []
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 3	Enter choice: 3
List is empty	List is empty
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 2	Enter choice: 2
List is empty	List is empty
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 8	Enter choice: 8
Invalid choice	Invalid choice
1. Add	1. Add
2. Remove	2. Remove

< Prev

Reset

Submit

Next >

List is empty	List is empty
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 8	Enter choice: 8
Invalid choice	Invalid choice
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 4	Enter choice: 4

< Prev

Reset

Submit

Next >

2.1.2. Dictionary Operations

07:23

Write a Python program to perform insertion, update, deletion, and traversal operations on a dictionary. An initial dictionary containing 10 predefined records is already given in the program.

Operations to be Performed:

1. Insertion – Insert a new key-value pair into the dictionary using user input.
2. Update – Update the value of an existing key using user input.
3. Deletion – Delete a specified key from the dictionary using user input.
4. Traversal – Traverse the final dictionary and display all key-value pairs.

Input and Output Format:

1. Read an integer representing the key to be inserted and a string representing its value. Insert this new key-value pair into the dictionary and display the dictionary after insertion.
2. Read an integer representing the key to be updated and a string representing the new value. Update the value of the specified key (only if it exists) and display the dictionary after the update.
3. Read an integer representing the key to be deleted. Delete the specified key from the dictionary (only if it exists) and display the dictionary after deletion.
4. Finally, traverse the dictionary and display all key-value pairs.

The program should also display the original dictionary before performing any operations. Each output should be printed with appropriate messages.

Note:

- All operations must be performed using dictionary methods.
- Perform deletion only if possible; leave the dictionary unchanged.
- Refer to the visible test cases for better understanding and strictly match with the input/outputs.

```
# Initial dictionary with 10 predefined records
```

```
student = {
```

```
    1: "Amit",
```

```
    2: "Riya",
```

```
    3: "Kiran",
```

```
    4: "Neha",
```

```
    5: "Arjun",
```

```
    6: "Pooja",
```



```
7: "Rahul",  
8: "Sneha",  
9: "Vikram",  
10: "Anjali"  
}
```

```
# Display original dictionary
```

```
print("Original Dictionary:", student)
```

```
# Insertion
```

```
key = int(input())
```

```
value = input()
```

```
student[key] = value
```

```
print("After Insertion:", student)
```

```
# Update
```

```
upd_key = int(input())
```

```
upd_value = input()
```

```
if upd_key in student:
```

```
    student[upd_key] = upd_value
```

```
print("After Update:", student)
```

```
# Deletion
```

```
del_key = int(input())
```

```
if del_key in student:
```

```
    student.pop(del_key)
```

```
print("After Deletion:", student)
```



```
# Traversal
```

```
print("Traversing Dictionary:")
```

```
for k, v in student.items():
```

```
    print(k, ":", v)
```

Average time: 0.027 s, Maximum time: 0.044 s. 2 out of 2 shown test case(s) passed, 2 out of 2 hidden test case(s) passed.

Expected output	Actual output
Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}	Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}
11: Suresh	11: Suresh
After Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}	After Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
3: Karthik	3: Karthik
After Update: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}	After Update: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
5: Suresh	5: Suresh
After Deletion: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}	After Deletion: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
Traversing Dictionary:	Traversing Dictionary:
1: Amit	1: Amit
2: Riya	2: Riya
3: Karthik	3: Karthik
4: Neha	4: Neha
6: Pooja	6: Pooja
7: Rahul	7: Rahul
8: Sneha	8: Sneha
9: Vikram	9: Vikram
10: Anjali	10: Anjali
11: Suresh	11: Suresh

Terminal Test cases < Prev Reset Submit Next >

2.2.1. Linear search Technique

04:45

Write a program to check whether the given element is present or not in the array of elements using linear search.

Input format:

- The first line of input contains the array of integers which are separated by space
- The last line of input contains the key element to be searched

Output format:

- If the element is found, print the index.
- If the element is not found, print **Not found**.

Sample Test Case:**Input:**

1 2 3 4 3 5 6

3

Output:

2

```
# Read input array
```

```
arr = list(map(int, input().split()))
```

```
# Read key element
```

```
key = int(input())
```

```
# Linear search
```

```
found = False
```

```
for i in range(len(arr)):
```

```
    if arr[i] == key:
```



```
print(i)

found = True

break
```

If not found

if not found:

```
print("Not found")
```

The screenshot displays a code execution environment with the following details:

- Performance Metrics:**
 - Average time: 0.010 s (9.75 ms)
 - Maximum time: 0.012 s (12.00 ms)
- Test Results Summary:**
 - 2 out of 2 shown test case(s) passed
 - 2 out of 2 hidden test case(s) passed
- Test Case 1 Details:**
 - Status: Passed (10 ms)
 - Buttons: Debug, Menu, Calendar
 - Expected output:**
1 2 3 4 3 5 6
3
2
 - Actual output:**
1 2 3 4 3 5 6
3
2
- Test Case 2:** Passed (12 ms)

2.2.2. Captain of the Team

01:32

You are provided with the heights of 11 cricket players (in centimeters). Your task is to identify the tallest player, who will be selected as the captain of the team.

Input Format:

The first line of input will contain 11 integers, each representing the height of a player (in centimeters), each separated by a space.

Output Format

The output should be the height (in centimeters) of the tallest player.


```
# Read heights of 11 players
```

```
heights = list(map(int, input().split()))
```

```
# Find the tallest player
```

```
tallest = max(heights)
```

```
# Output the tallest height
```

```
print(tallest)
```

Average time
0.005 s
5.33 ms

Maximum time
0.006 s
6.00 ms

✓ 1 out of 1 shown test case(s) passed
✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 6 ms Debug

Expected output
171 169 185 156 174 191 186 190 187 172 160
191

Actual output
171 169 185 156 174 191 186 190 187 172 160
191

Terminal Test cases

< Prev Reset Submit Next >