

MACHINE LEARNING

ASSIGNMENT-6 (Submitted by:Anshul dubey) **Intership-28**

In Q1 to Q5, only one option is correct, Choose the correct option:

1. In which of the following you can say that the model is overfitting?
- A) High R-squared value for train-set and High R-squared value for test-set.
 - B) Low R-squared value for train-set and High R-squared value for test-set.
 - C) High R-squared value for train-set and Low R-squared value for test-set.
 - D) None of the above

ANS: High R-squared value for train-set and Low R-squared value for test-set.

2. Which among the following is a disadvantage of decision trees?
- A) Decision trees are prone to outliers.
 - B) Decision trees are highly prone to overfitting.
 - C) Decision trees are not easy to interpret
 - D) None of the above.

ANS: Decision trees are highly prone to overfitting.

3. Which of the following is an ensemble technique?
- A) SVM
 - C) Random Forest
 - B) Logistic Regression
 - D) Decision tree

ANS: Random Forest

4. Suppose you are building a classification model for detection of a fatal disease where detection of the disease is most important. In this case which of the following metrics you would focus on?

- B) Sensitivity
- D) None of the above
- A) Accuracy
- C) Precision

ANS: Sensitivity

5. The value of AUC (Area under Curve) value for ROC curve of model A is 0.70 and of model B is 0.85. Which of these two models is doing better job in classification?

- A) Model A
- C) both are performing equal
- B) Model B
- D) Data Insufficient

Ans: Model B

In Q6 to Q9, more than one options are correct, Choose all the correct options:

6. Which of the following are the regularization technique in Linear Regression??

- A) Ridge C) MSE
- B) R-squared D) Lasso

ANS: Ridge and Lasso

7. Which of the following is not an example of boosting technique?

- A) Adaboost C) Random Forest
- B) Decision Tree D) Xgboost

ANS: Random Forest and Decision Tree

8. Which of the techniques are used for regularization of Decision Trees?

- A) Pruning
- B) L2 regularization
- C) Restricting the max depth of the tree
- D) All of the above

ANS: Pruning AND Restricting the max depth of the tree

9. Which of the following statements is true regarding the Adaboost technique?

- A) We initialize the probabilities of the distribution as $1/n$, where n is the number of data-points
- B) A tree in the ensemble focuses more on the data points on which the previous tree was not performing well
- C) It is example of bagging technique
- D) None of the above

ANS: We initialize the probabilities of the distribution as $1/n$, where n is the number of data-points AND A tree in the ensemble focuses more on the data points on which the previous tree was not

Q10 to Q15 are subjective answer type questions, Answer them briefly.

10. Explain how does the adjusted R-squared penalize the presence of unnecessary predictors in the model?

ANS: The adjusted R-squared is a modified version of R-squared that has been adjusted for the number of predictors in the model. The adjusted R-squared increases only if the new term improves the model more than would be expected by chance. It decreases when a predictor improves the model by less than expected by chance. The adjusted R-squared can be negative, but it's usually not. It is always lower than the R-squared.

11. Differentiate between Ridge and Lasso Regression.

ANS: The difference between ridge and lasso regression is that it tends to make coefficients to absolute zero as compared to Ridge which never sets the value of coefficient to absolute zero.

In the lasso regression, ridge regression puts a similar constraint on the coefficients by introducing a penalty factor. However, while lasso regression takes the magnitude of the coefficients, ridge regression takes the square. Ridge regression is also referred to as L2 Regularization.

12. What is VIF? What is the suitable value of a VIF for a feature to be included in a regression modelling?

ANS: It explains multicollinearity. In general, a VIF above 10 indicates high correlation and is cause for concern

13. Why do we need to scale the data before feeding it to the train the model?

ANS: To ensure that the gradient descent moves smoothly towards the minima and that the steps for gradient descent are updated at the same rate for all the features, we scale the data before feeding it to the model. Having features on a similar scale can help the gradient descent converge more quickly towards the minima.

14. What are the different metrics which are used to check the goodness of fit in linear regression?

ANS: The sum of squares due to error (SSE)

- R-square
- Adjusted R-square
- Root mean squared error (RMSE)

15. From the following confusion matrix calculate sensitivity, specificity, precision, recall and accuracy.

Actual/Predicted	True	False
True	1000	50
1000	250	1200

ANS: Sensitivity = $1000/1050 = 0.95$

Specificity = $1200/1450 = 0.83$

Precision = $1000/1250 = 0.8$

Recall = $1000/1050 = 0.95$

Accuracy = $2200/2500 = 0.8$