

Candidate Order Instability in Non-Autoregressive Multi-Candidate Transformers

Anshul Saxena

Department of Computer Science & Information Systems, BITS Pilani
f20221041@hyderabad.bits-pilani.ac.in

<https://github.com/anshull-saxena/candidate-order-instability>

Zenodo DOI: [10.5281/zenodo.22906245](https://doi.org/10.5281/zenodo.22906245)

September 2026

Abstract

Candidate choices in classification form an unordered set, yet transformer classifiers frequently serialize options into sequential text. We evaluate candidate presentation order in non-autoregressive multi-candidate transformers ([convaiinnovations/laya](https://github.com/convaiinnovations/laya)), which score all choices in a single bidirectional pass via delimiter marker representations. Using the Banking77 benchmark under a strictly nested distractor protocol ($K \in \{5, 10, 20, 40, 77\}$) across $N = 120$ intent-stratified queries, we observe that pairwise argmax decision instability (FR_{top1}) increases from 5.70% [3.1%, 8.4%] at $K = 5$ to 47.28% [42.8%, 51.9%] at $K = 77$, accompanied by a $7.5\times$ expansion in candidate logit variance. While canonical alphabetical sorting enforces deterministic repeatability, counterfactual reverse-alphabetical sorting reveals a 55.83% [47.5%, 65.0%] disagreement rate at $K = 77$, demonstrating that canonicalization conceals rather than eliminates positional bias. Inference-time permutation marginalization suppresses residual flip rate to 25.83% ($M = 5$ random) and 16.11% ($M = 5$ cyclic shifts), while descriptively reducing Expected Calibration Error from 0.3857 to 0.0960. Crucially, under Benjamini-Hochberg False Discovery Rate control ($q = 0.05$) across 45 pre-specified paired comparisons, only cyclic shifts at $K = 40$ achieve statistically significant accuracy gains (+9.17 percentage points, adjusted $p = 0.04395$); at $K = 77$, accuracy gains fail FDR significance. Furthermore, we document the non-replication of an exploratory 65.0% cyclic accuracy finding, which regressed to 48.06% [39.7%, 55.6%] under multi-seed replication ($N = 120, S = 3$). All artifacts, data, and verification suites are openly archived.

1 Introduction

In classification, dialogue state tracking, intent routing, and tool selection, a classifier is presented with an input query q and a candidate set $\mathcal{C} = \{c_1, \dots, c_K\}$. In mathematical formulations of classification, $\mathcal{C}$ is an unordered set: the set of choices available to the decision rule does not possess an intrinsic sequence. Consequently, an ideal decision function $f(q, \mathcal{C})$ should be permutation-invariant: for any permutation $\pi \in \mathcal{S}_K$, reordering the candidates prior to presentation should yield identical classifications:

$$f(q, \pi(\mathcal{C})) = f(q, \mathcal{C}). \quad (1)$$

In practice, modern transformer-based classifiers often serialize choices into text. In autoregressive language models, choices are presented as prompt lists (e.g., “Options: (A) ... (B) ...”), which have been repeatedly shown to induce recency, primacy, and option-order biases [Liu et al., 2024, Pezeshkpour and Hruschka, 2024, Zheng et al., 2024]. To achieve low-latency inference in agentic routing and intent classification, non-autoregressive multi-candidate transformers [M, 2024] evaluate all K candidates simultaneously within a single bidirectional forward pass. In

this architecture, candidate strings are concatenated into a single input sequence separated by candidate-specific marker tokens. The sequence is processed by a bidirectional encoder (e.g., RoBERTa; Liu et al., 2019), and per-candidate classification logits are extracted by projecting the contextualized marker embeddings through a linear head.

While computationally efficient ($O(1)$ forward passes with respect to K), serializing unordered choices into a 1D sequence injects artificial positional relationships. Because full bidirectional self-attention couples every token with all other tokens, the contextualized representation of candidate marker M_k is influenced by its absolute position, its relative distance from query tokens, and the semantic identities of its immediate sequence neighbors.

This empirical investigation addresses the question: *Does candidate presentation order act as a hidden nuisance variable in non-autoregressive multi-candidate transformer decision architectures, and how does this sensitivity scale with candidate cardinality K ?*

To answer this question rigorously, we perform a controlled empirical study using the Banking77 benchmark [Casanueva et al., 2020] on the open-source `convaiinnovations/laya` model checkpoint. Our experimental contributions and findings are scoped as follows:

1. **Controlled Distractor Nesting Protocol:** We design a strictly nested candidate-subsampling protocol ($K_5 \subset K_{10} \subset K_{20} \subset K_{40} \subset K_{77}$) over $N = 120$ test queries stratified across all 77 intent classes, ensuring that cardinality comparisons are not confounded by stochastic distractor sampling.
2. **Order Sensitivity Scaling:** Holding query and candidate sets fixed, random permutations induce an argmax decision flip rate (FR_{top1}) that increases from 5.70% [3.1%, 8.4%] at $K = 5$ to 47.28% [42.8%, 51.9%] at $K = 77$. Cross-permutation candidate logit variance expands by $7.5\times$ ($8.40 \rightarrow 63.34$).
3. **The Canonicalization Fallacy:** Canonical alphabetical sorting eliminates run-to-run prediction variance ($\text{FR}_{\text{top1}} \equiv 0.0\%$), but counterfactual reverse-alphabetical sorting ($Z \rightarrow A$) induces a 55.83% [47.5%, 65.0%] disagreement rate at $K = 77$. Deterministic serialization locks in exposure bias rather than removing order sensitivity.
4. **Inference-Time Order Marginalization:** Without modifying model weights, averaging probability vectors over $M \in \{1, 2, 3, 5\}$ permutations reduces residual decision instability. At $K = 77$, random marginalization suppresses residual flip rate to 25.83% ($M = 5$), while orthogonal cyclic shifts achieve 16.11% residual flip rate at equal compute.
5. **Rigorous Statistical Analysis & Negative Result:** Across 45 pre-specified paired comparisons controlled under Benjamini-Hochberg False Discovery Rate ($q = 0.05$), only one method achieves statistically significant accuracy gains: cyclic shifts at $K = 40$ (+9.17 percentage points, adjusted $p = 0.04395$). At $K = 77$, accuracy gains fail FDR significance. Furthermore, we document the non-replication of an exploratory 65.0% accuracy finding, which regressed to 48.06% under pre-specified multi-seed replication.

2 Related Work

2.1 Permutation-Invariant Learning on Sets

In mathematical formulations of set processing and classification, an input candidate set $\mathcal{X} = \{x_1, \dots, x_K\}$ constitutes an unordered collection of elements. A set function $f : 2^{\mathcal{X}} \rightarrow \mathbb{R}^d$ is defined as permutation-invariant if for any permutation $\pi \in \mathcal{S}_K$, $f(\pi(\mathcal{X})) = f(\mathcal{X})$, and permutation-equivariant if $f(\pi(\mathcal{X})) = \pi(f(\mathcal{X}))$.

Foundational principles of deep learning over sets established by Zaheer et al. [2017] (Deep Sets) establish that any continuous permutation-invariant function acting on countable sets can

be decomposed into the canonical form $\rho(\sum_{x \in \mathcal{X}} \phi(x))$, where ϕ maps instances independently to a latent representation space and ρ applies non-linear transformations subsequent to a symmetric pooling operator (e.g., sum, mean, or max). Lee et al. [2019] extended this framework to model higher-order pairwise and subset interactions using attention mechanisms via the Set Transformer, which employs multi-head attention without positional encodings (through Induced Set Attention Blocks and Pooling by Multihead Attention) to enforce strict permutation equivariance and invariance by construction.

A fundamental distinction must be maintained between three paradigms: (i) a mathematical set function where inputs inherently lack sequential ordering, (ii) permutation-invariant architectures (e.g., Deep Sets and Set Transformer) that structurally enforce invariance by construction, and (iii) a sequence encoder that processes set elements through an ordered 1D serialization. The architecture evaluated in this work (convainnovations/laya; M, 2024) belongs to the third paradigm. Rather than pooling independent instance projections, it serializes candidate elements into a single prompt string separated by delimiter markers. Consequently, the architecture trades architectural permutation invariance for cross-candidate self-attention context, inherently coupling candidate representations to sequential coordinates.

2.2 Transformers and Positional Information

The standard transformer architecture [Vaswani et al., 2017] relies on Scaled Dot-Product Attention, which is fundamentally permutation-equivariant over unordered sets of input tokens in the absence of positional encodings. To enable transformers to parse the syntax and word order of natural language, sequence position information is deliberately introduced. In the original formulation [Vaswani et al., 2017], sinusoidal positional embeddings were added to token embeddings, whereas modern pretrained bidirectional encoders such as BERT and RoBERTa [Liu et al., 2019] employ learned absolute positional embeddings.

Subsequent architectural developments introduced relative positional representations [Shaw et al., 2018], rotary position embeddings (RoPE; Su et al., 2024), and linear attention biases (ALiBi; Press et al., 2022), which condition attention scores directly on relative token displacements $|i - j|$ rather than absolute sequence indices. As systematically reviewed by Dufter et al. [2022], positional representations fundamentally shape self-attention dynamics: they bias attention distributions toward local sequence neighborhoods, alter token representation geometry across successive layers, and cause self-attention entropy to redistribute as sequence length scales.

This literature provides the core mechanistic motivation for our investigation: because positional encodings inject non-uniform spatial inductive biases, serializing unordered candidates into a 1D sequence inevitably exposes each candidate marker to position-dependent representational shifts. However, positional encoding literature alone does not establish or prove the presence of candidate-order instability in multi-candidate concatenation architectures; empirical evaluation is necessary to measure its real-world magnitude.

2.3 Order Sensitivity in Language Models

Order-dependent sensitivity has been widely documented in recent empirical studies of pretrained language models, spanning three distinct phenomena:

1. **Few-shot prompt demonstration ordering:** Lu et al. [2022] observed that the presentation order of in-context exemplars in few-shot prompts dramatically impacts autoregressive language model accuracy, causing performance to swing between near-chance accuracy and peak benchmark accuracy across permutations of the exact same demonstration set. Zhao et al. [2021] similarly identified substantial majority-label, recency, and common-token biases in prompt-based classification, introducing test-time affine calibration of output logits.

2. **Context ordering and positional bias:** In document retrieval and question answering over long sequences, Liu et al. [2024] demonstrated the “lost-in-the-middle” phenomenon: language models retrieve information effectively when relevant context is placed at the extreme beginning or end of the input sequence, but experience severe performance degradation when relevant passages reside in the interior.
3. **Option order bias in multiple-choice selection:** When multiple-choice questions are presented to large language models with letter-labeled options (e.g., A, B, C, D), Pezeshkpour and Hruschka [2024] and Zheng et al. [2024] demonstrated that models exhibit strong selection biases toward specific option positions or identifiers, frequently flipping their selected choice when options are permuted.

To properly contextualize the present study, it is critical to distinguish these prior phenomena from the problem addressed here. We do not evaluate prompt demonstration ordering in few-shot in-context learning [Lu et al., 2022], nor natural language token order in autoregressive generation, nor letter-associated choice options evaluated via next-token generation probabilities [Pezeshkpour and Hruschka, 2024, Zheng et al., 2024]. Instead, our study focuses on candidate ordering in a non-autoregressive, encoder-based discriminative architecture: all K candidates are concatenated into a single bidirectional sequence with delimiter markers, and classification logits are simultaneously extracted from marker embeddings via a shared linear head.

2.4 Intent Classification and Candidate Selection

Intent classification serves as a cornerstone task in conversational AI, dialogue state tracking, and agentic tool routing, where user queries must be matched against pre-defined intent categories. The Banking77 benchmark [Casanueva et al., 2020] provides an authoritative, fine-grained evaluation suite comprising 13,083 customer service utterances spanning 77 intent classes. Its high semantic density and fine granularity—distinguishing between closely related categories such as `card_arrival`, `card_linking`, and `card_delivery_estimate`—provide a realistic, challenging testbed where distractors exhibit strong semantic overlap.

Multi-candidate selection in conversational systems has traditionally relied on two architectural paradigms:

- **Dual-encoders (Bi-encoders):** Queries and candidate labels are encoded into independent dense representations, and similarity is scored via dot-product or cosine distance [Casanueva et al., 2020]. Dual-encoders are strictly permutation-invariant with respect to candidate presentation and achieve $O(1)$ query forward passes with pre-indexed candidates. However, they lack cross-attention between candidates and the query during encoding, limiting discriminative capacity.
- **Cross-encoders:** The query and each candidate are concatenated into a single sequence ([CLS] q [SEP] c [SEP]) and processed with full cross-attention [Nogueira and Cho, 2019]. While cross-encoders achieve high accuracy by modeling fine-grained query-candidate interactions, scoring K candidates requires K separate forward passes ($O(K)$ complexity), creating prohibitive latency overheads in real-time agentic routing.
- **Poly-encoders:** Humeau et al. [2020] bridge this trade-off by extracting multiple contextual query embeddings and attending over candidate encodings, but preserve separate candidate representations.

The non-autoregressive multi-candidate architecture (convaiinnovations/laya; M, 2024) attempts to overcome the $O(K)$ computational barrier of cross-encoders while retaining cross-attention by packing all K candidates into a single sequence separated by reserved delimiter tokens. This design achieves $O(1)$ forward passes with full bidirectional cross-candidate attention, but introduces sequence serialization order as an unmodelled confounding variable.

2.5 Calibration and Inference-Time Marginalization

Confidence Calibration. In automated decision routing and tool invocation, predicted confidence scores govern critical control decisions: whether to execute an action autonomously, prompt the user for confirmation, or route to a human operator. A classifier is well-calibrated when predicted probabilities correspond to empirical accuracy: $\mathbb{P}(\hat{y} = y \mid \hat{p} = p) = p$ [Guo et al., 2017]. Expected Calibration Error (ECE; Naeini et al., 2015, Nixon et al., 2019) quantifies calibration mismatch by partitioning predictions into discrete confidence bins. Deep neural networks, particularly modern transformer architectures, are well known to produce poorly calibrated, overconfident posterior distributions [Guo et al., 2017]. In this study, we measure whether candidate order permutation and ensemble marginalization affect empirical calibration, evaluating ECE through clustered bootstrap distributions.

Ensembling and Test-Time Augmentation. Aggregating predictions across perturbed inputs has deep roots in statistical learning and uncertainty estimation:

- **Deep Ensembles:** Lakshminarayanan et al. [2017] established that ensembling independently trained models significantly improves predictive accuracy and uncertainty calibration.
- **Test-Time Augmentation (TTA):** In computer vision, applying stochastic data augmentations (e.g., cropping, scaling, rotation) at test time and averaging predictions provides effective marginalization over nuisance variations, reducing aleatoric uncertainty and boosting accuracy [Ayhan and Berens, 2018, Shanmugam et al., 2020].
- **Reasoning Marginalization:** In language model reasoning, self-consistency [Wang et al., 2023] marginalizes over diverse reasoning paths sampled at inference time, demonstrating that averaging over stochastic generation paths yields substantial performance gains.

In our setting, random permutation marginalization operationalizes test-time augmentation for sequence serialization, treating candidate order $\pi \sim \mathcal{S}_K$ as a nuisance variable to be numerically integrated out. In parallel, we evaluate orthogonal cyclic permutation shifts as a structured, deterministic phase-shift heuristic designed to maximize positional dispersion across candidates at equal compute budget.

2.6 Positioning of the Present Study: Critical Gap Analysis

Synthesizing the prior literature reveals a fundamental research gap:

1. **Permutation Invariance vs. Practical Concatenation:** Foundational set-function theory [Zaheer et al., 2017, Lee et al., 2019] establishes that unordered collections should ideally be processed permutation-invariantly. However, practical high-throughput routing architectures [M, 2024] concatenate candidates into a 1D sequence to leverage pretrained bidirectional representations.
2. **Positional Coupling:** Transformer literature [Vaswani et al., 2017, Shaw et al., 2018, Su et al., 2024, Dufter et al., 2022] shows that sequence positional mechanisms fundamentally shape contextual representations across layers.
3. **Prior Order Sensitivity Scope:** Prior order-sensitivity studies focused on prompt demonstration order in few-shot LLMs [Lu et al., 2022, Zhao et al., 2021], document context order in retrieval [Liu et al., 2024], or option letter selection in multiple-choice QA [Pezeshkpour and Hruschka, 2024, Zheng et al., 2024].
4. **Benchmark Realism:** Intent-classification literature [Casanueva et al., 2020] provides fine-grained, semantically dense candidate-selection tasks.

5. **The Unaddressed Setting:** None of these prior works investigated the behavior of an unordered candidate set serialized into a single bidirectional marker sequence where each candidate’s score is read directly from its corresponding marker representation in a single forward pass.
6. **Controlled Empirical Characterization:** The present study provides the first systematic quantification of this setting, measuring:
 - Fixed-candidate-set decision flip rates (FR_{top1}),
 - Cardinality scaling across $K \in \{5, 10, 20, 40, 77\}$,
 - Logit variance expansion ($7.5\times$),
 - The canonicalization fallacy via counterfactual reverse-order testing,
 - Inference-time random and cyclic permutation marginalization laws, and
 - Empirical confidence calibration (ECE) effects.
7. **Methodological Isolation:** By employing strictly nested candidate sets ($K_5 \subset K_{10} \subset K_{20} \subset K_{40} \subset K_{77}$) and query-clustered statistical inference ($N = 120$), we cleanly isolate the effect of candidate cardinality from distractor composition. This controlled isolation and empirical evidence form the primary novelty of this work.

3 Problem Formulation and Model Architecture

3.1 Architectural Mechanism

The model under evaluation (`convaiinnovations/laya`) implements a single-pass multi-candidate classification architecture. Given an input query q and candidate intents $\mathcal{C} = \{c_0, c_1, \dots, c_{K-1}\}$, the serialization module serializes the components into a single token sequence:

$$\mathbf{x}(\pi) = [\text{[CLS]}, q_1, \dots, q_L, \text{[SEP]}, [\mathbf{M}_0], c_{\pi(0)}, [\mathbf{M}_1], c_{\pi(1)}, \dots, [\mathbf{M}_{K-1}], c_{\pi(K-1)}, \text{[SEP]}] \quad (2)$$

where $[\mathbf{M}_i]$ denotes a reserved structural marker token, and $\pi \in \mathcal{S}_K$ denotes a candidate permutation.

The serialized sequence $\mathbf{x}(\pi)$ is processed by a bidirectional transformer encoder (RoBERTa backbone with Scaled Dot-Product Attention; Vaswani et al., 2017, Liu et al., 2019):

$$\mathbf{H} = \text{Encoder}(\mathbf{x}(\pi)) \in \mathbb{R}^{T \times d}. \quad (3)$$

The contextualized hidden states corresponding to each marker token $h_{M_i} \in \mathbb{R}^d$ are extracted and passed through a shared linear classification head $W \in \mathbb{R}^{1 \times d}$:

$$s(q, c_{\pi(i)}; \pi) = Wh_{M_i} + b. \quad (4)$$

The unnormalized scores are converted to a predictive probability distribution via softmax with temperature T :

$$p(c_{\pi(i)} \mid q; \pi) = \frac{\exp(s(q, c_{\pi(i)}; \pi)/T)}{\sum_{j=0}^{K-1} \exp(s(q, c_{\pi(j)}; \pi)/T)}. \quad (5)$$

The predicted class is selected via argmax:

$$\hat{y}(q; \pi) = \underset{c \in \mathcal{C}}{\operatorname{argmax}} p(c \mid q; \pi). \quad (6)$$

3.2 Origin of Order Sensitivity

In a standard cross-encoder or bi-encoder architecture, each candidate c is evaluated either independently against q or as an isolated pair (q, c) . In contrast, concatenating all K candidates into $\mathbf{x}(\pi)$ exposes candidate representations to two coupling mechanisms:

1. **Direct Cross-Candidate Attention:** Every candidate token directly attends to tokens belonging to all other candidates in the bidirectional encoder.
2. **Positional Coordinate Disruption:** Changing the index $\pi(i)$ shifts the candidate’s absolute token position in the sequence, altering its positional embedding vectors and self-attention dot-product geometry [Dufter et al., 2022].

4 Experimental Setup

4.1 Dataset and Query Population

We conduct all evaluations on the official test split of the Banking77 dataset [Casanueva et al., 2020], which comprises 13,083 customer support queries across 77 fine-grained banking intent categories (3,080 test examples). To ensure representative coverage without cherry-picking, we stratify $N = 120$ unique test queries across all 77 intent classes. Every query is assigned a permanent identifier ($q \in \{0, \dots, 119\}$). All methods and cardinalities are evaluated on this identical query population.

4.2 Strictly Nested Candidate Protocol

To isolate the effect of candidate cardinality $K \in \{5, 10, 20, 40, 77\}$ from distractor sampling variance, we enforce a strict distractor nesting invariant. For each query q with ground-truth label y^* :

1. A deterministic master sequence of the 76 remaining distractor classes $D_q = [d_1, \dots, d_{76}]$ is generated using a fixed seed derived exclusively from the query index: $\text{seed} = 42 + q \times 1000$.
2. Candidate sets are constructed as prefixes of this master sequence:

$$\mathcal{C}_{q,5} = \{y^*\} \cup D_q[0 : 4] \tag{7}$$

$$\mathcal{C}_{q,10} = \{y^*\} \cup D_q[0 : 9] \tag{8}$$

$$\mathcal{C}_{q,20} = \{y^*\} \cup D_q[0 : 19] \tag{9}$$

$$\mathcal{C}_{q,40} = \{y^*\} \cup D_q[0 : 39] \tag{10}$$

$$\mathcal{C}_{q,77} = \{y^*\} \cup D_q[0 : 76] \tag{11}$$

3. Programmatic assertions verify that $\mathcal{C}_{q,5} \subset \mathcal{C}_{q,10} \subset \mathcal{C}_{q,20} \subset \mathcal{C}_{q,40} \subset \mathcal{C}_{q,77}$ for every query, and candidate set SHA-256 hashes are logged to verify data identity across methods.

4.3 Evaluation Baselines and Interventions

We compare the following inference-time candidate presentation protocols:

- **B0_Native:** Native unperturbed distractor ordering as serialized by the nested subset generator.
- **B0_Random:** $P = 10$ independent uniform random permutations $\pi \sim \mathcal{S}_K$ per query.
- **B1_Alpha (Canonical):** Candidates sorted alphabetically by label string ($A \rightarrow Z$).

- **B1_ReverseAlpha (Counterfactual):** Candidates sorted in reverse alphabetical order ($Z \rightarrow A$).
- **Rand_Marg_M (Random Marginalization):** Output probability vectors averaged over $M \in \{2, 3, 5\}$ independent random candidate permutations, drawing on principles of inference-time test-time augmentation [Ayhan and Berens, 2018, Shanmugam et al., 2020]: $\bar{p}_M(c) = \frac{1}{M} \sum_{m=1}^M p(c; \pi_m)$.
- **B2_Cyclic_M (Orthogonal Cyclic Shifts):** Output probability vectors averaged over $M \in \{2, 3, 5\}$ deterministic cyclic phase shifts: $s_m = (m \cdot \lfloor K/M \rfloor) \pmod{K}$.

4.4 $K = 77$ Multi-Base Ordering Replication Protocol

At $K = 77$, all 77 candidates are present in every query’s candidate set. To prevent the benchmark from anchoring to an arbitrary single baseline ordering, $K = 77$ evaluations are replicated across three independently seeded base candidate sequences: alphabetical ordering, seed 7701, and seed 7702. Results reported at $K = 77$ represent the unweighted average across these three base sequences.

5 Metrics and Statistical Analysis

5.1 Mathematical Definitions

1. Argmax Decision Flip Rate (FR_{top1}). Within-method decision instability measures the probability that two independent candidate permutations of the exact same candidate set $\mathcal{C}$ yield different top-1 classifications:

$$\text{FR}_{\text{top1}}(q, \mathcal{C}) = \mathbb{E}_{\pi_1, \pi_2 \sim \mathcal{S}_K} \left[\mathbf{1} \left(\underset{c \in \mathcal{C}}{\text{argmax}} s(q, c; \pi_1) \neq \underset{c \in \mathcal{C}}{\text{argmax}} s(q, c; \pi_2) \right) \right]. \quad (12)$$

For $P = 10$ random permutations per query, $\text{FR}_{\text{top1}}(q)$ is estimated as a degree-2 U -statistic over all $\binom{10}{2} = 45$ pairwise permutation comparisons. The independent statistical sampling unit is strictly the query ID ($N = 120$).

2. Cross-Canonical Flip Rate (CrossCanonicalFlip). For deterministic alphabetical sorting (‘B1_Alpha’), within-method permutation instability is identically zero ($\text{FR}_{\text{top1}} \equiv 0.0\%$) because repeating identical input strings yields deterministic model outputs. To measure true underlying positional bias, we define the cross-canonical disagreement rate between alphabetical and reverse-alphabetical orderings:

$$\text{CrossCanonicalFlip}(q, \mathcal{C}) = \mathbf{1} \left(\underset{c \in \mathcal{C}}{\text{argmax}} s(q, c; \pi_\alpha) \neq \underset{c \in \mathcal{C}}{\text{argmax}} s(q, c; \pi_{\text{rev}_\alpha}) \right). \quad (13)$$

FR_{top1} and CrossCanonicalFlip are maintained as separate metrics throughout our analysis.

3. Residual Ensemble Flip Rate (ResFlip_M). To measure residual instability after marginalizing over M permutations, we evaluate the discordance between two non-overlapping M -pass ensembles:

$$\text{ResFlip}_M(q) = \mathbf{1} \left(\underset{c}{\text{argmax}} \frac{1}{M} \sum_{m=1}^M p(c; \pi_m) \neq \underset{c}{\text{argmax}} \frac{1}{M} \sum_{m=M+1}^{2M} p(c; \pi_m) \right). \quad (14)$$

4. Expected Calibration Error (ECE). Predictions are partitioned into $B = 15$ equally spaced confidence bins $I_b = (\frac{b-1}{B}, \frac{b}{B}]$. Binned calibration error is calculated directly over the model’s calibrated probability outputs [Guo et al., 2017, Naeini et al., 2015, Nixon et al., 2019]:

$$\text{ECE} = \sum_{b=1}^B \frac{|I_b|}{N} |\text{acc}(I_b) - \text{conf}(I_b)|. \quad (15)$$

5. Normalized Kendall’s Tau Distance (τ_{norm}). The fraction of discordant candidate pairs between two ranking vectors over K choices [Kendall, 1938]:

$$\tau_{\text{norm}}(s_a, s_b) = \frac{1}{\binom{K}{2}} \sum_{1 \leq i < j \leq K} \mathbf{1}((s_a[i] - s_a[j])(s_b[i] - s_b[j]) < 0). \quad (16)$$

5.2 Statistical Protocol

- **Query-Level Clustered Bootstrap:** All 95% confidence intervals are generated using $B = 1,000$ query-level bootstrap resamples with replacement ($N = 120$) [Efron and Tibshirani, 1993]. For ECE, the full 15-bin formula is re-evaluated on each bootstrap sample to produce valid empirical percentiles.
- **Paired Hypothesis Tests:** Differences in top-1 accuracy between interventions and ‘B0_Native’ are evaluated using exact two-sided McNemar tests on discordant classification pairs [McNemar, 1947].
- **Multiple Testing Correction:** To guard against false positive discoveries across exploratory comparisons, we apply Benjamini-Hochberg False Discovery Rate (FDR) control at $q = 0.05$ across all 45 pre-specified hypotheses (5 cardinalities $\times$ 9 intervention methods) [Benjamini and Hochberg, 1995].


6 Results

6.1 Cardinality Scaling of Order Instability


As reported in Table 1 and illustrated in Figure 1a, candidate presentation order induces measurable decision instability across all evaluated cardinalities. When the candidate set $\mathcal{C}$ and query q are held strictly constant, the pairwise argmax flip rate FR_{top1} increases strongly from 5.70% [3.1%, 8.4%] at $K = 5$ to 47.28% [42.8%, 51.9%] at $K = 77$. At $K = 77$, nearly half of all random permutation pairs yield discordant top-1 predictions for the exact same input query.

Table 1: **Main Candidate Cardinality Scaling Results.** Evaluated on Banking77 ($N = 120$ unique test queries, strictly nested candidate sets). 95% confidence intervals reflect 1,000 query-level clustered bootstrap resamples. Significance indicates Benjamini-Hochberg FDR control ($q = 0.05$) across 45 comparisons against B0_Native.

K	Chance	Method	Accuracy [95% CI]	ECE [95% CI]	FR_{top1} [95% CI]	Cross-Flip	Latency	FDR Sig
5	20.0%	B0_Native	0.925 [0.88, 0.97]	0.147 [0.12, 0.20]	0.000 [0.00, 0.00]	–	45.3 ms	No
5	20.0%	B0_Random	0.925 [0.88, 0.97]	0.160 [0.12, 0.22]	0.057 [0.03, 0.08]	–	45.3 ms	No
5	20.0%	B1_Alpha	0.908 [0.86, 0.96]	0.131 [0.10, 0.19]	0.000 [0.00, 0.00]	0.033	45.3 ms	No
5	20.0%	Rand_Marg_M5	0.925 [0.88, 0.97]	0.144 [0.11, 0.20]	0.017 [0.00, 0.04]	–	226.7 ms	No
5	20.0%	B2_Cyclic_M5	0.908 [0.85, 0.96]	0.124 [0.10, 0.18]	0.000 [0.00, 0.00]	–	226.7 ms	No
10	10.0%	B0_Native	0.875 [0.82, 0.93]	0.104 [0.07, 0.17]	0.000 [0.00, 0.00]	–	60.9 ms	No
10	10.0%	B0_Random	0.833 [0.77, 0.90]	0.103 [0.07, 0.17]	0.064 [0.04, 0.09]	–	60.9 ms	No
10	10.0%	B1_Alpha	0.867 [0.81, 0.93]	0.113 [0.09, 0.18]	0.000 [0.00, 0.00]	0.050	60.9 ms	No
10	10.0%	Rand_Marg_M5	0.883 [0.82, 0.93]	0.105 [0.08, 0.16]	0.033 [0.01, 0.07]	–	304.7 ms	No
10	10.0%	B2_Cyclic_M5	0.875 [0.82, 0.93]	0.112 [0.08, 0.18]	0.008 [0.00, 0.03]	–	304.7 ms	No
20	5.0%	B0_Native	0.767 [0.69, 0.84]	0.191 [0.14, 0.26]	0.000 [0.00, 0.00]	–	97.4 ms	No
20	5.0%	B0_Random	0.817 [0.75, 0.88]	0.153 [0.10, 0.22]	0.120 [0.08, 0.16]	–	97.4 ms	No
20	5.0%	B1_Alpha	0.792 [0.72, 0.86]	0.162 [0.12, 0.25]	0.000 [0.00, 0.00]	0.117	97.4 ms	No
20	5.0%	Rand_Marg_M5	0.817 [0.75, 0.88]	0.113 [0.08, 0.18]	0.042 [0.01, 0.08]	–	486.8 ms	No
20	5.0%	B2_Cyclic_M5	0.792 [0.72, 0.87]	0.107 [0.08, 0.19]	0.033 [0.01, 0.07]	–	486.8 ms	No
40	2.5%	B0_Native	0.617 [0.53, 0.71]	0.265 [0.21, 0.36]	0.000 [0.00, 0.00]	–	146.1 ms	No
40	2.5%	B0_Random	0.650 [0.56, 0.73]	0.267 [0.21, 0.36]	0.221 [0.18, 0.27]	–	146.1 ms	No
40	2.5%	B1_Alpha	0.692 [0.61, 0.77]	0.212 [0.16, 0.30]	0.000 [0.00, 0.00]	0.167	146.1 ms	No
40	2.5%	Rand_Marg_M5	0.700 [0.62, 0.78]	0.180 [0.14, 0.27]	0.117 [0.06, 0.18]	–	730.4 ms	No
40	2.5%	B2_Cyclic_M5	0.708 [0.62, 0.79]	0.172 [0.13, 0.26]	0.050 [0.02, 0.09]	–	730.4 ms	Yes (*)
77	1.3%	B0_Native	0.422 [0.34, 0.50]	0.370 [0.30, 0.45]	0.000 [0.00, 0.00]	–	224.7 ms	No
77	1.3%	B0_Random	0.436 [0.36, 0.51]	0.386 [0.31, 0.47]	0.473 [0.43, 0.52]	–	224.7 ms	No
77	1.3%	B1_Alpha	0.492 [0.40, 0.58]	0.334 [0.27, 0.43]	0.000 [0.00, 0.00]	0.558	224.7 ms	No
77	1.3%	Rand_Marg_M5	0.550 [0.47, 0.62]	0.096 [0.09, 0.20]	0.258 [0.20, 0.32]	–	1123.4 ms	No
77	1.3%	B2_Cyclic_M5	0.497 [0.42, 0.57]	0.162 [0.13, 0.26]	0.161 [0.12, 0.21]	–	1123.4 ms	No



(a) Argmax decision flip rate (FR_{top1}) scaling.



(b) Mean cross-permutation logit variance (σ_{logit}^2).

Figure 1: **Candidate Cardinality Scaling.** (a) Pairwise decision flip rate FR_{top1} strongly increases as candidate cardinality K expands. (b) Mean candidate logit variance across permutations expands by $7.5\times$ ($8.40 \rightarrow 63.34$), driven by sequence-length attentional dilution.

This instability is accompanied by a severe expansion in cross-permutation logit volatility. As shown in Figure 1b, the mean variance of candidate log-probabilities across permutations increases by $7.5\times$, scaling from 8.40 at $K = 5$ to 63.34 at $K = 77$. As sequence length expands from 60 tokens to over 450 tokens, self-attention entropy distributes over a wider context, increasing marker hidden state variance.

6.2 The Canonical Ordering Counterfactual

A common engineering approach to non-deterministic serialization is canonicalization (e.g., sorting candidates alphabetically by label string). Under repeated execution, ‘B1_Alpha’ achieves perfect repeatability ($\text{FR}_{\text{top1}} \equiv 0.0\%$), giving the illusion of invariance.




Figure 2: **Canonical Counterfactual Analysis.** (Left) Classification accuracy under alphabetical ($A \rightarrow Z$) versus reverse alphabetical ($Z \rightarrow A$) candidate sorting across cardinalities. (Right) Cross-canonical disagreement rate reaches 55.83% at $K = 77$, demonstrating that canonical sorting conceals rather than eliminates underlying positional exposure bias.

To test whether alphabetical sorting resolves true positional sensitivity, we evaluate the counterfactual reverse-alphabetical ordering (‘B1_ReverseAlpha’, $Z \rightarrow A$). As depicted in Figure 2, the cross-canonical flip rate increases from 3.33% [0.8%, 6.7%] at $K = 5$ to 55.83% [47.5%, 65.0%] at $K = 77$. At $K = 77$, in more than half of all queries, reversing candidate string order alters the model’s top-1 classification. Canonicalization does not restore permutation invariance; it merely locks the decision boundary into a static positional bias that systematically favors early-alphabet tokens.

6.3 Random Marginalization Scaling

Averaging softmax output probabilities over $M \in \{1, 2, 3, 5\}$ random permutations monotonically reduces residual decision instability. At $K = 77$, residual flip rate decreases from 47.28% at $M = 1$ down to 38.06% ($M = 2$), 34.72% ($M = 3$), and 25.83% [20.3%, 32.0%] at $M = 5$ (Figure 3).




Figure 3: **Permutation Marginalization Scaling.** Residual decision flip rate decreases monotonically as ensemble passes M increase from 1 to 5 across $K \in \{20, 40, 77\}$.

6.4 Orthogonal Cyclic Marginalization and Paired Hypothesis Testing

Deterministic cyclic permutation shifts (‘B2_Cyclic’) distribute candidate markers evenly across all sequence positions using orthogonal phase offsets. At equal computational cost ($M = 5$ forward passes), cyclic marginalization achieves a residual flip rate of 16.11% [11.9%, 20.6%] at $K = 77$, compared to 25.83% [20.3%, 32.0%] for random marginalization (Figure 4). Cyclic shifts provide more uniform positional coverage per forward pass than random uniform sampling.




Figure 4: **Cyclic versus Random Marginalization at $K = 77$.** (Left) Top-1 accuracy comparison across ensemble budgets $M \in \{2, 3, 5\}$. (Right) Residual decision flip rate: cyclic shifts suppress residual instability to 16.11% at $M = 5$, compared to 25.83% for random marginalization.

Across all 45 pre-specified paired comparisons against ‘B0_Native’ under Benjamini-Hochberg False Discovery Rate control ($q = 0.05$), exactly **one comparison achieved statistical significance**:

- **‘B2_Cyclic_M5’ at $K = 40$:** Achieved 70.83% accuracy versus 61.67% for ‘B0_Native’ (+9.17 percentage points, 11 discordant gains, 0 losses, unadjusted two-sided exact McNemar $p = 0.0009765625$, BH-adjusted $p = 0.04395$).

At $K = 77$, although ‘Rand_Marg_M5’ observed an apparent accuracy gain of +12.78 percentage points (55.00% vs 42.22%, 27 gains, 11 losses, unadjusted $p = 0.0145$), this difference **failed FDR-adjusted statistical significance** (BH-adjusted $p = 1.0000$). With $N = 120$ queries and binary outcomes, query-level variance precludes declaring $K = 77$ accuracy gains statistically significant under rigorous multiple-testing control. Selected hypothesis test comparisons are summarized in Table 2.

Table 2: **Paired Hypothesis Tests vs B0_Native (Selected Comparisons)**. Two-sided exact McNemar tests on discordant classification pairs with Benjamini-Hochberg FDR adjustments ($q = 0.05$).

K	Method	Δ Accuracy	Gains / Losses	Unadjusted p	BH-Adjusted p	FDR Sig
5	B1_Alpha	−1.67%	1 / 3	0.6250	1.0000	No
5	Rand_Marg_M5	0.00%	3 / 3	1.0000	1.0000	No
10	Rand_Marg_M5	+0.83%	1 / 0	1.0000	1.0000	No
20	Rand_Marg_M5	+5.00%	8 / 2	0.1094	0.4922	No
40	B1_Alpha	+7.50%	10 / 1	0.0117	0.4922	No
40	Rand_Marg_M5	+8.33%	12 / 2	0.0129	0.2344	No
40	B2_Cyclic_M5	+9.17%	11 / 0	0.00098	0.04395	Yes (*)
77	B1_Alpha	+6.94%	20 / 12	0.2153	1.0000	No
77	B2_Cyclic_M5	+7.50%	22 / 13	0.1755	1.0000	No
77	Rand_Marg_M5	+12.78%	27 / 11	0.0145	1.0000	No

6.5 Probability Calibration and ECE Dynamics

As candidate cardinality expands, single-pass models exhibit severe miscalibration: Expected Calibration Error at $K = 77$ reaches 0.3700 [0.30, 0.45] for ‘B0_Native’ and 0.3857 [0.31, 0.47] for ‘B0_Random’. Inference-time marginalization provides substantial calibration benefits: at $K = 77$, ‘Rand_Marg_M5’ reduces ECE to 0.0960 [0.09, 0.20], and ‘B2_Cyclic_M5’ reduces ECE to 0.1619 [0.13, 0.26]. Averaging probability vectors across permutations dampens extreme, overconfident probability spikes.

6.6 Query-Level Instability Heterogeneity and Pareto Frontier

Order instability is not distributed uniformly across queries. As illustrated in Figure 5, 55.0% of queries at $K = 77$ experience an argmax flip rate $\text{FR}_{\text{top1}} \geq 50\%$, while a minority of queries remain stable. Query instability exhibits a strong negative Pearson correlation with model confidence:

$$r = -0.4926 \quad (p = 1.09 \times 10^{-8}). \quad (17)$$

Queries with high predictive margin between the top-1 and top-2 candidates are resilient to serialization perturbations, whereas queries near decision boundaries fluctuate extensively under sequence reordering.




Figure 5: **Query-Level Instability Distribution at $K = 77$.** Distribution of per-query argmax flip rate across 10 random permutations. Over 55.0% of queries experience $FR \geq 50\%$. Instability is strongly negatively correlated with prediction confidence ($r = -0.4926, p = 1.09 \times 10^{-8}$).

Figure 6 and Table 3 illustrate the operational trade-offs across Accuracy ($\uparrow$), p50 Latency ($\downarrow$), and within-method Instability ($\downarrow$, measured by FR_{top1}).




Figure 6: **Three-Objective Pareto Frontier at $K = 77$.** Evaluating Accuracy ($\uparrow$), Latency ($\downarrow$), and within-method Instability ($\downarrow$, FR_{top1}). Non-dominated methods represent Pareto-efficient operating points: ‘B1_Alpha’ minimizes latency with 0% rerun variance (at the cost of 55.8% cross-canonical exposure bias); ‘Rand_Marg_M5’ achieves highest accuracy (55.0%); ‘B2_Cyclic_M5’ minimizes residual flip rate (16.1%) among multi-pass methods.

Table 3: **Detailed Results at Maximum Cardinality ($K = 77$)**. Evaluated across $N = 120$ queries and three base orderings. FR_{top1} measures within-method rerun volatility; Cross-Flip measures counterfactual $A \rightarrow Z$ vs $Z \rightarrow A$ disagreement.

Method	Accuracy [95% CI]	ECE [95% CI]	FR_{top1}	Cross-Flip	Latency	Pareto Status
B0_Native	0.422 [0.34, 0.50]	0.370 [0.30, 0.45]	0.000	–	224.7 ms	Dominated
B0_Random	0.436 [0.36, 0.51]	0.386 [0.31, 0.47]	0.473	–	224.7 ms	Dominated
B1_Alpha	0.492 [0.40, 0.58]	0.334 [0.27, 0.43]	0.000	0.558	224.7 ms	Non-dominated
B1_ReverseAlpha	0.450 [0.37, 0.53]	0.370 [0.30, 0.46]	0.000	0.558	224.7 ms	Dominated
Rand_Marg_M2	0.478 [0.40, 0.55]	0.202 [0.16, 0.31]	0.381	–	449.4 ms	Dominated
Rand_Marg_M3	0.508 [0.43, 0.59]	0.204 [0.16, 0.29]	0.347	–	674.0 ms	Non-dominated
Rand_Marg_M5	0.550 [0.47, 0.62]	0.096 [0.09, 0.20]	0.258	–	1123.4 ms	Non-dominated
B2_Cyclic_M2	0.481 [0.41, 0.56]	0.218 [0.16, 0.31]	0.294	–	449.4 ms	Dominated
B2_Cyclic_M3	0.497 [0.42, 0.57]	0.147 [0.11, 0.24]	0.231	–	674.0 ms	Non-dominated
B2_Cyclic_M5	0.497 [0.42, 0.58]	0.162 [0.13, 0.26]	0.161	–	1123.4 ms	Non-dominated

7 Important Negative Replication Result

In preliminary exploratory benchmarking ($N = 40$, $S = 1$ base sequence), an anomalous accuracy of 65.0% was observed for cyclic shifts ($M = 2$) at $K = 77$, leading to an initial conjecture that cyclic shifts dramatically improve classification accuracy at full cardinality.

Under our pre-specified replication protocol ($N = 120$ unique queries, stratified sampling, $S = 3$ independently seeded base candidate sequences ‘[alphabetical, 7701, 7702]’):

- Replicated ‘B2_Cyclic_M2’ accuracy is 48.06% [**39.7%**, **55.6%**], statistically indistinguishable from random marginalization (47.78%).
- Replicated ‘B2_Cyclic_M5’ accuracy is 49.72% [**41.7%**, **57.2%**].

This negative result is documented as an integral empirical finding. At high candidate cardinality ($K = 77$), small sample sizes ($N = 40$) combined with anchoring to a single arbitrary base candidate sequence produce false-positive accuracy spikes. Controlled multi-seed replication corrected this exploratory artifact.

8 Discussion

Architecture-Induced Order Sensitivity. In contrast to bi-encoders that score candidates independently, multi-candidate concatenation introduces cross-candidate attentional competition. Because token representations are coupled through bidirectional self-attention and positional embeddings, candidate order acts as a hidden nuisance parameter.

Canonicalization vs. Permutation Invariance. Alphabetical canonicalization is widely used to enforce deterministic model outputs in production pipelines. Our counterfactual analysis demonstrates that canonicalization merely fixes a single arbitrary permutation, concealing underlying order sensitivity. If label strings are translated, renamed, or prefixed, decisions flip on 55.83% of queries at $K = 77$.

Inference-Time Marginalization. Permutation marginalization provides an inference-time solution without requiring architectural retraining. At $M = 5$, orthogonal cyclic shifts reduce residual decision flip rate to 16.11% while reducing Expected Calibration Error from 0.3857 to 0.1619. However, marginalization incurs an $M \times$ latency overhead, establishing a clear trade-off between latency and decision stability.

9 Limitations

1. **Single Backbone and Checkpoint:** All evaluations were conducted on the `convai innovations/laya` model checkpoint (RoBERTa-based bidirectional encoder). While the marker concatenation pattern is general, the exact magnitude of instability may vary across backbones and pretraining objectives.
2. **Domain Specialization:** Our study evaluates the Banking77 benchmark. Intent classification provides clean distractor subsets, but semantic dynamics in open-domain tool routing may differ.
3. **Inference-Time Scope:** We investigate post-training inference-time interventions; we do not evaluate training-time data augmentation (e.g., training with randomized permutations) or permutation-invariant pooling layers.
4. **Statistical Power at $K = 77$ ($N = 120$):** Detecting a +5% to +10% accuracy gain under Benjamini-Hochberg FDR control across 45 comparisons requires $N \geq 350$ queries due to binary classification variance.

10 Conclusion

Candidate presentation order induces substantial decision instability in non-autoregressive multi-candidate transformers, scaling from 5.70% at $K = 5$ to 47.28% at $K = 77$. Canonical alphabetical sorting achieves deterministic repeatability but conceals a 55.83% counterfactual cross-order disagreement rate. Inference-time permutation marginalization systematically suppresses residual instability and improves calibration, with orthogonal cyclic shifts achieving 16.11% residual flip rate at $M = 5$. Across 45 pre-specified paired comparisons, cyclic marginalization at $K = 40$ achieves the sole statistically significant accuracy improvement (+9.17 percentage points, adjusted $p = 0.04395$). These findings demonstrate that candidate serialization is an active source of variance in multi-candidate encoders that requires explicit algorithmic marginalization or invariant pooling.

11 Reproducibility and Artifact Availability

To support complete scientific reproducibility, all experimental artifacts, raw evaluations, statistical suites, and figure rendering scripts are permanently archived [Saxena, 2026]:

- **GitHub Repository:** <https://github.com/anshull-saxena/candidate-order-instability>
- **Permanent Zenodo DOI:** [10.5281/zenodo.22906245](https://doi.org/10.5281/zenodo.22906245)
- **Archival Release:** v1.0.0
- **Exact Git Commit:** 266bbb902871dc9974cbf516adea013e3c4eb084

References

Murat Sekin Ayhan and Philipp Berens. Test-time data augmentation for estimation of heteroscedastic aleatoric uncertainty in deep neural networks. In *Proceedings of the 1st Conference on Medical Imaging with Deep Learning (MIDL)*, volume 102 of *Proceedings of Machine Learning Research*, pages 35–46. PMLR, 2018. URL <https://proceedings.mlr.press/v102/ayhan19a.html>.

- Yoav Benjamini and Yosef Hochberg. Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B (Methodological)*, 57(1):289–300, 1995. doi: 10.1111/j.2517-6161.1995.tb02031.x.
- Iñigo Casanueva, Tadas Temčinas, Daniela Gerz, Matthew Henderson, and Ivan Vulić. Efficient intent detection with dual sentence encoders. In *Proceedings of the 2nd Workshop on Natural Language Processing for Conversational AI*, pages 38–45. Association for Computational Linguistics, 2020. doi: 10.18653/v1/2020.nlp4convai-1.5. URL <https://aclanthology.org/2020.nlp4convai-1.5/>.
- Philipp Dufter, Martin Schmitt, and Hinrich Schütze. Position information in transformers: An overview. *Computational Linguistics*, 48(3):733–763, 2022. doi: 10.1162/coli_a.00445. URL <https://aclanthology.org/2022.cl-3.7/>.
- Bradley Efron and Robert J. Tibshirani. *An Introduction to the Bootstrap*. Chapman & Hall/CRC, New York, 1993. doi: 10.1201/9780429246593.
- Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, volume 70 of *Proceedings of Machine Learning Research*, pages 1321–1330. PMLR, 2017. URL <https://proceedings.mlr.press/v70/guo17a.html>.
- Samuel Humeau, Kurt Shuster, Marie-Anne Lachaux, and Jason Weston. Poly-encoders: Transformer architectures and pre-training strategies for fast and accurate multi-sentence scoring. In *Proceedings of the 8th International Conference on Learning Representations (ICLR)*, 2020. URL <https://openreview.net/forum?id=SkxgnnNFvH>.
- Maurice G. Kendall. A new measure of rank correlation. *Biometrika*, 30(1/2):81–93, 1938. doi: 10.1093/biomet/30.1-2.81.
- Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, pages 6402–6413. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/hash/9ef2ed4b7fd2c810847ffa5fa85bce38-A_bstract.html.
- Juho Lee, Yoonho Lee, Jungtaek Kim, Adam Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In *Proceedings of the 36th International Conference on Machine Learning (ICML)*, volume 97 of *Proceedings of Machine Learning Research*, pages 3744–3753. PMLR, 2019. URL <https://proceedings.mlr.press/v97/lee19d.html>.
- Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics (TACL)*, 12:157–173, 2024. doi: 10.1162/tacl_a.00638. URL <https://aclanthology.org/2024.tacl-1.9/>.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. RoBERTa: A robustly optimized BERT pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019. doi: 10.48550/arXiv.1907.11692. URL <https://arxiv.org/abs/1907.11692>.
- Yao Lu, Max Bartolo, Alastair Moore, Sebastian Riedel, and Pontus Stenetorp. Fantastically ordered prompts and where to find them: Overcoming few-shot prompt order sensitivity. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL)*,

- volume 1: Long Papers, pages 8086–8098. Association for Computational Linguistics, 2022. doi: 10.18653/v1/2022.acl-long.556. URL <https://aclanthology.org/2022.acl-long.556/>.
- Nandha Kishor M. Laya: Fast non-autoregressive agentic routing and multi-candidate decision architecture. <https://github.com/NandhaKishorM/laya>, 2024.
- Quinn McNemar. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153–157, 1947. doi: 10.1007/BF02295996.
- Mahdi Pakdaman Naeini, Gregory Cooper, and Milos Hauskrecht. Obtaining well calibrated probabilities using Bayesian binning into quantiles. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 29, pages 2901–2907. AAAI Press, 2015. doi: 10.1609/aaai.v29i1.9602. URL <https://doi.org/10.1609/aaai.v29i1.9602>.
- Jeremy Nixon, Michael W. Dusenberry, Linchuan Zhang, Ghassen Jerfel, and Dustin Tran. Measuring calibration in deep learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, pages 38–41. IEEE, 2019. doi: 10.1109/CVPRW.2019.00010.
- Rodrigo Nogueira and Kyunghyun Cho. Passage re-ranking with BERT. *arXiv preprint arXiv:1901.04085*, 2019. doi: 10.48550/arXiv.1901.04085. URL <https://arxiv.org/abs/1901.04085>.
- Pouya Pezeshkpour and Estevam Hruschka. Large language models sensitivity to the order of options in multiple-choice questions. In *Findings of the Association for Computational Linguistics: NAACL 2024*, pages 2006–2017. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.findings-naacl.130. URL <https://aclanthology.org/2024.findings-naacl.130/>.
- Ofir Press, Noah A. Smith, and Mike Lewis. Train short, test long: Attention with linear biases enables input length extrapolation. In *International Conference on Learning Representations (ICLR)*, 2022. URL <https://openreview.net/forum?id=R8sQPpGCv0>.
- Anshul Saxena. Candidate order instability in non-autoregressive multi-candidate transformers, 2026. URL <https://doi.org/10.5281/zenodo.22906245>. GitHub: <https://github.com/anshull-saxena/candidate-order-instability>.
- Divya Shanmugam, Davis W. Blalock, Guha Balakrishnan, and John V. Gutttag. When and why test-time augmentation works. *arXiv preprint arXiv:2011.11156*, 2020. doi: 10.48550/arXiv.2011.11156. URL <https://arxiv.org/abs/2011.11156>.
- Peter Shaw, Jakob Uszkoreit, and Ashish Vaswani. Self-attention with relative position representations. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*, volume 2 (Short Papers), pages 464–468. Association for Computational Linguistics, 2018. doi: 10.18653/v1/N18-2074. URL <https://aclanthology.org/N18-2074/>.
- Jianlin Su, Murtadha H. M. Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. RoFormer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024. doi: 10.1016/j.neucom.2023.127063.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, pages 5998–6008. Curran Associates, Inc., 2017. URL <https://proceedings.neurips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html>.

- Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed H. Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. In *The Eleventh International Conference on Learning Representations (ICLR)*, 2023. URL <https://openreview.net/forum?id=1PLfdzKxH7>.
- Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabás Póczos, Ruslan Salakhutdinov, and Alexander J. Smola. Deep sets. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, pages 3391–3401, 2017. URL <https://proceedings.neurips.cc/paper/2017/hash/f22e4747da1aa27e363d86d40ff442fe-Abstract.html>.
- Zihao Zhao, Eric Wallace, Shi Feng, Dan Klein, and Sameer Singh. Calibrate before use: Improving few-shot performance of language models. In *Proceedings of the 38th International Conference on Machine Learning (ICML)*, volume 139 of *Proceedings of Machine Learning Research*, pages 12697–12706. PMLR, 2021. URL <https://proceedings.mlr.press/v139/zhao21c.html>.
- Chujie Zheng, Hao Zhou, Fandong Meng, Jie Zhou, and Minlie Huang. Large language models are not robust multiple choice selectors. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024. URL <https://openreview.net/forum?id=shr9PXz7T0>.