

Dropout

Dropout [1] is a technique for regularizing neural networks by randomly setting some features to zero during the forward pass. In this exercise you will implement a dropout layer and modify your fully-connected network to optionally use dropout.

[1] [Geoffrey E. Hinton et al, "Improving neural networks by preventing co-adaptation of feature detectors", arXiv 2012 \(https://arxiv.org/abs/1207.0580\)](https://arxiv.org/abs/1207.0580)

```
In [1]: # As usual, a bit of setup
from __future__ import print_function
import time
import numpy as np
import matplotlib.pyplot as plt
from cs682.classifiers.fc_net import *
from cs682.data_utils import get_CIFAR10_data
from cs682.gradient_check import eval_numerical_gradient, eval_numerical_gradient_array
from cs682.solver import Solver

%matplotlib inline
plt.rcParams['figure.figsize'] = (10.0, 8.0) # set default size of plots
plt.rcParams['image.interpolation'] = 'nearest'
plt.rcParams['image.cmap'] = 'gray'

# for auto-reloading external modules
# see http://stackoverflow.com/questions/1907993/autoreload-of-modules-in-ipython
%load_ext autoreload
%autoreload 2

def rel_error(x, y):
    """ returns relative error """
    return np.max(np.abs(x - y) / (np.maximum(1e-8, np.abs(x) + np.abs(y))))
```

```
In [2]: # Load the (preprocessed) CIFAR10 data.
```

```
data = get_CIFAR10_data()
for k, v in data.items():
    print('%s: ' % k, v.shape)
```

```
X_train: (49000, 3, 32, 32)
y_train: (49000,)
X_val: (1000, 3, 32, 32)
y_val: (1000,)
X_test: (1000, 3, 32, 32)
y_test: (1000,)
```

Dropout forward pass

In the file `cs682/layers.py`, implement the forward pass for dropout. Since dropout behaves differently during training and testing, make sure to implement the operation for both modes.

Once you have done so, run the cell below to test your implementation.

```
In [5]: np.random.seed(231)
x = np.random.randn(500, 500) + 10

for p in [0.25, 0.4, 0.7]:
    out, _ = dropout_forward(x, {'mode': 'train', 'p': p})
    out_test, _ = dropout_forward(x, {'mode': 'test', 'p': p})

    print('Running tests with p = ', p)
    print('Mean of input: ', x.mean())
    print('Mean of train-time output: ', out.mean())
    print('Mean of test-time output: ', out_test.mean())
    print('Fraction of train-time output set to zero: ', (out == 0).mean()
    ())
    print('Fraction of test-time output set to zero: ', (out_test == 0).me
    an())
    print()
```

```
Running tests with p = 0.25
Mean of input: 10.000207878477502
Mean of train-time output: 10.014059116977283
Mean of test-time output: 10.000207878477502
Fraction of train-time output set to zero: 0.749784
Fraction of test-time output set to zero: 0.0
```

```
Running tests with p = 0.4
Mean of input: 10.000207878477502
Mean of train-time output: 9.977917658761159
Mean of test-time output: 10.000207878477502
Fraction of train-time output set to zero: 0.600796
Fraction of test-time output set to zero: 0.0
```

```
Running tests with p = 0.7
Mean of input: 10.000207878477502
Mean of train-time output: 9.987811912159426
Mean of test-time output: 10.000207878477502
Fraction of train-time output set to zero: 0.30074
Fraction of test-time output set to zero: 0.0
```

Dropout backward pass

In the file `cs682/layers.py`, implement the backward pass for dropout. After doing so, run the following cell to numerically gradient-check your implementation.

```
In [7]: np.random.seed(231)
x = np.random.randn(10, 10) + 10
dout = np.random.randn(*x.shape)

dropout_param = {'mode': 'train', 'p': 0.2, 'seed': 123}
out, cache = dropout_forward(x, dropout_param)
dx = dropout_backward(dout, cache)
dx_num = eval_numerical_gradient_array(lambda xx: dropout_forward(xx, dropout_param)[0], x, dout)

# Error should be around e-10 or less
print('dx relative error: ', rel_error(dx, dx_num))

dx relative error: 1.8928938043362133e-11
```

Inline Question 1:

What happens if we do not divide the values being passed through inverse dropout by p in the dropout layer? Why does that happen?

Answer:

On average, the activations after dropout are reduced by a factor of p if we do not divide by p . Therefore, during test, when there is no dropout, the activation would be larger than during train time and the network would not perform well. Hence, to make it consistent, we divide by p during the forward pass at train time. Alternatively, we could also multiply by p during test time.

Fully-connected nets with Dropout

In the file `cs682/classifiers/fc_net.py`, modify your implementation to use dropout. Specifically, if the constructor of the net receives a value that is not 1 for the `dropout` parameter, then the net should add dropout immediately after every ReLU nonlinearity. After doing so, run the following to numerically gradient-check your implementation.

```

In [8]: np.random.seed(231)
N, D, H1, H2, C = 2, 15, 20, 30, 10
X = np.random.randn(N, D)
y = np.random.randint(C, size=(N,))

for dropout in [1, 0.75, 0.5]:
    print('Running check with dropout = ', dropout)
    model = FullyConnectedNet([H1, H2], input_dim=D, num_classes=C,
                              weight_scale=5e-2, dtype=np.float64,
                              dropout=dropout, seed=123)

    loss, grads = model.loss(X, y)
    print('Initial loss: ', loss)

    # Relative errors should be around e-6 or less; Note that it's fine
    # if for dropout=1 you have W2 error be on the order of e-5.
    for name in sorted(grads):
        f = lambda _: model.loss(X, y)[0]
        grad_num = eval_numerical_gradient(f, model.params[name], verbose=False, h=1e-5)
        print('%s relative error: %.2e' % (name, rel_error(grad_num, grads[name])))
    print()

```

```

Running check with dropout = 1
Initial loss: 2.3004790897684924
W1 relative error: 1.48e-07
W2 relative error: 2.21e-05
W3 relative error: 3.53e-07
b1 relative error: 5.38e-09
b2 relative error: 2.09e-09
b3 relative error: 5.80e-11

```

```

Running check with dropout = 0.75
Initial loss: 2.302371489704412
W1 relative error: 1.90e-07
W2 relative error: 4.76e-06
W3 relative error: 2.60e-08
b1 relative error: 4.73e-09
b2 relative error: 1.82e-09
b3 relative error: 1.70e-10

```

```

Running check with dropout = 0.5
Initial loss: 2.3042759220785896
W1 relative error: 3.11e-07
W2 relative error: 1.84e-08
W3 relative error: 5.35e-08
b1 relative error: 2.58e-08
b2 relative error: 2.99e-09
b3 relative error: 1.13e-10

```

Regularization experiment

As an experiment, we will train a pair of two-layer networks on 500 training examples: one will use no dropout, and one will use a keep probability of 0.25. We will then visualize the training and validation accuracies of the two networks over time.

```
In [9]: # Train two identical nets, one with dropout and one without
np.random.seed(231)
num_train = 500
small_data = {
    'X_train': data['X_train'][:num_train],
    'y_train': data['y_train'][:num_train],
    'X_val': data['X_val'],
    'y_val': data['y_val'],
}

solvers = {}
dropout_choices = [1, 0.25]
for dropout in dropout_choices:
    model = FullyConnectedNet([500], dropout=dropout)
    print(dropout)

    solver = Solver(model, small_data,
                    num_epochs=25, batch_size=100,
                    update_rule='adam',
                    optim_config={
                        'learning_rate': 5e-4,
                    },
                    verbose=True, print_every=100)
    solver.train()
    solvers[dropout] = solver
```

1


```
(Iteration 1 / 125) loss: 7.856643
(Epoch 0 / 25) train acc: 0.260000; val_acc: 0.184000
(Epoch 1 / 25) train acc: 0.416000; val_acc: 0.258000
(Epoch 2 / 25) train acc: 0.482000; val_acc: 0.276000
(Epoch 3 / 25) train acc: 0.532000; val_acc: 0.277000
(Epoch 4 / 25) train acc: 0.600000; val_acc: 0.271000
(Epoch 5 / 25) train acc: 0.708000; val_acc: 0.299000
(Epoch 6 / 25) train acc: 0.722000; val_acc: 0.282000
(Epoch 7 / 25) train acc: 0.832000; val_acc: 0.255000
(Epoch 8 / 25) train acc: 0.878000; val_acc: 0.269000
(Epoch 9 / 25) train acc: 0.902000; val_acc: 0.275000
(Epoch 10 / 25) train acc: 0.888000; val_acc: 0.261000
(Epoch 11 / 25) train acc: 0.926000; val_acc: 0.278000
(Epoch 12 / 25) train acc: 0.960000; val_acc: 0.302000
(Epoch 13 / 25) train acc: 0.964000; val_acc: 0.306000
(Epoch 14 / 25) train acc: 0.966000; val_acc: 0.310000
(Epoch 15 / 25) train acc: 0.978000; val_acc: 0.290000
(Epoch 16 / 25) train acc: 0.980000; val_acc: 0.307000
(Epoch 17 / 25) train acc: 0.982000; val_acc: 0.309000
(Epoch 18 / 25) train acc: 0.994000; val_acc: 0.319000
(Epoch 19 / 25) train acc: 0.990000; val_acc: 0.313000
(Epoch 20 / 25) train acc: 0.990000; val_acc: 0.311000
(Iteration 101 / 125) loss: 0.000313
(Epoch 21 / 25) train acc: 0.992000; val_acc: 0.308000
(Epoch 22 / 25) train acc: 0.986000; val_acc: 0.304000
(Epoch 23 / 25) train acc: 0.990000; val_acc: 0.313000
(Epoch 24 / 25) train acc: 0.998000; val_acc: 0.310000
(Epoch 25 / 25) train acc: 0.996000; val_acc: 0.319000
```

0.25

```
(Iteration 1 / 125) loss: 17.318480
(Epoch 0 / 25) train acc: 0.230000; val_acc: 0.177000
(Epoch 1 / 25) train acc: 0.378000; val_acc: 0.243000
(Epoch 2 / 25) train acc: 0.402000; val_acc: 0.254000
(Epoch 3 / 25) train acc: 0.502000; val_acc: 0.276000
(Epoch 4 / 25) train acc: 0.528000; val_acc: 0.298000
(Epoch 5 / 25) train acc: 0.562000; val_acc: 0.296000
(Epoch 6 / 25) train acc: 0.626000; val_acc: 0.291000
(Epoch 7 / 25) train acc: 0.622000; val_acc: 0.297000
(Epoch 8 / 25) train acc: 0.686000; val_acc: 0.313000
(Epoch 9 / 25) train acc: 0.712000; val_acc: 0.297000
(Epoch 10 / 25) train acc: 0.724000; val_acc: 0.305000
(Epoch 11 / 25) train acc: 0.768000; val_acc: 0.309000
(Epoch 12 / 25) train acc: 0.768000; val_acc: 0.289000
(Epoch 13 / 25) train acc: 0.830000; val_acc: 0.302000
(Epoch 14 / 25) train acc: 0.802000; val_acc: 0.359000
(Epoch 15 / 25) train acc: 0.852000; val_acc: 0.342000
(Epoch 16 / 25) train acc: 0.838000; val_acc: 0.305000
(Epoch 17 / 25) train acc: 0.856000; val_acc: 0.294000
(Epoch 18 / 25) train acc: 0.854000; val_acc: 0.310000
(Epoch 19 / 25) train acc: 0.874000; val_acc: 0.320000
(Epoch 20 / 25) train acc: 0.872000; val_acc: 0.300000
(Iteration 101 / 125) loss: 4.683146
(Epoch 21 / 25) train acc: 0.910000; val_acc: 0.329000
(Epoch 22 / 25) train acc: 0.900000; val_acc: 0.302000
(Epoch 23 / 25) train acc: 0.894000; val_acc: 0.306000
```

```
(Epoch 24 / 25) train acc: 0.924000; val_acc: 0.328000  
(Epoch 25 / 25) train acc: 0.918000; val_acc: 0.304000
```

```
In [10]: # Plot train and validation accuracies of the two models  
  
train_accs = []  
val_accs = []  
for dropout in dropout_choices:  
    solver = solvers[dropout]  
    train_accs.append(solver.train_acc_history[-1])  
    val_accs.append(solver.val_acc_history[-1])  
  
plt.subplot(3, 1, 1)  
for dropout in dropout_choices:  
    plt.plot(solvers[dropout].train_acc_history, 'o', label='%.2f dropout' %  
 dropout)  
plt.title('Train accuracy')  
plt.xlabel('Epoch')  
plt.ylabel('Accuracy')  
plt.legend(ncol=2, loc='lower right')  
  
plt.subplot(3, 1, 2)  
for dropout in dropout_choices:  
    plt.plot(solvers[dropout].val_acc_history, 'o', label='%.2f dropout' %  
 dropout)  
plt.title('Val accuracy')  
plt.xlabel('Epoch')  
plt.ylabel('Accuracy')  
plt.legend(ncol=2, loc='lower right')  
  
plt.gcf().set_size_inches(15, 15)  
plt.show()
```



Inline Question 2:

Compare the validation and training accuracies with and without dropout -- what do your results suggest about dropout as a regularizer?

Answer:

With dropout, the difference between training and validation accuracies falls, hence dropout acts as a regularizer. Without dropout, the model overfits on the training data and there is a larger gap between training and validation accuracies.

Inline Question 3:

Suppose we are training a deep fully-connected network for image classification, with dropout after hidden layers (parameterized by keep probability p). How should we modify p , if at all, if we decide to decrease the size of the hidden layers (that is, the number of nodes in each layer)?

Answer:

p should be increased. Reducing the number of hidden layers would decrease the capacity of the model and thus, the regularization should be reduced by increasing p by dropping lesser values.

In []: