

Mechanized Verification of Graph-manipulating Programs

Shengyi Wang[†], Qingxiang Cao[‡], Anshuman Mohan[†], Aquinas Hobor[†]



INRIA

November 14, 2019

Our Focus

We would like to verify **graph-manipulating** programs written in **real C** with end-to-end **machine-checked** correctness proofs.

- Graph algorithms are hard to reason about but occur in critical areas of real systems
- Real C code has achingly subtle semantics in some places
- Machine-checked proofs are merciless and lengthy: we want to reuse existing codebases

Our Strategy

We will use the **CompCert** certified compiler's definition of C and the **Verified Software Toolchain's** (VST) version of **Separation Logic** to certify our code against strong specifications expressed with **mathematical graphs**.


- Between them, CompCert and VST have 50+ person-years worth of development effort. **It is highly desirable to fit within their frameworks rather than reinventing the wheel.**
- We make no changes to CompCert. We make minimal (**approximately 1% of codebase**) additions to VST (two new tacticals, assorted lemmas).
- Our techniques use vanilla separation logic (albeit with \rightarrow^* and quantifiers).
- We have developed an expressive machine-checked framework for mathematical graphs that is **powerful enough to verify real code.**

Our Results


We have verified half a dozen graph algorithms, including:

- Graph visiting/coloring; ditto for DAG
- Graph reclamation (*i.e.* spanning tree followed by tree reclamation)
- Union-find (both for heap- and array-represented nodes)
- Garbage collector for CertiCoq project
 - Generational OCaml-style GC for a purely functional language
 - ≈ 400 lines of (rather devilish) C
 - We pinpoint two places where C is too weak to define an OCaml-style GC
 - Verify (almost) full graph isomorphism
 - $\approx 14,000$ lines of example-specific proof script


Union-Find Algorithm




Union-Find Algorithm



Union-Find Algorithm



Union-Find Algorithm




Union-Find Algorithm: Disjoint-Set Data Structure

```
struct Node {  
    unsigned int rank;  
    struct Node *parent;  
};
```


Union-Find Algorithm: Disjoint-Set Data Structure

```
struct Node {  
    unsigned int rank;  
    struct Node *parent;  
};
```



Union-Find Algorithm: Find

```
struct Node {  
    unsigned int rank;  
    struct Node *parent;  
};  
  
struct Node* find(struct Node* x) {  
    struct Node *p, *p0;  
    p = x -> parent;  
    if (p != x) {  
        p0 = find(p);  
        p = p0;  
        x -> parent = p;  
    }  
    return p;  
};
```




Union-Find Algorithm: Find

```

struct Node {
    unsigned int rank;
    struct Node *parent;
};

struct Node* find(struct Node* x) {
    struct Node *p, *p0;
    p = x -> parent;
    if (p != x) {
        p0 = find(p);
        p = p0;
        x -> parent = p;
    }
    return p;
};

```




Union-Find Algorithm: Find

```

struct Node {
    unsigned int rank;
    struct Node *parent;
};

struct Node* find(struct Node* x) {
    struct Node *p, *p0;
    p = x -> parent;
    if (p != x) {
        p0 = find(p);
        p = p0;
        x -> parent = p;
    }
    return p;
};

```




Union-Find Algorithm: Find

```

struct Node {
    unsigned int rank;
    struct Node *parent;
};

struct Node* find(struct Node* x) {
    struct Node *p, *p0;
    p = x -> parent;
    if (p != x) {
        p0 = find(p);
        p = p0;
        x -> parent = p;
    }
    return p;
};


```



Union-Find Algorithm: Find

```
struct Node {
    unsigned int rank;
    struct Node *parent;
};


struct Node* find(struct Node* x) {
    struct Node *p, *p0;
    p = x -> parent;
    if (p != x) {
        p0 = find(p);
        p = p0;
        x -> parent = p;
    }
    return p;
};
```



Union-Find Algorithm: Find

```
struct Node {
    unsigned int rank;
    struct Node *parent;
};

struct Node* find(struct Node* x) {
    struct Node *p, *p0;
    p = x -> parent;
    if (p != x) {
        p0 = find(p);
        p = p0;
        x -> parent = p;
    }
    return p;
};
```




Union-Find Algorithm: Find

```

struct Node {
    unsigned int rank;
    struct Node *parent;
};

struct Node* find(struct Node* x) {
    struct Node *p, *p0;
    p = x -> parent;
    if (p != x) {
        p0 = find(p);
        p = p0;
        x -> parent = p;
    }
    return p;
};

```




Union-Find Algorithm: Find

```

struct Node {
    unsigned int rank;
    struct Node *parent;
};

struct Node* find(struct Node* x) {
    struct Node *p, *p0;
    p = x -> parent;
    if (p != x) {
        p0 = find(p);
        p = p0;
        x -> parent = p;
    }
    return p;
};

```




Union-Find Algorithm: Find

```

struct Node {
    unsigned int rank;
    struct Node *parent;
};

struct Node* find(struct Node* x) {
    struct Node *p, *p0;
    p = x -> parent;
    if (p != x) {
        p0 = find(p);
        p = p0;
        x -> parent = p;
    }
    return p;
};


```



Union-Find Algorithm: Find


```
struct Node {
    unsigned int rank;
    struct Node *parent;
};

struct Node* find(struct Node* x) {
    struct Node *p, *p0;
    p = x -> parent;
    if (p != x) {
        p0 = find(p);
        p = p0;
        x -> parent = p;
    }
    return p;
};
```




Union-Find Algorithm: Find

```
struct Node {  
    unsigned int rank;  
    struct Node *parent;  
};  
  
struct Node* find(struct Node* x) {  
    struct Node *p, *p0;  
    p = x -> parent;  
    if (p != x) {  
        p0 = find(p);  
        p = p0;  
        x -> parent = p;  
    }  
    return p;  
};
```




Union-Find Algorithm: Find

```
struct Node {  
    unsigned int rank;  
    struct Node *parent;  
};  
  
struct Node* find(struct Node* x) {  
    struct Node *p, *p0;  
    p = x -> parent;  
    if (p != x) {  
        p0 = find(p);  
        p = p0;  
        x -> parent = p;  
    }  
    return p;  
};
```




Union-Find Algorithm: Find

```
struct Node {  
    unsigned int rank;  
    struct Node *parent;  
};  
  
struct Node* find(struct Node* x) {  
    struct Node *p, *p0;  
    p = x -> parent;  
    if (p != x) {  
        p0 = find(p);  
        p = p0;  
        x -> parent = p;  
    }  
    return p;  
};
```




Union-Find Algorithm: Find

```
struct Node {  
    unsigned int rank;  
    struct Node *parent;  
};  
  
struct Node* find(struct Node* x) {  
    struct Node *p, *p0;  
    p = x -> parent;  
    if (p != x) {  
        p0 = find(p);  
        p = p0;  
        x -> parent = p;  
    }  
    return p;  
};
```




Union-Find Algorithm: Find


```
struct Node {  
    unsigned int rank;  
    struct Node *parent;  
};  
  
struct Node* find(struct Node* x) {  
    struct Node *p, *p0;  
    p = x -> parent;  
    if (p != x) {  
        p0 = find(p);  
        p = p0;  
        x -> parent = p;  
    }  
    return p;  
};
```




Verifying Graph-Manipulating Algorithm is Hard




Verifying Graph-Manipulating Algorithm is Hard




Verifying Graph-Manipulating Algorithm is Hard




Verifying Graph-Manipulating Algorithm is Hard




Verifying Graph-Manipulating Algorithm is Hard



Verifying Graph-Manipulating Algorithm is Hard



Verifying Graph-Manipulating Algorithm is Hard




- Motivation ✓
- The Mathematical Graph Library
 - Core Definitions
 - Architecture
 - Selection of Properties
- The Spatial Representation of Graphs
 - CompCert and VST
 - Hoare Logic and Separation Logic
 - Spatial Representation of Graphs
 - Localize Rule
- Verification of the Find function
 - Specification
 - Proof Skeleton
 - Modularity
- A Generational Garbage Collector

Statistics


Component	Files	LOC
Common Utilities	10	2,842
Math Graph Library	19	12,723
Memory Model & Logic	13	2,373
Spatial Graph Library	10	6,458
Integration into VST	12	1,917
Examples (excluding GC)	13	3,290
GC, subdivided into	18	14,170
• mathematical graph	1	5,764
• spatial graph	1	1,618
• function specifications	1	461
• function Hoare proofs	14	3,062
• isomorphism proof	1	3,265
Total Development	95	43,773

Graph Library: A General Definition of Graph



A general definition of graph should have


Graph Library: A General Definition of Graph



A general definition of graph should have

- Vertices
- Pairs of vertices as Edges


Graph Library: A General Definition of Graph



A general definition of graph should have

- Vertices
- Pairs of vertices as Edges


Graph Library: A General Definition of Graph



A general definition of graph should have

- Vertices
- Edges, sources and destinations


Graph Library: A General Definition of Graph



A general definition of graph should have

- Vertices
- Edges, sources and destinations


Graph Library: A General Definition of Graph




A general definition of graph should have

- Vertices
- Edges, sources and destinations
- Validity of vertices and edges


Graph Library: A General Definition of Graph


$$\text{PreGraph} \stackrel{\text{def}}{=} \{ V, E, \text{vvalid}, \text{evalid}, \\ \text{src}, \text{dst} \}$$

Graph Library: A General Definition of Graph


$$\text{PreGraph} \stackrel{\text{def}}{=} \{V, E, \text{vvalid}, \text{evalid}, \\ \text{src}, \text{dst}\}$$


Graph Library: A General Definition of Graph



$$\text{PreGraph} \stackrel{\text{def}}{=} \{ V, E, \text{vvalid}, \text{evalid}, \\ \text{src}, \text{dst} \}$$

$$\text{LabeledGraph} \stackrel{\text{def}}{=} \{ \text{PreGraph}, L_V, L_E, L_G, \\ \text{vlabel}, \text{elabel}, \text{glabel} \}$$

Graph Library: A General Definition of Graph




$$\text{PreGraph} \stackrel{\text{def}}{=} \{V, E, \text{vvalid}, \text{evalid}, \\ \text{src}, \text{dst}\}$$

$$\text{LabeledGraph} \stackrel{\text{def}}{=} \{\text{PreGraph}, L_V, L_E, L_G, \\ \text{vlabel}, \text{elabel}, \text{glabel}\}$$

$$\text{GeneralGraph} \stackrel{\text{def}}{=} \{\text{LabeledGraph}, \text{sound_gg}\}$$

Graph Library: A General Definition of Graph




$$\text{PreGraph} \stackrel{\text{def}}{=} \{V, E, \text{vvalid}, \text{evalid}, \text{src}, \text{dst}\}$$

$$\text{LabeledGraph} \stackrel{\text{def}}{=} \{\text{PreGraph}, L_V, L_E, L_G, \text{vlabel}, \text{elabel}, \text{glabel}\}$$

$$\text{GeneralGraph} \stackrel{\text{def}}{=} \{\text{LabeledGraph}, \text{sound_gg}\}$$


For Example: Acyclic

Graph Library: Definition of Path




- Path is used in defining reachability.

Graph Library: Definition of Path



- Path is used in defining reachability.
- A path is a sequence of edges which connect a sequence of vertices.


Graph Library: Definition of Path



- Path is used in defining reachability.
- A path is a sequence of edges which connect a sequence of vertices.

$$\text{Path} \stackrel{\text{def}}{=} [v_0, e_0, v_1, e_1, \dots, v_{k-1}, e_{k-1}, v_k]$$

Graph Library: Definition of Path




- Path is used in defining reachability.
- A path is a sequence of edges which connect a sequence of vertices.

$$\text{Path} \stackrel{\text{def}}{=} [v_0, e_0, v_1, e_1, \dots, v_{k-1}, e_{k-1}, v_k]$$

$$\text{Path} \stackrel{\text{def}}{=} [e_0, e_1, \dots, e_k]$$

Graph Library: Definition of Path



- Path is used in defining reachability.
- A path is a sequence of edges which connect a sequence of vertices.

$$\text{Path} \stackrel{\text{def}}{=} [v_0, e_0, v_1, e_1, \dots, v_{k-1}, e_{k-1}, v_k]$$

$$\text{Path} \stackrel{\text{def}}{=} [e_0, e_1, \dots, e_k]$$

$$\text{Path} \stackrel{\text{def}}{=} (v_0, [e_0, e_1, \dots, e_k])$$

Other Derived Definitions: A Peek

$$\text{s_evalid}(\gamma, e) \stackrel{\text{def}}{=} \text{evalid}(\gamma, e) \wedge \\ \text{vvalid}(\gamma, \text{src}(\gamma, e)) \wedge \text{vvalid}(\gamma, \text{dst}(\gamma, e))$$

Other Derived Definitions: A Peek

$$\text{s_evalid}(\gamma, e) \stackrel{\text{def}}{=} \text{evalid}(\gamma, e) \wedge \\ \text{vvalid}(\gamma, \text{src}(\gamma, e)) \wedge \text{vvalid}(\gamma, \text{dst}(\gamma, e))$$

$$\text{valid_path}(\gamma, (v, [])) \stackrel{\text{def}}{=} \text{vvalid}(\gamma, v)$$

$$\text{valid_path}(\gamma, (v, [e_1, e_2, \dots, e_n])) \stackrel{\text{def}}{=} v = \text{src}(\gamma, e_1) \wedge \text{s_evalid}(\gamma, e_1) \wedge \\ \text{dst}(\gamma, e_1) = \text{src}(\gamma, e_2) \wedge \\ \text{s_evalid}(\gamma, e_2) \wedge \dots$$

Other Derived Definitions: A Peek

$$\text{s_evalid}(\gamma, e) \stackrel{\text{def}}{=} \text{evalid}(\gamma, e) \wedge \\ \text{vvalid}(\gamma, \text{src}(\gamma, e)) \wedge \text{vvalid}(\gamma, \text{dst}(\gamma, e))$$

$$\text{valid_path}(\gamma, (v, [])) \stackrel{\text{def}}{=} \text{vvalid}(\gamma, v)$$

$$\text{valid_path}(\gamma, (v, [e_1, e_2, \dots, e_n])) \stackrel{\text{def}}{=} v = \text{src}(\gamma, e_1) \wedge \text{s_evalid}(\gamma, e_1) \wedge \\ \text{dst}(\gamma, e_1) = \text{src}(\gamma, e_2) \wedge \\ \text{s_evalid}(\gamma, e_2) \wedge \dots$$


$$\text{end}(\gamma, (v, [])) \stackrel{\text{def}}{=} v$$

$$\text{end}(\gamma, (v, [e_1, e_2, \dots, e_n])) \stackrel{\text{def}}{=} \text{dst}(\gamma, e_n)$$


$$\gamma \models s \overset{p}{\rightsquigarrow} t \stackrel{\text{def}}{=} \text{valid_path}(\gamma, p) \wedge \text{fst}(p) = s \wedge \text{end}(\gamma, p) = t$$

$$\gamma \models s \rightsquigarrow t \stackrel{\text{def}}{=} \exists p \text{ s.t. } \gamma \models s \overset{p}{\rightsquigarrow} t$$


Architecture



Various Properties: MathGraph, LstGraph and FiniteGraph



Various Properties: MathGraph, LstGraph and FiniteGraph



$$\text{MathGraph}(\gamma) \stackrel{\text{def}}{=} \left\{ \right.$$


$$\text{null} : V$$

$$\text{weak_valid}(v) \stackrel{\text{def}}{=} v = \text{null} \vee \text{vvalid}(\gamma, v)$$

$$\begin{aligned} \text{valid_graph} : \forall e. \text{evalid}(\gamma, e) \Rightarrow \\ \text{vvalid}(\gamma, \text{src}(\gamma, e)) \wedge \\ \text{weak_valid}(\text{dst}(\gamma, e)) \end{aligned}$$


$$\begin{aligned} \text{valid_not_null} : \forall v. \text{vvalid}(\gamma, v) \Rightarrow \\ v \neq \text{null} \end{aligned} \left. \right\}$$

Various Properties: MathGraph, LstGraph and FiniteGraph




$$\begin{aligned} \text{LstGraph}(\gamma) \stackrel{\text{def}}{=} \{ & \\ & \text{out} : V \rightarrow E \\ \text{only_one_edge} : & \forall v, e. \text{vvalid}(\gamma, v) \Rightarrow \\ & \left(\text{src}(\gamma, e) = v \wedge \right. \\ & \left. \text{evalid}(\gamma, e) \right) \Leftrightarrow \\ & e = \text{out}(v) \\ \text{acyclic_path} : & \forall v, p. \gamma \models v \stackrel{p}{\rightsquigarrow} v \Rightarrow \\ & p = (v, []) \} \end{aligned}$$

Various Properties: MathGraph, LstGraph and FiniteGraph




$$\text{FiniteGraph}(\gamma) \stackrel{\text{def}}{=} \left\{ \begin{array}{l} \text{finite_v} : \exists S_v, M_v \text{ s.t. } |S_v| \leq M_v \wedge \\ \quad \forall v. \text{vvalid}(\gamma, v) \Rightarrow v \in S_v \\ \text{finite_e} : \exists S_e, M_e \text{ s.t. } |S_e| \leq M_e \wedge \\ \quad \forall e. \text{evalid}(\gamma, e) \Rightarrow e \in S_e \end{array} \right\}$$


Various Properties




Various Properties




Various Properties



Various Properties




Various Properties



- Motivation ✓
- The Mathematical Graph Library ✓
 - Core Definitions ✓
 - Architecture ✓
 - Selection of Properties ✓
- The Spatial Representation of Graphs
 - CompCert and VST
 - Hoare Logic and Separation Logic
 - Spatial Representation of Graphs
 - Localize Rule
- Verification of the Find function
 - Specification
 - Proof Skeleton
 - Modularity
- A Generational Garbage Collector


CompCert and VST



- CompCert

(Leroy et al. , Appel et al.)


CompCert and VST



- CompCert
 - $C \rightarrow \text{Coq (Clight)} \rightarrow \text{Machine}$

(Leroy et al. , Appel et al.)


CompCert and VST



- CompCert
 - $C \rightarrow \text{Coq (Clight)} \rightarrow \text{Machine}$
 - Full-Scale C Specification

(Leroy et al. , Appel et al.)


CompCert and VST



- CompCert
 - $C \rightarrow \text{Coq (Clight)} \rightarrow \text{Machine}$
 - Full-Scale C Specification
- Verified Software Toolchain

(Leroy et al. , Appel et al.)


CompCert and VST



- CompCert
 - $C \rightarrow \text{Coq (Clight)} \rightarrow \text{Machine}$
 - Full-Scale C Specification
- Verified Software Toolchain
 - Separation Hoare Logic

(Leroy et al. , Appel et al.)


CompCert and VST



- CompCert
 - $C \rightarrow \text{Coq (Clight)} \rightarrow \text{Machine}$
 - Full-Scale C Specification
- Verified Software Toolchain
 - Separation Hoare Logic
 - Verifiable C

(Leroy et al. , Appel et al.)

CompCert and VST



- CompCert
 - $C \rightarrow \text{Coq (Clight)} \rightarrow \text{Machine}$
 - Full-Scale C Specification
- Verified Software Toolchain
 - Separation Hoare Logic
 - Verifiable C
 - Interactive Symbolic Execution

(Leroy et al. , Appel et al.)

Recap: Hoare Logic

$$\{P\} C \{Q\}$$


(C. A. R. Hoare)

Recap: Separation Logic

$$P \star Q$$

(Reynolds et al.)

Recap: Separation Logic



$$h \models P \star Q \stackrel{\text{def}}{=} \exists h_1, h_2 \text{ s.t. } h_1 \oplus h_2 = h \wedge h_1 \models P \wedge h_2 \models Q$$


(Reynolds et al.)

Recap: Separation Logic

$$P \multimap Q$$

(Reynolds et al.)

Recap: Separation Logic



$$h \models P \star Q \stackrel{\text{def}}{=} \forall h_1, h_2. h_1 \oplus h = h_2 \Rightarrow h_1 \models P \Rightarrow h_2 \models Q$$

(Reynolds et al.)

Recap: Separation Logic

$$\forall P, Q. P \star (P \multimap Q) \vdash Q$$

(Reynolds et al.)

Recap: Separation Logic

emp

(Reynolds et al.)

Recap: Separation Logic

$$a \mapsto v$$

(Reynolds et al.)


Recap: Separation Logic

$$\frac{\{P\} C \{Q\}}{\{P \star F\} C \{Q \star F\}} (\text{mod}(C) \cap \text{fv}(F) = \emptyset)$$

(Reynolds et al.)



Spatial Representation of Graphs

```
struct Node {  
    unsigned int rank;  
    struct Node *parent;  
};
```





Spatial Representation of Graphs

```
struct Node {  
    unsigned int rank;  
    struct Node *parent;  
};
```



Spatial Representation of Graphs



```
struct Node {
  unsigned int rank;
  struct Node *parent;
};
```



$$\text{graph_rep}(\gamma) \stackrel{\text{def}}{=} \star_{\text{vvalid}(\gamma, v)} \text{v_rep}(\gamma, v)$$

Spatial Representation of Graphs

```
struct Node {
    unsigned int rank;
    struct Node *parent;
};
```





$$\text{graph_rep}(\gamma) \stackrel{\text{def}}{=} \star_{v \text{ valid}(\gamma, v)} v_rep(\gamma, v)$$

$$\star_{\{v_1, v_2, \dots, v_n\}} P \stackrel{\text{def}}{=} P(v_1) * P(v_2) * \dots * P(v_n)$$

Spatial Representation of Graphs

```
struct Node {
    unsigned int rank;
    struct Node *parent;
};
```





$$\text{graph_rep}(\gamma) \stackrel{\text{def}}{=} \star_{v \text{ valid}(\gamma, v)} \text{v_rep}(\gamma, v)$$

$$\star_{\{v_1, v_2, \dots, v_n\}} P \stackrel{\text{def}}{=} P(v_1) \star P(v_2) \star \dots \star P(v_n)$$

$$\begin{aligned} \text{v_rep}(\gamma, v) &\stackrel{\text{def}}{=} v \mapsto \text{vlabel}(\gamma, v) \star \\ &\quad (v + 4) \mapsto \text{prt}(\gamma, v) \end{aligned}$$

Spatial Representation of Graphs

```
struct Node {
    unsigned int rank;
    struct Node *parent;
};
```




$$\text{graph_rep}(\gamma) \stackrel{\text{def}}{=} \star_{v \text{ valid}(\gamma, v)} v_rep(\gamma, v)$$

$$\star_{\{v_1, v_2, \dots, v_n\}} P \stackrel{\text{def}}{=} P(v_1) * P(v_2) * \dots * P(v_n)$$

$$v_rep(\gamma, v) \stackrel{\text{def}}{=} v \mapsto vlabel(\gamma, v) * \\ (v + 4) \mapsto prt(\gamma, v)$$


$$prt(\gamma, v) \stackrel{\text{def}}{=} \begin{cases} dst(\gamma, out(v)) & \neq \text{null} \\ v & \text{otherwise} \end{cases}$$

Ramify Rule



(Hobor and Villard)


Ramify Rule



$$\frac{\{L_1\} C \{L_2\}}{\{G_1\} C \{G_2\}}$$

(Hobor and Villard)


Ramify Rule



$$\frac{\{L_1\} C \{L_2\}}{\{G_1\} C \{G_2\}}$$

(Hobor and Villard)

Ramify Rule




$$\frac{\{L_1\} C \{L_2\}}{\{G_1\} C \{G_2\}}$$

Hint: $\forall P, Q. P \star (P \rightarrow \star Q) \vdash Q$

(Hobor and Villard)

Ramify Rule




$$\frac{\{L_1\} C \{L_2\}}{\{G_1\} C \{G_2\}}$$

Hint: $\forall P, Q. P * (P \rightarrow Q) \vdash Q$

(Hobor and Villard)

Ramify Rule



$$\frac{\{L_1\} C \{L_2\} \quad G_1 \vdash L_1 \star (L_2 \rightarrow G_2)}{\{G_1\} C \{G_2\}} \quad (\text{mod}(C) \cap \text{fv}(L_2 \rightarrow G_2) = \emptyset)$$

(Hobor and Villard)

Localize Rule

$$\frac{\{L_1\} C\{ \quad L_2\} \quad G_1 \vdash L_1 \star R \quad R \vdash \quad L_2 \rightarrow \star G_2}{\{G_1\} C\{ \quad G_2\}}$$

Localize Rule

$$\frac{\{L_1\} C\{\exists x. L_2\} \quad G_1 \vdash L_1 \star R \quad R \vdash \forall x. (L_2 \rightarrowstar G_2)}{\{G_1\} C\{\exists x. G_2\}}$$

Localize Rule

$$\frac{\{L_1\} C\{\exists x. L_2\} \quad G_1 \vdash L_1 \star R \quad R \vdash \forall x. (L_2 \rightarrowstar G_2)}{\{G_1\} C\{\exists x. G_2\}} \quad (\dagger)$$

$$(\dagger) \quad \text{mod}(C) \cap \text{fv}(R) = \emptyset$$

Localize Rule

$$\frac{\{L_1\} C\{\exists x. L_2\} \quad G_1 \vdash L_1 \star R \quad R \vdash \forall x. (L_2 \multimap G_2)}{\{G_1\} C\{\exists x. G_2\}} \quad (\dagger)$$

$$(\dagger) \quad \text{mod}(C) \cap \text{fv}(R) = \emptyset$$

Comparing to Ramify rule:

$$\frac{\{L_1\} C\{L_2\} \quad G_1 \vdash L_1 \star (L_2 \multimap G_2)}{\{G_1\} C\{G_2\}} \quad (\ddagger)$$

$$(\ddagger) \quad \text{mod}(C) \cap \text{fv}(L_2 \multimap G_2) = \emptyset$$

- Motivation ✓
- The Mathematical Graph Library ✓
 - Core Definitions ✓
 - Architecture ✓
 - Selection of Properties ✓
- The Spatial Representation of Graphs ✓
 - CompCert and VST ✓
 - Hoare Logic and Separation Logic ✓
 - Spatial Representation of Graphs ✓
 - Localize Rule ✓
- Verification of the Find function
 - Specification
 - Proof Skeleton
 - Modularity
- A Generational Garbage Collector


Union-Find Algorithm: Find

```

struct Node {
    unsigned int rank;
    struct Node *parent;
};

struct Node* find(struct Node* x) {
    struct Node *p, *p0;
    p = x -> parent;
    if (p != x) {
        p0 = find(p);
        p = p0;
        x -> parent = p;
    }
    return p;
};

```



The Specification of Find

PRE: $\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)$

POST: $\exists \gamma', t \text{ s.t. } \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge$
 $\text{root}(\gamma', x, t)$

The Specification of Find

PRE: $\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)$

POST: $\exists \gamma', t \text{ s.t. } \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, t)$

$$\text{graph_rep}(\gamma) \stackrel{\text{def}}{=} \bigstar_{\text{vvalid}(\gamma, v)} \text{v_rep}(\gamma, v)$$

$$\text{root}(\gamma, x, t) \stackrel{\text{def}}{=} \gamma \models x \rightsquigarrow t \wedge \forall y. \gamma \models t \rightsquigarrow y \Rightarrow y = t$$

$$\begin{aligned} \text{uf_eq}(\gamma_1, \gamma_2) \stackrel{\text{def}}{=} & (\forall x. \text{vvalid}(\gamma_1, x) \Leftrightarrow \text{vvalid}(\gamma_2, x)) \wedge \\ & \forall x, r_1, r_2. \text{root}(\gamma_1, x, r_1) \Rightarrow \\ & \text{root}(\gamma_2, x, r_2) \Rightarrow r_1 = r_2 \end{aligned}$$

Proof Skeleton of Find

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)\}$$
$$p = x \rightarrow \text{parent};$$
$$p0 = \text{find}(p);$$
$$x \rightarrow \text{parent} = p0$$
$$\{\exists \gamma'. \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, p0)\}$$

Proof Skeleton of Find

```
{graph_rep( $\gamma$ )  $\wedge$  vvalid( $\gamma$ , x)}  
  p = x -> parent;  
{graph_rep( $\gamma$ )  $\wedge$  vvalid( $\gamma$ , x)  $\wedge$  p = prt( $\gamma$ , x)}  
  p0 = find(p);  
  
  x -> parent = p0
```

```
{ $\exists \gamma'$ . graph_rep( $\gamma'$ )  $\wedge$  uf_eq( $\gamma$ ,  $\gamma'$ )  $\wedge$  root( $\gamma'$ , x, p0)}
```

Proof Skeleton of Find

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)\}$$
$$p = x \rightarrow \text{parent};$$
$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x) \wedge p = \text{prt}(\gamma, x)\}$$
$$p0 = \text{find}(p);$$
$$x \rightarrow \text{parent} = p0$$
$$\{\exists \gamma'. \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, p0)\}$$

Proof Skeleton of Find

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)\}$$
$$p = x \rightarrow \text{parent};$$
$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x) \wedge p = \text{prt}(\gamma, x)\}$$
$$p0 = \text{find}(p);$$
$$\{\text{graph_rep}(\gamma_1) \wedge \text{uf_eq}(\gamma, \gamma_1) \wedge \text{root}(\gamma_1, p, p0) \wedge p = \text{prt}(\gamma, x)\}$$
$$x \rightarrow \text{parent} = p0$$
$$\{\exists \gamma'. \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, p0)\}$$

Proof Skeleton of Find

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)\}$$
$$p = x \rightarrow \text{parent};$$
$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x) \wedge p = \text{prt}(\gamma, x)\}$$
$$p0 = \text{find}(p);$$
$$\{\text{graph_rep}(\gamma_1) \wedge \text{uf_eq}(\gamma, \gamma_1) \wedge \text{root}(\gamma_1, p, p0) \wedge p = \text{prt}(\gamma, x)\}$$
$$x \rightarrow \text{parent} = p0$$
$$\{\exists \gamma'. \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, p0)\}$$

Proof Skeleton of Find

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)\}$$
$$p = x \rightarrow \text{parent};$$
$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x) \wedge p = \text{prt}(\gamma, x)\}$$
$$p0 = \text{find}(p);$$
$$\{\text{graph_rep}(\gamma_1) \wedge \text{uf_eq}(\gamma, \gamma_1) \wedge \text{root}(\gamma_1, p, p0) \wedge p = \text{prt}(\gamma, x)\}$$
$$x \rightarrow \text{parent} = p0$$
$$\{\text{graph_rep}(\gamma_2) \wedge \gamma_2 = \text{redirect_parent}(\gamma_1, x, p0) \wedge \dots\}$$
$$\{\exists \gamma'. \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, p0)\}$$

Proof Skeleton of Find

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)\}$$

$$p = x \rightarrow \text{parent};$$

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x) \wedge p = \text{prt}(\gamma, x)\}$$

$$p0 = \text{find}(p);$$

$$\{\text{graph_rep}(\gamma_1) \wedge \text{uf_eq}(\gamma, \gamma_1) \wedge \text{root}(\gamma_1, p, p0) \wedge p = \text{prt}(\gamma, x)\}$$

$$\{x \mapsto \text{vlabel}(\gamma_1, x), \text{prt}(\gamma_1, x)\}$$

$$x \rightarrow \text{parent} = p0$$

$$\{x \mapsto \text{vlabel}(\gamma_1, x), p0\}$$

$$\{\text{graph_rep}(\gamma_2) \wedge \gamma_2 = \text{redirect_parent}(\gamma_1, x, p0) \wedge \dots\}$$

$$\{\exists \gamma'. \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, p0)\}$$

Proof Skeleton of Find

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)\}$$

$$p = x \rightarrow \text{parent};$$

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x) \wedge p = \text{prt}(\gamma, x)\}$$

$$p0 = \text{find}(p);$$

$$\{\text{graph_rep}(\gamma_1) \wedge \text{uf_eq}(\gamma, \gamma_1) \wedge \text{root}(\gamma_1, p, p0) \wedge p = \text{prt}(\gamma, x)\}$$

$$\rightarrow \{x \mapsto \text{vlabel}(\gamma_1, x), \text{prt}(\gamma_1, x)\}$$

$$x \rightarrow \text{parent} = p0$$

$$\rightarrow \{x \mapsto \text{vlabel}(\gamma_1, x), p0\}$$

$$\{\text{graph_rep}(\gamma_2) \wedge \gamma_2 = \text{redirect_parent}(\gamma_1, x, p0) \wedge \dots\}$$

$$\{\exists \gamma'. \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, p0)\}$$

Proof Skeleton of Find

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)\}$$

$$p = x \rightarrow \text{parent};$$

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x) \wedge p = \text{prt}(\gamma, x)\}$$

$$p0 = \text{find}(p);$$

$$\{\text{graph_rep}(\gamma_1) \wedge \text{uf_eq}(\gamma, \gamma_1) \wedge \text{root}(\gamma_1, p, p0) \wedge p = \text{prt}(\gamma, x)\}$$

$$\rightarrow \{x \mapsto \text{vlabel}(\gamma_1, x), \text{prt}(\gamma_1, x)\}$$

$$x \rightarrow \text{parent} = p0$$

$$\checkmark \{x \mapsto \text{vlabel}(\gamma_1, x), p0\}$$

$$\{\text{graph_rep}(\gamma_2) \wedge \gamma_2 = \text{redirect_parent}(\gamma_1, x, p0) \wedge \dots\}$$

$$\{\exists \gamma'. \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, p0)\}$$

Proof Skeleton of Find

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)\}$$

$$p = x \rightarrow \text{parent};$$

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x) \wedge p = \text{prt}(\gamma, x)\}$$

$$p0 = \text{find}(p);$$

$$\{\text{graph_rep}(\gamma_1) \wedge \text{uf_eq}(\gamma, \gamma_1) \wedge \text{root}(\gamma_1, p, p0) \wedge p = \text{prt}(\gamma, x)\}$$

$$\rightarrow \{x \mapsto \text{vlabel}(\gamma_1, x), \text{prt}(\gamma_1, x)\}$$

$$x \rightarrow \text{parent} = p0$$

$$\checkmark \{x \mapsto \text{vlabel}(\gamma_1, x), p0\}$$

$$\{\text{graph_rep}(\gamma_2) \wedge \gamma_2 = \text{redirect_parent}(\gamma_1, x, p0) \wedge \dots\}$$

$$\{\text{graph_rep}(\gamma_2) \wedge \text{uf_eq}(\gamma, \gamma_2) \wedge \text{root}(\gamma_2, x, p0)\}$$

$$\{\exists \gamma'. \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, p0)\}$$

Proof Skeleton of Find

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x)\}$$

$$p = x \rightarrow \text{parent};$$

$$\{\text{graph_rep}(\gamma) \wedge \text{vvalid}(\gamma, x) \wedge p = \text{prt}(\gamma, x)\}$$

$$p0 = \text{find}(p);$$

$$\{\text{graph_rep}(\gamma_1) \wedge \text{uf_eq}(\gamma, \gamma_1) \wedge \text{root}(\gamma_1, p, p0) \wedge p = \text{prt}(\gamma, x)\}$$

$$\rightarrow \{x \mapsto \text{vlabel}(\gamma_1, x), \text{prt}(\gamma_1, x)\}$$

$$x \rightarrow \text{parent} = p0$$

$$\rightarrow \{x \mapsto \text{vlabel}(\gamma_1, x), p0\}$$

$$\{\text{graph_rep}(\gamma_2) \wedge \gamma_2 = \text{redirect_parent}(\gamma_1, x, p0) \wedge \dots\}$$

$$\{\text{graph_rep}(\gamma_2) \wedge \text{uf_eq}(\gamma, \gamma_2) \wedge \text{root}(\gamma_2, x, p0)\}$$

$$\{\exists \gamma'. \text{graph_rep}(\gamma') \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, p0)\}$$

Proof Obligation of Find

$$\begin{aligned} \text{graph_rep}(\gamma_1) \vdash & \left(x \mapsto \text{vlabel}(\gamma_1, x), \text{prt}(\gamma_1, x) \right) * \\ & \left(\left(x \mapsto \text{vlabel}(\gamma_1, x), p_0 \right) \rightarrow * \right. \\ & \left. \text{graph_rep}(\text{redirect_parent}(\gamma_1, x, p_0)) \right) \end{aligned}$$

Proof Obligation of Find

$$\begin{aligned} \text{graph_rep}(\gamma_1) \vdash & \left(x \mapsto \text{vlabel}(\gamma_1, x), \text{prt}(\gamma_1, x) \right) * \\ & \left(\left(x \mapsto \text{vlabel}(\gamma_1, x), p_0 \right) \multimap \right. \\ & \left. \text{graph_rep}(\text{redirect_parent}(\gamma_1, x, p_0)) \right) \end{aligned}$$

$$\begin{aligned} \text{uf_eq}(\gamma, \gamma_1) \Rightarrow & \text{root}(\gamma_1, p, p_0) \Rightarrow \text{dst}(\gamma, \text{out}(x)) = p \\ \gamma_2 = & \text{redirect_parent}(\gamma_1, x, p_0) \Rightarrow \\ \text{uf_eq}(\gamma, \gamma_2) \wedge & \text{root}(\gamma_2, x, p_0) \end{aligned}$$


Modularity: The Array Version of Find

```

struct subset {
    int parent;
    unsigned int rank;
};

int find(struct subset subs[], int i) {
    int p0 = 0;
    int p = subs[i].parent;
    if (p != i) {
        p0 = find(subs, p);
        p = p0;
        subs[i].parent = p;
    }
    return p;
}

```



The same specification but a different representation

PRE: $\text{graph_rep}(\gamma, s) \wedge \text{vvalid}(\gamma, x)$

POST: $\exists \gamma', t \text{ s.t. } \text{graph_rep}(\gamma', s) \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, t)$

The same specification but a different representation

PRE: $\text{graph_rep}(\gamma, s) \wedge \text{vvalid}(\gamma, x)$

POST: $\exists \gamma', t \text{ s.t. } \text{graph_rep}(\gamma', s) \wedge \text{uf_eq}(\gamma, \gamma') \wedge \text{root}(\gamma', x, t)$

$$\begin{aligned} \text{graph_rep}(g, s) \stackrel{\text{def}}{=} & \exists n. \left(\forall v. 0 \leq v < n \Leftrightarrow \text{vvalid}(\gamma, v) \wedge \right. \\ & \left. (n \leq \text{MaxInt}/8) \wedge \right. \\ & \left. s \mapsto \text{map}(\lambda v. \text{v_rep}(\gamma, v)) [0, 1, 2, \dots, n] \right) \end{aligned}$$

- Motivation ✓
- The Mathematical Graph Library ✓
 - Core Definitions ✓
 - Architecture ✓
 - Selection of Properties ✓
- The Spatial Representation of Graphs ✓
 - CompCert and VST ✓
 - Hoare Logic and Separation Logic ✓
 - Spatial Representation of Graphs ✓
 - Localize Rule ✓
- Verification of the Find function ✓
 - Specification ✓
 - Proof Skeleton ✓
 - Modularity ✓
- A Generational Garbage Collector

A Generational Garbage Collector

- 12 generations; mutator allocates only into the first
- Functional mutator, so no backward pointers


A Generational Garbage Collector

- 12 generations; mutator allocates only into the first
- Functional mutator, so no backward pointers
- Cheney's mark-and-copy collects generation to its successor
- Receiving generation may exceed fullness bound, triggering cascade of further pairwise collections


A Generational Garbage Collector

- 12 generations; mutator allocates only into the first
- Functional mutator, so no backward pointers
- Cheney's mark-and-copy collects generation to its successor
- Receiving generation may exceed fullness bound, triggering cascade of further pairwise collections
- Most tasks are handled by two key functions: **forward** (to copy individual objects) and **do_scan** (to repair the copied objects)


Overview of forward and do_scan




Overview of forward and do_scan




Overview of forward and do_scan



Overview of forward and do_scan



Overview of forward and do_scan



Bugs in the source C code

- Cheney was executed too conservatively, only part of `to` needs to be scanned.

Bugs in the source C code

- Cheney was executed too conservatively, only part of `to` needs to be scanned.
- Overflow in the following calculation:

```
int space_size =  
    h->spaces[i].limit - h->spaces[i].start;
```

Undefined behavior in C

- Double-bounded pointer comparisons:

```
int Is_from(value * from_start,  
            value * from_limit, value * v) {  
    return (from_start <= v && v < from_limit); }
```

Resolved using CompCert's "extcall_properties".

Undefined behavior in C

- Double-bounded pointer comparisons:

```
int Is_from(value * from_start,  
            value * from_limit, value * v) {  
    return (from_start <= v && v < from_limit); }
```

Resolved using CompCert's "extcall_properties".

- A classic OCaml trick:

```
int test_int_or_ptr (value x) {  
    return (int)(((intnat)x)&1); }
```

Discussing char alignment issues with CompCert.

Separation between pure and spatial reasoning

