

SMART AGRICULTURAL SOIL-MOISTURE MONITORING GATEWAY

Using Linux Device Driver, System Programming and C++

1. Project Introduction

1.1 Project Overview

The Smart Agricultural Soil-Moisture Monitoring Gateway is a Linux-based software prototype designed to monitor soil-moisture conditions from multiple sensor nodes.

The system demonstrates the integration of Linux device-driver development, hardware abstraction, system programming, C++, backend services, database storage and web-based monitoring.

The current prototype uses simulated sensor nodes so that the complete software architecture can be developed and tested without requiring physical agricultural sensor hardware.

1.2 Problem Statement

Agricultural irrigation requires information about soil conditions to avoid unnecessary watering and to identify dry areas.

A multi-node monitoring system can collect sensor information from different locations and process it through a central gateway.

The project addresses this requirement by designing a Linux-based gateway capable of processing sensor information, classifying soil conditions and providing monitoring information through a web dashboard.

1.3 Objectives

The main objectives are:

- Develop a Linux-based agricultural monitoring gateway.
- Demonstrate Linux device-driver interaction.
- Implement a hardware abstraction layer.
- Process sensor information using C++.
- Support multiple sensor nodes.
- Detect dry-soil conditions.
- Generate irrigation recommendations.
- Store historical sensor information.
- Provide REST APIs.

- Develop a web-based monitoring dashboard.
 - Demonstrate complete system integration.
-

2. Scope

The project includes:

- Simulated multi-node soil-moisture sensors.
- Linux device-driver interface.
- Hardware Abstraction Layer.
- C++ gateway and sensor processing.
- C++ HTTP backend backend.
- SQLite database.
- REST API endpoints.
- Monitoring dashboard.
- Sensor analytics.
- Git-based version control.

The current prototype does not include physical sensors or automatic irrigation hardware.

3. System Architecture

The final system architecture is shown below.

4. Major System Components

4.1 Simulated Sensor Nodes

The prototype uses eight simulated sensor nodes to represent agricultural field sensing devices. Each node provides soil-moisture, temperature and battery values.

4.2 Hardware Abstraction Layer

The Hardware Abstraction Layer (HAL) provides an interface between the gateway application and the lower-level Linux device interface. This separates hardware-access logic from the application-level gateway.

4.3 Linux Device Driver

A Linux character device driver named `soil_gateway` was developed. The driver creates the device interface:




Figure 1: System Architecture

`/dev/soil_gateway`

The driver was successfully loaded using the Linux `insmod` command and verified using `lsmod`.

4.4 Gateway Daemon

The gateway daemon is implemented in C++. It communicates with the device interface and processes sensor-node information. The daemon was successfully executed during testing.

4.5 C++ Sensor Processor

The C++ sensor processor handles sensor information and classifies soil moisture conditions.

The classification rules are:

- Moisture below 40%: DRY
- Moisture from 40% to 60%: NORMAL
- Moisture above 60%: WET

For a DRY condition, the system generates an irrigation recommendation.

4.6 C++ HTTP Backend

The backend is implemented using C++ HTTP backend. It provides REST API endpoints for sensor information, historical data and analytics.

The main endpoints are:

- `/api/nodes`
- `/api/history`
- `/api/analytics`

4.7 SQLite Database

SQLite is used for local storage of sensor readings. The database stores timestamp, node ID, moisture, temperature, battery level, status and recommendation information.

4.8 Monitoring Dashboard

A web-based dashboard provides a visual interface for monitoring sensor information, historical readings and analytics generated by the backend.

5. Functional Requirements

The system shall:

1. Simulate multiple agricultural sensor nodes.

2. Collect sensor readings through the gateway architecture.
3. Provide access through a Linux device interface.
4. Process sensor data using C++.
5. Classify soil moisture conditions.
6. Generate irrigation recommendations for dry conditions.
7. Store sensor readings in SQLite.
8. Provide REST APIs through the C++ HTTP backend.
9. Display monitoring information through a web dashboard.
10. Provide basic sensor analytics.

6. Non-Functional Requirements

The system should provide:

- Modular software architecture.
- Reliable communication between software components.
- Clear separation between hardware access and application logic.
- Maintainable C++ code.
- Local data persistence.
- Version control using Git.
- A structure that can later support real sensor hardware.

7. Technologies Used

Technology	Purpose
Linux	Operating system and driver environment
C	Linux device driver
C++	HAL, gateway and sensor processing
C++	Backend development
C++ HTTP Server	REST API and web backend
SQLite	Sensor data storage
HTML/CSS/JavaScript	Monitoring dashboard
Git	Version control
Graphviz	System diagrams

8. Implementation

The implementation was developed incrementally through the six-stage development process.

8.1 Driver Implementation

The Linux kernel module was compiled and loaded using:

```
“text sudo insmod driver/soil_gateway.ko
```