

MAINCRAFTS TECHNOLOGIES

Embedded Systems & Internet of Things (IoT)

TASK – 1

INTRODUCTION TO EMBEDDED SYSTEMS & IoT DEVICE DESIGN

Motion Detection Alarm System Using Arduino Uno

Submitted By: Anshu Saini

Internship Program: Embedded Systems & Internet of Things (IoT)

Organization: Maincrafts Technologies

Task Description

Design and simulation of a Motion Detection Alarm System using Arduino Uno and PIR Motion Sensor. The system detects human movement and generates visual and audible alerts using an LED and buzzer.

Tools Used

- Arduino Uno Rev3
- PIR Motion Sensor (HC-SR501)
- LED
- Piezo Buzzer
- Arduino IDE (Wokwi Simulator)
- Arduino C/C++

Submission Date: 22/6/2026

1. INTRODUCTION

1.1 Embedded System

An embedded system is a computer-based system designed to perform one or a few dedicated functions, often with real-time computing constraints. Embedded systems are integrated into larger devices and are optimized for specific control functions. According to Raj Kamal in *Embedded Systems: Architecture, Programming and Design*, an embedded system consists of hardware and software components that work together to perform dedicated tasks with reliability and efficiency.

Embedded systems have become an essential part of modern electronic devices and are widely used in consumer electronics, industrial automation, automotive systems, healthcare equipment, communication devices, and smart home applications.

Characteristics of Embedded Systems

1. Dedicated functionality
2. Real-time operation
3. High reliability
4. Low power consumption
5. Compact size
6. Cost effectiveness

1.2 Applications of Embedded Systems

Smart Home Systems

Embedded systems are used in smart lighting, security alarms, smart locks, and home automation systems.

Automotive Systems

Modern vehicles contain numerous embedded systems such as Engine Control Units (ECUs), Anti-lock Braking Systems (ABS), airbag controllers, and navigation systems.

Healthcare Devices

Medical equipment including ECG monitors, digital thermometers, infusion pumps, and wearable health monitoring systems rely on embedded technology.

Robotics and Automation

Industrial robots, autonomous vehicles, and automated manufacturing systems use embedded controllers for precise operation.

1.3 MICROCONTROLLER VS MICROPROCESSOR

A microcontroller is a compact integrated circuit designed to govern a specific operation in an embedded system. It contains a processor core, memory, and programmable input/output peripherals on a single chip.

A microprocessor, on the other hand, contains only the CPU and requires external memory and peripheral devices for operation. Microprocessors are generally used in personal computers and high-performance computing systems.

Microcontrollers are preferred for embedded applications because of their low cost, low power consumption, and ease of integration.

Feature	Microcontroller	Microprocessor
Definition	CPU, RAM, ROM and I/O on a single chip	CPU only
Cost	Low	High
Power Consumption	Low	High
Application	Embedded Systems	Computers
Examples	Arduino, ESP32	Intel Core i5, AMD Ryzen

Microcontrollers are preferred for embedded systems because they integrate all required components on a single chip, reducing cost and power consumption.

2. COMPONENT STUDY

2.1 Microcontrollers

A microcontroller is a compact integrated circuit designed to govern a specific operation in an embedded system. According to Muhammad Ali Mazidi in *The AVR Microcontroller and Embedded Systems Using Arduino Uno*, a microcontroller integrates a Central Processing Unit (CPU), memory, timers, communication interfaces, and input/output peripherals on a single chip. Microcontrollers are widely used in embedded applications because they provide low-cost, low-power, and reliable solutions for dedicated control tasks.

Unlike general-purpose computers, microcontrollers are optimized for performing specific functions such as monitoring sensors, controlling actuators, and processing real-time data.

Role of Microcontrollers in Embedded Systems:

- Processing data received from sensors.

- Controlling output devices such as LEDs, motors, and buzzers.
- Performing real-time decision-making.
- Communicating with external devices and networks.
- Managing automation and control systems.

2.1.1 Arduino Uno

Arduino Uno is one of the most widely used microcontroller development boards. It is based on the ATmega328P microcontroller developed by Microchip Technology. The Arduino platform provides an easy-to-use hardware and software environment for embedded systems development.

Technical Specifications:

- Microcontroller: ATmega328P
- Operating Voltage: 5V
- Clock Frequency: 16 MHz
- Digital I/O Pins: 14
- Analog Input Pins: 6
- Flash Memory: 32 KB
- SRAM: 2 KB

Role in Embedded Systems:

Arduino Uno acts as the central controller of an embedded system. It receives information from sensors, processes the data according to programmed instructions, and controls output devices. Due to its simplicity and extensive community support, Arduino Uno is widely used in educational projects, robotics, home automation, and IoT applications.

Applications:

- Home automation
- Security systems
- Robotics
- Environmental monitoring
- Educational projects

2.1.2 ESP32

ESP32 is a low-cost and high-performance microcontroller developed by Espressif Systems. It integrates Wi-Fi and Bluetooth communication capabilities, making it highly suitable for Internet of Things (IoT) applications.

Technical Specifications:

- Dual-Core Processor
- Clock Speed: Up to 240 MHz
- Wi-Fi Support

- Bluetooth Support
- Multiple GPIO Pins
- Low Power Modes

Role in Embedded Systems:

The ESP32 serves as both a processing and communication unit. It can collect data from sensors and transmit it over the internet to cloud platforms or mobile applications. Because of its wireless communication capabilities, ESP32 is widely used in smart devices and connected systems.

Applications:

- Smart homes
- IoT devices
- Wearable electronics
- Wireless monitoring systems
- Smart agriculture

2.1.3 Raspberry Pi Pico

Raspberry Pi Pico is a microcontroller development board based on the RP2040 microcontroller developed by Raspberry Pi Foundation. It offers high processing capability while maintaining low cost and low power consumption.

Technical Specifications:

- RP2040 Microcontroller
- Dual-Core ARM Cortex-M0+
- Clock Speed: Up to 133 MHz
- 264 KB SRAM
- 26 GPIO Pins
- Supports C/C++ and Python

Role in Embedded Systems:

Raspberry Pi Pico provides a flexible platform for embedded systems development. It can interface with sensors, communication modules, and actuators to perform control and monitoring tasks. The board is suitable for educational, industrial, and IoT applications.

Applications:

- Embedded control systems
- Robotics
- Industrial automation
- Sensor monitoring
- IoT prototypes

2.2 Sensor Study

Sensors are devices that detect changes in physical quantities and convert them into electrical signals that can be processed by a microcontroller. According to Raj Kamal, sensors serve as the interface between the physical environment and the embedded system.

2.2.1 Temperature Sensor

A temperature sensor is an electronic device that measures temperature and converts it into an electrical signal. One commonly used temperature sensor is the LM35, which provides an output voltage directly proportional to temperature.

Working Principle:

The sensor detects thermal energy from its surroundings and generates a corresponding electrical signal. This signal is processed by a microcontroller to determine the temperature value.

Applications:

- Weather monitoring systems
- Industrial process control
- Smart thermostats
- Healthcare equipment
- HVAC systems

Role in Embedded Systems:

Temperature sensors enable embedded systems to monitor environmental conditions and take corrective actions when temperature exceeds predefined limits.

2.2.2 Motion Sensor (PIR Sensor)

A Passive Infrared (PIR) sensor detects motion by sensing changes in infrared radiation emitted by objects. Since the human body emits infrared radiation, the sensor can detect the movement of people within its sensing range.

Working Principle:

The PIR sensor continuously monitors infrared energy levels. When a moving object enters the sensing area, the infrared pattern changes and the sensor generates a digital output signal indicating motion detection.

Applications:

- Security systems
- Intruder detection
- Automatic doors

- Smart lighting
- Occupancy monitoring

Role in Embedded Systems:

Motion sensors provide real-time information about movement and are commonly used in automation and security applications.

2.2.3 Light Sensor (LDR)

A Light Dependent Resistor (LDR) is a sensor whose resistance changes according to the intensity of light falling on its surface.

Working Principle:

As light intensity increases, the resistance of the LDR decreases. The resulting change in voltage can be measured by a microcontroller and used to determine ambient light levels.

Applications:

- Automatic street lights
- Solar tracking systems
- Brightness control systems
- Smart home lighting
- Camera exposure control

Role in Embedded Systems:

Light sensors allow embedded systems to respond automatically to changes in environmental lighting conditions, improving energy efficiency and automation.

3. PROJECT DESCRIPTION

3.1 Project Title

Motion Detection Alarm System Using Arduino Uno

3.2 Objective

To design and simulate a motion detection alarm system that activates an LED and buzzer whenever motion is detected by a PIR sensor.

3.3 WORKING PRINCIPLE

The system continuously monitors its surroundings using a PIR motion sensor. The sensor detects changes in infrared radiation caused by moving objects such as humans. When

motion is detected, the sensor output becomes HIGH.

The Arduino reads this signal through a digital input pin and immediately activates:

- LED for visual indication
- Buzzer for audible indication


When no motion is present, both outputs remain OFF.

System Flow

1. PIR sensor monitors surroundings.
2. Motion occurs.
3. PIR sensor output becomes HIGH.
4. Arduino reads sensor signal.
5. LED turns ON.
6. Buzzer turns ON.
7. Alert message appears on Serial Monitor.

3.4 CIRCUIT CONNECTIONS

Component	Arduino Pin
PIR VCC	5V
PIR GND	GND
PIR OUT	D2
LED Positive	D13
LED Negative	GND through 1K Ω Resistor
Buzzer Positive	D8
Buzzer Negative	GND



3.5 ARDUINO PROGRAM

```
const int pirPin = 2;

const int ledPin = 13;

const int buzzerPin = 8;


void setup() {

  pinMode(pirPin, INPUT);

  pinMode(ledPin, OUTPUT);

  pinMode(buzzerPin, OUTPUT);


  Serial.begin(9600);

}
```

```
void loop() {  
  
    int motion = digitalRead(pirPin);  
  
  
    if (motion == HIGH) {  
  
        digitalWrite(ledPin, HIGH);  
  
        digitalWrite(buzzerPin, HIGH);  
  
  
        Serial.println("Motion Detected!");  
    } else {  
  
        digitalWrite(ledPin, LOW);  
  
        digitalWrite(buzzerPin, LOW);  
  
  
        Serial.println("No Motion");  
    }  
  
  
  
    delay(500);  
}
```

3.6 CODE EXPLANATION

Setup Function

The setup function initializes the PIR sensor pin as input and the LED and buzzer pins as outputs. Serial communication is started at 9600 baud rate.

Motion Detection

The Arduino continuously reads the PIR sensor output using `digitalRead()`.

Alarm Activation

If the sensor output is HIGH, the LED and buzzer are activated.

Alarm Deactivation

If no motion is detected, the LED and buzzer remain OFF.


3.7 RESULTS

The motion detection alarm system was successfully simulated using Wokwi. The PIR sensor correctly detected movement and triggered the LED and buzzer. The Serial Monitor displayed appropriate status messages.


Observations:

Condition	LED	Buzzer	Serial Monitor
No Motion	OFF	OFF	No Motion
Motion Detected	ON	ON	Motion Detected!

- Circuit without motion



- Motion detected with LED ON.



3.8 REAL-WORLD APPLICATIONS

Home Security Systems

Detect unauthorized entry into homes.

Smart Buildings

Automate security monitoring.

Office Surveillance

Monitor restricted areas.

Industrial Safety

Detect movement in hazardous zones.

Smart Lighting

Automatically activate lights when motion is detected.

3.9 ADVANTAGES

- Low cost
- Easy implementation
- Low power consumption
- Real-time monitoring
- Suitable for IoT applications

3.10 FUTURE ENHANCEMENTS

- Integration with Wi-Fi using ESP32
- Mobile app notifications
- Cloud-based monitoring
- Camera-based security system
- Smart home integration

3.11 CONCLUSION

The Motion Detection Alarm System using Arduino Uno successfully demonstrates the fundamentals of embedded systems and sensor interfacing. The system effectively detects motion using a PIR sensor and provides visual and audible alerts through an LED and buzzer. The project highlights the practical application of embedded systems in security and automation and serves as a foundation for more advanced IoT-based monitoring solutions.