

224- *Transport Management Commands*

224.1 Transport Management Command Tree
224.2 IP Net-to-media Management Command

224-7290
224-7291

224.1 Transport Management Command Tree

Description

This chapter gives an overview of nodes that are handled by "Transport Management Commands".

Command Tree

```
----admin
  ----transport
    ----ip-net-to-media
      - (interface-name)
      - network-addr
      - phy-addr
      - (delete)
```

224.2 IP Net-to-media Management Command

Command Description

This command allows the operator to delete the IP address out of the ARP table.

User Level

The command can be accessed by operators with transport privileges, and executed by operators with transport privileges.

Command Syntax

The command has the following syntax:

```
> admin transport ip-net-to-media (interface-name) network-addr <Ip::V4AddressHex> phy-addr <Sys::MacAddr>
[ (delete) ]
```

Command Parameters

Table 224.2-1 "IP Net-to-media Management Command" Resource Parameters

Resource Identifier	Type	Description
(interface-name)	Format: eth1 Possible values: - eth1 : control interface	name of the interface
network-addr	Parameter type: <Ip::V4AddressHex> Format: - IPv4-address	ip addr corresponding to media-dependent physical addr
phy-addr	Parameter type: <Sys::MacAddr> Format: - a mac-address (example : 01:02:03:04:05:06) - length: 6	media-dependent physical addr

Table 224.2-2 "IP Net-to-media Management Command" Command Parameters

Parameter	Type	Description
(delete)	Format: delete Possible values: - delete : delete a ip-net to media entry	<i>optional parameter</i> delete a ip-net-to-media