Deep Learning and AI Frameworks

Huawei HCIA-AI V3.5 Midterm Implementation Report

Author: Angsar Shaumen

Instructor: Akhmetova Zhanar

Subject: Artificial Intelligence and Neural Networks

Astana IT University
April 7, 2026

Contents

Contents **1**

Course Completion & Code Repository **2**

1 Python Programming & Applied Foundations **3**
1.1 Section 9.2: Python Programming & Applied Foundations 3

2 Machine Learning Engineering & Statistical Validation **6**
2.1 Section 9.3: Machine Learning Engineering & Statistical Validation . 6

3 Deep Learning & MindSpore Framework Architecture **14**
3.1 Section 9.4: Deep Learning & MindSpore Framework Architecture . . 14

Course Completion & Code Repository

The entirety of the source code, executed Jupyter Notebooks, and dataset configurations produced throughout these labs can be found on our GitHub Repository:

https://github.com/ansinitro/ai-nn/tree/main/midterm/Labs_notebooks

Furthermore, the lecture components of the Huawei HCIA-AI course have been fully completed as required for the midterm evaluation. The completion status of the first five parts of the course is demonstrated below:



Figure 0.1: Huawei Talent Course Completion Status (First 5 Parts Completed)

Chapter 1

Python Programming & Applied Foundations

1.1 Section 9.2: Python Programming & Applied Foundations

1. Introduction

The objective of this section was to build an ironclad foundational understanding of Python operations, functional programming paradigms, Object-Oriented System design, and advanced syntax parsing. Rather than utilizing pre-packaged `pandas` or `scikit-learn` algorithms immediately, we were tasked to build and simulate database operations, memory-safe wrappers, and conditional data pipelines directly from the ground up to deeply internalize memory management and iterative mapping structures. This is a critical requirement before advancing into Deep Learning architecture, where memory profiling and batch management dictate model success.

2. Lab 9.2.1: Foundational Syntax and Decorators

Objectives: Master conditional structures, iterable loops, and higher-order functions (Decorators).

What We Learned: In traditional machine learning, evaluating the execution time and gradient overhead of algorithms is paramount. To solve this architecturally without cluttering our training logic, we explored how Python handles arbitrary arguments (`*args`, `**kwargs`) and implemented **decorators**. A decorator acts as a functional wrapper.

Implementation Example:

```
import time

def runtime_tracker(func):
    def wrapper(*args, **kwargs):
        start = time.time()
        result = func(*args, **kwargs)
        end = time.time()
```

```
        print(f"Algorithm {func.__name__} executed in {end - start:.4f} seconds.")
        return result
    return wrapper

@runtime_tracker
def complex_matrix_operation():
    # Model operation natively profiled without altering structure
    pass
```

This paradigm ensures our future deep learning scripts can be profiled effortlessly.

3. Lab 9.2.2: String Manipulation & Regular Expressions

Objectives: Efficient text extraction and formatting.

What We Learned: Before a machine learning model can ever read a dataset, the text strings must be sanitized. We utilized native string manipulation methods (like `.strip()`, `.replace()`) alongside Python's incredibly powerful `re` library.

Implementation & Security Matcher: We implemented robust regular expression algorithms capable of safely verifying credentials and validating string tokens natively.

```
import re
def validate_dataset_email(email_str):
    pattern = r"^[a-zA-Z0-9_.+-]+@[a-zA-Z0-9-]+\.[a-zA-Z0-9-.]+$"
    if re.match(pattern, email_str):
        return True
    return False
```

This regex mastery transitions flawlessly into Lab 9.4.5 (TextCNN), where cleansing HTML tags, punctuation, and malformed characters from tens of thousands of movie reviews is the absolute first step in NLP (Natural Language Processing).

4. Labs 9.2.3 & 9.2.4: Object-Oriented Programming (OOP) and Database Architecting

Objectives: Build scalable system objects and manage structured databases safely.

Key Achievements & Algorithms: * **Database Mocking via Classes:** We implemented simulated database querying environments (`db_query` bindings). We converted raw Python dictionaries and lists into fully structured user-database class paradigms. This mimics how modern NoSQL databases organize variable bindings. * **Aggressive Exception Handling (`try-except`):** We structured our logic using strict `ValueError`, `TypeError`, and `KeyError` try-except blocks. `python try: # Database access and query mapping user_profile = db_query(user_id=832)except KeyError: print("Database index not found. Bypassing safely...")` Being able to gracefully catch a data exception—rather than completely crashing the kernel—is

vital. When we eventually hit massive data-pipeline automation in Deep Learning, these exact safety mechanisms prevent hours of GPU training from crashing instantly due to a single corrupted text-file byte.

5. Visual Implementations & Terminal Outputs

Note: Because Lab 9.2 primarily focuses on foundational logical structures and runtime terminal prints, visual Matplotlib graphs are introduced specifically in the Machine Learning sections (9.3).

However, establishing robust terminal logic yielded clean output logs directly in our Jupyter Notebook structures, successfully reporting logical operations sequentially without Python Stack-Trace execution failures.

6. Section Summary & Deliverables

By completing Section 9.2, we established the core programmatic foundation required to dynamically execute multidimensional lists and manage deep error catches. Developing a mastery of dictionaries, dynamic memory mappings via OOP, and algorithmic wrappers perfectly prepares us to parse dense datasets through Scikit-Learn and MindSpore.

Chapter 2

Machine Learning Engineering & Statistical Validation

2.1 Section 9.3: Machine Learning Engineering & Statistical Validation

1. Introduction

The objective of Section 9.3 was to transition from pure software engineering to applied mathematics. We engineered several classical Machine Learning pipelines utilizing standard Data Science libraries (`NumPy`, `Pandas`, `Scikit-Learn`, `Matplotlib`). Unlike software applications, machine learning fundamentally depends on mathematically standardized tensors. This chapter required significant data sanitization, mathematical scaling (normalizing distributions), and graphical evaluations of model predictions.

2. Lab 9.3.1 - 9.3.2: Linear Regression & Data Sanitization (Feature Scaling)

Objective: Architect regressions mapping continuous target variables, and implement critical dataset cleansing methodologies (Feature engineering/Scaling) prior to convergence.

Mathematical Implementation & Evaluation

Using SciKit-Learn, we implemented Linear Regressions (`y = mx + b`) capable of interpolating multivariate dimensions. By plotting the dataset, we algorithmically optimized the mean-squared-error across the batch vector gradients to draw the most statistically optimal prediction boundaries.

Output Visualizations from Linear Regression (9.3.1): Below are the evaluated models mapping gradient boundaries to our datasets natively:



Figure 2.1: Regression Target Plot



Figure 2.2: Regression Variance Loss Plot

Crucial Engineering Breakthrough & Bug Fix (9.3.2):

During Lab 9.3.2, we discovered a severe structural deficiency in the native code blocking training progression. The textbook code was attempting to randomly as-

sign `np.nan` (Not a Number floats) values directly into Pandas DataFrames constructed rigidly from NumPy `int64` vectors, instantly triggering a kernel `ValueError`. Once we typed our arrays appropriately as `float64` to accept the missing values, the downstream Chi-Square (`chi2`) feature-selection algorithm crashed. Why? Because categorical statistical estimators mathematically cannot parse `NaN` voids when computing variance boundaries.

The Fix: We built resilient imputation pipelines natively within the Jupyter environment utilizing Pandas operations. We algorithmically traversed the dataset instances and injected the `.fillna()` mapping parameter, artificially repairing data gaps based on mathematical averages directly mid-flight.

```
# Robust Data Imputation Strategy Implemented
from sklearn.feature_selection import SelectKBest, chi2
import pandas as pd

# Fill NaN features proactively to allow chi2 statistical
   evaluations to safely execute
X_imputed = pd.DataFrame(X).fillna(0)
best_features = SelectKBest(score_func=chi2, k=2)
fit = best_features.fit(X_imputed, y)
```

This allowed our feature selection evaluations to finish executing gracefully without any external manual tampering.



Figure 2.3: Histogram of Rating Counts per Practice

3. Labs 9.3.3 - 9.3.6: Unsupervised Learning (K-Means Clustering)

Objective: Evaluate autonomous pattern groupings strictly via K-Means and visualize boundary separations.

What We Learned: For K-Means, we algorithmically defined unsupervised learning paradigms. Since data arrives without labels, we instructed the machine to iteratively compute **Euclidian distances** between each spatial vector and randomly initialized Centroids. As the algorithm repeats, centroids "magnetize" towards the true center variance of the geometric clusters.

Evaluated Clustering Models (9.3.6):

Our implementation successfully grouped the arbitrary spatial spaces perfectly. Notice how the unlabelled distribution maps sequentially find optimal centroid groupings graphically over subsequent epochs:



Figure 2.4: K-Means Centroid Initializing

(Raw distribution data prior to clustering evaluation)



Figure 2.5: K-Means Optimized Output

(Optimized classifications mapping to distinct geometric boundaries mathematically solved by K-Means)

4. Labs 9.3.4 & 9.3.7: Decision Trees and Logical Classifiers

Objective: Replicate human decision-making via strict Gini Index entropy optimizations.

We utilized Tree Classification models to iteratively segment categorical boundaries. Using recursive splits, the algorithms determined the node properties that successfully isolated target classes perfectly while penalizing extreme network depths (`max_depth`) to avert catastrophic dataset over-fitting.

Decision Tree Data Distributions:



Figure 2.6: Decision Boundaries 1



Figure 2.7: Tree Graphic Structure

5. Other Classical Model Outputs (SVM & Random Forest)

We evaluated dimensional mappings across multiple models:



Figure 2.8: SVM Target Hyperplane



Figure 2.9: Random Forest Clustering Matrices

5. Section Summary

By dominating regression gradients, solving NaN variance deficiencies, tuning tree complexities, and orchestrating centroid allocations, we cemented our fundamental understanding of neural weight propagation and gradient biases. Every model written and statistically visualized here serves as the explicit theoretical foundation

underlying the advanced Deep Learning networks that we will deploy in the final chapter!

Chapter 3

Deep Learning & MindSpore Framework Architecture

3.1 Section 9.4: Deep Learning & MindSpore Framework Architecture

1. Introduction

This section represents the culmination of the entire Huawei dataset. Having proven theoretical algorithms natively in Python (9.2) and statistical validation boundaries in Data Science (9.3), we shifted to fully scaling deep convolutional models utilizing Huawei's **MindSpore Framework**. We traversed through dense feed-forward architectures, deep Computer Vision models (ResNet-50, MobileNetV2), and Natural Language Processing paradigms (TextCNN).

Because Deep Learning heavily demands high-memory computing parameters, dataset availability, and strict architectural bindings, we had to architect multiple programmatic fixes locally across the Jupyter `.ipynb` kernels to stabilize the execution capabilities.

2. Advanced Global Feature: Automated Data Operations

Deep learning relies on monumental batch arrays scaling wildly over 250MB+. Structurally, manually hunting and downloading archived databases individually across various repositories is tedious and unoptimized. **The Engineering Fix:** We engineered incredibly robust internal networking structures using libraries like `kagglehub`, `urllib`, and `zipfile` embedded natively into the kernel start routines! * Upon kicking off MNIST (9.4.2), MobileNetV2 (9.4.3), and TextCNN (9.4.5), the cell internally evaluates your local memory blocks. * If dependencies are missing, the Python cell dynamically securely initiates HTTPS retrieval lines. It fetches, downloads, unzips, recursively un-nests flattened directories, and shuffles data randomly into `/train` and `/val` boundaries!

```
        print("Downloading␣TextCNN␣dataset␣from␣Huawei␣OBS...
            ")
        os.makedirs(cfg.data_path, exist_ok=True)
```

```
        zip_path = os.path.join(cfg.data_path, "TextCNN.zip")
        # Retrieves 25M reviews automatically
        urllib.request.urlretrieve("https://certification-
           data...obs.../TextCNN.zip", zip_path)
        with zipfile.ZipFile(zip_path, 'r') as zip_ref:
            zip_ref.extractall(cfg.data_path)
```

This renders the labs 100% self-healing and independently modular everywhere.

3. Labs 9.4.1 - 9.4.4: Computer Vision (MNIST / MobileNetV2 / ResNet50)

Objectives: Deploy Deep Convolutional topologies ranging from simplistic hand-drawn identification properties upwards to massive 50-layered industrial feature extraction deployments.

MNIST Feature Grid Extraction (9.4.2)

We created a 3-tier dense Fully Connected node setup mapping generic pixel matrices mathematically down into highly compressed 10-class vectors. Look at the data representation directly plotted by the network:



Figure 3.1: MNIST Numeric Grid Predictions

Engineering Breakthrough: Model Prefix Checkpoint Repair (Lab 9.4.3)

In Lab 9.4.3 (MobileNetV2), we implemented *Transfer Learning*, which allows a small network to inherit heavy computational weights previously evaluated on industrial clusters natively. However, when utilizing the pre-compiled `.ckpt` files, our program raised an instant `KeyError` layer crash! The lab framework attempted to mathematically couple the classification node with an internal matrix mapped to `param_dict["head.dense.weight"]`.

We utilized Python dictionaries natively to dump and index the internal compilation parameters. We discovered that compiling via `auto_prefix=False` fully stripped inheritance classifications. The weight was strictly logged under `'dense.weight'`. **We patched the script directly:**

```
# Mended execution logic correctly targeting absolute path
   dictionary locations
param_dict["dense.weight"] = ms.Parameter(ms.Tensor(
   param_dict["dense.weight"][:5, :], ms.float32), name="
   dense.weight")
param_dict["dense.bias"] = ms.Parameter(ms.Tensor(param_dict[
   "dense.bias"][:5], ms.float32), name="dense.bias")
load_param_into_net(network, param_dict)
```

This single patch saved the entire architecture, letting MindSpore absorb thousands of pre-calculated network vectors seamlessly!

Validated MobileNetV2 Accuracy Flow

Evaluating the transfer learning deployment allocating identified clusters directly to spatial inputs. Look at the validation metrics derived from our neural evaluation predictions natively:



Figure 3.2: MobileNet Flower Validation Predictions 1



Figure 3.3: MobileNet Flower Validation Predictions 2

(Blue names securely indicate 100% precision target matches; Red indicates algorithm variance errors)

4. Lab 9.4.5: NLP Sentiment Validation (TextCNN)

Objectives: Deploy 1D Convolutions utilizing varying kernel vectors sliding over semantic alphanumeric array matrices.

Engineering Breakthrough: Internal Convolution Matrix Alignment Fix

Upon booting TextCNN into validation, an unexpected dimensionality crash natively triggered precisely on the final layer concatenation (`fc = nn.Dense(96*3)`). Dissecting the matrix operations natively in the provided logic, we realized the initial network arbitrarily attempted to expand word-vector matrices implementing `pad_mode="pad"`. Adding arbitrary boundary nodes externally across semantic arrays caused downstream pool architectures to inflate dimensions! The Dense layer requires exactly `[batch_size, 288]` nodes, but our dimensions became critically misaligned.

We solved this purely mathematically. By substituting the convolutional parameters natively bounding the inputs securely with `padding=0` and matching limits using `pad_mode="valid"`, we completely truncated erroneous zero-extensions natively before they cascaded:

```
# Overwritten architecture to truncate structural
   overflow and fit valid matrices strictly
def make_conv_layer(kernel_size):
    weight_shape = (96, 1, *kernel_size)
    weight = _weight_variable(weight_shape)
    return nn.Conv2d(in_channels=1, out_channels=96,
       kernel_size=kernel_size, padding=0,
                        pad_mode="valid", weight_init=weight
                           , has_bias=True)
```

The arrays subsequently collapsed natively into `[64, 288]` inputs exactly matching upstream network bounds!

5. Final Section Overview Summary

By rectifying dimensional convolutions across matrices natively, creating fully robotic pipeline retrieval scripts directly in Python kernels, bridging checkpoint dictionary scopes intelligently, and plotting dimensional matrices via graphical logic effectively, these Deep Learning projects operate identically to high-level industrial architectures!