

Data types and structures

AUTHOR

Ralf Ansorg

PUBLISHED

30 September 2025

Exercise 1

Suppose you got the following data or data frame:

```
a <- c(1:5) # mouse ID
b <- c(5, 6, 3, 10, 7) # licks per hours
c <- c("17.18", "16.03", "15.9", "17.99", "14") # length in cm
d <- c("Female", "Male", "Male", "Female", "Maile") # sex of mouse
e <- c(TRUE, FALSE, TRUE, TRUE, FALSE) # healthy mouse
```

```
df <- data.frame(a=a, b=b, c=c, d=d, e=e)
```

Question 1

Which vectors (or columns of the data frame) need some work-over? If so, please write the correct code. *Hint*: try to figure this out by looking at its structure or class; recall coercion and accessing elements of vectors, and factors. Think about on how to assign new a value to a particular element of a vector, e.g. `my_example_vector[1]`.

Solution

Vector `c` has quotation marks and looks suspicious (the code coloring above gives it already away). The length should be a decimal number. For convenience, we are using the vectors directly since we already have them. Otherwise, with the `data.frame`, it's `df$c` for accessing or manipulation. What about vector `d`? Isn't it a category (factor in R)?

Let's check the data type of `c` to be sure first.

Length vector

```
class(c)
## [1] "character"
c
## [1] "17.18" "16.03" "15.9"  "17.99" "14"
```

As assumed, it is of type `character`. We need to transform the values to decimal numbers, `numeric` in R.

Length vector (2)

```
c <- as.numeric(c)
c
## [1] 17.18 16.03 15.90 17.99 14.00
class(c)
## [1] "numeric"
```

Perfect! Our length vector is now of type `numeric`. We can now apply mathematical or statistical functions to it.

Vector `d` is rather a categorical variable with `Female` and `Male` as the only possible values. Since categories are factors in R, we coerce the vector using the `as.factor()` function. Note that this

is, strictly speaking, *not* necessary in our example. However, in some cases, factors behave differently than characters or strings in computations (including statistical tests) and plotting.

Sex vector

```
d <- as.factor(d)
d
## [1] Female Male   Male   Female Maile
## Levels: Female Maile Male
```

Wait, the levels indicate all available categories. There are three of them, obviously due to a spelling mistake. Let's correct it and run it again.

Sex vector (2)

```
d[5] <- "Male" # was misspelled as "Maile"
d <- as.factor(d)
d
## [1] Female Male   Male   Female Male
## Levels: Female Maile Male
```

The levels haven't changed although we corrected the spelling. What happened? Since `d` already had levels assigned when we coerced it to a factor, we also need to re-assign the levels¹.

Sex vector (3)

```
d <- factor(d, levels = c("Female", "Male"))
d
## [1] Female Male   Male   Female Male
## Levels: Female Male
```

It would have been easier to first correct the spelling (cleaning the data) and then make it a factor (i.e. just running (2)). Note that we *must* use the `factor()` function to set the levels, it is not a parameter of the `as.factor()` function!

If you have an *ordered* factor, you can also change the order like this (there is, however, an entire package for it, `forcats`, which is part of the `tidyverse` package we will use later).

If you used the `str()` function for the data frame, you saw the incorrect data types at a glance, that is, `c` is of type character (`chr` — and also the quotation marks) and `e` of type logical (`logi`).

```
str(df)
## 'data.frame':    5 obs. of  5 variables:
## $ a: int  1 2 3 4 5
## $ b: num  5 6 3 10 7
## $ c: chr  "17.18" "16.03" "15.9" "17.99" ...
## $ d: chr  "Female" "Male" "Male" "Female" ...
## $ e: logi  TRUE FALSE TRUE TRUE FALSE
```

Question 2

Add all vectors to a new data frame `df_clean` with proper/meaningful headers (instead of a ... e).

Solution

You can simply use column names you want to use and assign the vectors `a ... e`. Best practice is to avoid spaces. Use a single word or combine words with `_` (underscore): `length_cm` or `licks_hr`. In this example, adding the unit(s) may even enhance the readability of your data (for humans).

¹Or remove variable `d` from the memory, which is rather complicated.

If you get data with messy headers, the `janitor` package helps.

Clean data frame

```
df_clean <- data.frame(ID=a, licks_hr=b, length_cm=c, sex=d, healthy=e)
df_clean
##   ID licks_hr length_cm    sex healthy
## 1  1         5    17.18 Female     TRUE
## 2  2         6    16.03   Male    FALSE
## 3  3         3    15.90   Male     TRUE
## 4  4        10    17.99 Female     TRUE
## 5  5         7    14.00   Male    FALSE
```

Question 3

What is the mean of the length of the mice? *Hint:* you could use the `mean()` function. What is the median?

Solution

We can simply run the `mean()` and `median()` functions on the `length` column.

```
mean(df_clean$length_cm)
## [1] 16.22
median(df_clean$length_cm)
## [1] 16.03
```

Inline computations are also possible if you want to insert values or the result of a function in your text:

The mean length of the mice is 16.22 and the median is 16.03.²

Question 4

Look at the structure **and** summary if your cleaned-up data is reasonable and briefly explain why (what you did). Bullet points only (use the `*` or `-` symbol), no essay.

Solution

Review the structure and summary from Question 1 and compare it to our cleaned data frame (Question 2). If you want to check for data types, `str()` is probably the better and more compact choice. When we start working with the `tidyverse` package, there is an advanced `data.frame` (called a `tibble`) which prints the data types below the column names.

```
str(df)
## 'data.frame':    5 obs. of  5 variables:
##  $ a: int  1 2 3 4 5
##  $ b: num  5 6 3 10 7
##  $ c: chr  "17.18" "16.03" "15.9" "17.99" ...
##  $ d: chr  "Female" "Male" "Male" "Female" ...
##  $ e: logi TRUE FALSE TRUE TRUE FALSE
summary(df)
##           a           b           c           d
## Min.   :1   Min.   : 3.0   Length:5   Length:5
## 1st Qu.:2   1st Qu.: 5.0   Class :character Class :character
## Median :3   Median : 6.0   Mode  :character Mode  :character
## Mean   :3   Mean   : 6.2
## 3rd Qu.:4   3rd Qu.: 7.0
## Max.   :5   Max.   :10.0
##           e
```

²Check the `.qmd` file on how to have inline code! The `>` is for emphasis.

```
## Mode :logical
## FALSE:2
## TRUE :3
##
##
##

str(df_clean)
## 'data.frame':    5 obs. of  5 variables:
## $ ID      : int  1 2 3 4 5
## $ licks_hr : num  5 6 3 10 7
## $ length_cm: num  17.2 16 15.9 18 14
## $ sex      : Factor w/ 2 levels "Female","Male": 1 2 2 1 2
## $ healthy  : logi  TRUE FALSE TRUE TRUE FALSE
summary(df_clean)
##      ID      licks_hr      length_cm      sex      healthy
## Min.   :1   Min.    : 3.0   Min.    :14.00   Female:2   Mode :logical
## 1st Qu.:2   1st Qu.: 5.0   1st Qu.:15.90   Male  :3   FALSE:2
## Median :3   Median : 6.0   Median :16.03                TRUE :3
## Mean   :3   Mean    : 6.2   Mean    :16.22
## 3rd Qu.:4   3rd Qu.: 7.0   3rd Qu.:17.18
## Max.   :5   Max.    :10.0   Max.    :17.99
```

Comments/Bullet points

- Variable/vector length had to be converted to numerical (from character)
- Variable/vector sex is categorical, hence a factor (without any order)
- Factors and logicals are displayed differently: counts instead of the descriptive statistics³

Bonus

If you know that FALSE and TRUE are internally represented as 0 and 1. What is the number of healthy mice (computed)?

Use the `sum()` function to count all TRUEs in column `healthy` which returns 3 (compare it to the `summary()` output above).

³Min, 25% Qrt, Median, Mean, 75% Qrt, Max