

PORSCHE

* Scanners are devices that can transmit thousands of codes a minute and be adjusted to suit most typical alarms. When the correct code is transmitted the alarm will switch off, and if connected, the central locking will unlock.

** Grabbers are radio frequency recording devices, used by an ever increasing number of car thieves, that can literally 'grab' the code from the air when a remote control is used to operate a typical alarm system. Once recorded, the code can then be used to activate/deactivate the alarm system.

Additional remote handsets are available from your official Porsche Centre.

Part Number: 999 999 710 01

Key Learning Instructions

**Porsche Alarm/Immobiliser
PA1000**

KEY LEARNING

IMPORTANT

Please read the following instructions very carefully.

This Instruction Sheet together with the Red Master Handset must be kept in a secure place away from the vehicle.

The PA1000 Alarm/Immobiliser incorporates an advanced military standard encryption system that can resist the most powerful scanners* and grabbers**.

The signal that is transmitted from the remote handset is encryption coded, therefore making every code completely different. No matter how many codes are analysed a pattern cannot be identified making the alarm system very secure and theft resistant.

New remote handsets can be programmed onto the system and old remote handsets removed by using the unique RED MASTER remote handset.

The RED MASTER remote handset is supplied in sealed packaging, with the battery removed. This ensures that no other remote handsets, other than the 2 supplied, have been programmed onto your system.

The maximum number of remote handsets that can be programmed onto a system is 5. If a 6th remote handset is programmed onto the system one of the existing remote handsets will be automatically removed.

LEARNING PROCEDURE

Firstly, remove the RED MASTER remote handset from its sealed packaging and insert the battery prior to programming.

(a) To Add A Remote Handset.

With the alarm in its 'off' state press the RED MASTER remote handset button once. 2 short beeps will be heard from the internal buzzer.

Press the raised button on the new remote handset for 2 seconds, release and wait 1 second, press the raised button again for 2 seconds and release.

Press the raised button on the new remote handset for the third time and the alarm system will activate (turn on). Press the indented button to de-activate the alarm (turn off). On occasion due to atmospheric disturbance, the remote handset raised button may have to be pressed 4 times.

This remote handset is now programmed onto the system.

(b) To Remove A Remote Handset.

Carry out procedure (a) using the same remote handset 5 times. This procedure will erase all other remote handsets previously programmed onto the system, therefore rendering them inoperative.

To re-programme any other remote handsets back onto the system follow procedure (a).