# Ansys Actions

**Version: main**

## Check pr title

**Check pull-request title follows conventional commits**

```
- uses: ansys/actions/check-pr-title@main
  with:
    token: ${{ secrets.GITHUB_TOKEN }}
```

***Ref***: Check pull-request title follows conventional commits

## Doc deploy changelog

**Update changelog for new tag**

```
- uses: ansys/actions/doc-deploy-changelog@main
  with:
    bot-email: ${{ secrets.PYANSYS_CI_BOT_EMAIL }}
    bot-user: ${{ secrets.PYANSYS_CI_BOT_USERNAME
        }}
    token: ${{ secrets.PYANSYS_CI_BOT_TOKEN }}
```

***Ref***: Update CHANGELOG for new tag

## Doc deploy dev

**Deploy developers documentation**

```
- name: Deploy the latest documentation
  uses: ansys/actions/doc-deploy-dev@main
  with:
    bot-email: ${{ secrets.PYANSYS_CI_BOT_EMAIL }}
    bot-user: ${{ secrets.PYANSYS_CI_BOT_USERNAME
        }}
    cname: <library>.docs.pyansys.com
    token: ${{ secrets.GITHUB_TOKEN }}
```

***Ref***: Deploy developers documentation

## Build wheelhouse

**Build wheelhouse for latest python versions**

```
- name: Build a wheelhouse of the Python library
  uses: ansys/actions/build-wheelhouse@main
  with:
    library-name: <ansys-product-library>
    operating-system: ${{ matrix.os }}
    python-version: ${{ matrix.python-version }}
```

***Ref***: Build wheelhouse for latest Python versions

## Doc deploy stable

**Deploy stable documentation**

```
- name: Deploy the stable documentation
  uses: ansys/actions/doc-deploy-stable@main
  with:
    bot-email: ${{ secrets.PYANSYS_CI_BOT_EMAIL }}
    bot-user: ${{ secrets.PYANSYS_CI_BOT_USERNAME
        }}
    cname: <library>.docs.pyansys.com
    token: ${{ secrets.GITHUB_TOKEN }}
```

***Ref***: Deploy stable documentation

## Release pypi private

**Release to private pypi**

```
- name: Release to the private PyPI repository
  uses: ansys/actions/release-pypi-private@main
  with:
    library-name: ansys-<product>-<library>
    twine-token: ${{
        secrets.PYANSYS_PYPI_PRIVATE_PAT }}
    twine-username: __token__
```

***Ref***: Release to private PyPI

## Check environment approval

**Check environment approval**

```
- id: block
  name: Decide which environment should be used
  uses:
      ansys/actions/check-environment-approval@main
```

***Ref***: Check environment approval

## Doc changelog

**Create changelog fragment**

```
- uses: ansys/actions/doc-changelog@main
  with:
    bot-email: ${{ secrets.PYANSYS_CI_BOT_EMAIL }}
    bot-user: ${{ secrets.PYANSYS_CI_BOT_USERNAME
        }}
    token: ${{ secrets.PYANSYS_CI_BOT_TOKEN }}
```

***Ref***: Create changelog fragment

## Check vulnerabilities

**Check library vulnerabilities**

```
- uses: ansys/actions/check-vulnerabilities@main
  with:
    dev-mode: ${{ github.ref != 'refs/heads/main'
        }}
    python-package-name: ansys-<product>-<library>
    python-version: ${{ env.MAIN_PYTHON_VERSION }}
    token: ${{ secrets.PYANSYS_CI_BOT_TOKEN }}
```

***Ref***: Check library vulnerabilities

## Release pypi test

**Release to test pypi**

```
- name: Release to the test PyPI repository
  uses: ansys/actions/release-pypi-test@main
  with:
    library-name: ansys-<product>-<library>
    twine-token: ${{ secrets.PYANSYS_PYPI_TEST_PAT
        }}
    twine-username: __token__
```

***Ref***: Release to test PyPI

## Build ci wheels

**Build a c-extension library**

```
- name: Build a C-extension library wheel artifacts
  uses: ansys/actions/build-ci-library@main
```

***Ref***: Build a C-extension library

## Hk package clean except

**Perform versions cleanup - except certain tags**

```
- name: Perform versions cleanup - except certain
    tags
  uses: ansys/actions/hk-package-clean-except@main
  with:
    package-name: mypackage
    tags-kept: latest, latest-unstable
    token: ${{ secrets.GITHUB_TOKEN }}
```

***Ref***: Perform versions cleanup - except certain tags

## Doc style

**Running documentation style checks**

```
- name: Running documentation style checks
  uses: ansys/actions/doc-style@main
  with:
    token: ${{ secrets.GITHUB_TOKEN }}
```

***Ref***: Running documentation style checks

## Build library

**Build library basic example**

```
- name: Build library source and wheel artifacts
  uses: ansys/actions/build-library@main
  with:
    library-name: ansys-<product>-<library>
```

***Ref***: Build library basic example

# Hk automerge prs

**Automerging dependabot and pre-commit.ci prs**

```
- name: Automerging dependabot and pre-commit.ci
    PRs
  uses: ansys/actions/hk-automerge-prs@main
  with:
    approver: ${{ secrets.PYANSYS_CI_BOT_USERNAME
        }}
    approver-token: ${{
        secrets.PYANSYS_CI_BOT_TOKEN }}
```

***Ref***: Automerging dependabot and pre-commit.ci PRs

# Docker style

**Docker style**

```
- uses: ansys/actions/docker-style@main
  with:
    directory: docker
    error-level: 1
    recursive: true
```

***Ref***: Docker style

# Release pypi public

**Release to public pypi**

```
- name: Release to the public PyPI repository
  uses: ansys/actions/release-pypi-public@main
  with:
    library-name: ansys-<product>-<library>
    twine-token: ${{ secrets.PYPI_TOKEN }}
    twine-username: __token__
```

***Ref***: Release to public PyPI

# Release github

**Release to github**

```
- name: Release to GitHub
  uses: ansys/actions/release-github@main
  with:
    library-name: ansys-<product>-<library>
```

***Ref***: Release to GitHub

# Tests pytest

**Optimized testing with different operating systems and python versions**

```
- name: Login into the GitHub container registry
  uses:
      docker/login-action@f4ef78c080cd8ba55a85445d5b36e214a81df20a
  with:
    password: ${{ secrets.GITHUB_TOKEN }}
    registry: ghcr.io
    username: ${{ secrets.GH_USERNAME }}
- env:
    LICENSE_SERVER: ${{ secrets.LICENSE_SERVER }}
  name: Pull, launch and verify desired Ansys
      service
  run: '...'
- name: Run pytest with desired markers and extra
    arguments
  uses: ansys/actions/tests-pytest@main
  with:
    pytest-extra-args: ${{ matrix.cfg.extra-args }}
    pytest-markers: ${{ matrix.cfg.markers }}
    requires-xvfb: true
```

***Ref***: Optimized testing with different operating systems and Python versions

**Testing library with different operating systems and python versions**

```
- name: Run pytest
  uses: ansys/actions/tests-pytest@main
  with:
    pytest-extra-args: --cov=ansys.<library>
        --cov-report=term
        --cov-report=html:.cov/html
    pytest-markers: -k 'mocked'
```

***Ref***: Testing library with different operating systems and Python versions

# Hk package clean untagged

**Perform untagged versions cleanup**

```
- name: Perform untagged versions cleanup
  uses:
      ansys/actions/hk-package-clean-untagged@main
  with:
    package-name: mypackage
    token: ${{ secrets.GITHUB_TOKEN }}
```

***Ref***: Perform untagged versions cleanup

# Doc deploy pr

**Deploy pr documentation**

```
- uses: ansys/actions/doc-deploy-pr@main
  with:
    bot-email: ${{ secrets.PYANSYS_CI_BOT_EMAIL }}
    bot-user: ${{ secrets.PYANSYS_CI_BOT_USERNAME
        }}
    cname: ${{ env.DOCUMENTATION_CNAME }}
    maximum-pr-doc-deployments: 3
    token: ${{ secrets.GITHUB_TOKEN }}
```

***Ref***: Deploy PR documentation

# Check licenses

**Check library dependencies ship with valid licenses**

```
- name: Validate third party licenses
  uses: ansys/actions/check-licenses@main
  with:
    python-version: ${{ env.MAIN_PYTHON_VERSION }}
```

***Ref***: Check library dependencies ship with valid licenses

# Check actions security

**Check actions security**

```
- uses: ansys/actions/check-actions-security@main
  with:
    auditing-level: high
    generate-summary: true
    token: ${{ secrets.GITHUB_TOKEN }}
    trust-ansys-actions: true
```

***Ref***: Check actions security

# Doc build

**Installing additional system dependencies for building documentation**

```
- name: Run Ansys documentation building action
  uses: ansys/actions/doc-build@main
  with:
    dependencies: graphviz mermaid-cli
```

***Ref***: Installing additional system dependencies for building documentation

**Building library documentation that using xvfb**

```
- name: Run Ansys documentation building action
  uses: ansys/actions/doc-build@main
  with:
    requires-xvfb: true
```

***Ref***: Building library documentation that using XVFB

**Building library documentation**

```
- name: Run Ansys documentation building action
  uses: ansys/actions/doc-build@main
```

***Ref***: Building library documentation

# Code style

**Running code style checks**

```
- name: Run PyAnsys code style checks
  uses: ansys/actions/code-style@main
```

***Ref***: Running code style checks