

## When To Use

A simple and compact dialog used for asking for user confirmation.

The difference with the `confirm` modal dialog is that it's more lightweight than the static popped full-screen confirm modal.

## Examples

### Basic

```
import React from 'react';
import type { PopconfirmProps } from 'antd';
import { Button, message, Popconfirm } from 'antd';

const confirm: PopconfirmProps['onConfirm'] = (e) => {
  console.log(e);
  message.success('Click on Yes');
};

const cancel: PopconfirmProps['onCancel'] = (e) => {
  console.log(e);
  message.error('Click on No');
};

const App: React.FC = () => (
  <Popconfirm
    title="Delete the task"
    description="Are you sure to delete this task?"
    onConfirm={confirm}
    onCancel={cancel}
    okText="Yes"
    cancelText="No"
  >
    <Button danger>Delete</Button>
  </Popconfirm>
);

export default App;
```

### Locale text

```
import React from 'react';
import { Button, Popconfirm } from 'antd';

const App: React.FC = () => (
```

```

    <Popconfirm
      title="Delete the task"
      description="Are you sure to delete this task?"
      okText="Yes"
      cancelText="No"
    >
      <Button danger>Delete</Button>
    </Popconfirm>
  );

  export default App;

```

## Placement

```

import React from 'react';
import { Button, ConfigProvider, Flex, Popconfirm } from 'antd';

const text = 'Are you sure to delete this task?';
const description = 'Delete the task';
const buttonWidth = 80;

const App: React.FC = () => (
  <ConfigProvider button={{ style: { width: buttonWidth, margin: 4 } }}>
    <Flex vertical justify="center" align="center" className="demo">
      <Flex justify="center" align="center" style={{ whiteSpace: 'nowrap'
    >>
        <Popconfirm
          placement="topLeft"
          title={text}
          description={description}
          okText="Yes"
          cancelText="No"
        >
          <Button>TL</Button>
        </Popconfirm>
        <Popconfirm
          placement="top"
          title={text}
          description={description}
          okText="Yes"
          cancelText="No"
        >
          <Button>Top</Button>
        </Popconfirm>
        <Popconfirm
          placement="topRight"

```

```

        title={text}
        description={description}
        okText="Yes"
        cancelText="No"
    >
        <Button>TR</Button>
    </Popconfirm>
</Flex>
<Flex style={{ width: buttonWidth * 5 + 32 }} justify="space-between"
align="center">
    <Flex align="center" vertical>
        <Popconfirm
            placement="leftTop"
            title={text}
            description={description}
            okText="Yes"
            cancelText="No"
        >
            <Button>LT</Button>
        </Popconfirm>
        <Popconfirm
            placement="left"
            title={text}
            description={description}
            okText="Yes"
            cancelText="No"
        >
            <Button>Left</Button>
        </Popconfirm>
        <Popconfirm
            placement="leftBottom"
            title={text}
            description={description}
            okText="Yes"
            cancelText="No"
        >
            <Button>LB</Button>
        </Popconfirm>
    </Flex>
    <Flex align="center" vertical>
        <Popconfirm
            placement="rightTop"
            title={text}
            description={description}
            okText="Yes"
            cancelText="No"

```

```

    >
      <Button>RT</Button>
    </Popconfirm>
    <Popconfirm
      placement="right"
      title={text}
      description={description}
      okText="Yes"
      cancelText="No"
    >
      <Button>Right</Button>
    </Popconfirm>
    <Popconfirm
      placement="rightBottom"
      title={text}
      description={description}
      okText="Yes"
      cancelText="No"
    >
      <Button>RB</Button>
    </Popconfirm>
  </Flex>
</Flex>
<Flex justify="center" align="center" style={{ whiteSpace: 'nowrap'
}}>

  <Popconfirm
    placement="bottomLeft"
    title={text}
    description={description}
    okText="Yes"
    cancelText="No"
  >
    <Button>BL</Button>
  </Popconfirm>
  <Popconfirm
    placement="bottom"
    title={text}
    description={description}
    okText="Yes"
    cancelText="No"
  >
    <Button>Bottom</Button>
  </Popconfirm>
  <Popconfirm
    placement="bottomRight"
    title={text}

```

```

        description={description}
        okText="Yes"
        cancelText="No"
      >
        <Button>BR</Button>
      </Popconfirm>
    </Flex>
  </Flex>
</ConfigProvider>
);

export default App;

```

## Auto Shift

```

import React from 'react';
import { Button, Popconfirm } from 'antd';

const style: React.CSSProperties = {
  width: '300vw',
  height: '300vh',
  display: 'flex',
  alignItems: 'center',
  justifyContent: 'center',
};

const App: React.FC = () => {
  React.useEffect(() => {
    document.documentElement.scrollTop =
document.documentElement.clientHeight;
    document.documentElement.scrollLeft =
document.documentElement.clientWidth;
  }, []);
  return (
    <div style={style}>
      <Popconfirm title="Thanks for using antd. Have a nice day !" open>
        <Button type="primary">Scroll The Window</Button>
      </Popconfirm>
    </div>
  );
};

export default App;

```

## Conditional trigger

```

import React, { useState } from 'react';
import { Button, message, Popconfirm, Switch } from 'antd';

const App: React.FC = () => {
  const [open, setOpen] = useState(false);
  const [condition, setCondition] = useState(true);

  const changeCondition = (checked: boolean) => {
    setCondition(checked);
  };

  const confirm = () => {
    setOpen(false);
    message.success('Next step.');
```

```

    >
    <Button danger>Delete a task</Button>
  </Popconfirm>
  <br />
  <br />
  Whether directly execute:
  <Switch defaultChecked onChange={changeCondition} />
</div>
);
};

export default App;

```

### Customize icon

```

import React from 'react';
import { QuestionCircleOutlined } from '@ant-design/icons';
import { Button, Popconfirm } from 'antd';

const App: React.FC = () => (
  <Popconfirm
    title="Delete the task"
    description="Are you sure to delete this task?"
    icon={<QuestionCircleOutlined style={{ color: 'red' }} />}
  >
    <Button danger>Delete</Button>
  </Popconfirm>
);

export default App;

```

### Asynchronously close

```

import React, { useState } from 'react';
import { Button, Popconfirm } from 'antd';

const App: React.FC = () => {
  const [open, setOpen] = useState(false);
  const [confirmLoading, setConfirmLoading] = useState(false);

  const showPopconfirm = () => {
    setOpen(true);
  };

  const handleOk = () => {

```

```

    setConfirmLoading(true);

    setTimeout(() => {
      setOpen(false);
      setConfirmLoading(false);
    }, 2000);
  };

  const handleCancel = () => {
    console.log('Clicked cancel button');
    setOpen(false);
  };

  return (
    <Popconfirm
      title="Title"
      description="Open Popconfirm with async logic"
      open={open}
      onConfirm={handleOk}
      okButtonProps={{ loading: confirmLoading }}
      onCancel={handleCancel}
    >
      <Button type="primary" onClick={showPopconfirm}>
        Open Popconfirm with async logic
      </Button>
    </Popconfirm>
  );
};

export default App;

```

### Asynchronously close on Promise

```

import React from 'react';
import { Button, Popconfirm } from 'antd';

const App: React.FC = () => {
  const confirm = () =>
    new Promise((resolve) => {
      setTimeout(() => resolve(null), 3000);
    });

  return (
    <Popconfirm
      title="Title"
      description="Open Popconfirm with Promise"
    >

```



```

    onConfirm={confirm}
    onOpenChange={() => console.log('open change')}
  >
    <Button type="primary">Open Popconfirm with Promise</Button>
  </Popconfirm>
);
};

export default App;

```

## **\_InternalPanelDoNotUseOrYouWillBeFired**

Debug

```

import React from 'react';
import { Popconfirm } from 'antd';

const { _InternalPanelDoNotUseOrYouWillBeFired: InternalPopconfirm } =
  Popconfirm;

const App: React.FC = () => (
  <>
    <InternalPopconfirm title="Are you OK?" description="Does this look
good?" />
    <InternalPopconfirm
      title="Are you OK?"
      description="Does this look good?"
      placement="bottomRight"
      style={{ width: 250 }}
    />
    <InternalPopconfirm icon={null} title="Are you OK?" />
    <InternalPopconfirm icon={null} title="Are you OK?" description="Does
this look good?" />
  </>
);

export default App;

```

## **Wireframe**

Debug

```

import React from 'react';
import { ConfigProvider, Popconfirm } from 'antd';

const { _InternalPanelDoNotUseOrYouWillBeFired: InternalPopconfirm } =

```

```

Popconfirm;

const App: React.FC = () => (
  <ConfigProvider theme={{ token: { wireframe: true } }}>
    <InternalPopconfirm title="Are you OK?" />
    <InternalPopconfirm title="Are you OK?" placement="bottomRight" style=
  {{ width: 250 }} />
  </ConfigProvider>
);

export default App;

```

## API

Common props ref: [Common props](#)

Param	Description	Type	Default value	Version
cancelButtonProps	The cancel button props	<a href="#">ButtonProps</a>	-	
cancelText	The text of the Cancel button	string	Cancel	
disabled	Whether show popconfirm when click its childrenNode	boolean	false	
icon	Customize icon of confirmation	ReactNode	<ExclamationCircle />	
okButtonProps	The ok button props	<a href="#">ButtonProps</a>	-	
okText	The text of the Confirm button	string	OK	
okType	Button type of the Confirm button	string	primary	
showCancel	Show cancel button	boolean	true	4.18.0
title	The title of the confirmation box	ReactNode   () => ReactNode	-	

description	The description of the confirmation box title	ReactNode   () => ReactNode	-	5.1.0
onCancel	A callback of cancel	function(e)	-	
onConfirm	A callback of confirmation	function(e)	-	
onPopupClick	A callback of popup click	function(e)	-	5.5.0

# 404

The requested path could not be found

## Semantic DOM

演示

```
import React from 'react';
import { Popconfirm } from 'antd';

import SemanticPreview from '../../../dumi/components/SemanticPreview';
import useLocale from '../../../dumi/hooks/useLocale';

const locales = {
  cn: {
    root: '根元素（包含箭头、内容元素）',
    body: '内容元素',
  },
  en: {
    root: 'Root element (including arrows, content elements)',
    body: 'Body element',
  },
};

const BlockList: React.FC<React.PropsWithChildren> = (props: any) => {
  const divRef = React.useRef<HTMLDivElement>(null);

  return (
```

```

<div ref={divRef} style={{ position: 'absolute', marginTop: 60 }}>
  <Popconfirm
    title="prompt text"
    open
    placement="top"
    autoAdjustOverflow={false}
    getPopupContainer={() => divRef.current}
    {...props}
  />
</div>
);
};

const App: React.FC = () => {
  const [locale] = useLocale(locales);
  return (
    <SemanticPreview
      componentName="Popconfirm"
      semantics={[
        { name: 'root', desc: locale.root, version: '5.23.0' },
        { name: 'body', desc: locale.body, version: '5.23.0' },
      ]}
    >
      <BlockList />
    </SemanticPreview>
  );
};

export default App;

```

## Design Token

## FAQ

# 404

The requested path could not be found

For more questions, please refer to [Tooltip FAQ](#).