```
/* Name-Antara Mangle
  /PRN-25070521199/
  SECTION-D-I
  Value Added Problem-1 */
#include <stdio.h>
#include <stdlib.h>
struct Node {
   int data;
   struct Node* left;
   struct Node* right;
};
struct Node* createNode(int data) {
   struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
   newNode->data = data;
   newNode->left = newNode->right = NULL;
   return newNode;
}
struct Node* insert(struct Node* root, int data) {
   if (root == NULL)
      return createNode(data);
      if (data < root->data)
      root->left = insert(root->left, data);
   else
      root->right = insert(root->right, data);

   return root;
}
void printInRange(struct Node* root, int low, int high) {
   if (root == NULL)
```

```
        return;

    if (root->data > low)
        printInRange(root->left, low, high);

    if (root->data >= low && root->data <= high)
        printf("%d ", root->data);

    if (root->data < high)
        printInRange(root->right, low, high);
}
int main() {
    struct Node* root = NULL;
    printf("Name :Antara Mangle \n");
    printf("PRN :25070521199\n");
    printf("Section :D-1\n");
    printf("Value Added Problem : 1\n");
    printf("---------------------------\n");

    root = insert(root, 17);
    insert(root, 4);
    insert(root, 18);
    insert(root, 2);
    insert(root, 9);
    int low = 4, high = 24;
    printf("Output: ");
    printInRange(root, low, high);

    return 0;
```

}

main.c

Run

```c
/* Name-Antara Mangle
   /PRN-25070521199/
   SECTION-D-I
   Value Added Problem-1 */
#include <stdio.h>
#include <stdlib.h>
struct Node {
    int data;
    struct Node* left;
    struct Node* right;
```

Output

Clear

```
Name :Antara Mangle
PRN :25070521199
Section :D-1
Value Added Problem : 1
---------------------------
Output: 4 9 17 18

=== Code Execution Successful ===
```