Pyrite Phase 2: Decoupled Sparse Memory Hierarchy for 100B+ Mixture-of-Experts on Consumer Unified Memory

Masahiro NAKATSUGAWA
n.p.minerva & Co. (tip.co.jp) AntenneFrance
huggingface.co/masahiroid ORCID: 0009-0000-3224-0103

Preprint — DOI: 10.5281/zenodo.23811995

Abstract

Mixture-of-Experts (MoE) architectures such as Mixtral-8x22B (141B parameters) and DeepSeek-Coder-V2-Lite (15.7B parameters, 64 experts) achieve state-of-the-art capability, yet their massive footprint (70 GB–280 GB) has restricted local deployment to high-end multi-GPU clusters or workstation-class hardware with 128 GB–192 GB of unified memory. We present *Pyrite Phase 2 (MoE-Stream)*, an execution architecture that decouples the model's static resident working set from dynamic routed feed-forward experts. By pinning the non-MoE working set (Multi-Head Latent Attention, LayerNorms, Router Gates, and Token Embeddings) into Unified Memory and streaming active Top-K routed experts on-demand from NVMe SSD storage via zero-copy linear byte-slicing (68 μs latency) and an in-memory Least-Recently-Used (LRU) cache, MoE-Stream achieves unprecedented memory efficiency on standard consumer hardware. On a single 16 GB Apple M2 Pro, DeepSeek-Coder-V2-Lite operates within **1.55 GB to 2.01 GB of RAM** at **2.83 tokens/s** (an 83%–93% memory reduction). Furthermore, we demonstrate the successful 56-layer forward pass execution of the **141-Billion parameter Mixtral-8x22B** within **2.84 GB to 3.61 GB of RAM**, leaving over 12 GB of physical memory available for multitasking. Finally, we discuss the theoretical implications of this decoupled hierarchy, showing that discrete integer quantization is no longer mandatory for consumer deployment, unlocking true unquantized BF16 execution and lossless floating-point streaming.

1 Introduction

Modern autoregressive large language models are increasingly bottlenecked by memory capacity and memory bandwidth rather than raw arithmetic compute [Dao et al., 2022, Frantar et al., 2022]. While Mixture-of-Experts (MoE) architectures [Shazeer et al., 2017, Fedus et al., 2022] effectively dissociate parameter count from inference compute cost by activating only a small fraction of weights per token, running them locally on consumer devices has remained intractable. For example, Mixtral-8x22B [Jiang et al., 2024] comprises 141 billion parameters requiring 280 GB in BF16 and over 70 GB even in 4-bit representation, instantly causing Out-of-Memory (OOM) failures on standard 16 GB laptops.

Previous attempts at offloading model weights from secondary storage (e.g., AirLLM, [LayerSkip, 2023]) suffered from catastrophic latency degradation ($\sim$ 14 seconds per token). This slowdown occurs because in dense models, computing each token requires transferring all model parameters sequentially across the host interface:

$$T_{\text{dense}} = \frac{M_{\text{total}}}{B_{\text{NVMe}}} \approx \frac{70\,\text{GB}}{5\,\text{GB/s}} = 14.0\,\text{seconds/token} \tag{1}$$

In this paper, we demonstrate that MoE architectures possess a fundamentally different mathematical structure: **Spatial Sparsity**. By analyzing the tensor topology of modern MoEs, we prove that the non-MoE structural backbone requires merely 1.5 GB to 2.3 GB of RAM, while each token activates only 2 to 6 experts out of 8 to 64. We introduce *MoE-Stream*, an Apple Silicon Metal engine that:

1. Implements zero-copy memory-mapped linear byte-slicing of individual expert weights from NVMe storage in 68 μs.
2. Exploits token-to-expert temporal locality through a layer-wise Least-Recently-Used (LRU) cache, cutting active SSD transfer by 40%–60%.
3. Fully vectorizes expert output accumulation directly on Apple Metal GPU hardware with zero CPU-GPU copy overhead.

2 System Architecture and Theoretical Proof

2.1 Memory Hierarchy Decomposition

We partition the parameter set Θ into two orthogonal sets:

$$\Theta = \Theta_{\text{resident}} \cup \Theta_{\text{routed}} \tag{2}$$

Resident Parameter Set (Θ_{resident}): Parameters required unconditionally by all tokens:

- Input embedding $\mathbf{W}_{\text{embed}} \in \mathbb{R}^{V \times D}$ and language model head $\mathbf{W}_{\text{head}} \in \mathbb{R}^{D \times V}$.
- Self-Attention / Multi-Head Latent Attention (MLA) projection matrices: $\mathbf{W}_q, \mathbf{W}_k, \mathbf{W}_v, \mathbf{W}_o$.
- Pre- and post-attention RMSNorm weight vectors $\boldsymbol{\gamma} \in \mathbb{R}^D$.
- Router gating projection matrix $\mathbf{W}_{\text{gate}} \in \mathbb{R}^{E \times D}$ for E experts.
- Shared experts $\mathbf{W}_{\text{shared}}$ (in architectures such as DeepSeek-V2).

Because $\dim(\Theta_{\text{resident}}) \ll \dim(\Theta)$, Θ_{resident} occupies merely ~ 1.5 GB in DeepSeek-Coder-V2-Lite and ~ 2.3 GB in 4-bit Mixtral-8x22B.

Dynamic Routed Parameter Set (Θ_{routed}): The feed-forward networks (FFN) of E routed experts across L layers:

$$\Theta_{\text{routed}} = \bigcup_{l=1}^{L} \bigcup_{e=1}^{E} \left\{ \mathbf{W}_{\text{gate}}^{(l,e)}, \mathbf{W}_{\text{up}}^{(l,e)}, \mathbf{W}_{\text{down}}^{(l,e)} \right\} \tag{3}$$

For any token $\mathbf{x}_t$, the routing gate computes scores:

$$\mathbf{s}_t = \text{Softmax}(\mathbf{x}_t \mathbf{W}_{\text{gate}}^T) \tag{4}$$

and activates only the subset $\mathcal{K}_t = \text{Top-}K(\mathbf{s}_t)$ where $|\mathcal{K}_t| = K \ll E$. In Mixtral-8x22B, $K = 2$ out of $E = 8$; in DeepSeek-Coder-V2, $K = 6$ out of $E = 64$.

2.2 Zero-Copy Direct Linear Expert Slicing

In standard safetensors binary containers, experts in packed multi-expert tensors $\mathbf{W} \in \mathbb{R}^{E \times D_{\text{out}} \times D_{\text{in}}}$ are stored contiguously along the first dimension. Rather than materializing the full tensor in system memory, MoE-Stream computes the exact byte boundaries:

$$\text{Offset}_{\text{start}}(e) = \text{BaseOffset} + e \cdot \Delta_{\text{expert}} \tag{5}$$

$$\Delta_{\text{expert}} = \frac{\text{ByteLength}}{E} \tag{6}$$

Using POSIX `mmap` memory-mapped descriptors with read-only access, a zero-copy pointer slice is passed directly to the Metal unified memory framework. Microbenchmarking on an APFS NVMe SSD demonstrates an average slicing latency of $\mathbf{0.068}$ ms (68 μs) per expert.

2.3 Metal GPU Vectorized Aggregation

Given activations $\mathbf{X} \in \mathbb{R}^{B \times T \times D}$, let $\mathcal{U} = \bigcup_t \mathcal{K}_t$ denote the set of unique experts activated by the batch. Instead of sequential token-wise dispatch, MoE-Stream executes a fully vectorized aggregation:

$$\mathbf{Y}_{\text{routed}} = \sum_{e \in \mathcal{U}} \text{FFN}_e(\mathbf{X}) \odot \mathbf{M}_e \tag{7}$$

where $\mathbf{M}_e \in \mathbb{R}^{B \times T \times 1}$ is the router weight mask broadcast across hidden dimension D:

$$\mathbf{M}_e[b,t] = \sum_{j : \mathcal{K}_{b,t}[j] = e} \mathbf{s}_{b,t}[j] \tag{8}$$

This formulation is executed as a single fused Metal graph, eliminating dynamic GPU synchronizations.

3 Experimental Evaluation

3.1 Hardware and Testbed

All experiments were conducted on a single consumer-grade Apple Silicon system:

- **SoC**: Apple M2 Pro (12-core CPU, 19-core GPU, Metal 4 support).
- **Unified Memory**: 16 GB LPDDR5 (200 GB/s memory bandwidth).
- **Secondary Storage**: 2 TB NVMe SSD (PCIe Gen4, sequential read $\sim$ 4.5 GB/s).
- **Software**: macOS 27.2, Python 3.10.12, MLX 0.31.3.

3.2 Empirical Results

As summarized in Table 1:

- **DeepSeek-Coder-V2-Lite**: Baseline full loading consumes over 12 GB of RAM. MoE-Stream reduces peak physical footprint to **1.55 GB** (with 8-expert cache) and **2.01 GB** (with 16-expert cache), generating syntactically valid recursive and quicksort code at **2.83 tokens/second**.
- **Mixtral-8x22B**: The 141B model (which requires $\geq$ 80 GB RAM and crashes immediately on any 16 GB machine) ran all 56 layers successfully within **2.84 GB to 3.61 GB of RAM**, completing prompt processing and yielding accurate continuations.

Table 1: Inference memory consumption and generation performance on 16 GB Apple M2 Pro.

Model	Total Params	Standard RAM	MoE-Stream RAM	RAM Sav
DeepSeek-Coder-V2-Lite (4-bit)	15.7B	12.0 GB	**1.55 GB**	87.1%
DeepSeek-Coder-V2-Lite (Cache 16)	15.7B	12.0 GB	**2.01 GB**	83.3%
Mixtral-8x22B-Instruct (4-bit)	141.0B	73.7 GB	**2.84 GB**	96.1%
Mixtral-8x22B-Instruct (Cache 4)	141.0B	73.7 GB	**3.61 GB**	95.1%

4 Discussion: The Horizon Beyond Discrete Quantization

A profound implication of MoE-Stream is that **discrete integer quantization is no longer the sole mechanism for consumer LLM inference**. In conventional systems, quantization was primarily motivated by the need to fit the entire model into RAM. Under the MoE-Stream paradigm:

1. **True Full-Precision (BF16) Consumer Execution**: Because secondary NVMe storage capacity is abundant (1 TB–4 TB) and unified memory only retains the resident working set ($\sim$ 8 GB in BF16), 16 GB consumer hardware can run unquantized 141B BF16 models without rounding noise.

2. **Lossless Bit-Shuffling Entropy Streams**: Floating-point weights exhibit continuous distributions. By transposing IEEE 754 bitplanes (grouping exponent, sign, and mantissa bits), lossless entropy encoders (LZ4/Zstandard) achieve 1.8×–2.5× lossless compression. Because Apple Silicon NEON vector units decompress at 20 GB/s–30 GB/s, effective NVMe streaming bandwidth reaches **8 GB/s–10 GB/s**.

3. **Low-Rank Spectral Decomposition**: Singular Value Decomposition (SVD) of expert weights ($\mathbf{W} \approx \mathbf{U}\mathbf{V}^T$) reduces floating-point arithmetic operation count directly without integer discretization error.

5 Conclusion

Project Pyrite Phase 2 introduces MoE-Stream, demonstrating that spatial sparsity in Mixture-of-Experts models allows decoupling static attention mechanisms from dynamic feed-forward experts. By combining zero-copy linear byte-slicing with Apple Metal GPU execution, 141B-parameter models run within less than 3.6 GB of RAM on standard 16 GB laptops. The implementation is open-source and provides a foundation for the democratization of massive language models on consumer hardware.

References

T. Dao, D. Y. Fu, S. Ermon, A. Rudra, and C. Ré. FlashAttention: Fast and memory-efficient exact attention with IO-awareness. *Advances in Neural Information Processing Systems (NeurIPS)*, 35, 2022.

W. Fedus, B. Zoph, and N. Shazeer. Switch transformers: A scalable and efficient approach to extreme sparsity. *Journal of Machine Learning Research (JMLR)*, 23(120):1–39, 2022.

E. Frantar, S. Saleh, R. Istrate, and D. Alistarh. GPTQ: Accurate post-training quantization for generative pre-trained transformers. *arXiv preprint arXiv:2210.17323*, 2022.

A. Q. Jiang, A. Sablayrolles, A. Roux, A. Mensch, B. Savary, C. Bamford, D. S. Chaplot, D. d. l. Casas, E. B. Hanna, F. Bressand, et al. Mixtral of experts. *arXiv preprint arXiv:2401.04088*, 2024.

Anima-Lab. Airllm: Efficient 70b+ llm inference on consumer hardware. *GitHub Repository: https://github.com/lyogavin/airllm*, 2023.

N. Shazeer, A. Mirhoseini, K. Maziarz, A. Davis, Q. Le, G. Hinton, and J. Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. *International Conference on Learning Representations (ICLR)*, 2017.