REGENERATIVE BLOWER · SINGLE STAGE

Single-stage regenerative blower.

Oil-free side channel blower for vacuum or pressure, direct-driven by a 50/60 Hz motor.



Vacuum or pressure · Continuous duty

100 m³/h	2.3 psi	−2.2 psi	0.28–0.5 kW	56 dB(A)	9–11 kg
59 CFM	0.16 bar	−0.15 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT

Values at 60 Hz

TECHNICAL DATA

CONFIGURATION	USE	MOTOR	AMBIENT / INLET
Single stage	Vacuum pump or compressor	50/60 Hz, class F, IP55	−25 to 40 °C

MODELS · 60 Hz

TYPE	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRC0080-1MT250-6	0.28	220-275 Δ / 380-480 Y	2.0 Δ / 1.15 Y	100 m³/h 59 CFM	−1.5 psi −0.10 bar	1.5 psi 0.10 bar	56	9
STRC0080-1MA370-1	0.43	230	3	100 m³/h 59 CFM	−1.9 psi −0.13 bar	2.0 psi 0.14 bar	56	11
STRC0080-1MT400-6	0.5	220-275 Δ / 380-480 Y	2.6 Δ / 1.5 Y	100 m³/h 59 CFM	−2.2 psi −0.15 bar	2.3 psi 0.16 bar	56	10

50 Hz data and other voltages on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.


PERFORMANCE CURVES

FLOW VS PRESSURE

← VACUUM

60 Hz ---- 50 Hz

COMPRESSION →




POWER VS PRESSURE

← VACUUM

60 Hz ---- 50 Hz


COMPRESSION →



Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.

DIMENSIONS

All dimensions in mm



Type	A	B	C	D	E	F	G	H	J	K	L	M	N	O	P	Q	ϕR	S	U	V	V'	Y_Z	X-Holes	ϕX
STRC0080-1MT250-6	246	247	90	205	230	219	92	128	111	83	108	75	71	39	G 1 1/4"	64	10	2.5	M6 × 17	M25 × 1.5	M16 × 1.5	M6 × 15	0/120°/240°	140
STRC0080-1MA370-1	246	247	90	205	230	256	135	128	111	83	108	75	71	39	G 1 1/4"	64	10	2.5	M6 × 17	M16 × 1.5	M25 × 1.5	M6 × 15	0/120°/240°	140
STRC0080-1MT400-6	246	247	90	205	230	256	135	128	111	83	108	75	71	39	G 1 1/4"	64	10	2.5	M6 × 17	M25 × 1.5	M16 × 1.5	M6 × 15	0/120°/240°	140

Let's size your blower.

Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com