REGENERATIVE BLOWER · 2 STAGES IN PARALLEL

Double-flow regenerative blower.

Two impellers in parallel for twice the flow. Oil-free, direct-driven.

Vacuum or pressure · Continuous duty



595 m³/h	4.4 psi	−3.9 psi	4.6–8.6 kW	78 dB(A)	54–75 kg
350 CFM	0.30 bar	−0.27 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT

Values at 60 Hz

TECHNICAL DATA

CONFIGURATION	USE	MOTOR	AMBIENT / INLET
2 stages, parallel	Vacuum pump or compressor	50/60 Hz, class F, IP55	−25 to 40 °C

MODELS · 60 Hz

TYPE	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRC0495-2PT401-7	4.6	380-480 Δ / 660-720 Y	9.0 Δ / 5.2 Y	595 m³/h 350 CFM	−1.5 psi −0.10 bar	1.3 psi 0.09 bar	78	54
STRC0495-2PT551-7	6.3	380-480 Δ / 660-720 Y	13.3 Δ / 7.7 Y	595 m³/h 350 CFM	−3.0 psi −0.21 bar	2.9 psi 0.20 bar	78	69
STRC0495-2PT751-7	8.6	380-480 Δ / 660-720 Y	17.3 Δ / 10.0 Y	595 m³/h 350 CFM	−3.9 psi −0.27 bar	4.4 psi 0.30 bar	78	75

50 Hz data and other voltages on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.


PERFORMANCE CURVES

FLOW VS PRESSURE

← VACUUM

60 Hz ---- 50 Hz

COMPRESSION →




POWER VS PRESSURE

← VACUUM

60 Hz ---- 50 Hz


COMPRESSION →



Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.

DIMENSIONS

All dimensions in mm



Type	A	B	C	C'	D	E	F	G	H	J	K	L	M	N	O	P	Q	ϕR	S	U	V	ϕX	YxZ	X-Holes
STRC0495-2PT401-7	420	468	125	-	290	325	526	209	257	148	140	180	84	205	114	G 2"	83	15	64.5	M8 × 17	4 x M32 × 1.5	240	M10 × 06	0/120°/240°
STRC0495-2PT551-7	420	468	-	308	290	325	571	226	257	148	140	180	225	205	114	G 2"	83	15	64.5	M8 × 17	4 x M32 × 1.5	240	M10 × 06	0/120°/240°
STRC0495-2PT751-7	420	468	-	308	290	325	571	226	257	148	140	180	225	205	114	G 2"	83	15	64.5	M8 × 17	4 x M32 × 1.5	240	M10 × 06	0/120°/240°

Let's size your blower.

Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com