HIGH-PERFORMANCE BLOWER · 2 STAGES IN SERIES

High-performance regenerative blower.

Higher pressure and vacuum in a compact package. Oil-free, direct-driven by a 50/60 Hz motor.

Vacuum or pressure · Continuous duty



145 m³/h	11.7 psi	−7.7 psi	2.55–4.6 kW	71 dB(A)	40–51 kg
85 CFM	0.81 bar	−0.53 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT

Values at 60 Hz

TECHNICAL DATA

CONFIGURATION	USE	MOTOR	AMBIENT / INLET
2 stages, series	Vacuum pump or compressor	50/60 Hz, class F, IP55	−25 to 40 °C


MODELS · 60 Hz

TYPE	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRP0120-2ST221-6	2.55	220-275 Δ / 380-480 Y	Δ 11.2 / Y 6.5	145 m³/h 85 CFM	−7.3 psi −0.50 bar	6.5 psi 0.45 bar	70	40
STRP0120-2ST401-7	4.6	380-480 Δ / 660-720 Y	Δ 9.5 / Y 4.5	145 m³/h 85 CFM	−7.7 psi −0.53 bar	11.7 psi 0.81 bar	71	51


50 Hz data and other voltages on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.

PERFORMANCE CURVES

FLOW VS PRESSURE




POWER VS PRESSURE



Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.

DIMENSIONS

All dimensions in mm



Type	A	B	B'	C2	D	E	F	G	H	H1	J	K	M	N	O	P
STRP0120-2ST221-6	387	402	435	57	328	363	549	185	206	343	128	152	453	256	148	G1 ¼"
STRP0120-2ST401-7	387	402	435	57	328	363	603	211	206	343	148	152	453	256	148	G1 ¼"

Type	Q	ØR	S1	S2	S3	T	T1	U	V	V1	W
STRP0120-2ST221-6	64	14	4	140	31	137	138	M6 × 17	M25 × 1.5	M16 × 1.5	42
STRP0120-2ST401-7	64	14	4	140	31	137	138	M6 × 17	2 X M32 × 1.5	M16 × 1.5	32

Let's size your blower.
Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com