HIGH-PERFORMANCE BLOWER · 2 STAGES IN SERIES

High-performance regenerative blower.

Higher pressure and vacuum in a compact package. Oil-free, direct-driven by a 50/60 Hz motor.

Vacuum or pressure · Continuous duty



76 m³/h	8.7 psi	−8.1 psi	1.3–1.75 kW	63 dB(A)	29–32 kg
45 CFM	0.60 bar	−0.56 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT

Values at 60 Hz


CONFIGURATION	USE	MOTOR	AMBIENT / INLET
2 stages, series	Vacuum pump or compressor	50/60 Hz, class F, IP55	−25 to 40 °C

PERFORMANCE CURVES

FLOW VS PRESSURE

← VACUUM


60 Hz ---- 50 Hz
COMPRESSION →



POWER VS PRESSURE

← VACUUM


60 Hz ---- 50 Hz
COMPRESSION →



TEMPERATURE RISE VS PRESSURE

← VACUUM

60 Hz ---- 50 Hz
COMPRESSION →



Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.


MODELS · 60 Hz


TYPE	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRP0065-2ST111-6	1.3	220-275 Δ / 380-480 Y	Δ 5.4 / Y 3.1	76 m³/h 45 CFM	−7.0 psi −0.48 bar	7.0 psi 0.48 bar	63	29
STRP0065-2SA151-1	1.75	230	10.3	76 m³/h 45 CFM	−5.7 psi −0.39 bar	7.8 psi 0.54 bar	63	32
STRP0065-2ST151-6	1.75	220-275 Δ / 380-480 Y	Δ 7.6 / Y 4.4	76 m³/h 45 CFM	−8.1 psi −0.56 bar	8.7 psi 0.60 bar	63	30

50 Hz data and other voltages on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.

DIMENSIONS

All dimensions in mm





Type	A	B	B′	C2	D	E	F	G	H	H1	J	K	M	N	O	P
STRP0065-2ST111-6	331	345	380	47	290	325	390	153	177	291	120	105	431	243	130	G1 ¼″
STRP0065-2SA151-1	331	345	380	47	290	325	421	185	177	291	128	105	431	243	130	G1 ¼″
STRP0065-2ST151-6	331	345	380	47	290	325	421	185	177	291	128	105	431	243	130	G1 ¼″

Type	Q	ØR	S1	S2	S3	T	T1	U	V	V1	W
STRP0065-2ST111-6	64	14	4	140	31	114	116	M6 × 17	M25 × 1.5	M16 × 1.5	32
STRP0065-2SA151-1	64	14	4	140	31	114	116	M6 × 17	M25 × 1.5	M25 × 1.5	32
STRP0065-2ST151-6	64	14	4	140	31	114	116	M6 × 17	M25 × 1.5	M16 × 1.5	32

Let's size your blower.
Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com