

STRC0270-1M: Single stage Side Channel Blower




- Maintenance free. Oil free compression
- 50/60 Hz motors, insulation class F. IP55 protection rating. Thermal protection as standard
- Frequency converter operation allowed
- Customization

Suction







Curves are valid for continuous operation; medium: air at 15°C, measured at inlet port and 1013 hPa (mbar abs.) atmospheric backpressure, Tolerance: ± 10%; ambient temperature: -20° to +40°C

Compression

Curves are valid for continuous operation; medium: air at 15°C, measured at inlet port and 1013 hPa (mbar abs.) atmospheric pressure, Tolerance: ± 10%; ambient temperature: -20° to +40°C

Tel: +1 438-880-4655

STRC0270-1M: Single stage Side Channel Blower

Technical data

Type	kW	Hz	V[1)]	A	m³/h	hPa (mbar)[2)]	dB(A)[3)]	kg
STRC0270-1MT131-6	1,3	50	200-240 Δ / 345-415 Y	5,7 Δ / 3,3 Y	270	-100 / 100	65	23
	1,5	60	220-275 Δ / 380-480 Y	5,7 Δ / 3,3 Y	325	-70 / 50	71	
STRC0270-1MA151-1	1,5	50	230	9,5	270	-140 / 120	65	26
	1,75	60	230	10	325	-110 / 100	71	
STRC0270-1MT161-6	1,6	50	200-240 Δ / 345-415 Y	7,5 Δ / 4,3 Y	270	-150 / 150	65	24
	2,05	60	220-275 Δ / 380-480 Y	7,6 Δ / 4,4 Y	325	-150 / 130	71	
STRC0270-1MT221-6	2,2	50	200-240 Δ / 345-415 Y	9,7 Δ / 5,6 Y	270	-220 / 230	65	26
	2,55	60	220-275 Δ / 380-480 Y	9,0 Δ / 5,3 Y	325	-230 / 210	71	

1) Other voltages are available on request

2) Relief valves are available for limiting differential pressure

3) Noise level measured acc. to EN ISO 3744 at a distance of 1 m with hoses connected

Ambient temperature: -25°… 40°C


Inlet temperature: -25°… 40°C


Max. installation height: 1000 m


Bimetal motor protection

Type	Hz	V
STRC ….-..T...-1	50	185-225 Δ / 320-390 Y
	60	200-240 Δ / 345-415 Y
STRC ….-..T...-5	50	500 Δ
	60	575 Δ
STRC ….-..T...-6	50	200-240 Δ / 345-415 Y
	60	220-275 Δ / 380-480 Y
STRC ….-..T...-7	50	345-415 Δ / 600-720 Y
	60	380-480 Δ / 660-720 Y
STRC ….-..A...-1	50	230
	60	230
STRC ….-..S...-5	50	115/230
	60	115/230

Dimensions







Type	A	B	C	D	E	F	G	H	J	K	L	M	N	O	P	Q	ϕR	S	U	V	V'	Y_Z	X-Holes	ϕX	W
STRC0270-1MT131-6	334	337	120	260	295	334	156	175	120	115	155	96	87	48	G 2"	83	14	4	M8 x 17	M25 x 1,5	M16 x 1,5	M8 x 20	0/120º/240º	200	29
STRC0270-1MA151-1	334	337	120	260	295	365	191	175	128	115	155	96	87	48	G 2"	83	14	4	M8 x 17	M25 x 1,5	M16 x 1,5	M8 x 20	0/120º/240º	200	29
STRC0270-1MT161-6	334	337	120	260	295	365	191	175	128	115	155	96	87	48	G 2"	83	14	4	M8 x 17	M25 x 1,5	M16 x 1,5	M8 x 20	0/120º/240º	200	29
STRC0270-1MT221-6	334	337	120	260	295	365	191	175	128	115	155	96	87	48	G 2"	83	14	4	M8 x 17	M25 x 1,5	M16 x 1,5	M8 x 20	0/120º/240º	200	29