

STRP0120-3S: Triple stage High Performance Blower




- Maintenance free. Oil free compression
- 50/60 Hz motors, insulation class F. IP55 protection rating. Thermal protection as standard
- Frequency converter operation allowed
- Customization

Suction










Curves are valid for continuous operation; medium: air at 15°C, measured at inlet port and 1013 hPa (mbar abs.) atmospheric backpressure, Tolerance: ± 10%; ambient temperature: -20° to +40°C

Compression







Curves are valid for continuous operation; medium: air at 15°C, measured at inlet port and 1013 hPa (mbar abs.) atmospheric pressure, Tolerance: ± 10%; ambient temperature: -20° to +40°C

STRP0120-3S: Triple stage High Performance Blower

Technical data

Type	kW	Hz	V[1)]	A	m³/h	hPa (mbar)[2)]	dB(A)[3)]	kg
STRP0120-3ST401-7	4	50	345-415 Δ / 600-720 Y	Δ 9,0 / Y 4,4	122	-680 / 820	67	62
	4.6	60	380-480 Δ / 660-720 Y	Δ 9,5 / Y 4,5	147	-640 / 730	73	
STRP0120-3ST551-7	5.5	50	345-415 Δ / 600-720 Y	Δ 13.3 / Y 7.7	122	-680 / 1000	67	68
	6.3	60	380-480 Δ / 660-720 Y	Δ 13.3 / Y 7.7	147	-640 / 1030	73	

1) Other voltages are available on request

2) Relief valves are available for limiting differential pressure

3) Noise level measured acc. to EN ISO 3744 at a distance of 1 m with hoses connected

Ambient temperature: -25°… 40°C


Inlet temperature: -25°… 40°C

Max. installation height: 1000 m

Bimetal motor protection

Type	Hz	V
STRP ….-..T...-1	50	185-225 Δ / 320-390 Y
	60	200-240 Δ / 345-415 Y
STRP ….-..T...-5	50	500 Δ
	60	575 Δ
STRP ….-..T...-6	50	200-240 Δ / 345-415 Y
	60	220-275 Δ / 380-480 Y
STRP ….-..T...-7	50	345-415 Δ / 600-720 Y
	60	380-480 Δ / 660-720 Y
STRP ….-..A...-1	50	230
	60	230
STRP ….-..S...-5	50	115/230
	60	115/230

Dimensions



Type	A	B	B'	C2	D	E	F	G	H	H1	J	K	M	N	O	P
STRP0120-3ST401-7	387	402	432	57	328	363	682	252	206	344	148	152	532	333	149	G1 ¼"
STRP0120-3ST551-7	442	402	432	63	371	406	717	274	236	389	148	152	539	336	172	G1 ¼"

Type	Q	ØR	S1	S2	T	U	V	W1	W2
STRP0120-3ST401-7	64	14	5	143	137	M6 x 17	M32 x 1,5	42	120
STRP0120-3ST551-7	64	14	5	146	153	M6 x 17	M32 x 1,5	42	120

Tel: +1 438-880-4655