

REGENERATIVE BLOWER BOOSTER · 2:1

The first **leak-tight** electric air booster.

All the pressure of a piston booster, without the oil, the rings, the valves or the rebuilds.

Compressed air · Nitrogen · Other process gases



2:1

PRESSURE RATIO

400 psig

MAX. PRESSURE

35 SCFM

CONTINUOUS FLOW

15,000 RPM

HIGH-SPEED DESIGN

0 oil

100% OIL-FREE

THE PROBLEM WITH PISTON BOOSTERS

Electric piston boosters do the job, but they are built like small reciprocating compressors: **crankshaft, connecting rods, pistons, rings, valves and an oil sump.**

Every one of those parts rubs or cycles, so they wear. That means oil changes, valve and ring rebuilds, downtime, and a constant **risk of oil carry-over** into your air or nitrogen.

They are also heavy and bulky, which usually means a dedicated room or skid instead of installing at the point of use.

OUR ANSWER

Our booster is a high-speed **regenerative blower**. No piston, no ring, no valve, no oil. Nothing rubs inside the gas path.

TYPICAL PISTON BOOSTER

Crankshaft Connecting rods Pistons
Piston rings Valves Oil sump
Several bearings

Oil changes, rebuilds, oil carry-over risk

ID ELECTRIC BOOSTER

1 motor 1 shaft 2 impellers 2 bearings

Oil-free, nothing rubs, bearings every 2.5 to 3 years

RADICALLY SIMPLE BY DESIGN

A two-stage regenerative blower: one electric motor, one shaft, two impellers, two bearings. That's the whole machine. Running at up to **15,000 RPM**, it is far more compact and lighter than a piston booster of similar capacity.

1

Electric motor

1

Shaft

2

Impellers

2

Bearings

INLET
100 psig



OUTLET
200 psig

INLET
200 psig



OUTLET
400 psig

Need more?
Install in series.

WHY SWITCH FROM A PISTON BOOSTER

100% oil-free

No oil sump, no carry-over, no oil changes.

Almost no maintenance

No rings or valves to rebuild. Bearings every 2.5 to 3 years.

More flow per kW

35 SCFM from 2.6 kW, about 15% better than a typical 3 hp piston unit.

Up to 400 psig

Higher pressure and flow in the same power class.

Compact and light

15,000 RPM design. Install it right at the machine.

Runs 24/7

Built for continuous duty at full flow.

ID BOOSTER VS. ELECTRIC PISTON BOOSTERS

	ID ELECTRIC	PISTON, ~3 HP
Pressure / flow	400 psig / 35 SCFM	~360 psi / ~25 cfm
Power per unit of flow	~0.074 kW/SCFM	~0.088 kW/cfm
Oil in the machine	None	Oil sump
Rubbing wear parts	None	Rings, valves, rods
Routine maintenance	Bearings, 2.5 to 3 yrs	Oil, valves, rings

APPROX. PAYBACK VS. PISTON BOOSTER*

Day 1

Lower purchase price
 Lower yearly maintenance
 More pressure and flow for the power

* Approximate, compared with a typical ~3 hp oil-lubricated piston booster at list price. Actual results depend on your site.

TECHNICAL DATA

MODEL IDSC-2SHP-166-400

PRESSURE RATIO 2:1	MAX. PRESSURE 400 psig	MAX. FLOW 35 SCFM	SPEED 15,000 RPM
MOTOR POWER 2.6 kW (3.5 hp)	POWER SUPPLY 120/230 V, 1-phase 230 V, 3-phase	CONNECTION PORTS 1.25" MNPT	MEDIA Air, N₂, other gases
GAS PATH Oil-free, leak-tight	DUTY Continuous, 24/7	BEARING SERVICE 2.5 to 3 years	TECHNOLOGY Regenerative, 2-stage

Explosion-proof motors, other voltages and coatings available on request.

Let's size your booster.

Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com

PHONE +1 438-880-4655

WEB id-industries.com