




- Maintenance free. Oil free compression
- 50/60 Hz motors, insulation class F. IP55 protection rating. Thermal protection as standard
- Frequency converter operation allowed
- Customization

--- 60 Hz
— 50 Hz

Suction

Compression

--- 60 Hz
— 50 Hz



Curves are valid for continuous operation; medium: air at 15°C, measured at inlet port and 1013 hPa (mbar abs.) atmospheric backpressure, Tolerance: ± 10%; ambient temperature: -20° to +40°C

Curves are valid for continuous operation; medium: air at 15°C, measured at inlet port and 1013 hPa (mbar abs.) atmospheric pressure, Tolerance: ± 10%; ambient temperature: -20° to +40°C

Technical data

Type	kW	Hz	V ¹⁾	A	m³/h	hPa (mbar) ²⁾	dB(A) ³⁾	kg
STRC0055-1MA120-1	0,12	50	230	1,2	55	-60 / 60	46	5
	0,14	60	230	1,3	68	-60 / 60	48	
STRC0055-1MA200-1	0,2	50	230	1,5	55	-70 / 80	46	6
	0,23	60	230	1,6	68	-90 / 100	48	
STRC0055-1MT200-6	0,2	50	200-240 Δ / 345-415 Y	1,75 Δ / 1,0 Y	55	-80 / 90	46	5
	0,23	60	220-275 Δ / 380-480 Y	1,75 Δ / 1,0 Y	68	-110 / 120	48	

1) Other voltages are available on request

2) Relief valves are available for limiting differential pressure

3) Noise level measured acc. to EN ISO 3744 at a distance of 1 m with hoses connected

Ambient temperature: -25°... 40°C


Inlet temperature: -25°... 40°C

Max. installation height: 1000 m

Bimetal motor protection

Type	Hz	V
STRCT....-1	50	185-225 Δ / 320-390 Y
	60	200-240 Δ / 345-415 Y
STRCT....-5	50	500 Δ
	60	575 Δ
STRCT....-6	50	200-240 Δ / 345-415 Y
	60	220-275 Δ / 380-480 Y
STRCT....-7	50	345-415 Δ / 600-720 Y
	60	380-480 Δ / 660-720 Y
STRCA....-1	50	230
	60	230
STRCS....-5	50	115/230
	60	115/230

Dimensions



Type	A	B	C	D	E	F	G	H	J	K	L	M	N	O
STRC0055-1MA120-1	190	203	72	155	172	242	124	102	101	80	101	108	53	30
STRC0055-1MA200-1	190	203	72	155	172	242	124	102	101	80	101	108	53	30
STRC0055-1MT200-6	190	203	72	155	172	242	124	102	101	80	101	108	53	30
Type	P	Q	φR	S	U	V	Y_Z	X-Holes	φX					
STRC0055-1MA120-1	G 1"	46	8,5	2	M6 x 18	M16 x 1,5	M6 x 20	0/120º/240º	115					
STRC0055-1MA200-1	G 1"	46	8,5	2	M6 x 18	M16 x 1,5	M6 x 20	0/120º/240º	115					
STRC0055-1MT200-6	G 1"	46	8,5	2	M6 x 18	M16 x 1,5	M6 x 20	0/120º/240º	115					