
HIGH-PERFORMANCE BLOWER · SINGLE STAGE

High-performance regenerative blower.

Higher pressure and vacuum in a compact package. Oil-free, direct-driven by a 50/60 Hz motor.

Vacuum or pressure · Continuous duty



195 m³/h	7.7 psi	−5.5 psi	2.55–3.8 kW	71 dB(A)	32–35 kg
115 CFM	0.53 bar	−0.38 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT

Values at 60 Hz

TECHNICAL DATA

CONFIGURATION **Single stage**	COMPRESSION **Oil-free**	USE **Vacuum pump or compressor**	MOTOR **50/60 Hz, class F, IP55**
MOTOR PROTECTION **Thermal (bimetal), standard**	VARIABLE SPEED **Frequency converter allowed**	AMBIENT / INLET **−25 to 40 °C**	MAX. ALTITUDE **1000 m**

MODELS


TYPE	HZ	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRP0165-1MT221-6	50	2.2	200-240 Δ / 345-415 Y	Δ 11.4 / Y 6.6	165 m³/h 97 CFM	−4.9 psi −0.34 bar	5.2 psi 0.36 bar	65	32
	60	2.55	220-275 Δ / 380-480 Y	Δ 11.2 / Y 6.5	195 m³/h 115 CFM	−5.2 psi −0.36 bar	4.6 psi 0.32 bar	71	
STRP0165-1MT331-6	50	3.3	200-240 Δ / 345-415 Y	Δ 13.0 / Y 7.5	165 m³/h 97 CFM	−4.9 psi −0.34 bar	7.0 psi 0.48 bar	65	35
	60	3.8	220-275 Δ / 380-480 Y	Δ 14.2 / Y 8.2	195 m³/h 115 CFM	−5.5 psi −0.38 bar	7.7 psi 0.53 bar	71	

Other voltages available on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.


PERFORMANCE CURVES

Flow, power and temperature rise versus differential pressure, in vacuum and in compression.


FLOW VS PRESSURE



POWER VS PRESSURE



TEMPERATURE RISE VS PRESSURE




Every unit can be used as a vacuum pump or as a compressor, in continuous duty.

Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.

DIMENSIONS

All dimensions in mm



Type	A	B	B1	C	D	E	F	G	H	J	K	M	N	O	P
STRP0165-1MT221-6	418	455	39	127	371	406	364	185	235	128	152	271	72	172	G1 ¼"
STRP0165-1MT331-6	418	455	39	127	371	406	390	211	235	128	152	271	72	172	G1 ¼"

Type	Q	R	S1	S2	S3	T	T1	U	V	V1	W	X	Y	x	Z
STRP0165-1MT221-6	64	14	5	140	31	153	155	M6	X 17	M16 X 1.5	32	228	M8	X	15
STRP0165-1MT331-6	64	14	5	140	31	153	155	M6	X 17	M16 X 1.5	32	228	M8	X	15

Let's size your blower.

Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com

Technical changes reserved