HIGH-PERFORMANCE BLOWER · 3 STAGES IN SERIES

High-performance regenerative blower.

Higher pressure and vacuum in a compact package. Oil-free, direct-driven by a 50/60 Hz motor.

Vacuum or pressure · Continuous duty



200 m³/h	15.1 psi	−10.2 psi	8.6 kW	76 dB(A)	86 kg
118 CFM	1.04 bar	−0.70 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT

Values at 60 Hz

TECHNICAL DATA

CONFIGURATION **3 stages, series**	COMPRESSION **Oil-free**	USE **Vacuum pump or compressor**	MOTOR **50/60 Hz, class F, IP55**
MOTOR PROTECTION **Thermal (bimetal), standard**	VARIABLE SPEED **Frequency converter allowed**	AMBIENT / INLET **−25 to 40 °C**	MAX. ALTITUDE **1000 m**

MODELS


TYPE	HZ	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRP0165-3ST751-7	50	7.5	345-415 Δ / 600-720 Y	Δ 16.0 / Y 8.0	170 m³/h 100 CFM	−10.6 psi −0.73 bar	15.1 psi 1.04 bar	72	86
	60	8.6	380-480 Δ / 660-720 Y	Δ 16.0 / Y 8.0	200 m³/h 118 CFM	−10.2 psi −0.70 bar	15.1 psi 1.04 bar	76	

Other voltages available on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.


PERFORMANCE CURVES

Flow, power and temperature rise versus differential pressure, in vacuum and in compression.


FLOW VS PRESSURE



POWER VS PRESSURE



TEMPERATURE RISE VS PRESSURE





Every unit can be used as a vacuum pump or as a compressor, in continuous duty.

Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.

DIMENSIONS

All dimensions in mm





Type	A	B	B'	C2	D	E	F	G	H	H1	J	K	M	N	O	P
STRP0165-3ST751-7	442	402	492	63	371	406	717	274	236	389	167	152	539	336	172	G1 ¼"

Type	Q	ØR	S1	S2	T	U	V	W1	W2
STRP0165-3ST751-7	64	14	5	146	153	M6 × 17	M32 × 1.5	42	120

Let's size your blower.

Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com

Technical changes reserved