




- Maintenance free. Oil free compression
- 50/60 Hz motors, insulation class F. IP55 protection rating. Thermal protection as standard
- Frequency converter operation allowed
- Customization



Curves are valid for continuous operation; medium: air at 15°C, measured at inlet port and 1013 hPa (mbar abs.) atmospheric backpressure, Tolerance: ± 10%; ambient temperature: -20° to +40°C

Curves are valid for continuous operation; medium: air at 15°C, measured at inlet port and 1013 hPa (mbar abs.) atmospheric pressure, Tolerance: ± 10%; ambient temperature: -20° to +40°C

Technical data

Type	kW	Hz	V ¹⁾	A	m³/h	hPa (mbar) ²⁾	dB(A) ³⁾	kg
STRP0120-1MT151-6	1,5	50	200-240 Δ / 345-415 Y	Δ 7,5 / Y 4,3	120	-310 / 360	64	26
	1,75	60	220-275 Δ / 380-480 Y	Δ 7,6 / Y 4,4	145	-340 / 320	68	
STRP0120-1MT221-6	2,2	50	200-240 Δ / 345-415 Y	Δ 11,4 / Y 6,6	120	-310 / 470	64	29
	2,55	60	220-275 Δ / 380-480 Y	Δ 11,2 / Y 6,5	145	-360 / 480	68	

1) Other voltages are available on request

2) Relief valves are available for limiting differential pressure

3) Noise level measured acc. to EN ISO 3744 at a distance of 1 m with hoses connected

Ambient temperature: -25°... 40°C


Inlet temperature: -25°... 40°C

Max. installation height: 1000 m

Bimetal motor protection

Type	Hz	V
STRPT....-1	50	185-225 Δ / 320-390 Y
	60	200-240 Δ / 345-415 Y
STRPT....-5	50	500 Δ
	60	575 Δ
STRPT....-6	50	200-240 Δ / 345-415 Y
	60	220-275 Δ / 380-480 Y
STRPT....-7	50	345-415 Δ / 600-720 Y
	60	380-480 Δ / 660-720 Y
STRPA....-1	50	230
	60	230
STRPS....-5	50	115/230
	60	115/230

Dimensions



Type	A	B	B1	C	D	E	F	G	H	J	K	M	N	O	P
STRP0120-1MT151-6	368	395	39	114	328	363	361	185	205	128	152	265	68	148	G1 1/4"
STRP0120-1MT221-6	368	395	39	114	328	363	361	185	205	128	152	265	68	148	G1 1/4"
Type	Q	R	S1	S2	S3	T	T1	U	V	V1	W	X	Y x Z		
STRP0120-1MT151-6	64	14	4	140	31	137	138	M6 X 17		M16 X 1,5	32	192	M8 X 15		
STRP0120-1MT221-6	64	14	4	140	31	137	138	M6 X 17		M16 X 1,5	32	192	M8 X 15		