HIGH-PERFORMANCE BLOWER · 3 STAGES IN SERIES

High-performance regenerative blower.

Higher pressure and vacuum in a compact package. Oil-free, direct-driven by a 50/60 Hz motor.



Vacuum or pressure · Continuous duty

200 m³/h	15.1 psi	−10.2 psi	8.6 kW	76 dB(A)	86 kg
118 CFM	1.04 bar	−0.70 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT

Values at 60 Hz

CONFIGURATION	USE	MOTOR	AMBIENT / INLET
3 stages, series	Vacuum pump or compressor	50/60 Hz, class F, IP55	−25 to 40 °C


PERFORMANCE CURVES

FLOW VS PRESSURE

← VACUUM

60 Hz ---- 50 Hz

COMPRESSION →




POWER VS PRESSURE

← VACUUM

60 Hz ---- 50 Hz

COMPRESSION →




TEMPERATURE RISE VS PRESSURE

← VACUUM

60 Hz ---- 50 Hz

COMPRESSION →



Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.

MODELS · 60 Hz

TYPE	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRP0165-3ST751-7	8.6	380-480 Δ / 660-720 Y	Δ 16.0 / Y 8.0	200 m³/h 118 CFM	−10.2 psi −0.70 bar	15.1 psi 1.04 bar	76	86


50 Hz data and other voltages on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.

MOTOR CODES · AVAILABLE VOLTAGES

CODE	50 HZ (V)	60 HZ (V)
STRP ….-..T...-1	185-225 Δ / 320-390 Y	200-240 Δ / 345-415 Y
STRP ….-..T...-5	500 Δ	575 Δ
STRP ….-..T...-6	200-240 Δ / 345-415 Y	220-275 Δ / 380-480 Y
STRP ….-..T...-7	345-415 Δ / 600-720 Y	380-480 Δ / 660-720 Y
STRP ….-..A...-1	230	230
STRP ….-..S...-5	115/230	115/230

DIMENSIONS

All dimensions in mm



Type	A	B	B'	C2	D	E	F	G	H	H1	J	K	M	N	O	P
STRP0165-3ST751-7	442	402	492	63	371	406	717	274	236	389	167	152	539	336	172	G1 ¼"

Type	Q	ØR	S1	S2	T	U	V	W1	W2
STRP0165-3ST751-7	64	14	5	146	153	M6 × 17	M32 × 1.5	42	120

Let's size your blower.
Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com