REGENERATIVE BLOWER · SINGLE STAGE

Single-stage regenerative blower.

Oil-free side channel blower for vacuum or pressure, direct-driven by a 50/60 Hz motor.



Vacuum or pressure · Continuous duty


325 m³/h	3.0 psi	−3.3 psi	1.5–2.55 kW	71 dB(A)	23–26 kg
191 CFM	0.21 bar	−0.23 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT

Values at 60 Hz


CONFIGURATION	USE	MOTOR	AMBIENT / INLET
Single stage	Vacuum pump or compressor	50/60 Hz, class F, IP55	−25 to 40 °C

PERFORMANCE CURVES

FLOW VS PRESSURE



POWER VS PRESSURE



Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.


MODELS · 60 Hz


TYPE	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRC0270-1MT131-6	1.5	220-275 Δ / 380-480 Y	5.7 Δ / 3.3 Y	325 m³/h 191 CFM	−1.0 psi −0.07 bar	0.73 psi 0.05 bar	71	23
STRC0270-1MA151-1	1.75	230	10	325 m³/h 191 CFM	−1.6 psi −0.11 bar	1.5 psi 0.10 bar	71	26
STRC0270-1MT161-6	2.05	220-275 Δ / 380-480 Y	7.6 Δ / 4.4 Y	325 m³/h 191 CFM	−2.2 psi −0.15 bar	1.9 psi 0.13 bar	71	24
STRC0270-1MT221-6	2.55	220-275 Δ / 380-480 Y	9.0 Δ / 5.3 Y	325 m³/h 191 CFM	−3.3 psi −0.23 bar	3.0 psi 0.21 bar	71	26


50 Hz data and other voltages on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.

DIMENSIONS

All dimensions in mm







Type	A	B	C	D	E	F	G	H	J	K	L	M	N	O	P	Q	ϕR	S	U	V	V'	Y_Z	X-Holes	ϕX	W
STRC0270-1MT131-6	334	337	120	260	295	334	156	175	120	115	155	96	87	48	G 2"	83	14	4	M8 × 17	M25 × 1.5	M16 × 1.5	M8 × 20	0/120°/240°	200	29
STRC0270-1MA151-1	334	337	120	260	295	365	191	175	128	115	155	96	87	48	G 2"	83	14	4	M8 × 17	M25 × 1.5	M16 × 1.5	M8 × 20	0/120°/240°	200	29
STRC0270-1MT161-6	334	337	120	260	295	365	191	175	128	115	155	96	87	48	G 2"	83	14	4	M8 × 17	M25 × 1.5	M16 × 1.5	M8 × 20	0/120°/240°	200	29
STRC0270-1MT221-6	334	337	120	260	295	365	191	175	128	115	155	96	87	48	G 2"	83	14	4	M8 × 17	M25 × 1.5	M16 × 1.5	M8 × 20	0/120°/240°	200	29

Let's size your blower.
Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com