
HIGH-PERFORMANCE BLOWER · SINGLE STAGE

High-performance regenerative blower.

Higher pressure and vacuum in a compact package. Oil-free, direct-driven by a 50/60 Hz motor.

Vacuum or pressure · Continuous duty



105 m³/h	5.7 psi	−4.9 psi	1.3 kW	62 dB(A)	23 kg
62 CFM	0.39 bar	−0.34 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT


Values at 60 Hz

CONFIGURATION	USE	MOTOR	AMBIENT / INLET
Single stage	Vacuum pump or compressor	50/60 Hz, class F, IP55	−25 to 40 °C

PERFORMANCE CURVES


FLOW VS PRESSURE

← VACUUM COMPRESSION →



POWER VS PRESSURE

← VACUUM COMPRESSION →



Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.


MODELS · 60 Hz

TYPE	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRP0085-1MA111-1	1.3	230	10.3	105 m³/h 62 CFM	−4.9 psi −0.34 bar	5.7 psi 0.39 bar	62	23
STRP0085-1MT111-6	1.3	220-275 Δ / 380-480 Y	Δ 5.4 / Y 3.1	105 m³/h 62 CFM	−4.9 psi −0.34 bar	5.4 psi 0.37 bar	62	23

50 Hz data and other voltages on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.

DIMENSIONS

All dimensions in mm



Type	A	B	B1	C	D	E	F	G	H	J	K	M	N	O	P
STRP0085-1MA111-1	346	375	38	103	315	350	321	153	195	120	130	260	66	143	G1 ¼"
STRP0085-1MT111-6	346	375	38	103	315	350	321	153	195	120	130	260	66	143	G1 ¼"

Type	Q	R	S1	S2	S3	T	T1	U	V	V1	W	X	YxZ
STRP0085-1MA111-1	64	14	4	140	31	125	127	M6 X 17	–	M16 X 1.5	32	167	M6 X 15
STRP0085-1MT111-6	64	14	4	140	31	125	127	M6 X 17	–	M16 X 1.5	32	167	M6 X 15

Let's size your blower.
Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com