HIGH-PERFORMANCE BLOWER · 2 STAGES IN SERIES

High-performance regenerative blower.

Higher pressure and vacuum in a compact package. Oil-free, direct-driven by a 50/60 Hz motor.

Vacuum or pressure · Continuous duty




105 m³/h	12.3 psi	−7.4 psi	1.75–3.8 kW	66 dB(A)	33–39 kg
62 CFM	0.85 bar	−0.51 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT

Values at 60 Hz


CONFIGURATION	USE	MOTOR	AMBIENT / INLET
2 stages, series	Vacuum pump or compressor	50/60 Hz, class F, IP55	−25 to 40 °C

PERFORMANCE CURVES

FLOW VS PRESSURE



POWER VS PRESSURE



Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.


MODELS · 60 Hz


TYPE	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRP0085-2ST151-6	1.75	220-275 Δ / 380-480 Y	Δ 7.6 / Y 4.4	105 m³/h 62 CFM	−6.2 psi −0.43 bar	5.9 psi 0.41 bar	66	33
STRP0085-2ST331-6	3.8	220-275 Δ / 380-480 Y	Δ 13.8 / Y 8.0	105 m³/h 62 CFM	−7.4 psi −0.51 bar	12.3 psi 0.85 bar	66	39

50 Hz data and other voltages on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.

DIMENSIONS

All dimensions in mm





Type	A	B	B'	C2	D	E	F	G	H	H1	J	K	M	N	O	P
STRP0085-2ST151-6	363	377	414	52	315	350	529	180	195	319	128	130	436	243	143	G1 ¼"
STRP0085-2ST331-6	363	377	414	52	315	350	554	211	195	319	128	130	436	243	143	G1 ¼"

Type	Q	ØR	S1	S2	S3	T	T1	U	V	V1	W
STRP0085-2ST151-6	64	14	4	140	31	125	127	M6 × 17	M25 × 1.5	M16 × 1.5	32
STRP0085-2ST331-6	64	14	4	140	31	125	127	M6 × 17	M25 × 1.5	M16 × 1.5	32

Let's size your blower.
Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com